Alphabetic List of Paths

Standard Dictionary for Path Semantics

by Sven Nilsen, 2017

Α

```
\begin{array}{l} add[(=0)] <=> \ and \\ add[(\neg=0)] <=> \ or \\ add_{\mathbb{C},\mathbb{Q},\mathbb{R},\mathbb{Z}}[neg_{\mathbb{C},\mathbb{Q},\mathbb{R},\mathbb{Z}}] <=> \ add_{\mathbb{C},\mathbb{Q},\mathbb{R},\mathbb{Z}} \\ add_{\mathbb{N}}[even] <=> \ eq \\ add_{\mathbb{N}}[odd] <=> \ xor \\ add_{\mathbb{R}}[swap \rightarrow id] <=> \ add_{\mathbb{R}} \\ add_{\mathbb{R}}[exp] <=> \ mul_{\mathbb{R}} \\ and[not] <=> \ or \\ \end{array}
```

C

```
\begin{split} & concat[len] <=> add \\ & concat[sum] <=> add \\ & concat[min] <=> min_2 \\ & concat[max] <=> max_2 \\ & cross\{[vec\_dim] \ 3, [vec\_dim] \ 3\}[unit \ \star \ unit \ \rightarrow \ vec\_dim] <=> construct_3 \end{split}
```

D

```
dec\{(\neg=0)\}[even] \le not

div_{\mathbb{R}}\{(\neg=0), (\neg=0)\}[swap \rightarrow id] \le inv \cdot div
```

Ε

```
eq[not] <=> xor
exc[not] <=> nrexc
```

I

```
\begin{array}{ll} id[id] <=> id \\ id_A[id \rightarrow f] <=> f & f: A \rightarrow B \\ id_A[f] <=> id_B & f: A \rightarrow B \\ id_A[f \rightarrow id_A] <=> f^{\text{-1}} & f: A \rightarrow B \\ inc[even] <=> not \\ inc[inc] <=> inc \end{array}
```

M

```
\begin{array}{l} mat\_id[id \to trace] <=> id \\ mat\_inv\{[det] \ (\neg=0)\}[id \to mat\_inv] <=> id \\ mat\_mul[det] <=> mul \\ mat\_mul[fst \cdot dim \times snd \cdot dim \to dim] <=> id \\ mul_{\mathbb{N}}[(=0)] <=> or \\ mul_{\mathbb{N}}[(=0)] <=> and \\ mul_{\mathbb{N}}\{(>=0), (>=0)\}[(>=0)] <=> true_1 \\ mul_{\mathbb{N}}\{(=1), (=1)\}[prime] <=> false_1 \\ mul_{\mathbb{N}}[(\% \ k: (=0))] <=> (\% \ k) \cdot mul_{\mathbb{N}} \\ mul_{\mathbb{N}}[even] <=> or \\ mul_{\mathbb{N}}[odd] <=> and \\ mull n_{\mathbb{R}}[neg \to id] <=> mul_{\mathbb{N}} \\ mul_{\mathbb{R}}[neg \to id] <=> mul_{\mathbb{N}} \\ mul_{\mathbb{N}}[swap \to id] <=> mul \\ \end{array}
```

N

nand[not] <=> nor
nexc[not] <=> rexc
nor[not] <=> nand
not[not] <=> not
nrexc[not] <=> exc

0

or[not] <=> and not[not] <=> not

P

```
\begin{array}{l} push[len \times unit \rightarrow len] <=> inc \\ push[sum \times id \rightarrow sum] <=> add \\ push[max \times id \rightarrow max] <=> max_2 \\ push[min \times id \rightarrow min] <=> min_2 \\ pop\{[len] (\neg= 0)\}[len \rightarrow len \cdot fst] <=> dec \\ pop\{[len] (\neg= 0)\}[(sum, snd \cdot pop) \rightarrow sum \cdot fst] <=> sub \\ pop\{[len] (\neg= 0)\}[(sum, fst \cdot pop) \rightarrow sum \cdot snd] <=> sub \\ \end{array}
```

R

rexc[not] <=> nexc

S

```
sort_f[unit \rightarrow sorted_f] \le true_1

split(\_)[id \rightarrow join] \le id

sub_{\mathbb{R}}[swap \rightarrow id] \le neg
```

T

 $\begin{aligned} & transpose[el(i, j) \rightarrow el(j, i)] <=> id \\ & transpose[dim] <=> swap \end{aligned}$

U

unit[unit] <=> unit

X

xor[not] <=> eq