

Stochastic Models for blockchain analysis

Blockchain fundamentals and applications

Pierre-O. Goffard

UNiversité de Strasbourg
goffard@unistra.fr


13 octobre 2023

Blockchain

Introduction

A data ledger made of a sequence of blocks maintained by a achieving consensus in a Peer-To-Peer network.

- Decentralized
- Public/private
- Permissionned/permissionless
- Immutable
- Incentive compatible



We will focus on public blockchain and their associated consensus protocol.

Blocks

Introduction

A block contains

- block height/ID
- Time stamp
- hash of the block
- hash of the previous block
- Set of transactions (data stored in the blockchain)

```
Block Height: 0
Block Hash: a52bea61a9f4131588cc101e8e1c731fa9f69f16934c5ab3a05a2134a42c13e0
Time:2021-07-12 10:03:04.812744
Block data: [{"sender": "Coinbase", "recipient": "Satoshi", "amount": 100, "fee": 1}]
Mined: False
Previous block hash: 0
-----
```

<https://www.blockchain.com/>

Consensus protocols

Introduction

The mechanism to make all the nodes agree on a common data history.

The three dimensions of blockchain systems analysis

1 Efficiency (Queueing theory)

- Throughputs
- Transaction confirmation time

2 Decentralization (Entropy)

- Fair distribution of the accounting right

3 Security (Insurance Risk Theory)

- Resistance to attacks



X. Fu, H. Wang, and P. Shi, "A survey of blockchain consensus algorithms : mechanism, design and applications," *Science China Information Sciences*, vol. 64, nov 2020.

Applications of blockchain : Cryptocurrency

Introduction

- DOC S. Nakamoto, "Bitcoin : A peer-to-peer electronic cash system." Available at <https://bitcoin.org/bitcoin.pdf>, 2008.

- Transaction anonymity
- No need for a trusted third party



How does it work ?

Introduction

- 1 No central authority (Decentralized network)
- 2 Ledger to record all the transactions and coin ownership (blockchain)
- 3 A coin generation process (block finding reward)
 - Incentive to the full nodes
- 4 Ownership can be proved cryptographically (wallet associated to a public/private key)
- 5 Transactions can be issued by an entity proving ownership of the cryptographic unit (through the private key)
- 6 The system cannot process more than one transaction associated to the same cryptographic unit (double spending)



J. Lansky, "Possible state approaches to cryptocurrencies," *Journal of Systems Integration*, vol. 9, pp. 19–31, jan 2018.

Consensus protocol

Consensus protocols

Definition

Algorithm to allows the full nodes to agree on a common data history

It must rely on the scarce resources of the network

- bandwidth
- computational power
- storage (disk space)

Types of consensus protocols

Consensus protocols

1 Voting based

-  L. Lamport, R. Shostak, and M. Pease, "The byzantine generals problem," *ACM Transactions on Programming Languages and Systems*, pp. 382–401, July 1982.

2 Leader based

- Proof-of-Work (computational power)
- Proof-of-Stake (tokens)