

Autumn Examinations 2022-2023

Course Instance Code(s) Exam(s)	3BCT BSc in Computer Science & Information Technology
Module Code(s) Module(s)	CT3531 Networks and Data Communications 2
Paper No.	1
External Examiner(s) Internal Examiner(s)	Dr. R. Trestian Prof. M. Madden *Dr. D. Chambers
	any 4 questions. tions carry equal marks.
Duration No. of Pages Department(s) Course Co-ordinator(s)	2 hours 6 School of Computer Science Dr Colm O'Riordan
Requirements: Release in Exam Venue	Yes X No
MCQ Answersheet	Yes No X
Handout Statistical/ Log Tables Cambridge Tables Graph Paper Log Graph Paper Other Materials	None None None None None None
Graphic material in colour	Yes X No

- a) Assume that you are working for a large corporation that wants to use the private IP address range starting at 172.16.0.0 for its internal network. The company management wants to be able to provision up to 16 separate sites in Ireland with a subnet for each site, with at least 4000 host IP addresses available per subnet. Ireland has been allocated the first /16 range available i.e. 172.16.0.0/16. You are requested to design the network layout. Answer the following questions and fully explain the logic behind each answer:
 - (i) What subnet mask will need to be used for the individual subnets in Ireland? Fully explain the logic behind your answer. 4 MARKS
 - (ii) What are the valid host addresses and the broadcast addresses for the first and second subnets in Ireland?

 4 MARKS
 - (iii) The company has operations in 15 other European countries and each country has been allocated a /16 address range. These individual /16 address ranges are contiguous and Ireland has been allocated the first of these ranges. What route summary or supernet could be used to define a single routing entry for all of the European address ranges?

3 MARKS

- b) Write a short essay, approximately 300 words, on one of the following topics. The essay should include a full description of the topic and also discuss its advantages, disadvantages, competitor technologies (if applicable) and its likely evolution:
 - (i) Virtual LANs
 - (ii) Packet Filtering and Firewalls
 - (iii) Dynamic Routing Protocols

14 MARKS

A company has an office building that has been fitted out with the Local Area Network topology shown in Figure 1 below:




Figure 1 - Local Area Network Topology

The office building has three floors and each floor has two network switches that are used to interconnect with other switches and to connect end user devices e.g. PCs. The company is organised into three departments i.e. Sales, Support and Accounts, each department has its own VLAN. There is also a Mikrotik router connected to one of the switches on the ground floor, this router also provides internet access via an ethernet connection provided by an ISP. Answer the following questions in relation to the design and configuration of this network.

- a) What are the advantages of using a VLAN for each Department? Suggest a suitable VLAN id and IP subnet for each VLAN.

 5 MARKS
- b) What port configuration would be required for Switch2-Floor1? In this context explain the purpose of the 802.1q protocol.

 5 MARKS
- c) Assume that the router gets a public IP address via DHCP from the ISP connected via ether2. What RouterOS commands are required on the router to ensure that NAT is used for outgoing internet traffic?

 5 MARKS
- d) What steps and additional configuration would be needed, on the router and the switches, to add another new VLAN to the existing setup? 5 MARKS
- e) What mechanism is used to ensure that a broadcast storm does not occur due to the fact that the switches are interconnected in a loop type topology? Explain the basic operation of this mechanism.

 5 MARKS

- a) Explain how traceroute works and what it shows using an appropriate example. 5 MARKS
- b) State and differentiate the three main means of interconnecting an Autonomous System with another Autonomous System. 3 MARKS
- c) Describe briefly each of the following: Border Gateway Protocol, Internet Exchange Point, Asymmetric Route. 6 MARKS
- d) Describe in your own words what a Route Server is, what function it performs and why it is necessary.

 5 MARKS
- e) The result of running the command /ip route print on a Mikrotik router is shown below. The router is running OSPF with other routers in the same Autonomous System:

```
\label{eq:continuity} \begin{array}{l} [admin@10.10.10.1] > ip\ route\ print \\ \text{Flags: } X - \text{ disabled, } A - \text{ active, } D - \text{ dynamic,} \\ C - \text{ connect, } S - \text{ static, } r - \text{rip, } b - \text{bgp, } o - \text{ospf, } m - \text{mme,} \\ \end{array}
B - blackhole, U - unreachable, P - prohibit
           DST-ADDRESS
                                       PREF-SRC
                                                              GATEWAY
                                                                                          DISTANCE
 0 ADo
           0.0.0.0/0
                                                              10.1.1.2
                                                                                                 110
 1 ADC
           10.1.1.0/24
                                       10.1.1.1
                                                              ether1
                                                                                                    0
                                                                                                 110
 2 ADo
           10.1.4.0/24
                                                              10.1.1.2
 3 ADC
           10.10.10.1/32
                                       10.10.10.1
                                                               loopback
 4 ADo
                                                              10.1.1.2
                                                                                                 110
           10.10.10.2/32
 5 ADo
           10.10.10.4/32
                                                              10.1.1.2
                                                                                                 110
 6 ADC
           172.21.1.0/30
                                       172.21.1.2
                                                              ether2
 7 ADC 192.168.10.0/24
                                       192.168.10.1
                                                              ether3
                                                                                                 110
 8 ADo 192.168.11.0/24
                                                              10.1.1.2
 9 ADo
           192.168.12.0/24
                                                              10.1.1.2
                                                                                                 110
10 ADo
           192.168.81.0/24
                                                              10.1.1.2
                                                                                                 110
                                       192.168.182.138 ether4
11 ADC
           192.168.182.0/24
```

Answer the following questions in relation to this routing table.

- i. What does the route entry for destination 0.0.0.0/0 mean and why is this route entry particularly important? 2 MARKS
- ii. Is the destination IP range 192.168.10.0/24 on the same router or a different router? How can you tell? 2 MARKS
- iii. What is the meaning of the GATEWAY value shown and how might this affect a routing decision? 2 MARKS

Assume that an Internet Service Provider has built a routed network in Co Galway as shown in Figure 2 below:




Figure 2 - ISP Regional Network

The routers are all Mikrotik routers running the RouterOS operating system. Answer the following questions in relation to the operation and configuration of this network. Please note that you do not need to build the network shown in the GNS3 simulator to answer these questions.

- a) Describe the operation and purpose of the OSPF protocol in the network shown.
 How is Dijkstra's Algorithm used by OSPF in this context and what would the sink tree look like from the Loughrea router?
 5 MARKS
- b) Describe the format of an OSPF Link State Announcement. Explain how a Link State Announcement from the Loughrea router would be disseminated throughout the network and how can this be done reliably.

 5 MARKS
- c) Suggest suitable IP subnets for the links connected to the Loughrea router. What RouterOS commands are required to assign appropriate IP addresses and to also fully enable OSPF on the Loughrea router?
 5 MARKS
- d) What route would a PC attached to the Inverin router normally take to get to the Gort router? What exactly would happen with OSPF if the link between Inverin and Mervue became unavailable for some reason?

 5 MARKS
- e) Assume that the Clifden router needs to have an additional local area network, attached to ether3, for some end user devices e.g. PCs. Suggest a suitable IP subnet for this new local area network. What RouterOS commands would be required on the Clifden router to assign an appropriate IP address for this additional local area network and to ensure that the new IP range is reachable from the other routers in the network?

 5 MARKS

- a) What types of Sockets are supported in the Java networking package and which type of Socket would you recommend for a VOIP type application and a File Transfer type application?
 5 MARKS
- b) Write a network Server program in Java where the Server waits for incoming client connections using stream type sockets. Once a Client connects it sends a String object to the server with a simple query the server then responds with a text based response. The connection is then terminated. The server should use a separate thread of execution for each new client connection and all interaction between the Server and the Client should be done within this thread. The answer only needs to include source code for the server side application.

 10 MARKS

c) Write another Java application with the same functionality as outlined in part b of this question, but this time using Datagram type sockets. Hint: you can use ByteArrayOutputStream and ByteArrayInputStream to populate and read the array associated with the DatagramPacket object. This application does not need to implement a reliable data transfer protocol or use multiple threads at the server for each new client. The answer only needs to include source code for the server side application.

10 MARKS