
## Signal Interpolation - Upsampling

This example we illustrates the process of signal interpolation using existing MatDeck functions. The interpolation is the increase of the sampling rate. First, the test signal is generated. We use the sum of two sinusoidal signals of different frequencies.

```
Hz, original sampling rate
Fs:=20000
              Sampling period
Ts:=1/Fs
Dt:= curve2d(x, 0, 0.005-Ts, 100)
                                          Time axis
dt = col2vec(Dt, 0)
            Hz, frequency of the first sinusoidal signal
f1 := 1000
              Hz, frequency of the second sinusoidal signal
f2 := 6000
y:= 5 \sin(2 \pi \cdot f1 dt) + 5 \sin(2 \pi \cdot f2 dt) The input test signal, sum of two sinusoidals
graf1 := join mat cols(dt, y) Time domain graph of the test signal
                                          Original signal
                 Amplitude
                       0.0008
                                0.0016
                                         0.0024
                                                   0.0032
                                                             0.004
```

We can investigate the signal spectrum as well. We determine the spectrum by using fft.

```
\label{eq:fift} \begin{split} &\text{nfft:=size}(y) \quad \text{Length of the input signal} \\ &\text{fy:=fft1}(y) \quad \text{Spectrum of the input signal} \\ &\text{fy1:=subset}(\text{fy , 0 , 0 , nfft/2-1 , 0}) \quad \text{Only half of the periodic spectrum is taken due to symmetry} \\ &\text{xfft:=curve2d}(x \,, 0 \,, (Fs/2 \,) \cdot (nfft/2-1 \,) / (nfft/2 \,) \,\,, 50) \quad \text{Frequency axis} \\ &\text{xfft1:=col2vec}(xfft \,, 1) \\ &\text{fyy1:=} \left | \text{fy1} \right | \quad \text{Amplitude spectrum of the input signal} \\ &\text{graf2:=join mat cols}(xfft1 \,, fyy1) \quad \text{Graph of the amplitude spectrum of the test signal} \end{split}
```



The following task is to increase the sampling rate by a factor of two, increasing the number of samples. When interpolation is performed, one should take care about proper timing, in order to illustrate the decimation.

```
N:=2 \quad \text{Upsampling factor} \\ \text{yinter:= upsample}(y \,,\, N) \quad \text{Upsampled signal} \\ \text{Fs1:=Fs N} \quad \text{New sampling rate} \\ \text{Ts1:=1/Fs1} \quad \text{New sampling period} \\ \text{Dt1:= curve} 2d(x \,,\, 0 \,,\, 0.005\text{-Ts1} \,,\, 200) \quad \text{New time axis} \\ \text{dt1:= col2vec}(\text{Dt1} \,,\, 0) \\ \text{graf3:= join mat cols}(\text{dt1} \,,\, \text{yinter}) \quad \text{Graph of the upsampled signal} \\ \end{aligned}
```

