

HTML Tag List with Description

NEW - New tag introduce in HTML5

REMOVE - Not Support in HTML5

NEW/REMOVE - New Tag introduce in HTML5, But now yet support in HTML5

Tag	Description	In HTML5?
<!--...-->	Describe a comment text in the source code	
<!doctype>	Defines a document type	
<a>	Specific a anchor (Hyperlink) Use for link in internal/external web documents.	
<article>	Defines an article	NEW
<aside>	Describes contain set(or write) on aside place in page contain	NEW
<audio>	Specific audio content	NEW
	Specific text weight bold	
<base>	Define a base URL for all the links with in a web page	
<basefont>	Describes a default font color, size, face in a document	REMOVE
<bb>	Define browser command, that command invoke as per client action	NEW/ REMOVE
<bdo>	Specific direction of text display	
<big>	Defines a big text	REMOVE

<blockquote>	Specifies a long quotation	
<body>	Defines a main section(body) part in HTML document	

	Specific a single line break	
<button>	Specifies a press/push button	
<canvas>	Specifies the display graphics on HTML web documment	NEW
<caption>	Define a table caption	
<center>	Specifies a text is display in center align	REMOVE
<cite>	Specifies a text citation	
<code>	Specifies computer code text	
<col>	Specifies a each column within a <colgroup> element in table	
<colgroup>	Defines a group of one or more columns inside table	
<command>	Define a command button, invoke as per user action	NEW
<datagrid>	Define a represent data in datagrid either list wise or tree wise	NEW/ REMOVE
<datalist>	Define a list of pre-defined options surrounding <input> tag	NEW
<dd>	Defines a definition description in a definition list	
	Specific text deleted in web document	

<details>	Define a additional details hide or show as per user action	NEW
<dfn>	Define a definition team	
<dialog>	Define a chat conversation between one or more person	NEW/ REMOVE
<dir>	Define a directory list	REMOVE
<div>	Define a division part	
<dl>	Define a definition list	
<dt>	Define a definition team	
	Define a text is emphasize format	
<embed>	Define a embedding external application using a relative plug-in	NEW
<eventsource>	Defines a source of event generates to remote server	NEW/ REMOVE
<fieldset>	Defines a grouping of related form elements	
<figcaption>	Represents a caption text corresponding with a figure element	NEW
<figure>	Represents self-contained content corresponding with a <figcaption> element	NEW
	Defines a font size, font face and font color for its text	REMOVE
<footer>	Defines a footer section containing details about the author, copyright, contact us, sitemap, or links to related documents.	NEW

<form>	Defines a form section that having interactive input controls to submit form information to a server.	
<frame>	Defines frame window.	REMOVE
<frameset>	Used to holds one or more <frame> elements.	REMOVE
<h1> to <h6>	Defines a Headings level from 1 to 6 different sizes.	
<head>	Defines header section of HTML document.	
<header>	Defines as a container that hold introductory content or navigation links.	NEW
<hgroup>	Defines the heading of a section that hold the h1 to h6 tags.	NEW/ REMOVE
<hr />	Represent a thematic break between paragraph-level tags. It is typically draw horizontal line.	
<html>	Define a document is a HTML markup language	
<i>	Defines a italic format text	
<iframe>	Defines a inline frame that embedded external content into current web document.	
	Used to insert image into a web document.	
<input>	Define a get information in selected input	
<ins>	Used to indicate text that is inserted into a page and indicates changes to a document.	

<isindex>	Used to create a single line search prompt for querying the contents of the document.	REMOVE
<kbd>	Used to identify text that are represents keyboard input.	
<keygen>	Used to generate signed certificate, which is used to authenticate to services.	NEW/ REMOVE
<label>	Used to caption a text label with a form <input> element.	
<legend>	Used to add a caption (title) to a group of related form elements that are grouped together into the <fieldset> tag.	
	Define a list item either ordered list or unordered list.	
<link>	Used to load an external stylesheets into HTML document.	
<map>	Defines an clickable image map.	
<mark>	Used to highlighted (marked) specific text.	NEW
<menu>	Used to display a unordered list of items/menu of commands.	
<meta>	Used to provide structured metadata about a web page.	
<meter>	Used to measure data within a given range.	NEW
<nav>	Used to defines group of navigation links.	NEW
<noframes>	Used to provide a fallback content to the browser that does not support the <frame> element.	REMOVE

<noscript>	Used to provide an fall-back content to the browser that does not support the JavaScript.	
<object>	Used to embedded objects such as images, audio, videos, Java applets, and Flash animations.	
	Defines an ordered list of items.	
<optgroup>	Used to create a grouping of options, the related options are grouped under specific headings.	
<option>	Represents option items within a <select> , <optgroup> or <datalist> element.	
<output>	Used for representing the result of a calculation.	NEW
<p>	Used to represents a paragraph text.	
<param>	Provides parameters for embedded object element.	
<pre>	Used to represents preformatted text.	
<progress>	Represents the progress of a task.	NEW
<q>	Represents the short quotation.	
<rp>	Used to provide parentheses around fall-back content to the browser that does not support the ruby annotations.	NEW
<rt>	Specifies the ruby text of ruby annotation.	NEW
<ruby>	Used to represents a ruby annotation.	NEW

<s>	Text display in strikethrough style.	
<samp>	Represents text that should be interpreted as sample output from a computer program.	
<script>	Defines client-side JavaScript.	
<section>	Used to divide a document into number of different generic section.	NEW
<select>	Used to create a drop-down list.	
<small>	Used to makes the text one size smaller.	
<source>	Used to specifies multiple media resources.	NEW
	Used to grouping and applying styles to inline elements.	
<strike>	Represents strikethrough text.	REMOVE
	Represents strong emphasis greater important text.	
<style>	Used to add CSS style to an HTML document.	
<sub>	Represents inline subscript text.	
<sup>	Represents inline superscript text.	
<table>	Used to defines a table in an HTML document.	
<tbody>	Used for grouping table rows.	
<td>	Used for creates standard data cell in HTML table.	

<textarea>	Create multi-line text input.	
<tfoot>	Used to adding a footer to a table that containing summary of the table data.	
<th>	Used for creates header of a group of cell in HTML table.	
<thead>	Used to adding a header to a table that containing header information of the table.	
<time>	Represents the date and/or time in an HTML document.	NEW
<title>	Represents title to an HTML document.	
<tr>	Defines a row of cells in a table.	
<track>	Represents text tracks for both the <audio> and <video> tags.	NEW
<tt>	Represents teletype text.	REMOVE
<u>	Represents underlined text.	
	Defines an unordered list of items.	
<var>	Represents a variable in a computer program or mathematical equation.	
<video>	Used to embed video content.	NEW
<wbr>	Defines a word break opportunity in a long string of text.	NEW