

Description

This package allows the transfer of data between a labkey database and an R session. Data can be imported from a labkey database into R by specifying the query schema information (`labkey.selectRows`) or by using sql commands (`labkey.executeSql`). From an R session, existing data can be updated (`labkey.updateRows`), new data can be inserted (`labkey.insertRows`) or data can be deleted from the labkey database (`labkey.deleteRows`).

The user must have the appropriate authorization on the labkey server in order to modify the database through the use of these functions.

Details

Package:	Rlabkey
Type:	Package
Version:	0.0.3
Date:	2008-09-02
License:	Apache 2.0
LazyLoad:	yes

Using this package to access a password protected labkey data base requires that the user has their login information in a netrc file. The netrc file contains configuration and autologin information for the File Transfer Protocol client (ftp) and other programs such as CURL.

On a UNIX system this file should be named `.netrc` (dot netrc) and on windows it should be named `_netrc` (underscore netrc). The file should be located in the users home directory and the permissions on the file should be unreadable for everybody except the owner.

To create the `_netrc` on a windows machine, first create an environment variable called 'HOME' that is set to your home directory (`c:/Users/<User-Name>` on Vista) or any directory you want to use. In that directory, create a text file named `_netrc` (note that it's underscore netrc, not dot netrc like it is on UNIX).

The following three lines must be included in the `.netrc` or `_netrc` file either separated by white space (spaces, tabs, or newlines) or commas.

```
machine <remote-machine-name>
login <user-email>
password <user-password>
```

One example would be:

```
machine atlas.scharp.org
login vobencha@fhcrc.org
password mypassword
```

Another example would be:

```
machine atlas.scharp.org login vobencha@fhcrc.org password mypassword
```

Author(s)

Valerie Obenchain

References

<http://www.omegahat.org/RCurl/>,
<http://dssm.unipa.it/CRAN/web/packages/rjson/rjson.pdf>,
<https://www.labkey.org/project/home/begin.view>

See Also

[labkey.selectRows](#), [labkey.executeSql](#), [makeFilter](#), [labkey.insertRows](#), [labkey.updateRows](#),
[labkey.deleteRows](#)

<code>labkey.deleteRows</code>	<i>Delete rows of data from a labkey database</i>
--------------------------------	---

Description

Specify rows of data to be deleted from the database.

Usage

```
labkey.deleteRows(baseUrl, folderPath, schemaName, queryName, toDelete,  
stripAllHidden = TRUE)
```

Arguments

<code>baseUrl</code>	a string specifying the <code>baseUrl</code> for labkey server
<code>folderPath</code>	a string specifying the <code>folderPath</code>
<code>schemaName</code>	a string specifying the <code>schemaName</code> for the query
<code>queryName</code>	a string specifying the <code>queryName</code>
<code>toDelete</code>	a data frame containing a single column of data containing the data identifiers of the rows to be deleted
<code>stripAllHidden</code>	(optional) a logical value indicating whether or not to return data columns that would normally be hidden from user view. If no value is specified, no hidden columns are returned.

Details

A single row or multiple rows of data can be deleted. The `toDelete` data frame should consist of a single column of data containing the data identifiers of the rows to be deleted (e.g., `lsid`). The data frame must be created with the `stringsAsFactors` set to `FALSE`.

NOTE: Each variable in a dataset has both a column label and a column name. The column label is visible at the top of each column on the web page and is longer and more descriptive.

The column name is shorter and is used “behind the scenes” for database manipulation. It is the column name that must be used in the Rlabkey functions when a column name is expected. To identify a particular column name in a dataset on a web site, use the “export to R script” option available as a drop down option under the “views” tab for each dataset.

Value

A list is returned with named categories of **command**, **rowsAffected**, **rows**, **queryName**, **containerPath** and **schemaName**. The **schemaName**, **queryName** and **containerPath** properties contain the same schema, query and folder path used in the request. The **rowsAffected** property indicates the number of rows affected by the API action. This will typically be the same number as passed in the request. The **rows** property contains a list of rows corresponding to the rows deleted.

Author(s)

Valerie Obenchain

References

<http://www.omegahat.org/RCurl/>,
<http://dssm.unipa.it/CRAN/web/packages/rjson/rjson.pdf>,
<https://www.labkey.org/project/home/begin.view>

See Also

[labkey.selectRows](#), [labkey.executeSql](#), [makeFilter](#), [labkey.insertRows](#), [labkey.updateRows](#)

Examples

```
## Delete two rows of data
#delrows <- data.frame(lsid=c('urn:lsid:labkey.org:****','urn:lsid:labkey.org:****',
# 'urn:lsid:labkey.org:****'),stringsAsFactors=FALSE))

#labkey.deleteRows(      baseUrl="https://www.labkey.org",
#                        # folderPath="/home/Study/demo",
#                        # schemaName="study",
#                        # queryName="HIV Test Results",
#                        # toDelete=delrows)
```

<code>labkey.executeSql</code>	<i>Retrieve data from a labkey database using SQL commands</i>
--------------------------------	--

Description

Use Sql commands to specify data to be imported into R. Prior to import, data can be manipulated through standard SQL commands supported in labkey SQL.

Usage

```
labkey.executeSql(baseUrl, folderPath, schemaName, sql, maxRows = NULL,  
rowOffset = NULL, stripAllHidden = TRUE)
```

Arguments

baseUrl	a string specifying the baseUrl for the labkey server
folderPath	a string specifying the folderPath
schemaName	a string specifying the schemaName for the query
sql	a string containing the sql commands to be executed
maxRows	(optional) an integer specifying the maximum number of rows to return. If no value is specified, all rows are returned.
rowOffset	(optional) an integer specifying which row of data should be the first row in the retrieval. If no value is specified, rows will begin at the start of the result set.
stripAllHidden	(optional) a logical value indicating whether or not to return data columns that would normally be hidden from user view. If no value is specified, no hidden columns are returned.

Details

Rows returned from the SQL query are imported into an R data frame using the `labkey.executeSql` function. Function arguments are components of the url that identify the location of the data and what SQL actions should be taken on the data prior to import.

NOTE: Each variable in a dataset has both a column label and a column name. The column label is visible at the top of each column on the web page and is longer and more descriptive. The column name is shorter and is used “behind the scenes” for database manipulation. It is the column name that must be used in the Rlabkey functions when a column name is expected. To identify a particular column name in a dataset on a web site, use the “export to R script” option available as a drop down option under the “views” tab for each dataset.

Value

The requested data are returned in a data frame with column names as they appear on the website.

Author(s)

Valerie Obenchain

References

<http://www.omegahat.org/RCurl/>,
<http://dssm.unipa.it/CRAN/web/packages/rjson/rjson.pdf>,
<https://www.labkey.org/project/home/begin.view>

See Also

[labkey.selectRows](#), [makeFilter](#), [labkey.insertRows](#), [labkey.updateRows](#), [labkey.deleteRows](#)

Examples

```
### Select participants who meet acute status requirements
#getacute <- labkey.executeSql(baseUrl="https://www.labkey.org",
#                             folderPath="/home/Study/demo",
#                             schemaName="study",
#                             sql = 'select "Status Assessment".ParticipantId from "Status Assessment" whe
#
#
### Average ages over different gender groups
#getage <- labkey.executeSql(baseUrl="https://www.labkey.org",
#                             folderPath="/home/Study/demo",
#                             schemaName="study",
#                             sql = "select Demographics.Gender, avg(Demographics.Age) as Number from Demo
#
### Select data for participants with partner information
#getpartners <- labkey.executeSql(baseUrl="https://www.labkey.org",
#                                 folderPath="/home/Study/demo",
#                                 schemaName="study",
#                                 sql = 'select "Status Assessment".StatusPartner1 from "Status Assessment" wh
#
```

<code>labkey.insertRows</code>	<i>Insert new rows of data into a labkey database</i>
--------------------------------	---

Description

Insert new rows of data into the database.

Usage

```
labkey.insertRows(baseUrl, folderPath, schemaName, queryName, toInsert,
stripAllHidden = TRUE)
```

Arguments

<code>baseUrl</code>	a string specifying the <code>baseUrl</code> for the labkey server
<code>folderPath</code>	a string specifying the <code>folderPath</code>
<code>schemaName</code>	a string specifying the <code>schemaName</code> for the query
<code>queryName</code>	a string specifying the <code>queryName</code>

toInsert a data frame containing rows of data to be inserted

stripAllHidden (optional) a logical value indicating whether or not to return data columns that would normally be hidden from user view. If no value is specified, no hidden columns are returned.

Details

A single row or multiple rows of data can be inserted. The **toInsert** data frame must contain values for each column in the dataset and must be created with the **stringsAsFactors** option set to **FALSE**. When inserting data into a study dataset, the sequence number must be specified.

NOTE: Each variable in a dataset has both a column label and a column name. The column label is visible at the top of each column on the web page and is longer and more descriptive. The column name is shorter and is used “behind the scenes” for database manipulation. It is the column name that must be used in the **Rlabkey** functions when a column name is expected. To identify a particular column name in a dataset on a web site, use the “export to R script” option available as a drop down option under the “views” tab for each dataset.

Value

A list is returned with named categories of **command**, **rowsAffected**, **rows**, **queryName**, **containerPath** and **schemaName**. The **schemaName**, **queryName** and **containerPath** properties contain the same schema, query and folder path used in the request. The **rowsAffected** property indicates the number of rows affected by the API action. This will typically be the same number as passed in the request. The **rows** property contains a list of row objects corresponding to the rows inserted.

Author(s)

Valerie Obenchain

References

<http://www.omegahat.org/RCurl/>,
<http://dssm.unipa.it/CRAN/web/packages/rjson/rjson.pdf>,
<https://www.labkey.org/project/home/begin.view>

See Also

[labkey.selectRows](#), [labkey.executeSql](#), [makeFilter](#), [labkey.updateRows](#), [labkey.deleteRows](#)

Examples

```
## Insert two rows of data:
#newrows <- data.frame(participantID=c(24932540, 24932541), SequenceNum=c(2,3), age=c(40, 25),
#height=c(70,65), gender=c("m","f"), city=c("Boston","New York"), state=c("MA","NY"),
#country=c("USA","USA"), stringsAsFactors=FALSE)
```

```
#labkey.insertRows(      baseUrl="https://www.labkey.org",
#                          folderPath="/home/Study/demo",
#                          schemaName="study",
#                          queryName="Demographics",
#                          toInsert=newrows)
```

labkey.selectRows	<i>Retrieve data from a labkey database</i>
-------------------	---

Description

Import full datasets or selected rows into R. The data can be sorted and filtered prior to import.

Usage

```
labkey.selectRows(baseUrl, folderPath, schemaName, queryName, viewName = NULL,
colSelect = NULL, maxRows = NULL, rowOffset = NULL, colSort = NULL,
colFilter = NULL, stripAllHidden = TRUE)
```

Arguments

baseUrl	a string specifying the baseUrl for the labkey server
folderPath	a string specifying the folderPath
schemaName	a string specifying the schemaName for the query
queryName	a string specifying the queryName
viewName	(optional) a string specifying the viewName
colSelect	(optional) a vector of comma separated strings specifying which columns of a dataset or view to import
maxRows	(optional) an integer specifying how many rows of data to return. If no value is specified, all rows are returned.
colSort	(optional) a string including the name of the column to sort preceeded by a "+" or "-" to indicate sort direction
rowOffset	(optional) an integer specifying which row of data should be the first row in the retrieval. If no value is specified, the retrieval starts with the first row.
colFilter	(optional) a vector or array object created by the makeFilter function which contains the column name, operator and value of the filter(s) to be applied to the retrieved data.
stripAllHidden	(optional) a logical value indicating whether or not to return data columns that would normally be hidden from user view. If no value is specified, no hidden columns are returned.

Details

A full dataset or user saved view can be imported into an R data frame using the `labkey.selectRows` function. Function arguments are the components of the url that identify the location of the data and what actions should be taken on the data prior to import (ie, sorting, selecting particular columns or maximum number of rows, etc.).

NOTE: Each variable in a dataset has both a column label and a column name. The column label is visible at the top of each column on the web page and is longer and more descriptive. The column name is shorter and is used “behind the scenes” for database manipulation. It is the column name that must be used in the Rlabkey functions when a column name is expected. To identify a particular column name in a dataset on a web site, use the “export to R script” option available as a drop down option under the “views” tab for each dataset.

Value

The requested data are returned in a data frame with column names as they appear on the website.

Author(s)

Valerie Obenchain

References

<http://www.omegahat.org/RCurl/>,
<http://dssm.unipa.it/CRAN/web/packages/rjson/rjson.pdf>,
<https://www.labkey.org/project/home/begin.view>

See Also

[labkey.executeSql](#), [makeFilter](#), [labkey.insertRows](#), [labkey.updateRows](#), [labkey.deleteRows](#)

Examples

```
# Retrieve HIV Test Results and plot Western Blot data
#getdata <- labkey.selectRows( baseUrl="https://www.labkey.org",
#                               folderPath="/home/Study/demo",
#                               schemaName="study",
#                               queryName="HIV Test Results")
#plot(factor(getdata$"HIV Western Blot"), main="HIV Western Blot")

# Select columns and apply filters
#myfilters<- makeFilter(c("HIVLoadQuant","GREATER_THAN",500), c("HIVRapidTest","EQUALS","Positive"))

#getdata <- labkey.selectRows( baseUrl="https://www.labkey.org",
#                               folderPath="/home/Study/demo",
#                               schemaName="study",
#                               queryName="HIV Test Results",
#                               colSelect=c("ParticipantId","HIVDate","HI
#                               colFilter=myfilters)
```

labkey.updateRows	<i>Update existing rows of data in a labkey database</i>
-------------------	--

Description

Send data from an R session to update existing rows of data in the database.

Usage

```
labkey.updateRows(baseUrl, folderPath, schemaName, queryName, toUpdate,  
stripAllHidden = TRUE)
```

Arguments

baseUrl	a string specifying the baseUrl for the labkey server
folderPath	a string specifying the folderPath
schemaName	a string specifying the schemaName for the query
queryName	a string specifying the queryName
toUpdate	a data frame containing the row(s) of data to be updated
stripAllHidden	(optional) a logical value indicating whether or not to return data columns that would normally be hidden from user view. If no value is specified, no hidden columns are returned.

Details

A single row or multiple rows of data can be updated. The **toUpdate** data frame should contain the rows of data to be updated and must be created with the **stringsAsFactors** option set to **FALSE**.

NOTE: Each variable in a dataset has both a column label and a column name. The column label is visible at the top of each column on the web page and is longer and more descriptive. The column name is shorter and is used “behind the scenes” for database manipulation. It is the column name that must be used in the Rlabkey functions when a column name is expected. To identify a particular column name in a dataset on a web site, use the “export to R script” option available as a drop down option under the “views” tab for each dataset.

Value

A list is returned with named categories of **command**, **rowsAffected**, **rows**, **queryName**, **containerPath** and **schemaName**. The **schemaName**, **queryName** and **containerPath** properties contain the same schema, query and folder path used in the request. The **rowsAffected** property indicates the number of rows affected by the API action. This will typically be the same number as passed in the request. The **rows** property contains a list of row objects corresponding to the rows updated.

Author(s)

Valerie Obenchain

References

<http://www.omegahat.org/RCurl/>,
<http://dssm.unipa.it/CRAN/web/packages/rjson/rjson.pdf>,
<https://www.labkey.org/project/home/begin.view>

See Also

[labkey.selectRows](#), [labkey.executeSql](#), [makeFilter](#), [labkey.insertRows](#), [labkey.deleteRows](#)

Examples

```
### Retrieve data from the database
#getdata <- labkey.selectRows( baseUrl="https://www.labkey.org",
#                               folderPath="/home/Study/demo",
#                               schemaName="study",
#                               queryName="Demographics")
#
### Modify the data
#modifyDat <- getdata[2,]
#modifyDat$City <- "Tacoma"
#
### Will need lsid for rows
### Update the rows in the database with the modified data
#labkey.updateRows(    baseUrl="https://www.labkey.org",
#                      folderPath="/home/Study/demo",
#                      schemaName="study",
#                      queryName="HIV Test Results",
#                      toUpdate=modifyDat)
#
#
```

`makeFilter`

Builds an array of filters

Description

This function takes inputs of column name, filter value and filter operator and returns an array of filters to be used in `labkey.selectRows`.

Usage

```
makeFilter(c(colname, operator,value))
```

Arguments

colname	a string specifying the name of the column to be filtered
operator	a string specifying what operator should be used in the filter (see options below)
value	an integer or string specifying the value the columns should be filtered on

Details

These filters are applied to the data prior to import into R. Currently this function allows the user to specify up to five filters. Multiple filters can be entered named or un-named vectors (see examples below).

Possible operator values are as follows: "EQUALS", "EQUALS_ONE_OF", "NOT_EQUALS", "GREATER_THAN", "GREATER_THAN_OR_EQUAL_TO", "LESS_THAN", "LESS_THAN_OR_EQUAL_TO", "DATE_EQUAL", "DATE_NOT_EQUAL", "NOT_EQUAL_OR_NULL", "IS_MISSING", "IS_NOT_MISSING", "CONTAINS", "DOES_NOT_CONTAIN", "STARTS_WITH", and "DOES_NOT_START_WITH".

Value

The function returns either a single string or an array of strings to be use in the `colFilter` argument of the `labkey.selectRows` function.

Author(s)

Valerie Obenchain

References

<http://www.omegahat.org/RCurl/>,
<http://dssm.unipa.it/CRAN/web/packages/rjson/rjson.pdf>,
<https://www.labkey.org/project/home/begin.view>

See Also

[labkey.selectRows](#)

Examples

```
# Specify two filters:
myfilters<- makeFilter(c("HIVLoadQuant","GREATER_THAN",500), c("HIVRapidTest","EQUALS","Positive"))

# Filter using "equals one of" operator:
myfilter2 <- makeFilter(filter1=c("HIVLoadIneq","EQUALS_ONE_OF","Equals ; Less than"))

# Use in labkey.selectRows function
getdata <- labkey.selectRows(baseUrl="https://www.labkey.org", folderPath="/home/Study/demo",
schemaName="study", queryName="HIV Test Results",
colSelect=c("ParticipantId","HIVDate","HIVLoadQuant","HIVRapidTest"), colFilter=myfilters)
```