

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Lift III

Other means of identification : Not applicable

Recommended use : Cleaning product

Product dilution information : 0,0 % - 5,0 %

Company : Champion Technologies del Ecuador, S.A.
S. Moreno OE1-195 y Francisco Garcia
Quito, Pichincha, Ecuador
59-32-247-7528

Emergency telephone : 59-32-247-7529

Issuing date : 07.06.2017

SECTION 2. HAZARDS IDENTIFICATION
GHS Classification
Product AS SOLD

Skin corrosion : Category 1A

Serious eye damage : Category 1

Product AT USE DILUTION

Not a hazardous substance or mixture.

GHS label elements
Product AS SOLD

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**
Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse.

Storage:
Store locked up.

Disposal:
Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

Lift III

Product AT USE DILUTION

Precautionary Statements : **Prevention:**
Wash hands thoroughly after handling.
Response:
Get medical advice/ attention if you feel unwell.
Storage:
Store in accordance with local regulations.

Product AS SOLD

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
sodium dodecylbenzene sulfonate	25155-30-0	1 - 5
poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy-, mono-c8-10-alkyl ethers, phosphates	68130-47-2	1 - 5
diphosphoric acid, tetrapotassium salt	7320-34-5	1 - 5
poly(oxy-1,2-ethanediyl), .alpha.-isotridecyl-.omega.-hydroxy-	9043-30-5	1 - 5
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	1 - 5
2-butoxyethanol	111-76-2	1 - 5
sodium metasilicate	6834-92-0	1 - 5
Sodium hydroxide	1310-73-2	0,1 - 1

Product AT USE DILUTION

Chemical name	CAS-No.	Concentration (%)
poly(oxy-1,2-ethanediyl), .alpha.-isotridecyl-.omega.-hydroxy-	9043-30-5	0,1 - 1

SECTION 4. FIRST AID MEASURES

Product AS SOLD

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms : See Section 11 for more detailed information on health effects and

SAFETY DATA SHEET

Lift III

and effects, both acute and delayed symptoms.

Product AT USE DILUTION

In case of eye contact	: Rinse with plenty of water.
In case of skin contact	: Rinse with plenty of water.
If swallowed	: Rinse mouth. Get medical attention if symptoms occur.
If inhaled	: Get medical attention if symptoms occur.

SECTION 5. FIRE-FIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Not flammable or combustible.
Hazardous combustion products	: Decomposition products may include the following materials: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus
Special protective equipment for fire-fighters	: Use personal protective equipment.
Specific extinguishing methods	: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures	: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.
Environmental precautions	: Do not allow contact with soil, surface or ground water.
Methods and materials for containment and cleaning up	: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Personal precautions, protective equipment and	: Refer to protective measures listed.
--	--

SAFETY DATA SHEET

Lift III

emergency procedures

Environmental precautions : No special environmental precautions required.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : -5 °C to 50 °C

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. For personal protection see section 8.

Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Ingredients with workplace control parameters

Ingredients	CAS-No.	Form of exposure	Permissible concentration	Basis
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	CMP	200 ppm	AR OEL
		CMP - CPT	150 ppm	AR OEL
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	STEL	150 ppm 909 mg/m3	PE OEL
		TWA	100 ppm 606 mg/m3	PE OEL
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	L-8/40	50 ppm 308 mg/m3	VE OEL
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	LMPE-PPT	100 ppm 60 mg/m3	MX OEL
		LMPE-CT	150 ppm 900 mg/m3	MX OEL
		VLE-PPT	100 ppm	NOM-010-STPS-2014
		VLE-CT	150 ppm	NOM-010-STPS-2014
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 900 mg/m3	NIOSH REL

SAFETY DATA SHEET

Lift III

		TWA	100 ppm 600 mg/m3	NIOSH REL
		TWA	100 ppm 600 mg/m3	OSHA Z1
2-butoxyethanol	111-76-2	CMP	20 ppm	AR OEL
2-butoxyethanol	111-76-2	LT	39 ppm 190 mg/m3	BR OEL
2-butoxyethanol	111-76-2	LPP	18 ppm 85 mg/m3	CL OEL
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m3	PE OEL
		STEL	50 ppm 242 mg/m3	PE OEL
2-butoxyethanol	111-76-2	L-8/40	20 ppm	VE OEL
2-butoxyethanol	111-76-2	LMPE-PPT	26 ppm 120 mg/m3	MX OEL
		LMPE-CT	75 ppm 360 mg/m3	MX OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z1
Sodium hydroxide	1310-73-2	CMP-C	2 mg/m3	AR OEL
Sodium hydroxide	1310-73-2	LPA	2 ppm	CL OEL
Sodium hydroxide	1310-73-2	CEIL	2 mg/m3	PE OEL
Sodium hydroxide	1310-73-2	LB	2 mg/m3	VE OEL
Sodium hydroxide	1310-73-2	P	2 mg/m3	MX OEL
		VLE-P	2 mg/m3	NOM-010-STPS-2014
Sodium hydroxide	1310-73-2	C	2 mg/m3	ACGIH
		Ceiling	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety goggles
Face-shield

Hand protection : Wear the following personal protective equipment:
Standard glove type.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use.
Wash face, hands and any exposed skin thoroughly after handling.

SAFETY DATA SHEET

Lift III

Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye protection : No special protective equipment required.

Hand protection : No special protective equipment required.

Skin protection : No special protective equipment required.

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Color	: clear, pink	colorless
Odor	: hydrocarbon-like	hydrocarbon-like
pH	: 12,9 - 13,5, (100 %)	10,3 - 11,3
Flash point	: Not applicable, Does not sustain combustion.	
Odor Threshold	: No data available	
Melting point/freezing point	: No data available	
Initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: No data available	
Flammability (solid, gas)	: No data available	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapor pressure	: No data available	
Relative vapor density	: No data available	
Relative density	: 1,053 - 1,067	
Water solubility	: soluble	
Solubility in other solvents	: No data available	
Partition coefficient: n-octanol/water	: No data available	
Autoignition temperature	: No data available	
Thermal decomposition	: No data available	
Viscosity, kinematic	: No data available	
Explosive properties	: No data available	
Oxidizing properties	: No data available	
Molecular weight	: No data available	

SAFETY DATA SHEET

Lift III

VOC : No data available

SECTION 10. STABILITY AND REACTIVITY

Product AS SOLD

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : None known.

Incompatible materials : Acids

Hazardous decomposition products : Decomposition products may include the following materials:
Carbon oxides
Nitrogen oxides (NO_x)
Sulfur oxides
Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

SAFETY DATA SHEET

Lift III

Product AT USE DILUTION

Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Toxicity

Product AS SOLD

Product

Acute oral toxicity	: Acute toxicity estimate : > 5.000 mg/kg
Acute inhalation toxicity	: 4 h Acute toxicity estimate : > 40 mg/l
Acute dermal toxicity	: Acute toxicity estimate : > 5.000 mg/kg
Skin corrosion/irritation	: No data available
Serious eye damage/eye irritation	: No data available
Respiratory or skin sensitization	: No data available
Carcinogenicity	: No data available
Reproductive effects	: No data available
Germ cell mutagenicity	: No data available
Teratogenicity	: No data available
STOT-single exposure	: No data available
STOT-repeated exposure	: No data available
Aspiration toxicity	: No data available

SECTION 12. ECOLOGICAL INFORMATION

Product AS SOLD

Ecotoxicity

Environmental Effects	: This product has no known ecotoxicological effects.
-----------------------	---

Product

Toxicity to fish	: No data available
Toxicity to daphnia and other aquatic invertebrates	: 48 h EC50: > 120 mg/l
Toxicity to algae	: No data available

Ingredients

Toxicity to fish	: sodium dodecylbenzene sulfonate 96 h LC50: 3,2 mg/l
	poly(oxy-1,2-ethanediyl), .alpha.-isotridecyl-.omega.-hydroxy- 96 h LC50 Fish: 0,25 mg/l
	1-(2-methoxy-2-methylethoxy)-2-propanol

SAFETY DATA SHEET

Lift III

96 h LC50 Fish: > 1.000 mg/l

2-butoxyethanol
96 h LC50: 1.474 mg/l

sodium metasilicate
96 h LC50 Fish: 210 mg/l

Ingredients

Toxicity to algae : 2-butoxyethanol
72 h EC50: 911 mg/l

Persistence and degradability

Product AS SOLD

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Product AT USE DILUTION

Disposal methods : Diluted product can be flushed to sanitary sewer.

Disposal considerations : Dispose of in accordance with local, state, and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport: generally applicable for transport in Ecuador.

UN number : 1824
Description of the goods : SODIUM HYDROXIDE SOLUTION
Class : 8
Packing group : III
Environmentally hazardous : no

SAFETY DATA SHEET

Lift III

Air transport (IATA)

Contact Regulatory for air freight eligibility

Sea transport (IMDG/IMO)

UN number : 1824
Description of the goods : SODIUM HYDROXIDE SOLUTION
Class : 8
Packing group : III
Marine pollutant : no


SECTION 15. REGULATORY INFORMATION

Ecuador: Our MSDS complies with the requirements established by Ecuadorian Technical Regulation INEN 2266:2013

SECTION 16. OTHER INFORMATION

Product AS SOLD

NFPA:




HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Product AT USE DILUTION

NFPA:



HMIS III:

HEALTH	0
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 07.06.2017
Version : 1.0
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

SAFETY DATA SHEET

Lift III

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.