

XML and its validation: XML DTD, XML Schema

Web Engineering

XML Applications?

- Specialized markup languages (eg: MathML, Office Open XML)
- Communication Protocols (SOAP)
- Configuration (setup) parameters
- ...

```

<math xmlns="http://www.w3.org/1998/Math/MathML" display="block">
  <munderover>
    <mo>&Sum;</mo>
    <mrow>
      <mi>i</mi>
      <mo>=</mo>
      <mn>1</mn>
    </mrow>
    <mi>n</mi>
  </munderover>
  <mfenced separators=''>
    <msub>
      <mi>a</mi>
      <mi>i</mi>
    </msub>
  </mfenced>
</math>

```

What does it means?

$$\sum_{i=1}^n (a_i)$$



What are the elements of an XML document?

```
<?xml version='1.0' encoding='UTF-16' standalone='yes'?>
```

```
<name nickname='Shiny John'>
```

```
<first>John</first>
```

```
<!--John lost his middle name in a fire-->
```

```
<middle/>
```

```
<?nameprocessor SELECT * FROM blah?>
```

```
<last>Doe</last>
```

```
</name>
```

- XML Declaration
- Elements
- Empty elements
- Attributes
- Comments
- Processing instructions

View in <https://www.codeproject.com/Articles/845/Beginning-XML-Chapter-2-Well-Formed-XML>

Rules for Elements

- Every start-tag must have a matching end-tag
- Tags can't overlap
- XML documents can have only one root element
- Element names must obey XML naming conventions
 - Element names must start with a letter or underscore
 - Element names cannot start with the letters xml (or XML, or Xml, etc.)
 - Element names can contain letters, digits, hyphens, underscores, and periods
 - Element names cannot contain spaces
- XML is case-sensitive
- XML will keep white space in your text



- What determines that an XML document is well formed?
- Are all well formed documents valid? Why?
- Are all valid documents well formed? Why?

Is this XML document well formed?

YES

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<note>
<to>Tove</to>
<from>Jani</from>
<heading>Reminder</heading>
<body>Don't forget me this weekend!</body>
</note>
```

Is it valid?

NO

Why?

*“An XML document is **well formed** if it includes document declaration, satisfies element nesting and other syntactic constraints, and does not include undefined entities. A well-formed XML document is **valid** if it satisfies constraints as specified in the associated DTD or a Schema. Of course, only a well-formed document may be valid.”*

Is this XML document valid?

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE note SYSTEM "Note.dtd">
<note>
<to>Tove</to>
<from>Jani</from>
<heading>Reminder</heading>
<body>Don't forget me this weekend!</body>
</note>
```

Note.dtd

```
<!DOCTYPE note [
    <!ELEMENT note (to,from,heading,body)>
    <!ELEMENT to (#PCDATA)>
    <!ELEMENT from (#PCDATA)>
    <!ELEMENT heading (#PCDATA)>
    <!ELEMENT body (#PCDATA)>
]>
```



WIKIPEDIA
The Free Encyclopedia

Main page
Contents
Featured content
Current events
Random article
Donate to Wikipedia
Wikipedia store

Interaction

Help
About Wikipedia
Community portal
Recent changes
Contact page

Tools

What links here
Related changes
Upload file
Special pages
Permanent link
Page information
Wikidata item
Cite this page

Print/export

Create a book
Download as PDF
Printable version

Languages

Čeština

Not logged in [Talk](#) [Contributions](#) [Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)



Wikipedia Asian Month. Come join us.

List of XML markup languages

From Wikipedia, the free encyclopedia

For a similar list sorted by purpose, see [List of types of XML schemas](#).

This is a list of **XML markup languages**.

Contents : [A](#) · [B](#) · [C](#) · [D](#) · [E](#) · [F](#) · [G](#) · [H](#) · [I](#) · [J](#) · [K](#) · [L](#) · [M](#) · [N](#) · [O](#) · [P](#) · [Q](#) · [R](#) · [S](#) · [T](#) · [U](#) · [V](#) · [W](#) · [X](#) · [Y](#) · [Z](#)

A [edit]

- **AdsML** Markup language used for interchange of data between advertising systems.
- **Agricultural Ontology Service**
- **AIML** Markup language used for creating artificial intelligence chatterbots.
- **AnIML** Markup language used for data created by scientific analytical instruments.^[1]
- **Attention Profiling Mark-up Language** (APML): format for capturing a person's interests and dislikes
- **Atom** (standard): The *Atom Syndication Format* is a language used for [web feeds](#)
- **Automated Test Markup Language** (ATML): defines a standard exchange medium for sharing information between components of automatic test systems.
- **Attention.xml**: used for [RSS](#) and similar online subscription-tracking applications^{[2][3]}
- **aecXML**: a mark-up language which uses [Industry Foundation Classes](#) to create a vendor-neutral means to access data generated by [Building Information Modeling](#).
- **Auto-lead Data Format**: an open XML-based standard specifically for communicating consumer purchase requests to automotive dealerships.

B [edit]

- **BeerXML**: a free XML based data description standard for the exchange of brewing data ^[1]
- **Binary Format Description language**: an extension of [XSIL](#) which has added conditionals and the ability to reference files by their stream numbers, rather than by their public URLs
- **Biological Dynamics Markup Language** (BDML) is an XML format for quantitative data describing biological dynamics.

https://en.wikipedia.org/wiki/List_of_XML_markup_languages

GPS Exchange Format

Article Talk

From Wikipedia, the free encyclopedia

(Redirected from [GPS eXchange Format](#))

GPS Exchange Format (GPX) is an [XML schema](#) designed as a common [GPS](#) data format for software applications. It can be used to describe [waypoints](#), [tracks](#), and routes. It is an [open format](#)^[2] and can be used without the need to pay license fees. Location data (and optionally elevation, time, and other information) is stored in tags and can be interchanged between GPS devices and software. Common software applications for the data include viewing tracks projected onto various map sources, annotating maps, and [geotagging photographs](#) based on the time they were taken.

Data types [edit]

A GPX file's main components include [waypoints](#), [routes](#), and [tracks](#):

- A waypoint (wptType) consists of the [WGS 84](#) (GPS) coordinates of a point and possibly other descriptive information.
- A route (rteType) is an ordered list of routepoints (or waypoints representing a series of significant turn or stage points) leading to a destination.^[3] In general, a route is used to describe directions for a journey which someone wants to take at some point in the future.
- A track (trkType) contains a series of waypoints what might also contain a timestamp. It is typically used to represent journeys which somebody has already completed or recorded.

In addition to the above, GPX files can also contain additional data. The minimum properties for a GPX file are latitude and longitude for every single point. Some vendors, such as [Humminbird](#) and [Garmin](#), use extensions to the GPX format for recording street address, phone number, business category, air temperature, depth of water, and other parameters.^{[4][5]}

Just an example...

19 languages

Read Edit View

GPS Exchange

| | |
|---------------------|-------------------------------------|
| Filename extension | .gpx |
| Internet media type | applicatio stream |
| Initial release | 2002 |
| Latest release | 1.1 ^[1] August ago |
| Extended from | XML |
| Open format? | yes |
| Website | www. .asp |

```
<?xml version="1.0" encoding="UTF-8" standalone="yes">
<gpx xmlns="http://www.topografix.com/GPX/1/1"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:schemaLocation="http://www.topografix.com/GPX/1/1
                           http://www.topografix.com/GPX/1/1/gpx.xsd">
  <!-- Comments look like this -->
  <metadata>
    <name>Data name</name>
    <desc>Valid GPX example without special characters</desc>
    <author>
      <name>Author name</name>
    </author>
  </metadata>
  <wpt lat="52.518611" lon="13.376111">
    <ele>35.0</ele>
    <time>2011-12-31T23:59:59Z</time>
    <name>Reichstag (Berlin)</name>
    <sym>City</sym>
  </wpt>
  <wpt lat="48.208031" lon="16.358128">
    <ele>179</ele>
    <time>2011-12-31T23:59:59Z</time>
    <name>Parlament (Wien)</name>
    <sym>City</sym>
  </wpt>
  <wpt lat="46.9466" lon="7.44412">
    <time>2011-12-31T23:59:59Z</time>
    <name>Bundeshaus (Bern)</name>
    <sym>City</sym>
  </wpt>
</gpx>
```



What is the importance of the CDATA field?

Characters like "<" and "&" are illegal in XML elements.

- "<" will generate an error because the parser interprets it as the start of a new element.
- "&" will generate an error because the parser interprets it as the start of a character entity.

treated as special characters



| Symbol (name) | Escape Sequence |
|--------------------------------|-----------------|
| < (less-than) | < or < |
| > (greater-than) | > or > |
| & (ampersand) | & |
| ' (apostrophe or single quote) | ' |
| " (double-quote) | " |

What is the importance of the CDATA field?

How to represent in XML the function `matchwo`?

```
<script type="text/javascript">
```

```
function matchwo(a,b)
{
    if (a < b && a < 0) {
        return 1;
    } else {
        return 0;
    }
}
```

```
</script>
```

```
<script type="text/javascript"><![CDATA[
```

```
function matchwo(a,b)
{
    if (a < b && a < 0) {
        return 1;
    } else {
        return 0;
    }
}
```

```
]]></script>
```

*“In addition to comments, XML possesses an even stronger mechanism for hiding XML fragments—**CDATA** sections. CDATA sections exclude enclosed text from XML parsing—all text is interpreted as **character data**. It is useful for hiding document fragments that contain comments, quotes, or ‘&’ characters. (...) The only character sequence that may not occur in the CDATA section is ‘]]>’, which terminates the section.”*



What are the limitations of DTD?

“DTDs do not provide easy ways of defining constraints that go beyond element nesting and recurrence. Similarly, while it is easy to associate elements with attributes and to define basic constraints on attribute types (e.g. predefined name token constraints, or enumeration), more complex cases are often an exercise in futility. And of course, DTD is no help in trying to define semantics.”

Present a valid XML document for this DTD:

```
<!DOCTYPE note [  
    <!ELEMENT note (to,from,heading,body)>  
    <!ELEMENT to (#PCDATA)>  
    <!ELEMENT from (#PCDATA)>  
    <!ELEMENT heading (#PCDATA)>  
    <!ELEMENT body (#PCDATA)>  
>
```

```
<?xml version="1.0" encoding="ISO-8859-1"?>  
<!DOCTYPE note SYSTEM "Note.dtd">  
<note>  
<to>Tove</to>  
<from>Jani</from>  
<heading>Reminder</heading>  
<body>Don't forget me this weekend!</body>  
</note>
```



Is there an alternative to DTD?

“XML Schema (...) does not have an analog in the SGML world (...) was designed as an alternative to the DTD mechanism; **it adds stronger typing and utilizes XML syntax.** XML Schema contains additional constructs that make it **a lot easier to define sophisticated constraints** (...) supports (...) **‘complex’ and ‘simple’ types.** Simple types are defined by imposing additional constraints on built-in types, while complex types are composed recursively from other complex and simple types. **Built-in types available in the XML Schema are much richer and more flexible than those available in the DTD context.** This is very important because it means that the XML Schema makes it possible to express sophisticated constraints without resorting to application logic, which must be coded using a procedural language (e.g. Java) and is much more expensive to maintain.”


XML Schema vs XML DTD ^{1/2}

- XML schemas are written in XML while DTD are derived from SGML syntax.
- XML schemas define datatypes for elements and attributes while DTD doesn't support datatypes.
- XML schemas allow support for namespaces while DTD does not.
- XML schemas define number and order of child elements, while DTD does not.

XML Schema vs XML DTD 2/2

- XML schemas can be manipulated on your own with XML DOM but it is not possible in case of DTD.
- using XML schema user need not to learn a new language but working with DTD is difficult for a user.
- XML schema provides secure data communication i.e. sender can describe the data in a way that receiver will understand, but in case of DTD data can be misunderstood by the receiver.
- XML schemas are extensible while DTD is not extensible.

XML Schema - primitive data types



XML Schema - Constraints for data types

| Restriction | Description |
|----------------|--|
| enumeration | Define a list of valid values |
| fractionDigits | Specifies the maximum number of decimal places allowed. Must be equal to or greater than zero |
| length | Specifies the exact number of characters or items allowed. Must be equal to or greater than zero |
| maxExclusive | Specifies the maximum value for numeric values (value must be less than this value) |
| maxInclusive | Specifies the maximum value for numeric values (value must be less than or equal to this value) |
| maxLength | Specifies the maximum number of characters or items allowed. Must be equal to or greater than zero |
| minExclusive | Specifies the minimum value for numeric values (value must be greater than this value) |
| minInclusive | Specifies the minimum value for numeric values (value must be greater than or equal to this value) |
| minLength | Specifies the minimum number of characters or items allowed. Must be equal to or greater than zero |
| pattern | Defines the exact sequence of characters allowed |
| totalDigits | Specifies the exact number of digits allowed. Must be greater than zero |
| whiteSpace | Specifies how empty characters (tabs, spaces and carriage returns) are handled |

XML Schema - Complex XML Elements

A complex element is an XML element that contains other elements and/or attributes.

There are four types of complex elements:

- empty elements
- elements that contain only other elements
- elements that contain text only
- elements that contain both other elements and text

```
<xs:element name="employee" type="personinfo"/>
<xs:complexType name="personinfo">
  <xs:sequence>
    <xs:element name="firstname" type="xs:string"/>
    <xs:element name="lastname" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Most common data types in XML Schema

- xs:string
- xs:decimal
- xs:integer
- xs:boolean
- xs:date
- xs:time
- ...



Are there any restrictions that can be expressed using an XML Schema but not with an DTD? Give some examples.

Elements can have default values and fixed values.

- If nothing is specified, the attribute “valid” is set to true.

```
<xs:element name="valid" type="xs:string" default="true"/>
```

- You cannot change a value that is set to “fixed”.

```
<xs:element name="valid" type="xs:string" fixed="true"/>
```

Attributes may be optional or required.

```
<xs:attribute name="height" type="xs:string" use="optional"/>
```

```
<xs:attribute name="height" type="xs:string" use="required"/>
```

Restrictions

- You can specify constraints for the values of elements or attributes.

Example: The value of the “maximum_speed” element must be between 50 and 120 inclusive.

```
<xs:element name="maximum_speed">
  <xs:simpleType>
    <xs:restriction base="xs:integer">
      <xs:minInclusive value="50"/>
      <xs:maxInclusive value="120"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

Restrictions (cont.)

- Values can be restricted to a enumerated set.

Example: only accept values **Yes, No, Maybe.**

```
<xs:element name="answer">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:enumeration value="Yes"/>
      <xs:enumeration value="No"/>
      <xs:enumeration value="Maybe"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```


Restrictions (cont.)

- Values can be restricted by a pattern.

Example: define the "first_name" element that should only allow an uppercase letter followed by lowercase letters.

```
<xs:element name="first_name">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="[A-Z][a-z]+"
```

What would be an XML Schema for this document?



```
<?xml version="1.0" encoding="ISO-8859-1"?>  
<note xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"  
xsi:noNamespaceSchemaLocation="example.xsd">  
  <to>Tove</to>  
  <from>Jani</from>  
  <heading>Reminder</heading>  
  <body>Don't forget me this weekend!</body>  
</note>
```

```
<xs:element name="note">
```

```
  <xs:complexType>
```

```
    <xs:sequence>
```

```
      <xs:element name="to" type="xs:string"/>
```

```
      <xs:element name="from" type="xs:string"/>
```

```
      <xs:element name="heading" type="xs:string"/>
```

```
      <xs:element name="body" type="xs:string"/>
```

```
    </xs:sequence>
```

```
  </xs:complexType>
```

```
</xs:element>
```

- In XML, tags are not predefined. We have to define our tags.

Is it True?



- Define a DTD and a Schema to validate the following XML!

```
<athlete>  
<name>Mantorras</name>  
<age>44</age>  
<birthdate>1979-03-27</birthdate>  
</athlete>
```



- XML DTD

```
<athlete>  
<name>Mantorras</name>  
<age>44</age>  
<birthdate>1979-03-27</birthdate>  
</athlete>
```

```
<!ELEMENT athlete (name, age, birthdate)>  
<!ELEMENT name (#PCDATA)>  
<!ELEMENT age (#PCDATA)>  
<!ELEMENT birthdate (#PCDATA)>
```




- XML Schema

```
<athlete>  
<name>Mantorras</name>  
<age>44</age>  
<birthdate>1979-03-27</birthdate>  
</athlete>
```

```
<xs:element name="athlete">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element name="name" type="xs:string"/>  
      <xs:element name="age" type="xs:integer"/>  
      <xs:element name="birthdate" type="xs:date"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```



Bibliography



Shklar, Leon & Rosen, Rich (2009). *Web Application Architecture: Principles, Protocols and Practices*. Chichester, Reino Unido: John Wiley & Sons.


Pages: 85 to 96

Chapter 5

5.1 CoreXML

5.2 XHTML

Next class



Shklar, Leon & Rosen, Rich (2009). Web Application Architecture: Principles, Protocols and Practices. Chichester, Reino Unido: John Wiley & Sons.

Pages: 100 to 119

Chapter 5

5.3 Web Services

5.4 XSL