



You haven't any signature yet.
[Logout](#)

[Home](#) [Problems](#) [Contests](#) [Courses](#) [Ranklist](#) [Contest Results](#) [Submit](#) [Setting](#) [Status](#) [Discuss](#) [<->](#)

1240. Faulty Odometer

Total: 4128 Accepted: 2486 Rating: 3.6/5.0(25 votes)

Description

Time Limit: 1sec Memory Limit: 32MB

You are given a car odometer which displays the miles traveled as an integer. The odometer has a defect, however: it proceeds from the digit 3 to the digit 5, always skipping over the digit 4. This defect shows up in all positions (the one's, the ten's, the hundred's, etc.). For example, if the odometer displays 15339 and the car travels one mile, odometer reading changes to 15350 (instead of 15340).

Input

Each line of input contains a positive integer in the range 1..999999999 which represents an odometer reading. (Leading zeros will not appear in the input.) The end of input is indicated by a line containing a single 0. You may assume that no odometer reading will contain the digit 4.

Output

Each line of input will produce exactly one line of output, which will contain: the odometer reading from the input, a colon, one blank space, and the actual number of miles traveled by the car.

Sample Input

[Copy](#)

```
13
15
2003
2005
239
250
1399
1500
999999
0
```

Sample Output

[Copy](#)

```
13: 12
15: 13
2003: 1461
2005: 1462
239: 197
250: 198
1399: 1052
1500: 1053
999999: 531440
```

[Status](#) [Submit](#) [Source Code](#)

[MathJax]/extensions/MathZoom.js加载中

