





THE PHYSICS OF THE MULTIROTOR

ANATOMY, AERODYNAMICS, AND THE CLOSED-LOOP CONTROL OF UNMANNED AERIAL SYSTEMS

UAS (Unmanned Aircraft System)







The System vs. The Vehicle

A drone is formally classified as a UAV (Unmanned Aerial Vehicle). However, the vehicle cannot function in isolation.

The Complete Infrastructure

Aviation authorities use the term UAS (Unmanned Aircraft System) because the infrastructure—the human controller and the bi-directional radio link—is just as critical as the hardware in the sky.


Dimension	Traditional RC Aircraft 	Modern Quadcopter (Drone) 
Primary Control	Direct Mechanical Link (Radio to Servos) 	Fly-by-Wire (Radio to Microprocessor to Motors) 
Inherent Stability	Aerodynamically Stable (wants to glide) 	Mechanically Unstable (wants to crash) 
Sensory Input	Visual Line of Sight (Human eyes) 	IMU, GPS, Barometer, Obstacle Sensors 
Autonomy Level	Zero (dependent on real-time human input)	High (auto-leveling, waypoint navigation) 

While RC aircraft rely entirely on human reflexes and aerodynamic glide, modern multirotors are essentially flying computers.



The Intentional Instability Thesis


Like modern fighter jets, multirotors are deliberately designed to be aerodynamically unstable. This instability maximizes agility and rapid directional changes.






Fly-By-Wire

This extreme agility makes manual human flight impossible. Without a flight control system running complex algorithms to self-stabilize hundreds of times per second, the aircraft would instantly plummet. You do not fly a drone; you guide a computer that flies a drone.


QUADCOPTER SYSTEMS: EXPLODED VIEW SCHEMATIC




CHASSIS TYPOLOGY MATRIX

H-Frame	X-Frame	+ (Plus) Frame
		
Structural capacity. Ideal for carrying large, central payloads (cameras, batteries) with high structural resistance.	Agility and maneuverability. The most common commercial carbon-fiber frame, keeping mass perfectly centralized for rapid rotation.	Directional flight. Less common, often used for specific aerodynamic testing or acrobatic variable-pitch setups.

PROPULSION / POWER MATRIX

	Endurance	Noise	Key Advantage
Lithium-Polymer (Li-Po)	20-40 mins 	Low 	High energy discharge rate, lightweight, reliable. The absolute standard for consumer/commercial multirotors.
Internal Combustion (ICE)	Hours 	High 	Extended range and heavy lifting. Often utilizes Wankel rotary engines for high power-to-weight ratio without seizing.
Hydrogen Fuel Cell	Hours 	Low 	Merges the quiet stealth of electric with the long endurance of combustion. Zero heat signature.

REACTION TORQUE & PROPELLER TYPES



THE REACTION TORQUE PROBLEM

Newton's third law dictates that every action has an equal and opposite reaction.



When a motor spins a propeller clockwise to push air down, the aerodynamic drag pushes back on the motor counterclockwise.

THE PULLER/PUSHER SOLUTION

If all four propellers spun the same way, the entire drone would spin uncontrollably on its axis.

Multicopters solve this by alternating CW and CCW propellers, perfectly cancelling out the total reaction torque during a stable hover.

BRUSHLESS DC (BLDC) MOTOR ANATOMY & OPERATION



Electronic Switching

Unlike traditional motors, BLDC motors have no physical brushes. Instead, they rely on electronic switching to generate movement without mechanical friction.




The Role of the ESC

The Electronic Speed Controller (ESC) sends rapid pulses of current to specific coils in the stator, turning them into electromagnets in a precise sequence. This sequence constantly pulls and pushes the permanent magnets on the outer bell, causing the propeller to spin. This allows for massive torque, zero friction, and instant RPM adjustments.


AXES OF ROTATION & LIFT GENERATION

PITCH (Lateral Axis):
Tilting forward or backward.
Causes forward/reverse
translation.



ROLL (Longitudinal Axis):
Tilting left or right. Causes lateral
translation.


YAW (Vertical Axis):
Spinning horizontally like a top.
Changes heading without
altering position.




LIFT (Z-Axis):
Vertical thrust
counteracting gravity.

AERODYNAMIC STATE: LEVEL STATIONARY FLIGHT (HOVER)

TOP-DOWN VIEW



SIDE-PROFILE VIEW



LEVEL STATIONARY FLIGHT (HOVER)


The simplest aerodynamic state. All four motors spin at the exact same RPM.

BALANCED EQUILIBRIUM

The combined vertical lift perfectly matches the mass of the drone (mg). Because the diagonal pairs spin in opposite directions, the resulting reaction torque is zero, preventing the chassis from spinning.

PITCH FORWARD

(Side Profile)




DECOMPENSATING PAIRS FOR ACCELERATION

To move horizontally, the drone does not physically point its motors forward. Instead, it alters the RPM of specific pairs of motors.


ROLL RIGHT

(Rear View)



FORCE VECTOR DECOMPOSITION

By increasing thrust in the rear, the drone pitches forward. The previously vertical thrust vector now splits into two components: one supporting weight, and one pushing the drone forward.



The Genius of Yaw Control

To spin on its vertical axis without banking, the drone cannot just tilt. It must intentionally unbalance the reaction torque.

Transverse Decompensation

The flight controller dramatically increases the speed of one diagonal pair while equally decreasing the speed of the other pair. Total lift remains identical (preventing altitude loss), but the immense drag torque from the faster-spinning pair forces the entire chassis to rotate in the opposite direction.


THE BLADE ELEMENT MOMENTUM (BEM) EQUATIONS


THRUST FORCE: $F_T = C_t \rho D^4 \omega^2$

DRAG TORQUE: $Q = \frac{C_p D^5 \omega^2}{2\pi}$

THE QUADRATIC REALITY:

The physics prove that resistance and thrust are quadratic to rotational speed (ω^2). A minor adjustment in RPM by the flight controller results in an exponential change in aerodynamic force, requiring microsecond precision to prevent fatal instability.





The Interception Point

In traditional RC, the pilot's command goes directly to the actuators. In a drone, the command is merely a "suggestion."

Digital Translation

The Flight Controller intercepts the pilot's input, checks it against the current physical reality of the drone (via sensors), and issues highly modified Pulse Width Modulation (PWM) signals to the ESCs to execute the move without crashing.

The Inertial Measurement Unit (IMU):

The critical hardware that defeated multirotor instability. A single MEMS (Micro-Electromechanical Systems) chip containing three sensory organs:

1. Gyroscope:


Measures angular velocity (how fast the drone is rotating on its Pitch, Roll, and Yaw axes).

2. Accelerometer:

Measures linear acceleration and gravitational pull (which way is "down").

3. Magnetometer:

A digital compass measuring the Earth's magnetic field to hold a precise heading.






Closed-Loop PID Control:

The Flight Controller utilizes
The Flight Controller utilizes
Proportional-Integral-Derivative
(PID) control loops.

The Math of Flight:

When a gust of wind hits the drone, the IMU detects an un-commanded roll. The PID controller instantly calculates the exact mathematical inverse of that error (Matrix K Inversion) and adjusts the specific RPM (ω) of all four motors to fight the wind. This feedback loop happens hundreds of times a second.

The Flying Computer



A drone is a masterclass in systems engineering. Its physical anatomy relies on aerodynamic instability to achieve unparalleled agility. That agility is harnessed through continuous, invisible wars of reaction torque. And that torque is tamed only by a digital nervous system calculating localized physics hundreds of times per second. It is not an aircraft; it is a closed-loop control system that happens to fly.