Java

```java
class BusBooking {

  public BusBooking(int n) {

  }

  public void toggle(String seat) {

  }

  public int getTotalTime() {

  }

  public int getMinTime() {

  }
}

/**
 * Your BusBooking object will be instantiated and called as such:
 * BusBooking obj = new BusBooking(n);
 * obj.toggle(seat);
 * int param_2 = obj.getTotalTime();
 * int param_3 = obj.getMinTime();
 */
```

JavaScript

```
/**
 * @param {number} n
 */
var BusBooking = function(n) {

};

/**
 * @param {string} seat
 * @return {void}
 */
BusBooking.prototype.toggle = function(seat) {

};

/**
 * @return {number}
 */
BusBooking.prototype.getTotalTime = function() {

};

/**
 * @return {number}
 */
BusBooking.prototype.getMinTime = function() {

};

/**
```

```
 * Your BusBooking object will be instantiated and called as such:
 * var obj = new BusBooking(n)
 * obj.toggle(seat)
 * var param_2 = obj.getTotalTime()
 * var param_3 = obj.getMinTime()
 */
```

TypeScript

```
class BusBooking {
  constructor(n: number) {

  }

  toggle(seat: string): void {

  }

  getTotalTime(): number {

  }

  getMinTime(): number {

  }
}

/**
 * Your BusBooking object will be instantiated and called as such:
```

```
* var obj = new BusBooking(n)
* obj.toggle(seat)
* var param_2 = obj.getTotalTime()
* var param_3 = obj.getMinTime()
*/
```

C++

```cpp
class BusBooking {
public:
  BusBooking(int n) {

  }

  void toggle(string seat) {

  }

  int getTotalTime() {

  }

  int getMinTime() {

  }
};

/**
* Your BusBooking object will be instantiated and called as such:
* BusBooking* obj = new BusBooking(n);
```

```
* obj->toggle(seat);
* int param_2 = obj->getTotalTime();
* int param_3 = obj->getMinTime();
*/
```

C#

```
public class BusBooking {

  public BusBooking(int n) {

  }

  public void Toggle(string seat) {

  }

  public int GetTotalTime() {

  }

  public int GetMinTime() {

  }
}

/**
 * Your BusBooking object will be instantiated and called as such:
 * BusBooking obj = new BusBooking(n);
 * obj.Toggle(seat);
```

```
 * int param_2 = obj.GetTotalTime();
 * int param_3 = obj.GetMinTime();
 */
```

Kotlin

```
class BusBooking(n: Int) {

  fun toggle(seat: String) {

  }

  fun getTotalTime(): Int {

  }

  fun getMinTime(): Int {

  }

}

/**
 * Your BusBooking object will be instantiated and called as such:
 * var obj = BusBooking(n)
 * obj.toggle(seat)
 * var param_2 = obj.getTotalTime()
 * var param_3 = obj.getMinTime()
 */
```

Go

```go
type BusBooking struct {

}

func Constructor(n int) BusBooking {

}

func (this *BusBooking) Toggle(seat string)  {

}

func (this *BusBooking) GetTotalTime() int {

}

func (this *BusBooking) GetMinTime() int {

}

/**
 * Your BusBooking object will be instantiated and called as such:
 * obj := Constructor(n);
 * obj.Toggle(seat);
 * param_2 := obj.GetTotalTime();
```

```
* param_3 := obj.GetMinTime();
*/
-----------------------------------------------------------------------
```