3885. Design Event Manager

Solved

Medium Hint

You are given an initial list of events, where each event has a unique `eventId` and a `priority`.

Implement the `EventManager` class:

- `EventManager(int[][] events)` Initializes the manager with the given events, where `events[i] = [eventId_i, priority_i]`.
- `void updatePriority(int eventId, int newPriority)` Updates the priority of the **active** event with id `eventId` to `newPriority`.
- `int pollHighest()` Removes and returns the `eventId` of the **active** event with the **highest** priority. If multiple active events have the same priority, return the **smallest** `eventId` among them. If there are no active events, return -1.

An event is called **active** if it has not been removed by `pollHighest()`.

Example 1:

> **Input:**
> ["EventManager", "pollHighest", "updatePriority", "pollHighest", "pollHighest"]
> [[[[5, 7], [2, 7], [9, 4]]], [], [9, 7], [], []]
>
> **Output:**
> [null, 2, null, 5, 9]
>
> **Explanation**
>
> EventManager eventManager = new EventManager([[5,7], [2,7], [9,4]]); // Initializes the manager with three events
> eventManager.pollHighest(); // both events 5 and 2 have priority 7, so return the smaller id 2
> eventManager.updatePriority(9, 7); // event 9 now has priority 7
> eventManager.pollHighest(); // remaining highest priority events are 5 and 9, return 5
> eventManager.pollHighest(); // return 9

Example 2:

> **Input:**
> ["EventManager", "pollHighest", "pollHighest", "pollHighest"]
> [[[[4, 1], [7, 2]]], [], [], []]
>
> **Output:**
> [null, 7, 4, -1]
>
> **Explanation**
>
> EventManager eventManager = new EventManager([[4,1], [7,2]]); // Initializes the manager with two events
> eventManager.pollHighest(); // return 7
> eventManager.pollHighest(); // return 4
> eventManager.pollHighest(); // no events remain, return -1

Constraints:

- `1 <= events.length <= 10^5`
- `events[i] = [eventId, priority]`
- `1 <= eventId <= 10^9`
- `1 <= priority <= 10^9`
- All the values of `eventId` in `events` are **unique**.
- `1 <= newPriority <= 10^9`
- For every call to `updatePriority`, `eventId` refers to an **active** event.
- At most `10^5` calls in **total** will be made to `updatePriority` and `pollHighest`.

Seen this question in a real interview before? 1/5

Yes No

Accepted 26,545 /52.4K | Acceptance Rate 50.7 %

Topics

Hint 1

Hint 2

Hint 3

Discussion (28)

Copyright © 2026 LeetCode. All rights reserved.