

Java

```
class Solution {  
    public List<Integer> filterRestaurants(int[][] restaurants, int veganFriendly, int maxPrice, int maxDistance) {  
  
    }  
}
```

JavaScript

```
/**  
 * @param {number[][]} restaurants  
 * @param {number} veganFriendly  
 * @param {number} maxPrice  
 * @param {number} maxDistance  
 * @return {number[][]}  
 */  
var filterRestaurants = function(restaurants, veganFriendly, maxPrice, maxDistance) {  
  
};
```

TypeScript

```
function filterRestaurants(restaurants: number[][], veganFriendly: number, maxPrice: number, maxDistance: number): number[] {  
  
};
```

C++

```
class Solution {
public:
    vector<int> filterRestaurants(vector<vector<int>>& restaurants, int veganFriendly, int maxPrice, int maxDistance) {

    }
};
```

C#

```
public class Solution {
    public IList<int> FilterRestaurants(int[][] restaurants, int veganFriendly, int maxPrice, int maxDistance) {

    }
}
```

Kotlin

```
class Solution {
    fun filterRestaurants(restaurants: Array<IntArray>, veganFriendly: Int, maxPrice: Int, maxDistance: Int): List<Int> {

    }
}
```

Go

```
func filterRestaurants(restaurants [][]int, veganFriendly int, maxPrice int, maxDistance int) []int {

}
```
