



Day 19

Explore

Problems

Interview

Contest

Discuss



September LeetCode Challenge 2021

Premium



Description

Solution

Discuss (106)

Submissions

Java

Autocomplete



2007. Find Original Array From Doubled Array

Medium

101

17

Add to List

Share

An integer array `original` is transformed into a **doubled** array `changed` by appending **twice the value** of every element in `original`, and then randomly **shuffling** the resulting array.

Given an array `changed`, return `original` if `changed` is a **doubled** array. If `changed` is not a **doubled** array, return an empty array. The elements in `original` may be returned in **any** order.

Example 1:

Input: `changed = [1,3,4,2,6,8]`

Output: `[1,3,4]`

Explanation: One possible original array could be `[1,3,4]`:

- Twice the value of 1 is $1 * 2 = 2$.
- Twice the value of 3 is $3 * 2 = 6$.
- Twice the value of 4 is $4 * 2 = 8$.

Other original arrays could be `[4,3,1]` or `[3,1,4]`.

Example 2:

Input: `changed = [6,3,0,1]`

Output: `[]`

Explanation: `changed` is not a doubled array.

Example 3:

Input: `changed = [1]`

Output: `[]`

Explanation: `changed` is not a doubled array.

Constraints:

- $1 \leq \text{changed.length} \leq 10^5$
- $0 \leq \text{changed}[i] \leq 10^5$

Accepted 4,834

Submissions 17,936

Seen this question in a real interview before?

Yes

No

Companies

Similar Questions

Show Hint 1

Show Hint 2

Show Hint 3

```
1 class Solution {
2     public int[] findOriginalArray(int[] changed) {
3
4     }
5 }
```



2007/2014



Console

Contribute

Run Code

Submit