

3952. Maximum Total Value of Covered Indices

Solved ●

Medium



Hint

You are given an integer array `nums` of length `n` and a binary string `s` of length `n`, where `s[i] == '1'` means index `i` initially contains a **token** and `s[i] == '0'` means it does not.

You may perform the following operation any number of times:

- Choose a token currently located at index `i`, where `i > 0`, such that this token has **not** been moved before.
- Move this token from index `i` to index `i - 1`.

An index is considered **covered** if it contains a token after all moves.

Return an integer denoting the **maximum total value** of `nums` at the covered indices after optimally performing the operations.

Example 1:

Input: `nums = [9,2,6,1]`, `s = "0101"`

Output: 15

Explanation:

- Initially, indices 1 and 3 contain tokens.
- Move the token from index 3 to index 2.
- Move the token from index 1 to index 0.
- The covered indices are `[0, 2]`, so the total value is `nums[0] + nums[2] = 9 + 6 = 15`.

Example 2:

Input: `nums = [5,1,4]`, `s = "001"`

Output: 4

Explanation:

- Initially, only index 2 contains a token.
- It is optimal to leave the token at index 2.
- The covered index is `[2]`, so the total value is `nums[2] = 4`.

Example 3:

Input: `nums = [9,3,5]`, `s = "011"`

Output: 14

Explanation:

- Initially, indices 1 and 2 contain tokens.
- Move the token from index 1 to index 0.
- The covered indices are `[0, 2]`, so the total value is `nums[0] + nums[2] = 9 + 5 = 14`.

Constraints:

- `1 <= n == nums.length == s.length <= 105`
- `1 <= nums[i] <= 105`
- `s[i]` is either '0' or '1'

Seen this question in a real interview before? 1/6

Yes No

Accepted 14,585/53.7K | Acceptance Rate 27.2%

Topics



Hint 1	▼
Hint 2	▼
Hint 3	▼
Hint 4	▼
Discussion (31)	▼

Copyright © 2026 LeetCode. All rights reserved.