

Java

```
class Solution {  
    public int minMovesToCaptureTheQueen(int a, int b, int c, int d, int e, int f) {  
  
    }  
}
```

JavaScript

```
/**  
 * @param {number} a  
 * @param {number} b  
 * @param {number} c  
 * @param {number} d  
 * @param {number} e  
 * @param {number} f  
 * @return {number}  
 */  
var minMovesToCaptureTheQueen = function(a, b, c, d, e, f) {  
  
};
```

TypeScript

```
function minMovesToCaptureTheQueen(a: number, b: number, c: number, d: number, e: number, f: number): number {  
  
};
```

C++

```
class Solution {  
public:  
    int minMovesToCaptureTheQueen(int a, int b, int c, int d, int e, int f) {  
  
    }  
};  
-----
```

C#

```
public class Solution {  
    public int MinMovesToCaptureTheQueen(int a, int b, int c, int d, int e, int f) {  
  
    }  
}  
-----
```

Kotlin

```
class Solution {  
    fun minMovesToCaptureTheQueen(a: Int, b: Int, c: Int, d: Int, e: Int, f: Int): Int {  
  
    }  
}  
-----
```

Go

```
func minMovesToCaptureTheQueen(a int, b int, c int, d int, e int, f int) int {
```

}
