

LeetCode

Explore

Problems

Interview

Contest

Discuss

Store

LeetCode is hiring! Apply NOW.

Description

Solution

Discuss (191)

Submissions

i

JavaAutocomplete

i{}↺⌛↻

2161. Partition Array According to Given Pivot

Medium👍 141🗨️ 12💖 Add to List🔖 Share

You are given a **0-indexed** integer array `nums` and an integer `pivot`. Rearrange `nums` such that the following conditions are satisfied:

- Every element less than `pivot` appears **before** every element greater than `pivot`.
- Every element equal to `pivot` appears **in between** the elements less than and greater than `pivot`.
- The **relative order** of the elements less than `pivot` and the elements greater than `pivot` is maintained.
 - More formally, consider every p_i , p_j where p_i is the new position of the i^{th} element and p_j is the new position of the j^{th} element. For elements less than `pivot`, if $i < j$ and `nums[i] < pivot` and `nums[j] < pivot`, then $p_i < p_j$. Similarly for elements greater than `pivot`, if $i < j$ and `nums[i] > pivot` and `nums[j] > pivot`, then $p_i < p_j$.

Return `nums` *after the rearrangement*.

Example 1:

Input: `nums = [9,12,5,10,14,3,10]`, `pivot = 10`

Output: `[9,5,3,10,10,12,14]`

Explanation:

The elements 9, 5, and 3 are less than the pivot so they are on the left side of the array.

The elements 12 and 14 are greater than the pivot so they are on the right side of the array.

The relative ordering of the elements less than and greater than pivot is also maintained. `[9, 5, 3]` and `[12, 14]` are the respective orderings.

Example 2:

Input: `nums = [-3,4,3,2]`, `pivot = 2`

Output: `[-3,2,4,3]`

Explanation:

The element -3 is less than the pivot so it is on the left side of the array.

The elements 4 and 3 are greater than the pivot so they are on the right side of the array.

The relative ordering of the elements less than and greater than pivot is also maintained. `[-3]` and `[4, 3]` are the respective orderings.

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^6 \leq \text{nums}[i] \leq 10^6$
- `pivot` equals to an element of `nums`.

Accepted 13,632

Submissions 16,843

Seen this question in a real interview before?

YesNo

Companies

i

▼

Related Topics

▼

Similar Questions

▼

Show Hint 1

▼

Show Hint 2

▼

1

2

3

4

5

```
class Solution {
    public int[] pivotArray(int[] nums, int pivot) {
    }
}
```

Problems

Pick One

< Prev2161/2174Next >

ConsoleContribute i

Run Code

Submit

https://leetcode.com/problems/partition-array-according-to-given-pivot/

1/1