

LeetCode

Day 21

Explore

Problems

Interview

Contest

Discuss

Store

Premium

Description

Solution

Discuss (387)

Submissions

i

Java

Autocomplete

i

{ }

↺

↻

⌕

838. Push Dominoes

Medium

1125

85

Add to List

Share

There are n dominoes in a line, and we place each domino vertically upright. In the beginning, we simultaneously push some of the dominoes either to the left or to the right.

After each second, each domino that is falling to the left pushes the adjacent domino on the left. Similarly, the dominoes falling to the right push their adjacent dominoes standing on the right.

When a vertical domino has dominoes falling on it from both sides, it stays still due to the balance of the forces.

For the purposes of this question, we will consider that a falling domino expends no additional force to a falling or already fallen domino.

You are given a string `dominoes` representing the initial state where:

- `dominoes[i] = 'L'`, if the i^{th} domino has been pushed to the left,
- `dominoes[i] = 'R'`, if the i^{th} domino has been pushed to the right, and
- `dominoes[i] = '.'`, if the i^{th} domino has not been pushed.

Return *a string representing the final state*.


Example 1:

Input: dominoes = "RR.L"

Output: "RR.L"

Explanation: The first domino expends no additional force on the second domino.

Example 2:



Input: dominoes = ".L.R...LR..L.."

Output: "LL.RR.LLRRLL.."

Constraints:

- `n == dominoes.length`
- `1 <= n <= 10^5`
- `dominoes[i]` is either `'L'`, `'R'`, or `'.'`.

Accepted 39,258

Submissions 75,855

Seen this question in a real interview before?

Yes

No

Companies

Related Topics

```
1 class Solution {
2     public String pushDominoes(String dominoes) {
3     }
4 }
5
```