LeetCode Explore Problems Interview New Contest Discuss Store LeetCoding Challenge + GIVEAWAY! Premium

Description Solution Discuss (999+) Submissions

33. Search in Rotated Sorted Array

Medium 10762 782 Add to List Share

There is an integer array `nums` sorted in ascending order (with **distinct** values).

Prior to being passed to your function, `nums` is **possibly rotated** at an unknown pivot index `k` (`1 <= k < nums.length`) such that the resulting array is `[nums[k], nums[k+1], ..., nums[n-1], nums[0], nums[1], ..., nums[k-1]]` (**0-indexed**). For example, `[0,1,2,4,5,6,7]` might be rotated at pivot index `3` and become `[4,5,6,7,0,1,2]` .

Given the array `nums` **after** the possible rotation and an integer `target` , return *the index of* `target` *if it is in* `nums` *, or* `-1` *if it is not in* `nums` .

You must write an algorithm with `O(log n)` runtime complexity.

Example 1:

```
Input: nums = [4,5,6,7,0,1,2], target = 0
Output: 4
```

Example 2:

```
Input: nums = [4,5,6,7,0,1,2], target = 3
Output: -1
```

Example 3:

```
Input: nums = [1], target = 0
Output: -1
```

Constraints:

- `1 <= nums.length <= 5000`
- -10^4 <= `nums[i]` <= 10^4
- All values of `nums` are **unique**.
- `nums` is an ascending array that is possibly rotated.
- -10^4 <= `target` <= 10^4

Accepted 1,196,064 Submissions 3,231,625

Seen this question in a real interview before? Yes No

Companies

Related Topics

Similar Questions

Java Autocomplete

```java
class Solution {
    public int search(int[] nums, int target) {

    }
}
```

Problems Pick One Prev 33/2061 Next Console Contribute Run Code Submit