🚀 July LeetCoding Challenge 2021 🚀   ⭐ Premium

Description | 🔒 Solution ⊙ | 💬 Discuss (999+) | 🕐 Submissions

Java ▾   Autocomplete

```java
class Solution {
    public boolean wordBreak(String s, List<String> wordDict) {

    }
}
```

139. Word Break

Medium   👍 7356   👎 342   ♡ Add to List   ⤴ Share

Given a string `s` and a dictionary of strings `wordDict`, return `true` if `s` can be segmented into a space-separated sequence of one or more dictionary words.

Note that the same word in the dictionary may be reused multiple times in the segmentation.

Example 1:

Input: s = "leetcode", wordDict = ["leet","code"]
Output: true
Explanation: Return true because "leetcode" can be segmented as "leet code".

Example 2:

Input: s = "applepenapple", wordDict = ["apple","pen"]
Output: true
Explanation: Return true because "applepenapple" can be segmented as "apple pen apple".
Note that you are allowed to reuse a dictionary word.

Example 3:

Input: s = "catsandog", wordDict = ["cats","dog","sand","and","cat"]
Output: false

Constraints:

- `1 <= s.length <= 300`
- `1 <= wordDict.length <= 1000`
- `1 <= wordDict[i].length <= 20`
- `s` and `wordDict[i]` consist of only lowercase English letters.
- All the strings of `wordDict` are **unique**.

Accepted   812,038   Submissions   1,906,411

Seen this question in a real interview before?   Yes   No

Companies 🔒   ⌄

Related Topics   ⌄

Similar Questions   ⌄

⊟ Problems | ✕ Pick One | ‹ Prev | 1/38 | Next › | Console ▴ | Contribute ⓘ   ▶ Run Code ▴ | Submit

```java
class Solution {
    public boolean wordBreak(String s, List<String> wordDict) {

    }
}
```