

Contents

Contents	i
Software Required	iii
0.1 Bash	v
0.1.1 Required Packages and Installation Instructions	v
0.2 Python	v
0.3 Montage	v
0.4 Hotpants	vi
0.4.1 CFITSIO	vi
0.5 ESO Reflex	vii
Instructions for Use	ix
0.6 General Use	ix
0.7 Parameter files	ix
0.7.1 FRB Files	ix
0.7.2 Epoch files	ix
0.7.3 Project files	ix
0.8 FORS2 Image Processing	x
0.8.1 Downloading data	x
0.8.2 Using the pipeline	x
0.8.3 Initialisation and download	xi
0.8.4 ESO Reflex	xii
0.8.5 Further processing	xiii
0.8.6 Co-addition with Montage	xiii

0.8.7	Astrometry	xiii
	Bibliography	xv

Software Required

Software	Version	Used for	Reference
Bash ¹	4.4.19(1)	Command prompt and pipeline scripts.	
ESO Reflex ² <i>FORS Pipeline</i>	2.9.1 5.3.32 & 5.4.3	Initial reduction of FORS2 images.	(1)
ESOrer ³	3.13.1	Standard-star image reduction.	
HOTPANTS ⁴	5.1.11	Image subtraction.	(2)
Montage ⁵	6.0	Coaddition of dithered FORS2 images.	(3)
PSFEx ⁶	3.17.1	Point spread function extraction for PSF-fitting with SExtractor.	(4)
Python	3.6.7 2.7.15	Analysis and pipeline code. Running Astrometry.net client code.	
PyCharm	PC- 191.7141.48	Writing bash and Python code. Non-essential, but an excellent, fully-featured IDE.	
SExtractor ⁷	2.19.5	Extraction of source magnitudes, both for calibration and science.	(5)

¹<https://www.gnu.org/software/bash/>

²<https://www.eso.org/sci/software/esoreflex/>

³<https://www.eso.org/sci/software/cpl/esorex.html>

⁴<https://github.com/acbecker/hotpants>

⁵<http://montage.ipac.caltech.edu/>

⁶<https://www.astromatic.net/software/psfex>

⁷<https://www.astromatic.net/software/sextractor>

0.1 Bash

0.1.1 Required Packages and Installation Instructions

- jq

0.2 Python

- astropy
- matplotlib
- numpy
- pandas
- ruamel-yaml (or equivalent YAML module)

For reasons unknown, the Astrometry.net client only works well with Python 2, submitting blank fits files to the service if used with Python 3. This necessitates both versions being installed. As Python 2 comes packaged with Ubuntu by default, this shouldn't present a major obstacle.

0.3 Montage

1. Montage can be installed using the instructions here:

<http://montage.ipac.caltech.edu/docs/build.html>

2. It can also be installed by cloning the repository at:

<https://github.com/Caltech-IPAC/Montage>

- (a) You should then follow steps 4. and 5. of the instructions; for this pipeline to work, you MUST add

```
export PATH=$PATH:<Install directory>/Montage/bin to your .bashrc  
or .bash-profile.
```

0.4 Hotpants

Hotpants is used for producing the difference images, and is necessary for running the scripts in `/scripts/subtraction`.

0.4.1 CFITSIO

HOTPANTS requires CFITSIO (<https://heasarc.gsfc.nasa.gov/docs/software/fitsio/>) to work, which I had some trouble installing - the steps I took to make it work are provided here.

1. Download the CFITSIO tar from <http://heasarc.gsfc.nasa.gov/FTP/software/fitsio/c/cfitsio-3.47.tar.gz> for the specific version I used, or http://heasarc.gsfc.nasa.gov/FTP/software/fitsio/c/cfitsio_latest.tar.gz for the latest version.
2. Extract the tar file to your desired install directory. You will have to rename the extracted folder to `cfitsio`, instead of `cfitsio-x.xx`; otherwise HOTPANTS will throw an error when you try to make it.
3. Enter the extracted directory in the terminal and:

```
$ ./configure
```



```
$ make
```



```
$ sudo make install
```
4. Clone HOTPANTS from <https://github.com/acbecker/hotpants> to your desired install directory.
5. In the HOTPANTS Makefile, change the variable `CFITSIOINCDIR` to `<your-cfitsio-directory>/include` and `LIBDIR` to `<your-cfitsio-directory>/lib`, where `<your-cfitsio-directory>` is the directory to which you unpacked the CFITSIO archive.
6. From inside `<your-hotpants-directory>`:

```
$ make
```

7. Add the HOTPANTS directory to the `PATH` variable, preferably in your `.bashrc` file:

```
PATH=$PATH:<your-hotpants-directory>
```

8. If, upon running `hotpants`, you receive an error like the following:

```
hotpants: error while loading shared libraries: libcfitsio.so.8:
cannot open shared object file: No such file or directory
```

Then try this command:

```
$ export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/<your-cfitsio-path>/lib
```

And maybe add this command to your `.bashrc` for good measure.

0.5 ESO Reflex

ESO Reflex is used for initial image reduction. The steps I took in order to successfully install it are provided here, as it can be tricky.

1. Install prerequisites⁸:

```
$ sudo apt-get install g++ zlib1g-dev make gzip tar perl gawk sed
grep coreutils pkg-config
```

```
$ sudo apt-get install python-matplotlib python-wxgtk3.0 python-astropy
python-numpy libffi-dev
```

2. Install correct version of Java - I have experienced particular difficulties with this step, so it is described in detail, with special thanks to John Pritchard of ESO User Support with his help in overcoming them:

- (a) Install Java 1.8:

```
$ sudo apt-get install openjdk-8-jdk
```

- (b) You must also be sure that `esoreflex` will not use a more recent version of Java, if one is installed:

```
$ apt list --installed | grep openjdk
```

If there are only `openjdk-8` packages installed, then no problem. Otherwise, eg if `openjdk-11` packages are present, either:

- i. Remove the `openjdk-11` packages:

```
$ sudo apt-get remove openjdk-11
```

⁸http://www.eso.org/sci/software/pipelines/installation/software_prerequisites.html

- ii. OR: Set the default version of Java to java-8:

```
$ sudo update-alternatives --config java
```

3. Download the `install_esoreflex` script from ftp://ftp.eso.org/pub/dfs/reflex/install_esoreflex to the preferred installation location (it does not create its own subfolder, so it's probably a good idea to put it in an 'ESOReflex' subdirectory).

4. Make executable and execute:

```
$ chmod u+x install_esoreflex
```

```
$ ./install_esoreflex
```

5. Follow the instructions given by the script. Install at least the FORS components.
6. Add the following alias to your `.bashrc` file, replacing `<install_directory>` with the location of your installation:

```
alias esoreflex=<install_directory>/install/bin/esoreflex
```

7. It is advisable to test the pipeline using the Demo Data. Instructions for doing so are here found under the individual instrument categories in <http://www.eso.org/sci/software/pipelines/>

Instructions for Use

0.6 General Use

Each of the pipelines must be run from the bash command line. For example, to run the FORS2 pipeline on the second FRB181112 epoch, execute:

```
$ ./scripts/pipeline_fors2/0-pipeline.sh FRB181112_1
```

0.7 Parameter files

0.7.1 FRB Files

0.7.2 Epoch files

Inside the /param directory, within subdirectories labelled epochs_INSTRUMENT, is a set of parameter files for each captured epoch. These, particularly the directories, must be set for each epoch you wish to process. Use the epoch_template.yaml and epoch_template_doc files in each directory for guidance.

0.7.3 Project files

Within the /param/project is project_template.yaml. You should make a copy of this and set it up for your workspace. Use project_param_doc for guidance.

0.8 FORS2 Image Processing

0.8.1 Downloading data

The raw data must be downloaded from the ESO archive:

1. To (kind of) automate this, go to the ESO Raw Observational Data Portal (https://archive.eso.org/eso/eso_archive_main.html).
2. Find the target by searching on this screen.
3. On the results screen, check the boxes for the desired target and epoch (this pipeline here is designed for use with one target and epoch at a time). Be careful to exclude any images with Category 'ACQUISITION', as this may later cause problems.
4. Click 'Request Marked Datasets'.
5. After logging in, select the 'Instant Download' and 'Selected files + associated raw calibrations' (this is important, as the pipeline requires the calibrations to run properly), then click submit.
6. Wait for all calibration slides to appear in the file list (the page should auto-refresh when they are available), and download the provided script to the directory you wish to use for the data processing. I suggest using the format: `data/FRBXXXXXX/FORS2/MJDXXXXX/`
7. The FORS2 pipeline will use this file to download the data.

0.8.2 Using the pipeline

1. First, ensure that there is a .yaml parameter file in the `/param` directory of the project corresponding to the epoch you are processing, as described in § 0.7. Don't worry about the .json file; the pipeline will generate one automatically. The most important parameters for the initial processing are `object`, `data_dir` & `data_title`; the rest can be ignored for now.
2. You should also ensure that the project param file is set up; `top_data_dir`, `esoreflex_input_dir`, `esoreflex_output_dir`, `proj_dir` and

3. To begin the pipeline, run:

```
$ ./scripts/pipeline_fors2/0-pipeline.sh FRBXXXXXX_X <project>
```

Where `FRBXXXXXX_X` is the title of the epoch parameter file (without the `.yaml`) and `<project>` is the title of the project parameter file to use.

4. Follow the instructions given by the pipeline to run the desired scripts. See below for further information on each step.

0.8.3 Initialisation and download

`1-initial` will first download the data, and then organise it within the directory. It will also copy the data to the project's ESO Reflex directory.

1. To skip the download portion of the script, change the `skip_download` argument in the epoch's parameter file to `'true'`. This is useful if you already have the data downloaded, eg if you are re-running the script.
2. The ESO download script that you saved in § 0.8.1 will run, and ask you for your password. If you do not wish to type in your ESO password every time you run this script, you can add the following line to your `.netrc` file (found at `$HOME/.netrc`), and the ESO download script will read it automatically: `machine dataportal.eso.org login _ESOusername_ password _yourpassword_`
3. The requested files will all download automatically.
4. Once the files are downloaded, the pipeline will decompress them and organise them.
5. It will also copy the files to the project's ESO Reflex directory for further processing. The copy step can also be skipped, by setting the parameter file's `skip_copy` argument to `true`; this is useful if you are running the script for a second time, as the copying can be time-consuming.
6. At this point, you will need to use ESO Reflex to process the images before proceeding (unless you've done this previously). You may leave the script hanging while you do this. See the following section.

0.8.4 ESO Reflex

1. Open ESO Reflex:

```
$ esoreflex
```

2. Click **File, Open**. Open the folder `fors-<version>` and the file `fors_imaging.xml`.
The workflow canvas will appear in a new window.
3. Under **Setup Directories** on the main canvas, check the parameters `ROOT_DATA_DIR` and `RAW_DATA_DIR`. Within your project `.yaml` file inside `PyCRAFT/param`, `esoreflex_input_dir` will need to be somewhere within `<RAW_DATA_DIR>/reflex_input/fors/`, and `esoreflex_output_dir` should be `<ROOT_DATA_DIR>/reflex_end_products/`. If this is not the case, you may need to change them and rerun `1-initial` (with `skip_download` enabled, for speed's sake). I've encountered problems with freezing when changing these parameters within ESO Reflex, which seems to be a tad temperamental about where it looks for data - so it's just easier to change our configuration file to match.
4. A helpful option, for those not content to trust that the pipeline is running without visual feedback (a group that includes myself), is under **Tools, Animate at Runtime**. `1000 ms` is a good setting for this.
5. Click the green triangle 'Play' button in the toolbar, and the reduction pipeline will begin executing.
6. You will be asked to select the files for reduction. Select all of the files corresponding to the object/epoch you are currently reducing, or, if this is the first time through, those that have not been reduced before will already be selected. Click **Continue**.
7. ESO Reflex will hopefully do its thing. This may take some time, but it will give you feedback.
8. When the reduction is complete, a **Product Explorer** window will pop up allowing you to explore the reduction results. You can close this and find the data directly in the directory.

0.8.5 Further processing

1. You can now run `3-sort-after-esoreflex`.

0.8.6 Co-addition with Montage

0.8.7 Astrometry

1. In order to perform the astrometry steps, you will need to sign up for an account on Astrometry.net and request an API key, which can be retrieved from http://nova.astrometry.net/api_help.
2. Copy this to the `astrometry` field, in the file `keys.yaml`, within the path `/<project-path>/parameters`.
3. The scripts should now work.

Bibliography

- [1] J. C. Jacob, D. S. Katz, G. B. Berriman, J. Good, A. C. Laity, E. Deelman, C. Kesselman, G. Singh, M.-H. Su, T. A. Prince, and R. Williams. *Montage: An Astronomical Image Mosaicking Toolkit* (2010). URL <http://ascl.net/1010.036>.
- [2] A. Becker and Andrew. *HOTPANTS: High Order Transform of PSF ANd Template Subtraction* (2015). URL <http://ascl.net/1504.004>.
- [3] W. Freudling, M. Romaniello, D. M. Bramich, P. Ballester, V. Forchi, C. E. Garcia-Dablo, S. Moehler, and M. J. Neeser. *Automated data reduction workflows for astronomy*. *Astronomy & Astrophysics* **559**, 96 (2013). URL <https://www.aanda.org/articles/aa/abs/2013/11/aa22494-13/aa22494-13.html>.
- [4] E. Bertin. *Automated Morphometry with SExtractor and PSFEx*. *Astronomical Data Analysis Software and Systems XX* **442**, 435 (2011). URL <http://aspbooks.org/custom/publications/paper/442-0435.html>.
- [5] E. Bertin and S. Arnouts. *SExtractor: Software for source extraction*. *Astronomy and Astrophysics Supplement Series* **117**(2), 393 (1996). URL <http://aas.aanda.org/10.1051/aas:1996164>.