

- ECOSYSTEM SURVEILLANCE (AusPlots) TUTORIAL: UNDERSTANDING AND USING THE ‘ausplotsR’ PACKAGE AND AusPlots DATA
  - REQUIRED LIBRARIES
  - ACCESSING AND INSTALLING THE `ausplotsR` PACKAGE (plus its Dependencies)
  - OBTAIN & EXPLORE AusPlots DATA: `get_ausplots` function
  - MANIPULATING AusPlots DATA
  - MAP THE SITES
  - SPECIES-LEVEL DATA: `species_table` function and species occurrence matrices
    - First step: Create a species occurrence matrix
    - Species Abundance
    - Species Occurrence (Presence/Absence)
    - Species Diversity
    - Rank-Abundance Curves & Relative Abundance Models
  - PROPORTIONAL VEGETATION COVER (= FRACTIONAL COVER): `fractional_cover` function
    - Latitudinal Pattern in Proportional Vegetation Cover
    - Temporal Variation in Fractional Cover: Explore, display, and assess (for 5 sites visited twice)
  - GROWTH FORM: `growth_form_table` function (for 5 most sampled bioregions)
  - TOTAL VEGETATION COVER BY GROWTH FORM AND/OR HEIGHT: `single_cover_value` function (for 5 most sampled bioregions).
    - Subsetting by Height only
    - Subsetting by Taxonomy only
    - Subsetting by Taxonomy and Height
  - BASAL AREA (OR NUMBER OF BASAL WEDGE HITS): `basal_area` function (for 5 most sampled bioregions).

# ECOSYSTEM SURVEILLANCE (AusPlots) TUTORIAL: UNDERSTANDING AND USING THE ‘ausplotsR’ PACKAGE AND AusPlots DATA

This document contains a tutorial on how to access and use TERN’s Ecosystem Surveillance (AusPlots) data. We will explore the use of both the package ‘ausplotsR’ & the ‘ausplots’ data that can be downloaded with this package.

`ausplotsR` is an R package for live extraction and preparation of TERN AusPlots ecosystem monitoring data. Through `ausplotsR`, users can: (1) directly obtain plot-based data on vegetation and soils across Australia, and (2) preprocess these data into structures that facilitate the visualisation and analysis of `ausplots` data. Data preprocessing includes the computation of species occurrence, vegetation cover, growth form, and basal area.

In this section of the workshop we will cover the following aspects:

1. ACCESSING AND INSTALLING THE `ausplotsR` PACKAGE (plus its Dependencies).
2. OBTAIN & EXPLORE AusPlots DATA: `get_ausplots` function:
  - `get_ausplots` function
  - Explore the structure of the obtained AusPlots data.
3. MANIPULATING AusPlots DATA:
  - Find the 5 most sampled Bioregions.
  - Subset sites in the 5 most sampled Bioregions (in all DFs in the list)

#### 4. MAP THE SITES

- Obtain and prepare a map of Australia
- Plot AusPlots sites in the 5 most sampled Bioregions on the map of Australia.

#### 5. SPECIES-LEVEL DATA: `species_table` function and species occurrence matrices (for the 5 most sampled Bioregions).

- First step: Create a species occurrence matrix. Compute Species by Site table using the function `species_table`
- Species Abundance/Percent Cover:
  - Percent Cover (Abundance) by Site Visit x Species (i.e. in all 'cells')
  - Abundance (Cover %) by Species. Find and plot 4 most abundant species on a map (dot size proportional to Abundance).
- Species Occurrence (Presence/Absence):
  - Presence/Absence across all Cells (i.e. Site Visit x Species).
  - Total Presence/Absence for each Species (i.e. per data frame Column):
    - Frequencies: Absolute and Relative.
    - Calculate and Plot (histogram): Presence (Absolute and Relative) Frequencies.
- Species Diversity:
  - Calculate various indices and create a data frame with these indices.
  - Plot 2 indices: Species Richness (from vouchers, more species recorded), and Shannon Index (from veg.PI for abundances) on a map (dot size proportional to the relevant diversity metric) .
- Rank-Abundance Curves (= Whittaker Plots) & Relative Abundance Models
  - Rank-Abundance Curves for the First 5 Site-Visits
  - Possible Models of Relative Abundance for one Community
  - Rank-Abundance Curves for each Bioregion (using the Species Mean Cover)

#### 6. PROPORTIONAL VEGETATION COVER (= FRACTIONAL COVER): `'fractional_cover'` function.

- Latitudinal pattern in proportional vegetation cover (for a random subset of 200 sites).
- Temporal Variation in Fractional Cover: Explore, display, and assess (for 5 sites visited twice).

#### 7. GROWTH FORM: `growth_form_table` function (for 5 most sampled bioregions)

- Plant Growth Forms Percent Cover against Sites : Compute using `growth_form_table`
- Cluster (Hierarchical Clustering) by Plant Growth Forms Percent Cover, colour branches by bioregion.

#### 8. TOTAL VEGETATION COVER BY GROWTH FORM AND/OR HEIGHT: `single_cover_value` function (for 5 most sampled bioregions).

- Total Vegetation Cover of Any Green Vegetation  $\geq 2$ m in Height
- Total Vegetation Cover of Trees  $\geq 5$ m in Height (i.e. default arguments)
- Total Vegetation Cover of "Tussoc grass" of any Height (i.e.  $\geq 0$ m height)

#### 9. BASAL AREA (OR NUMBER OF BASAL WEDGE HITS): `basal_area` function (for 5 most sampled bioregions).

- Basal Area for each plot (m<sup>2</sup>/ha): Compute using `basal_area` .
- Display Basal Areas on map of Australia (dots size proportional to Basal Area).
- Boxplot of Basal Areas by Bioregion.

## REQUIRED LIBRARIES

To run the R scripts in this tutorial a number of R packages (and their dependencies) must be installed. In addition to `ausplotsR` , which is at the core of this tutorial, the following packages are required: `dendextend` , `ggplot2` , `goeveg` , `gridExtra` , `mapdata` , `maps` , `maptools` , `sp` , and `vegan` .

The first step to install packages in R is selecting the CRAN (Comprehensive R Archive Network) mirror. Mirror selection and package installation can be done via R's menu (Packages/Set CRAN mirror... followed by Packages/install package(s)...) or programmatically the function `install.packages` (selecting the CRAN mirror using the argument `repos`). Typically is best to choose the `cloud` mirror (which automatically redirects to an appropriate server worldwide) or a mirror close to you (e.g. in your institution, country,..). A list of Comprehensive R Archive Network (CRAN) mirror URLs can be found here (<https://cran.r-project.org/mirrors.html>).

This is how you can install and load the R packages required for this tutorial.

If you need to install any of the required packages but `ausplotsR`, which is a special case (see below), uncomment the script below.

```
## Select the repository (i.e. CRAN mirror URL)
#my.repos = "https://cloud.r-project.org/"
#my.repos = "https://cran.csiro.au/" # Example of an Australian mirror

## Install other required libraries
#install.packages(c("vegan", "goeveg", "maps", "maptools", "mapdata", "sp", "ggplot2", "gridExtra", "ggspatial", "dendextend"), repos=my.repos)
```

Now the packages can be loaded using the `library` command.

```
# Load packages
library(ausplotsR) # If not loaded above
library(vegan)
library(goeveg)

library(maps)
library(maptools)
library(mapdata)
library(sp)
library(ggplot2)
library(gridExtra)
#library(ggspatial)

library(dendextend)
```

## ACCESSING AND INSTALLING THE `ausplotsR` PACKAGE (plus its Dependencies)

Currently `ausplotsR` must be installed directly from github using the 'devtools' package, which must have been previously installed. The GitHub site for `ausplotsR` contains the latest developments and information on the package; it can be found in this link (<https://github.com/ternaustralia/ausplotsR>).

```
## Install directly from github using the 'devtools' package
## Thus, 'devtools' must be previously installed
install.packages("devtools", repos="https://cloud.r-project.org/")
```

```
## package 'devtools' successfully unpacked and MD5 sums checked
##
## The downloaded binary packages are in
## C:\Users\uqbbblanc\AppData\Local\Temp\RtmpCusXJd\downloaded_packages
```

```
library(devtools)
install_github("ternaustralia/ausplotsR", build_vignettes = TRUE)

## Load the package
library(ausplotsR)

## Obtaining Help and Initial Steps
help(ausplotsR)
browseVignettes(package="ausplotsR")
```

## OBTAIN & EXPLORE AusPlots DATA: `get_ausplots` function

This function extracts and compiles AusPlots data.

Data of specific types, sites, geographical locations, and/or species can be requested via the function arguments.

**DATA TYPES:** Up to 8 different types of data can be obtained by setting the corresponding arguments to TRUE/FALSE:

- `site_info` : Site summary data. Includes (among others): plot and visit details, landform data, geographic coordinates, and notes. Included by default.
- `structural_summaries` : Site vegetation structural summaries
- `veg.vouchers` : Complete set of species records for the plot determined by a herbarium plus ID numbers for silica-dried tissue samples. Included by default.
- `veg.PI` : Point Intercept (PI) data. Includes data on: substrate, plant species, growth form and height, etc at each of (typically) 1010 points per plot. Included by default.
- `basal.wedge` : Basal Wedge Data Raw Hits. These data are required for the calculation of Basal Area by Species by Plot.
- `soil_subsites` : Information on what soil and soil metagenomics samples were taken at nine locations across the plot and their identification barcode numbers.
- `soil_bulk_density` :
- `soil_character` : Soil characterisation and sample ID data at 10 cm increments to a depth of 1 m.

**SPATIAL FILTERING:** AusPlot data can be spatially subset via the `get_ausplots` function arguments in two ways:

- `my.Plot_IDs` : Character vector with the plots IDs of specific AusPlots plots.
- `bounding_box` : Spatial filter for selecting AusPlots based on a rectangular box, in the format of e.g. `c(xmin, xmax, ymin, ymax)`. AusPlots spatial data are in longlat, thus x is the longitude and y is the latitude of the box/extent object (e.g., `c(120, 140, -30, -10)`).

**SPECIES FILTERING:** AusPlots data can also be subset by particular or sets of genus and/or species (i.e. as determined for the herbarium voucher) using the argument `species_name_search`. This optional argument takes the form of a character string indicating the terms to search and subset. Search terms are not case sensitive and do not require an exact taxonomic match (e.g. “Eucalyptus moderata”, “Eucalyptus”, and “euca” are all acceptable search terms). If `veg.vouch=TRUE`, which is the default, `veg.vouch` will return a data frame that only includes voucher records that match the `species_name_search`.

The R object resulting from calling `get_ausplots` is a list of data frames containing the requested AusPlots data. The list includes a data frame for each type of data requested (i.e. up to 8 data frames: ‘site\_info’, ‘structural\_summaries’, ...) and an auto-generated citation for the data extracted. Please cite `ausplotsR` and the TERN AusPlots data you use. In each data frame the columns correspond to the variables supplied for each type of data and the number of rows (directly or indirectly) depends on the sites (i.e. via `my.Plot_IDs` or `bounding_box` if subsetted) or species (i.e. via `species_name_search` if subset) retrieved.

There are several variables common to all data frames. These include `site_location_name`, `site_location_visit_id`, and `site_unique` (a combination of the previous two). These variables can be used to interrelate the data frames. For example, the contents of two data frames can be combined using the common

variable as a link (i.e. guidance to add the merged contents in the correct row). We will see multiple examples of data frame contents merges later in this tutorial. The variable 'site\_unique' is typically the best option to link data frames, as it is the most specific variable representing a single visit to a particular site and it should be used in most analyses. Otherwise, errors such including data from the wrong visit to a site can occur.

```
# Example 1: All available data (i.e. all data types) for 3 plots
# =====

# Obtain the data ('site_info', 'veg.vouchers', and 'veg.PI' are retrieved by default)
AP.data = get_ausplots( my.Plot_IDs=c("SATFLB0004", "QDAMGD0022", "NTASTU0002"),
                        structural_summaries=TRUE, basal.wedge=TRUE,
                        soil_subsites=TRUE, soil_bulk_density=TRUE, soil_character=
TRUE )
```

```
## User-supplied Plot_IDs located.
```

```
# Explore retrieved data
class(AP.data)
```

```
## [1] "list"
```

```
summary(AP.data)
```

```
##           Length Class      Mode
## site.info     43   data.frame list
## struct.summ   15   data.frame list
## soil.subsites 12   data.frame list
## soil.bulk     15   data.frame list
## soil.char     34   data.frame list
## veg.basal     10   data.frame list
## veg.vouch     12   data.frame list
## veg.PI        13   data.frame list
## citation       1   -none-    character
```

```
str(AP.data)
```

```
## List of 9
## $ site.info      : 'data.frame':  4 obs. of  43 variables:
##   ..$ site_location_name      : chr [1:4] "QDAMGD0022" "SATFLB0004" "SATFLB0004" "NTASTU
0002"
##   ..$ established_date        : chr [1:4] "2013-06-04T00:00:00" "2012-09-18T00:00:00" "2
012-09-18T00:00:00" "2016-05-01T16:58:00"
##   ..$ description             : chr [1:4] "Mackunda Downs Station, 500m east of homestea
d. 26km west of Middleton." "Brachina Gorge Heysen Range Lower. 63km North North East of Ade
laide" "Brachina Gorge Heysen Range Lower. 63km North North East of Adelaide" "Maryfield Stat
ion, 7.6km north north west of homestead. 27.5km south east of Larrimah"
##   ..$ bioregion_name          : chr [1:4] "MGD" "FLB" "FLB" "STU"
##   ..$ landform_pattern        : chr [1:4] "ALP" "MOU" "MOU" "PLA"
##   ..$ landform_element        : chr [1:4] "PLA" "HSL" "HSL" "PLA"
##   ..$ site_slope              : chr [1:4] "1" "17" "17" "0"
##   ..$ site_aspect             : chr [1:4] "180" "225" "225" NA
##   ..$ comments                : chr [1:4] "Astrebla pectinata / Cenchrus ciliaris / Astr
ebla elymoides low open tussock grassland on alluvial plain adjoin"| __truncated__ "Grazing i
mpact high- goat tracks and droppings. Rabbit droppings also. Lots of Yellow footed rock wall
abies clo"| __truncated__ "Grazing impact high- goat tracks and droppings. Rabbit droppings a
lso. Lots of Yellow footed rock wallabies clo"| __truncated__ "Plot is flat. Low mound ( Like
ly anthropogenic) made up of ironstone gravels at the north west corner. Minimal "| __truncat
ed__
##   ..$ outcrop_lithology       : chr [1:4] "NA" "SA" "SA" "NA"
##   ..$ other_outcrop_lithology : chr [1:4] "NA" "NC" "NC" "NC"
##   ..$ plot_dimensions         : chr [1:4] "100m x 100m." NA NA NA
##   ..$ site_location_visit_id  : int [1:4] 53501 58658 53705 58429
##   ..$ visit_start_date        : chr [1:4] "2013-05-18T09:34:00" "2018-08-28T09:20:29" "2
012-09-18T00:00:00" "2016-05-01T16:58:00"
##   ..$ visit_end_date          : chr [1:4] "2013-05-18T09:34:00" "2018-08-28T09:20:29" "2
012-09-18T00:00:00" "2016-05-01T16:58:00"
##   ..$ visit_notes             : chr [1:4] "" NA NA "Corymbia polycarpa and Corymbia term
inalis combined for Basal area\r\n\r\nunknown substrate in point intercept "| __truncated__
##   ..$ location_description     : chr [1:4] "Mackunda Station, north of Middleton." "Brach
ina lower.Largely unchanged since previous visit possibly more Carrichtera annua. Grazing imp
act goat, rab"| __truncated__ "Brachina Gorge Heysen Range Lower. 63km North North East of Ad
elaide.Grazing impact high- goat tracks and dropp"| __truncated__ "Maryfield Station, 7.6km n
orth north west of homestead. 27.5km south east of Larimah"
##   ..$ erosion_type            : chr [1:4] "G" "n/a" "n/a" "n/a"
##   ..$ erosion_abundance       : chr [1:4] "2" "X" "1" "X"
##   ..$ erosion_state           : chr [1:4] "NC" "n/a" "n/a" "n/a"
##   ..$ microrelief             : chr [1:4] "Z" "NH" "NC" "TM"
##   ..$ drainage_type           : int [1:4] 4 3 6 4
##   ..$ disturbance             : chr [1:4] "1L" "1L" "1H" "0"
##   ..$ climatic_condition       : chr [1:4] "DRY" "DRY" "WET" "DRY"
##   ..$ vegetation_condition     : chr [1:4] "DRY" "AVG" "AVG" "AVG"
##   ..$ observer_veg            : int [1:4] 3 1 16 1
##   ..$ observer_soil           : int [1:4] 2 31 1 2
##   ..$ described_by            : int [1:4] 3 1 16 1
##   ..$ pit_marker_easting       : num [1:4] 529568 268527 268528 326265
##   ..$ pit_marker_northing      : num [1:4] 7526350 6531518 6531576 8256078
##   ..$ pit_marker_mga_zones     : int [1:4] 54 54 53 53
##   ..$ pit_marker_datum         : chr [1:4] "WGS84" "WGS84" "GDA94" "WGS84"
##   ..$ pit_marker_location_method: chr [1:4] "GPS" NA "GPS" NA
##   ..$ soil_observation_type    : chr [1:4] "P" "PA" "P" "P"
##   ..$ a_s_c                   : chr [1:4] "NC" NA NA NA
##   ..$ plot_is_100m_by_100m    : logi [1:4] TRUE TRUE TRUE TRUE
##   ..$ plot_is_aligned_to_grid  : logi [1:4] TRUE TRUE TRUE TRUE
```

```
## ..$ plot_is_permanently_marked: logi [1:4] TRUE TRUE TRUE TRUE
## ..$ latitude : num [1:4] -22.4 -31.3 -31.3 -15.8
## ..$ longitude : num [1:4] 141 139 139 133
## ..$ point : chr [1:4] "SW" "SW" "SW" "SW"
## ..$ state : chr [1:4] "QLD" "SA" "SA" "NT"
## ..$ site_unique : chr [1:4] "QDAMGD0022-53501" "SATFLB0004-58658" "SATFLB0004-53705" "NTASTU0002-58429"
## $ struct.summ : 'data.frame': 4 obs. of 15 variables:
## ..$ site_location_name : chr [1:4] "QDAMGD0022" "SATFLB0004" "NTASTU0002" "SATFLB0004"
## ..$ site_location_visit_id: int [1:4] 53501 53705 58429 58658
## ..$ phenology_comment : chr [1:4] "" "Ptilotus obovatus var. obovatus flowering. Tr
iodia sp. has no seeds. No fruit on Callitris glaucophylla - no e"| __truncated__ "NC" "NC"
## ..$ upper_1_dominant : chr [1:4] "" "SAT 000251" "NTA017194" "SAT007365"
## ..$ upper_2_dominant : chr [1:4] "" "SAT 000229" "NTA017232" "SAT007407"
## ..$ upper_3_dominant : chr [1:4] "" NA "NTA017084" "None"
## ..$ mid_1_dominant : chr [1:4] "" "SAT 000244" NA "SAT007387"
## ..$ mid_2_dominant : chr [1:4] "" "SAT 000261" NA "SAT007423"
## ..$ mid_3_dominant : chr [1:4] "" NA NA "SAT007411"
## ..$ ground_1_dominant : chr [1:4] "QDA 003325" "SAT 000233" "NTA017070" "SAT007375"
## ..$ ground_2_dominant : chr [1:4] "QDA 003293" NA "NTA017076" "SAT007353"
## ..$ ground_3_dominant : chr [1:4] "QDA 003325" NA "NTA017082" "SAT007419"
## ..$ description : chr [1:4] "Astrebla pectinata / Cenchrus ciliaris / Astrebla
elymoides low open tussock grassland with scattered ." "Callitris glaucophylla / Eucalyptus i
ntertexta low woodland. A mid-stratum dominated by Rhagodia paradoxa and H"| __truncated__ "C
orymbia terminalis mixed mid woodland with Corymbia polycarpa / Eucalyptus pruinosa/ Eucalyp
tus chlorophylla "| __truncated__ "Eucalyptus intertexta low open woodland with Callitris gl
aucophylla. A mid-storey of Rhagodia parabolica, Do"| __truncated__
## ..$ mass_flowering_event : logi [1:4] FALSE FALSE FALSE FALSE
## ..$ site_unique : chr [1:4] "QDAMGD0022-53501" "SATFLB0004-53705" "NTASTU0002-58429" "SATFLB0004-58658"
## $ soil.subsites:'data.frame': 36 obs. of 12 variables:
## ..$ site_location_name : chr [1:36] "QDAMGD0022" "QDAMGD0022" "QDAMGD0022" "QDAMGD0022" ...
## ..$ site_location_visit_id : int [1:36] 53501 53501 53501 53501 53501 53501 53501 53501 53501 53501 53705 ...
## ..$ subsite_id : chr [1:36] "1" "2" "3" "4" ...
## ..$ zone : int [1:36] 54 54 54 54 54 54 54 54 54 54 53 ...
## ..$ easting : int [1:36] 529581 529580 529582 529592 529595 529620 529664 529587 529663 268530 ...
## ..$ northing : int [1:36] 7526343 7526338 7526335 7526338 7526345 7526378 7526417 7526423 7526333 6531529 ...
## ..$ ten_to_twenty_barcode : chr [1:36] "QDA 051589" "QDA 051592" "QDA 051595" "QDA 051598" ...
## ..$ zero_to_ten_barcode : chr [1:36] "QDA 051588" "QDA 051591" "QDA 051594" "QDA 051597" ...
## ..$ twenty_to_thirty_barcode: chr [1:36] "QDA 051590" "QDA 051593" "QDA 051596" "QDA 051599" ...
## ..$ comments : chr [1:36] "bare ground" "between grass tussocks" "between grass tussocks" "bare ground" ...
## ..$ metagenomic_barcode : chr [1:36] "QDA 053721" "QDA 053722" "QDA 053723" "QDA 053724" ...
## ..$ site_unique : chr [1:36] "QDAMGD0022-53501" "QDAMGD0022-53501" "QDAMGD0022-53501" "QDAMGD0022-53501" ...
## $ soil.bulk : 'data.frame': 9 obs. of 15 variables:
## ..$ site_location_name : chr [1:9] "QDAMGD0022" "QDAMGD0022" "QDAMGD0022" "NTASTU0002" ...
## ..$ site_location_visit_id : int [1:9] 53501 53501 53501 58429 58429 58429 58658 58658
```

58658

```
## ..$ sample_id      : chr [1:9] "0" "1" "2" "0" ...
## ..$ paper_bag_weight : logi [1:9] NA NA NA NA NA NA ...
## ..$ oven_dried_weight_in_bag: logi [1:9] NA NA NA NA NA NA ...
## ..$ ring_weight     : logi [1:9] NA NA NA NA NA NA ...
## ..$ gravel_weight   : int [1:9] NA NA NA 0 0 0 NA NA NA
## ..$ ring_volume     : num [1:9] NA NA NA 209 209 ...
## ..$ gravel_volume   : int [1:9] NA NA NA 0 0 0 NA NA NA
## ..$ fine_earth_weight_in_bag: int [1:9] NA NA NA 0 0 0 0 0 0
## ..$ fine_earth_weight : int [1:9] NA NA NA 0 0 0 0 0 0
## ..$ fine_earth_volume : num [1:9] NA NA NA 209 209 ...
## ..$ fine_earth_bulk_density : int [1:9] NA NA NA 0 0 0 0 0 0
## ..$ gravel_bulk_density : int [1:9] NA NA NA 0 0 0 0 0 0
## ..$ site_unique     : chr [1:9] "QDAMGD0022-53501" "QDAMGD0022-53501" "QDAMGD002
2-53501" "NTASTU0002-58429" ...
## $ soil.char      : 'data.frame':  28 obs. of  34 variables:
## ..$ site_location_name : chr [1:28] "SATFLB0004" "QDAMGD0022" "QDAMGD0022" "QDAMGD002
2" ...
## ..$ site_location_visit_id: int [1:28] 53705 53501 53501 53501 53501 53705 53501 53705 5
3501 53501 ...
## ..$ upper_depth      : num [1:28] 0 0.5 0.8 0.6 0.7 0.1 0.3 0.6 0.2 0 ...
## ..$ lower_depth     : num [1:28] 0.1 0.6 0.9 0.7 0.8 0.2 0.4 0.7 0.3 0.1 ...
## ..$ horizon         : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ texture_grade    : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ texture_qualifier : chr [1:28] NA "NC" "NC" "NC" ...
## ..$ texture_modifier : chr [1:28] NA "NC" "NC" "NC" ...
## ..$ colour_when_moist : chr [1:28] NA "NC" "NC" "NC" ...
## ..$ colour_when_dry  : chr [1:28] NA "NC" "NC" "NC" ...
## ..$ mottles_colour   : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ mottles_abundance : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ mottles_size     : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ segregations_abundance: chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ segregations_size  : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ segregations_nature : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ segregations_form  : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ comments         : chr [1:28] NA NA NA NA ...
## ..$ collected_by     : int [1:28] 8 4 4 4 4 NA 4 NA 4 4 ...
## ..$ smallest_size_1   : chr [1:28] "11" "11" "11" "11" ...
## ..$ smallest_size_2   : logi [1:28] NA NA NA NA NA NA ...
## ..$ effervescence     : chr [1:28] "N" "N" "N" "N" ...
## ..$ ec               : num [1:28] 0.07 0.18 0.54 0.38 0.52 0.03 0.07 1.84 0.06 0.04
...
## ..$ ph              : num [1:28] 6.3 8.3 8.1 8.3 8.1 7 8 8.3 7.9 7.8 ...
## ..$ pedality_grade   : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ pedality_fabric  : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ next_size_type_2 : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ next_size_type_1 : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ smallest_size_type_2 : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ smallest_size_type_1 : chr [1:28] "NC" "NC" "NC" "NC" ...
## ..$ next_size_2      : logi [1:28] NA NA NA NA NA NA ...
## ..$ next_size_1      : chr [1:28] "11" "11" "11" "11" ...
## ..$ layer_barcode    : chr [1:28] "SAT005230" "QDA 0051583" "QDA 0051586" "QDA
0051584" ...
## ..$ site_unique     : chr [1:28] "SATFLB0004-53705" "QDAMGD0022-53501" "QDAMGD0022
-53501" "QDAMGD0022-53501" ...
## $ veg.basal      : 'data.frame':  95 obs. of  10 variables:
## ..$ site_location_name : chr [1:95] "NTASTU0002" "SATFLB0004" "SATFLB0004" "SATFLB00
04" ...
```



```
## ..$ site_location_visit_id : int [1:95] 58429 53705 53705 53705 53705 53705 53705 53705
53705 53705 ...
## ..$ site_location_id       : int [1:95] 61138 60122 60122 60122 60122 60122 60122 60122
60122 60122 ...
## ..$ point_id              : chr [1:95] "NE" "W" "SW" "SE" ...
## ..$ herbarium_determination: chr [1:95] "Dead Tree/Shrub" "Alectryon oleifolius" "Alectr
yon oleifolius" "Alectryon oleifolius" ...
## ..$ veg_barcode           : chr [1:95] "NO_BARCODE_DEAD_TREE_804159" "SAT 000242" "SAT
000242" "SAT 000242" ...
## ..$ hits                  : int [1:95] 1 1 3 4 1 1 1 20 17 6 ...
## ..$ basal_area_factor     : num [1:95] 0.1 0.25 0.5 0.5 0.5 0.25 0.5 0.25 0.5 0.5 ...
## ..$ basal_area            : num [1:95] 0.1 0.25 1.5 2 0.5 0.25 0.5 5 8.5 3 ...
## ..$ site_unique           : chr [1:95] "NTASTU0002-58429" "SATFLB0004-53705" "SATFLB000
4-53705" "SATFLB0004-53705" ...
## $ veg.vouch      : 'data.frame':  208 obs. of  12 variables:
## ..$ site_location_name    : chr [1:208] "QDAMGD0022" "QDAMGD0022" "QDAMGD0022" "QDAM
GD0022" ...
## ..$ veg_barcode          : chr [1:208] "QDA 003331" "NO_BARCODE_FORB_950413164" "N
O_BARCODE_GRASS_656236361" "NO_BARCODE_DEAD_TREE_558409020" ...
## ..$ herbarium_determination : chr [1:208] "Glinus lotoides" "Annual forb" "Annual gras
s" "Dead tree/shrub" ...
## ..$ is_uncertain_determination: logi [1:208] FALSE NA NA NA NA NA ...
## ..$ visit_start_date       : chr [1:208] "2013-05-18T09:34:00" "2013-05-18T09:34:00"
"2013-05-18T09:34:00" "2013-05-18T09:34:00" ...
## ..$ site_location_visit_id : int [1:208] 53501 53501 53501 53501 53705 53705 53705 53
705 58429 58429 ...
## ..$ primary_gen_barcode    : chr [1:208] "QDA 003332" NA NA NA ...
## ..$ secondary_gen_barcode_1 : chr [1:208] NA NA NA NA ...
## ..$ secondary_gen_barcode_2 : chr [1:208] NA NA NA NA ...
## ..$ secondary_gen_barcode_3 : chr [1:208] NA NA NA NA ...
## ..$ secondary_gen_barcode_4 : chr [1:208] NA NA NA NA ...
## ..$ site_unique           : chr [1:208] "QDAMGD0022-53501" "QDAMGD0022-53501" "QDAMG
D0022-53501" "QDAMGD0022-53501" ...
## $ veg.PI      : 'data.frame':  4323 obs. of  13 variables:
## ..$ site_location_name    : chr [1:4323] "SATFLB0004" "SATFLB0004" "SATFLB0004" "SATFLB
0004" ...
## ..$ site_location_visit_id : int [1:4323] 58658 58658 58658 58658 58658 58658 58658 5865
8 58658 58658 ...
## ..$ transect              : Factor w/ 15 levels "E2-W2","E4-W4",...: 14 14 14 14 14 14 1
4 14 14 14 ...
## ..$ point_number          : int [1:4323] 35 73 74 75 75 76 77 78 79 80 ...
## ..$ veg_barcode           : chr [1:4323] "SAT007375" "SAT007407" "SAT007407" "SAT00741
1" ...
## ..$ herbarium_determination: chr [1:4323] "Ptilotus obovatus" "Eucalyptus intertexta" "E
ucalyptus intertexta" "Cassinia laevis" ...
## ..$ substrate             : chr [1:4323] "Crypto" "Litter" "Litter" "Litter" ...
## ..$ in_canopy_sky         : logi [1:4323] FALSE FALSE FALSE FALSE FALSE FALSE ...
## ..$ dead                  : logi [1:4323] FALSE FALSE FALSE FALSE FALSE TRUE ...
## ..$ growth_form           : chr [1:4323] "Forb" "Tree/Palm" "Tree/Palm" "Shrub" ...
## ..$ height                : num [1:4323] 0.05 7 8 0.6 8 0.45 NA NA NA NA ...
## ..$ hits_unique           : chr [1:4323] "W3-E3 35" "W3-E3 73" "W3-E3 74" "W3-E3 75"
...
## ..$ site_unique           : chr [1:4323] "SATFLB0004-58658" "SATFLB0004-58658" "SATFLB0
004-58658" "SATFLB0004-58658" ...
## $ citation      : chr "TERN (2019) AusPlots ecosystem surveillance monitoring dataset (UR
L: http://aekos.org.au/collection/adelaide.ed)" | __truncated__
```

```
# Example 2: Default data for a particular Geographic Extent
# =====

# 'site_info', 'veg.vouchers', and 'veg.PI' data retrived for Brisbane (27.4698S, 153.0251E)
# and its sourrounding area
AP.data = get_ausplots(bounding_box=c(152.5, 153.5, -28, -27))

# Explore retrieved data
#class(AP.data)  # As in Example 1 (can run uncommented if curious)
summary(AP.data)
```

```
##           Length Class      Mode
## site.info  43      data.frame list
## veg.vouch  12      data.frame list
## veg.PI     13      data.frame list
## citation   1      -none-   character
```

```
#str(AP.data)  # Similar to Example 1 (can run uncommented if curious)
```

```
# Example 3: Default data + basal.wedge + structural_summaries for the genus Eucalyptus
# =====
```

```
# Default data frames ('site_info', 'veg.vouchers', and 'veg.PI') + 'basal.wedge' + structura
L_summaries data frames for the genus Eucalyptus
AP.data = get_ausplots(basal.wedge=TRUE, structural_summaries=TRUE, species_name_search="Euca
lyptus")

# Explore retrieved data
#class(AP.data)  # As in Example 1 (can run uncommented if curious)
summary(AP.data)
```

```
##           Length Class      Mode
## site.info  43      data.frame list
## struct.summ 15      data.frame list
## veg.basal   10      data.frame list
## veg.vouch  12      data.frame list
## veg.PI     13      data.frame list
## citation   1      -none-   character
```

```
#str(AP.data)  # Similar to Example 1 (can run uncommented if curious)
```

```
# Explore species contained in each data frame
head(AP.data$veg.vouch) # Filtered species: Only eucalyptus
```

```
##   site_location_name veg_barcode
## 1      NTAMGD0003   NTA018666
## 2      NTASTU0003   NTA017292
## 3      NTASTU0004   NTA017646
## 4      SASMDD0008   SAS001838
## 5      SASMDD0008   SAS001782
## 6      WAAC000022 WAA   001863
##
##           herbarium_determination is_uncertain_determination
## 1           Eucalyptus tetrodonta                FALSE
## 2           Eucalyptus patellaris                 FALSE
## 3           Eucalyptus tectifera                  FALSE
## 4 Eucalyptus camaldulensis subsp. camaldulensis    FALSE
## 5           Eucalyptus largiflorens               FALSE
## 6 Eucalyptus celastroides subsp. celastroides     FALSE
##   visit_start_date site_location_visit_id primary_gen_barcode
## 1 2016-04-28T09:38:07           58431           <NA>
## 2 2016-05-01T15:10:00           58430           NTA017293
## 3 2016-05-03T09:41:51           58426           NTA017647
## 4 2015-04-26T08:29:02           57638           SAS001839
## 5 2015-04-26T08:29:02           57638           SAS001783
## 6 2013-11-01T16:06:00           53453           WAA   001864
##   secondary_gen_barcode_1 secondary_gen_barcode_2 secondary_gen_barcode_3
## 1           <NA>           <NA>           <NA>
## 2           <NA>           <NA>           <NA>
## 3           <NA>           <NA>           <NA>
## 4           SAS001841           SAS001840           SAS001842
## 5           SAS001784           SAS001785           SAS001786
## 6           WAA   001868           WAA   001867           WAA   001866
##   secondary_gen_barcode_4   site_unique
## 1           <NA> NTAMGD0003-58431
## 2           <NA> NTASTU0003-58430
## 3           <NA> NTASTU0004-58426
## 4           <NA> SASMDD0008-57638
## 5           SAS001787 SASMDD0008-57638
## 6           WAA   001865 WAAC000022-53453
```

```
head(AP.data$veg.PI) # Unfiltered species
```

```
##  site_location_name site_location_visit_id transect point_number
## 1      SATSTP0006           58640      N3-S3           48
## 2      SATSTP0006           58640      S4-N4           49
## 3      SATSTP0006           58640      S4-N4           50
## 4      SATSTP0006           58640      S4-N4           51
## 5      SATSTP0006           58640      S4-N4           52
## 6      QDACYP0013           58598      W2-E2            0
##  veg_barcode herbarium_determination substrate in_canopy_sky dead
## 1      <NA>           <NA>      Bare           NA      NA
## 2      <NA>           <NA>      Bare           NA      NA
## 3      <NA>           <NA>      Bare           NA      NA
## 4      <NA>           <NA>      Bare           NA      NA
## 5      <NA>           <NA>      Bare           NA      NA
## 6      QDA012869      Parinari nonda      Litter      FALSE FALSE
##  growth_form height hits_unique      site_unique
## 1      <NA>      NA      N3-S3 48 SATSTP0006-58640
## 2      <NA>      NA      S4-N4 49 SATSTP0006-58640
## 3      <NA>      NA      S4-N4 50 SATSTP0006-58640
## 4      <NA>      NA      S4-N4 51 SATSTP0006-58640
## 5      <NA>      NA      S4-N4 52 SATSTP0006-58640
## 6      Shrub      0.05      W2-E2 0 QDACYP0013-58598
```

```
head(AP.data$veg.basal) # Unfiltered species
```

```
##  site_location_name site_location_visit_id site_location_id point_id
## 1      WAAC000006           53438           59857      NW
## 2      WAAC000006           53438           59857      NW
## 3      WAAC000006           53438           59857      NW
## 4      WAAC000006           53438           59857      N
## 5      WAAC000006           53438           59857      N
## 6      WAAC000006           53438           59857      N
##  herbarium_determination veg_barcode hits basal_area_factor basal_area
## 1      Eucalyptus moderata WAA 001048      1           0.1      0.10
## 2      Eucalyptus salubris WAA 001083      5           0.1      0.50
## 3      Eucalyptus salubris WAA 001093      7           0.1      0.70
## 4      Eucalyptus moderata WAA 001048      0           0.1      0.00
## 5      Eucalyptus salubris WAA 001083      2           0.1      0.15
## 6      Eucalyptus salubris WAA 001093      4           0.1      0.40
##  site_unique
## 1 WAAC000006-53438
## 2 WAAC000006-53438
## 3 WAAC000006-53438
## 4 WAAC000006-53438
## 5 WAAC000006-53438
## 6 WAAC000006-53438
```

```
head(AP.data$struct.summ) # Unfiltered species
```

```

##   site_location_name site_location_visit_id
## 1      QDAMUL0003      53595
## 2      SASMDD0002      53711
## 3      SASMDD0016      57000
## 4      NSAMDD0005      56969
## 5      QDAMUL0001      53594
## 6      NTAGFU0032      53679
##
phenology_comment
## 1  Mulga have just finished flowering but no fruit. Tussock grasses mostly dry. Dom hibisc
us in ground layer has just finished fruiting throughout the site
## 2
None
## 3
NC
## 4
NC
## 5
<NA>
## 6
Melaleuca stenostachya has finished fl
owering and with not much fruit present. Tussock grasses all dry.
##   upper_1_dominant upper_2_dominant upper_3_dominant mid_1_dominant
## 1      QDA 001428      QDA 001432      QDA 001428
## 2      SAS 000461      SAS 000463      SAS 000462      SAS 000041
## 3      SAS001764      SAS001732      None      SAS001758
## 4      NSA 010375      NSA 010439      NSA 010391      NSA 010387
## 5      QDA 001355      QDA 001363      QDA 001329      QDA 001355
## 6                                     NTA 004067
##   mid_2_dominant mid_3_dominant ground_1_dominant ground_2_dominant
## 1                                     QDA 001438      QDA 001402
## 2      SAS 000047      SAS 000049      SAS 000453      SAS 000465
## 3      None      None      SAS001770      -1
## 4      None      None      NSA 010433      NSA 010453
## 5      <NA>      <NA>      QDA 001341      <NA>
## 6      NTA 004077      NTA 004037      NTA 004021
##   ground_3_dominant
## 1
## 2      <NA>
## 3      -1
## 4      NSA 010465
## 5      <NA>
## 6
##
description
## 1      Acacia aneura var. major low open forest w
ith emergent Eucalyptus crebra x E. melanophloia. Mid stratum of juvenile Acacia aneura var.
major. Sparse ground stratum dominated by Thyridolepis xerophila with Hibiscus sturtii
## 2      Eucalyptus oleosa / Eucalyptus socialis su
bsp. socialis / Eucalyptus dumosa mixed mid open Mallee forest. Sparse mid layer of isolated
shrubs and a sparse ground layer dominated by Maireana pentatropis and Austrostipa sp.
## 3 Eucalyptus oleosa mid Mallee woodland with Eucalyptus gracilis. Mid stratum of Senna ar
temisioides subsp. coriacea and a ground stratum dominated by Zygophyllum aurantiacum subsp.
aurantiacum and mixed scattered chenopods mainly Atriplex stipitata and Maireana spp.
## 4      Eucalyptus dumosa subsp. dumosa, E. socialis and E. gracilis Mallee low
woodland (4-6m) with mixed species mid layer dominated by Eremophila longifolia (1-3m) and gr
ound layer of Enchylaena tomentosa, Zygophyllum sp. and Maireana pentatropis on dunes.
## 5      Acacia aneura var. major

```

```

wood low open forest with emergent Eucalyptus populnea and Eucalyptus melanophloia - E. white
i intergrade. Mid stratum of juvenile Acacia aneura var. major. Minimal ground stratum
## 6                                Melaleuca stenostachya tall open shrubland with
a tussock grass ground stratum of Sorghum plumosum. and Aristida holathera. Some recruitment
in the Eucalyptus pruinosa and Melaleuca stenostachya with the cohort averaging 30cm.
##  mass_flowering_event      site_unique
## 1                        FALSE QDAMUL0003-53595
## 2                        FALSE SASMDD0002-53711
## 3                        FALSE SASMDD0016-57000
## 4                        FALSE NSAMDD0005-56969
## 5                        FALSE QDAMUL0001-53594
## 6                        FALSE NTAGFU0032-53679

```

```

# Example 4: 'site_info', 'veg.PI', and 'basal.wedge' data for all sites
# =====

```

```

# Retrieve data
start.time = Sys.time()
AP.data = get_ausplots(veg.vouchers=FALSE, basal.wedge=TRUE)
end.time = Sys.time()
end.time - start.time

```

```

## Time difference of 1.025919 mins

```

```

# Explore
#class(AP.data) # As in Example 1 (can run uncommented if curious)
summary(AP.data)

```

```

##           Length Class      Mode
## site.info 43      data.frame list
## veg.basal 10      data.frame list
## veg.PI    13      data.frame list
## citation  1      -none-  character

```

```

#str(AP.data) # Similar to Example 1 (can run uncommented if curious)

```

```

# Explore 'site_info' data
dim(AP.data$site.info)

```

```

## [1] 646 43

```

```

names(AP.data$site.info)

```

```
## [1] "site_location_name"      "established_date"
## [3] "description"             "bioregion_name"
## [5] "landform_pattern"        "landform_element"
## [7] "site_slope"              "site_aspect"
## [9] "comments"                "outcrop_lithology"
## [11] "other_outcrop_lithology" "plot_dimensions"
## [13] "site_location_visit_id"  "visit_start_date"
## [15] "visit_end_date"          "visit_notes"
## [17] "location_description"    "erosion_type"
## [19] "erosion_abundance"       "erosion_state"
## [21] "microrelief"             "drainage_type"
## [23] "disturbance"             "climatic_condition"
## [25] "vegetation_condition"    "observer_veg"
## [27] "observer_soil"           "described_by"
## [29] "pit_marker_easting"      "pit_marker_northing"
## [31] "pit_marker_mga_zones"    "pit_marker_datum"
## [33] "pit_marker_location_method" "soil_observation_type"
## [35] "a_s_c"                   "plot_is_100m_by_100m"
## [37] "plot_is_aligned_to_grid"  "plot_is_permanently_marked"
## [39] "latitude"                "longitude"
## [41] "point"                   "state"
## [43] "site_unique"
```

```
head(AP.data$site.info)
```

```

##   site_location_name    established_date
## 1      WAANUL0007 2014-09-06T15:24:41
## 2      NTAFIN0031 2012-10-25T00:00:00
## 3      QDAMUL0003 2013-04-26T00:00:00
## 4      NTAFIN0004 2011-10-06T00:00:00
## 5      NTAFIN0004 2011-10-06T00:00:00
## 6      SASMDD0002 2012-09-23T00:00:00
##
##                                     description
## 1      Great Victoria Desert Nature Reserve, 102.2km south east of Tjuntjuntjara
## 2 Umbeara Station 26.5km South East of Umbeara Homestead. 11km North of SA/Not Border
## 3                                     61km SE of Issiford on Idalia NP
## 4      Top of James Range, Owen Springs Reserve . 73km South West of Alice Springs
## 5      Top of James Range, Owen Springs Reserve . 73km South West of Alice Springs
## 6      Calperum Station, 23km North West of Renmark
##   bioregion_name landform_pattern landform_element site_slope site_aspect
## 1      NUL          PLA          DDE      <NA>      <NA>
## 2      FIN          LOW          HSL      <NA>      <NA>
## 3      MUL          PLT          HSL         4       225
## 4      MAC          HIL          HCR         8       135
## 5      MAC          HIL          HCR         8       135
## 6      MDD          LON          DUN         0      <NA>
##
comments
## 1 Plot is flat but sits in a drainage depression between very low rises. Some limestone co
bbles and gravel- larger ones with cryptogam crust. Some very low limestone outcrop- almost a
t ground level. Very long unburnt but difficult to tell exactly how long. Grazing effect is l
ow- some evidence of rabbits. Introduced plant effect is moderate- Carrichtera annua common t
hroughout the site. Homogeneity- community continues another 50m north of the road which is c
lose to the northern edge of the plot. 20m to the east and 50m to the west where there is a l
ow rise. 100m to the south along the drainage line.
## 2
Slope of low hill.
## 3
<NA>
## 4
On top of the James Range. Long unburnt. Weed impact minimal. Grazing impact nil.
## 5
On top of the James Range. Long unburnt. Weed impact minimal. Grazing impact nil.
## 6
2 km. south east of the Flux tower SASMDD0001, 100m in easterly direction from track.
##   outcrop_lithology other_outcrop_lithology plot_dimensions
## 1      LI          LI    100 x 100 m.
## 2      NC          NC    100 x 100 m.
## 3      NC          NC    100 x 100 m.
## 4      SA          M    100 x 100 m.
## 5      SA          M    100 x 100 m.
## 6      NC          NC    100 x 100 m.
##   site_location_visit_id   visit_start_date   visit_end_date
## 1      56932 2014-09-07T15:24:00 2014-09-07T15:24:00
## 2      53749 2012-10-25T00:00:00 2012-10-25T00:00:00
## 3      53595 2013-04-26T00:00:00 2013-04-26T00:00:00
## 4      58010 2016-03-02T00:00:00 2016-03-02T00:00:00
## 5      53624 2011-10-06T00:00:00 2011-10-06T00:00:00
## 6      53711 2012-09-23T00:00:00 2012-09-23T00:00:00
##
visit_notes
## 1

```



```

<NA>
## 2
## 3 Acacia aneura woodland. Rising a little more to the NE corner where it becomes rockier.
Site is on Plateau above Mitchell grass downs 10km to the north. Grazing impact low- lots of
echidna diggings in the site plus kangaroos. Weed impact low. Very long unburnt- no scarring
on Ironbark or Mulga and a varied cohort with old trees and younger shrubs.
## 4
Revisit collected Point intercept, vouchered plant specimens,DNA and Metagenomic samples.
## 5
<NA>
## 6
Low Mallee woodland in dune swale with dominant species of Eucalyptus oleosa subspecies oleos
a and Eucalyptus dumosa.
##
location_description
## 1 Great Victoria Desert Nature Reserve
## 2 Umbeara Station 26.5km South East of Umbeara Homestead. 11km North of SA/Nt Border
## 3 61km SE of Issiford on Idalia NP
## 4 Owen Springs
## 5 Top of James Range, Owen Springs Reserve approximately 73km South West of Alice Springs
## 6 Mallee swale. 23km North West of Renmark
## erosion_type erosion_abundance erosion_state microrelief drainage_type
## 1 NC X NC Y 3
## 2 R 1 A NC 5
## 3 NC X NC N 4
## 4 NC NC NC NC 7
## 5 NC NC NC NC 2
## 6 NC NC NC NC 7
## disturbance climatic_condition vegetation_condition observer_veg
## 1 0 DRY FFR 18
## 2 1L DRY FFR 1
## 3 0 DRY DRY 1
## 4 NC DRY AVG 1
## 5 0 WET DRY 1
## 6 NC DRY DRY 1
## observer_soil_described_by pit_marker_easting pit_marker_northing
## 1 2 1 383287 6676768
## 2 2 1 389476 7134938
## 3 2 1 875168 7257129
## 4 11 1 NA NA
## 5 2 1 335077 7324080
## 6 2 1 462393 6236497
## pit_marker_mga_zones pit_marker_datum pit_marker_location_method
## 1 52 WGS84 GPS
## 2 53 WGS84 DGPS
## 3 55 WGS84 DGPS
## 4 53 WGS84 <NA>
## 5 53 GDA94 DGPS
## 6 54 GDA94 GPS
## soil_observation_type a_s_c plot_is_100m_by_100m
## 1 P <NA> TRUE
## 2 P 3RUCYCZARFLT TRUE
## 3 P <NA> TRUE
## 4 NC <NA> TRUE
## 5 P 3RUCYCZAIKT TRUE
## 6 P <NA> TRUE
## plot_is_aligned_to_grid plot_is_permanently_marked latitude longitude
## 1 TRUE TRUE -30.03548 127.7895
## 2 TRUE TRUE -25.89989 133.8966

```

```
## 3      TRUE      TRUE -24.75512 144.7083
## 4      TRUE      TRUE -24.18724 133.3764
## 5      TRUE      TRUE -24.18724 133.3764
## 6      TRUE      TRUE -34.01170 140.5927
## point state      site_unique
## 1  SW      WA WAANUL0007-56932
## 2  SW      NT NTAFIN0031-53749
## 3  SW      QLD QDAMUL0003-53595
## 4  SW      NT NTAFIN0004-58010
## 5  SW      NT NTAFIN0004-53624
## 6  SW      SA SASMDD0002-53711
```

```
# Explore 'veg.PI' data
dim(AP.data$veg.PI)
```

```
## [1] 712488      13
```

```
names(AP.data$veg.PI)
```

```
## [1] "site_location_name"      "site_location_visit_id"
## [3] "transect"                "point_number"
## [5] "veg_barcode"             "herbarium_determination"
## [7] "substrate"               "in_canopy_sky"
## [9] "dead"                   "growth_form"
## [11] "height"                 "hits_unique"
## [13] "site_unique"
```

```
head(AP.data$veg.PI)
```

```
## site_location_name site_location_visit_id transect point_number
## 1      QDACYP0011      58596      W3-E3      7
## 2      QDACYP0011      58596      W3-E3      7
## 3      QDACYP0011      58596      W3-E3      8
## 4      QDACYP0011      58596      W3-E3      8
## 5      QDACYP0011      58596      W3-E3      9
## 6      QDACYP0011      58596      W3-E3      9
## veg_barcode      herbarium_determination substrate
## 1      QDA012343      Corymbia clarksoniana      Litter
## 2      QDA012421 Melaleuca viridiflora var. viridiflora      Litter
## 3      QDA012343      Corymbia clarksoniana      Litter
## 4      QDA012421 Melaleuca viridiflora var. viridiflora      Litter
## 5      QDA012343      Corymbia clarksoniana      Litter
## 6      QDA012331      Eragrostis cassa      Litter
## in_canopy_sky dead      growth_form height hits_unique      site_unique
## 1      TRUE FALSE      Tree/Palm      NA      W3-E3 7 QDACYP0011-58596
## 2      FALSE FALSE      Tree/Palm      9.00      W3-E3 7 QDACYP0011-58596
## 3      FALSE FALSE      Tree/Palm      6.00      W3-E3 8 QDACYP0011-58596
## 4      FALSE FALSE      Tree/Palm      9.00      W3-E3 8 QDACYP0011-58596
## 5      FALSE FALSE      Tree/Palm      4.00      W3-E3 9 QDACYP0011-58596
## 6      FALSE FALSE      Tussock grass      0.08      W3-E3 9 QDACYP0011-58596
```

# MANIPULATING AusPlots DATA

The retrieved data by the function 'get\_ausplots' can be manipulated as any other R data. However, the 'deep' structure of the data (a list of multiple data frames) and interrelation of the data frames (via a common a common link variable) can make manipulating the data a bit more daunting.

As an example, we will focus on the sites in the 5 most sampled Bioregions. We will first identify which are these regions, and then subset the sites in these regions.

```
#-----
# Find the 5 most 'sampled' Bioregions
#-----

# Create a derived Bioregions Factor Variable in the 'site.info' DF
AP.data$site.info$bioregion.f = factor(AP.data$site.info$bioregion_name)
#names(AP.data$site.info)

# Display the Bioregions number of visits (from most visited to least visited)
sort(summary(AP.data$site.info$bioregion.f), decreasing=TRUE)
```

```
## MDD SSD FLB GFU STP PIL MGD GUP BHC COO RIV MAC CYP FIN AUA CHC NUL SYB
## 52 48 44 41 40 35 34 33 32 32 32 28 18 18 15 13 13 9
## EIU MUL BRT HAM MUR STU GVD AVW KAN SWA VIB ARP CEK DAC DMR EYB GAW GES
## 7 7 6 6 6 6 5 4 4 4 4 3 3 3 3 3 3 3
## JAF LSD MAL NSS PCK BBS COP GAS MII NAN DAB DAL ESP GSD
## 3 3 3 3 3 2 2 2 2 2 2 1 1 1 1
```

```
# Get the Names of the 5 most visited Bioregions
Bioregs.Top5.s = names(sort(summary(AP.data$site.info$bioregion.f), decreasing=TRUE)[1:5])
Bioregs.Top5.s
```

```
## [1] "MDD" "SSD" "FLB" "GFU" "STP"
```

```
#-----
# Subset data for the 5 most 'visited/sampled' Bioregions
#-----

summary(AP.data)
```

```
##           Length Class      Mode
## site.info 44      data.frame list
## veg.basal 10      data.frame list
## veg.PI    13      data.frame list
## citation  1       -none-  character
```

```
# Subset the 5 most sampled Bioregions in the 'site.info' data frame
# =====
dim(AP.data$site.info)
```

```
## [1] 646 44
```

```
AP.BioregTop5.1 = AP.data
AP.BioregTop5.1$site.info = AP.BioregTop5.1$site.info[AP.BioregTop5.1$site.info$bioregion_name %in% Bioregs.Top5.s, ]
dim(AP.BioregTop5.1$site.info)
```

```
## [1] 225 44
```

```
# Drop unused levels in the bioregion.f factor (i.e. the levels corresponding to other bioregions are dropped).
levels(AP.BioregTop5.1$site.info$bioregion.f)
```

```
## [1] "ARP" "AUA" "AVW" "BBS" "BHC" "BRT" "CEK" "CHC" "COO" "COP" "CYP"
## [12] "DAB" "DAC" "DAL" "DMR" "EIU" "ESP" "EYB" "FIN" "FLB" "GAS" "GAW"
## [23] "GES" "GFU" "GSD" "GUP" "GVD" "HAM" "JAF" "KAN" "LSD" "MAC" "MAL"
## [34] "MDD" "MGD" "MII" "MUL" "MUR" "NAN" "NSS" "NUL" "PCK" "PIL" "RIV"
## [45] "SSD" "STP" "STU" "SWA" "SYB" "VIB"
```

```
AP.BioregTop5.1$site.info$bioregion.f = droplevels(AP.BioregTop5.1$site.info$bioregion.f)
levels(AP.BioregTop5.1$site.info$bioregion.f)
```

```
## [1] "FLB" "GFU" "MDD" "SSD" "STP"
```

```
# Subset the 5 most sampled Bioregions in the 'veg.PI' data frame
# =====
# Because we are just subsetting the sites within the 5 most
# sampled bioregions, using the variable 'site_location_name'
# is enough (i.e. we don't need to use the variable 'site_unique').
dim(AP.BioregTop5.1$veg.PI)
```

```
## [1] 712488 13
```

```
AP.BioregTop5.1$veg.PI = AP.BioregTop5.1$veg.PI[AP.BioregTop5.1$veg.PI$site_location_name %in% AP.BioregTop5.1$site.info$site_location_name, ]
dim(AP.BioregTop5.1$veg.PI)
```

```
## [1] 238111 13
```

```
# Subset the 5 most sampled Bioregions in the 'veg.basal' data frame
# =====
# Because we are just subsetting the sites within the 5 most
# sampled bioregions, using the variable 'site_location_name'
# is enough (i.e. we don't need to use the variable 'site_unique').
dim(AP.BioregTop5.1$veg.basal)
```

```
## [1] 8019 10
```

```
AP.BioregTop5.l$veg.basal = AP.BioregTop5.l$veg.basal[AP.BioregTop5.l$veg.basal$site_location_name %in% AP.BioregTop5.l$site.info$site_location_name, ]
dim(AP.BioregTop5.l$veg.basal)
```

```
## [1] 2224 10
```

## MAP THE SITES

Next we visualise the sites on a map of Australia. First we graph all the Sites currently in AusPlots and then the Sites in the 5 most sampled bioregions. To do so we first obtain the map from the `maps` package and convert it to `SpatialPolygons`. Then we plot the Sites on the `SpatialPolygon` object for the map of Australia using functions in the `ggplot2` package. To differentiate among bioregions, sites are represented by different shapes and colours in the first graph, and by dots of different colours in the second one.

```
#-----
# Get and Prepare a Map of Australia
#-----

# Maps in the package 'maps' are projected in Longlat by default
aus = map("worldHires", "Australia", fill=TRUE, xlim=c(110,160),ylim=c(-45,-5), mar=c(0,0,0,0), plot=FALSE)

# Convert map data to SpatialPolygons
#aus.sp = map2SpatialPolygons(aus, IDs=aus$names, proj4string=CRS("+proj=Longlat"))
CRS("+init=epsg:4326") # More info (i.e. provides a datum)
```

```
## CRS arguments:
## +init=epsg:4326 +proj=longlat +datum=WGS84 +no_defs +ellps=WGS84
## +towgs84=0,0,0
```

```

aus.sp = map2SpatialPolygons(aus, IDs=aus$names, proj4string=CRS("+init=epsg:4326"))

#-----
# Plot ALL AusPlots Sites on a Map of Australia
#-----


# We well use 7 distinct symbol shapes to represent the AusPlots Sites (combined with
# different colors). We will cycle through the 7 symbol shapes. We start by creating a
# vector of with symbol shapes codes as long as the number of bioregions in the current
# version of the AusPlots dataset, cycling among the 7 shapes. What complicates this
# process a bit is that the number of bioregions sampled changes with time, as additional
# sites in different bioregions are sampled. Thus, we need to estimate the required number
# of cycles of symbol shapes from the data. To do this we use the function ceiling, and
# the cut back to the required number of symbol shapes as we might not need full cycles
# (i.e. the number of sites might not be a multiple of 7; e.g. 50 sites require more than
# 7 cycles, so we use 8 and then trimm the vector from 56 (7 shapes * 8 cycles) to 50.

# Preparation: Create a vector with the symbol shapes values
bioregions.cnt = length(levels(AP.data$site.info$bioregion.f))
shape.cycles.num = ceiling(bioregions.cnt / 7) # Using 7 distinct Symbol Shapes
sites.shape.values = rep(c(15:18,3:4,8),shape.cycles.num)[1:bioregions.cnt]


# Create Plot
ggplot( data=AP.data$site.info,
        aes(x = longitude, y = latitude, group=bioregion.f), alpha =0.5) +
geom_point(aes(colour=bioregion.f, fill=bioregion.f, shape=bioregion.f), size=1.5) +
scale_shape_manual(values=sites.shape.values) + # Cycle through Symbol Types
ggtitle("Locations of all AusPlots sites") +
theme(plot.title = element_text(hjust = 0.5, face="bold", size=14)) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)

```

## Locations of all AusPlots sites



```
#-----
# Plot AusPlots sites in the 5 Bioregions on Map of Australia
#-----
ggplot(data=AP.BioregTop5.1$site.info, aes(x = longitude, y = latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
  geom_point(pch=21, size=1.5) + scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
  scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
  ggtitle("Locations of sites in the 5 most sampled bioregions") +
  theme(plot.title = element_text(hjust = 0.5, face="bold", size=14)) +
  geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)
```



## SPECIES-LEVEL DATA: `species_table` function and species occurrence matrices

In this section, we will explore to how to obtain and use species occurrence data from AusPlots raw data. In particular, we will examine species cover/abundance, species presence/absence, multiple indices of species diversity, and rank-abundance plots for the sites in the 5 most sampled bioregions.

### First step: Create a species occurrence matrix

The first step to work with species-level AusPlots data is to create a species occurrence matrix. The `species_table` function in the `ausplotsR` package can be used to effortlessly create this type of matrix. This function takes a data frame of individual raw point intercept hits (i.e. a `veg.PI` data frame) generated using the `get_ausplots` function and returns a 'species against sites' matrix. Four metrics can be selected to score species occurrence:

- *Presence/Absence* (argument `m_kind = PA`).
- *Percent Cover*: Based on total frequency of hits. This is the most commonly used metric (argument `m_kind = percent_cover`).
- *Frequency*: Based on proportional frequencies of presence on the 10 individual transects within a plot (argument `m_kind = freq`). It can be a measure of importance for low cover species.
- *IVI*: A combination of cover and frequency (argument `m_kind = IVI`).

If Percent Cover or IVI are used two types of cover type can be selected:

- *Projected Foliage Cover (PFC)*: Hits scored as 'in canopy sky' are removed (argument `cover_type = PFC`).
- *Opaque Canopy Cover (OCC)*: Hits scored as 'in canopy sky' are retained (argument `cover_type = OCC`).



```
# Use function 'species_table' in 'ausplotsR' package to create an Abundance per Site Table
# =====
SppBYSites.BioregTop5 = species_table(AP.BioregTop5.l$veg.PI, m_kind="percent_cover", cover_t
ype="PFC")
class(SppBYSites.BioregTop5)
```

```
## [1] "data.frame"
```

```
dim(SppBYSites.BioregTop5) # Number of rows and columns in the matrix: Sites x Species
```

```
## [1] 219 1176
```

```
SppBYSites.BioregTop5[1:5, 1:5]
```

```
##           Abutilon.fraseri Abutilon.halophilum Abutilon.otocarpum
## NSAMDD0001-56965           0                0                0
## NSAMDD0002-56952           0                0                0
## NSAMDD0003-56968           0                0                0
## NSAMDD0004-56953           0                0                0
## NSAMDD0005-56969           0                0                0
##           Abutilon.sp. Acacia.adoxa
## NSAMDD0001-56965           0          0
## NSAMDD0002-56952           0          0
## NSAMDD0003-56968           0          0
## NSAMDD0004-56953           0          0
## NSAMDD0005-56969           0          0
```

```
# Enrich Table with: Site_Location, Bioregion, Latitude, and Longitude
# =====

# Create a 'site_unique' variable in Species by Sites Table to relate both datasets
# -----
SppBYSites.BioregTop5$site_unique = rownames(SppBYSites.BioregTop5)

# Both DF have different number of rows!
dim(SppBYSites.BioregTop5)
```

```
## [1] 219 1177
```

```
dim(AP.BioregTop5.l$site.info)
```

```
## [1] 225 44
```

```
# Enrich with: Bioregion, Latitude, and Longitude
# -----
SppBYSites.BioregTop5 = merge(SppBYSites.BioregTop5, AP.BioregTop5.1$site.info,
by="site_unique")[,c(names(SppBYSites.BioregTop5),
                        "bioregion.f", "longitude", "latitude")]
SppBYSites.BioregTop5 = na.omit(SppBYSites.BioregTop5)
#head(SppBYSites.BioregTop5)
#summary(SppBYSites.BioregTop5)
head(names(SppBYSites.BioregTop5))
```

```
## [1] "Abutilon.fraseri"      "Abutilon.halophilum" "Abutilon.otocarpum"
## [4] "Abutilon.sp."         "Acacia.adoxa"        "Acacia.alleniana"
```

## Species Abundance

In AusPlots data percent cover is used as a measure of abundance. In this section, we will examine percent cover by:

- Site visit and species: That is, all cells in the ‘Species by Sites’ table.
- Species: By computing the column totals in the ‘Species by Sites’ table.

### Percent Cover (Abundance) by Site Visit x Species

```
# Minimum and Maximum Site Visit x Species Abundance values
# -----
# '-4' because we added 4 new columns (Plot, bioregion.f, longitude, and latitude)##
range(SppBYSites.BioregTop5[,1: (dim(SppBYSites.BioregTop5)[2]-4)])
```


```
## [1] 0.00000 81.18812
```

```
# Plot Highest Site Visit x Species Abundance values
# -----
Abundance = unlist(SppBYSites.BioregTop5[,1: (dim(SppBYSites.BioregTop5)[2]-4)])
head(Abundance)
```


```
## Abutilon.fraseri1 Abutilon.fraseri2 Abutilon.fraseri3 Abutilon.fraseri4
##                0                0                0                0
## Abutilon.fraseri5 Abutilon.fraseri6
##                0                0
```

```
#Length(Abundance)
#dim(SppBYSites.BioregTop5)

# Plot the 5 Site Visits x Species combination with the Highest Abundances
par(mfrow=c(1,1))
barplot(sort(Abundance, decreasing=TRUE)[1:5], las=1, xlab="Abundance class", ylab="Frequency")
```



```
# ggplot2 graph to make it look nicer. Now we plot the 25 species-site visit covers with horizontal bars
temp.labs = names(sort(Abundance, decreasing=TRUE))
temp.Abundances = sort(Abundance, decreasing=TRUE)
temp.df = data.frame(temp.Abundances, temp.labs)
# Order factor levels so that bars are sorted by Abundance in the plot. Otherwise they would be plotted in alphabetical order
# 'rev' to plot bars in decreasing order (i.e. larger bar at top; otherwise larger bar at bottom)
temp.df$temp.labs = factor(temp.df$temp.labs, levels=rev(temp.df$temp.labs))
ggplot(data=temp.df[1:25,], aes(x=temp.labs, y=temp.Abundances)) +
  geom_bar(stat="identity", fill="steelblue") +
  geom_text(aes(label=round(temp.Abundances,2)), hjust=-0.1, size=4)+
  labs(x="Species & Site Visit", y="Abundance (Cover %)") +
  theme_minimal() + coord_flip()
```



```
# Cleaning up
rm(list=ls(pattern="temp."))
```

## Abundance (Cover %) by Species

Now we compute the percent cover of all species across the sites in the 5 most sampled bioregions. Then we find and plot on a map of Australia the 4 most Abundant species in the 5 regions (across all regions pooled together).

```
# Compute Species Total Abundance (Cover %)
# -----
TotAbundances.BioregTop5 = colSums(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)])
head(TotAbundances.BioregTop5)
```

```
##      Abutilon.fraseri Abutilon.halophilum Abutilon.otocarpum
##      0.1980198      1.3861386      2.2787055
##      Abutilon.sp.      Acacia.adoxa      Acacia.alleniana
##      0.5944519      0.4950495      1.1881188
```

```
# Species with Highest Total Abundance
# -----
# Species with Highest Total Abundance
max(TotAbundances.BioregTop5)
```

```
## [1] 321.4717
```

```
which.max(TotAbundances.BioregTop5)
```

```
## Triodia.basedowii  
##                1113
```

```
# Species with Top 4 Highest Abundances  
TotAbundances4Highest.indices =  
  which(TotAbundances.BioregTop5 >= sort(TotAbundances.BioregTop5, decreasing=T)[4],  
    arr.ind=T)  
sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices], decreasing=TRUE)
```

```
##      Triodia.basedowii      Triodia.bitextura Schizachyrium.fragile  
##              321.4717              283.4677              256.2688  
##      Triodia.pungens  
##              251.6832
```

```

# Plot 4 Species with Highest Cover in the 5 Most Sampled Bioregions
# -----

# Most Abundant Species
spp = names(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE))[1]
plot.title = paste(spp, " (total cover over the 5 bioregions = ",
                    round(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE)[1],2) , ") ", sep="")
TotAbundance.spp1 =
ggplot(data=SppBYSites.BioregTop5, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
geom_point(aes_string(size=spp), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
ggtitle(plot.title) + theme(plot.title = element_text(hjust = 0.5)) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)

# 2nd Most Abundant Species
spp = names(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE))[2]
plot.title = paste(spp, " (total cover over the 5 bioregions = ",
                    round(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE)[2],2) , ") ", sep="")
TotAbundance.spp2 =
ggplot(data=SppBYSites.BioregTop5, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
geom_point(aes_string(size=spp), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
ggtitle(plot.title) + theme(plot.title = element_text(hjust = 0.5)) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)

# 3rd Most Abundant Species
spp = names(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE))[3]
plot.title = paste(spp, " (total cover over the 5 bioregions = ",
                    round(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE)[3],2) , ") ", sep="")
TotAbundance.spp3 =
ggplot(data=SppBYSites.BioregTop5, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
geom_point(aes_string(size=spp), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
ggtitle(plot.title) + theme(plot.title = element_text(hjust = 0.5)) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)

# 4th Most Abundant Species
spp = names(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE))[4]
plot.title = paste(spp, " (total cover over the 5 bioregions = ",
                    round(sort(TotAbundances.BioregTop5[TotAbundances4Highest.indices],
decreasing=TRUE)[4],2) , ") ", sep="")
TotAbundance.spp4 =
ggplot(data=SppBYSites.BioregTop5, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +


```

```
geom_point(aes_string(size=spp), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
ggtitle(plot.title) + theme(plot.title = element_text(hjust = 0.5)) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)
```


# Plot the 4 Graphs

```
grid.arrange(TotAbundance.spp1, TotAbundance.spp2, TotAbundance.spp3, TotAbundance.spp4, nrow
=2)
```


*Triodia.basedowii* (total cover over the 5 bioregions = 321.47)




*Triodia.bitextura* (total cover over the 5 bioregions = 283.47)



*zachyrium.fragile* (total cover over the 5 bioregions = 256.27)



*Triodia.pungens* (total cover over the 5 bioregions = 251.68)



## Species Occurrence (Presence/Absence)

We next focus on species occurrence data; that is, whether a species is Present/Absent. We can compute Presence/Absence data in several ways:

- Re-use the 'percent cover' data we used above: If percent cover is > 0 then the species is present, if percent cover = 0 then the species is absent.
- Use the `species_table` function with the argument `m_kind = PA` on the data frame with raw point intercept data (i.e. `veg.PI`) generated by the function `get_auplots`.
- Use the `species_table` function with the argument `m_kind = PA` on the data frame with vegetation vouchers data (a complete set of species records for the plot determined by a herbarium; i.e. `veg.vouchers`) generated by the function `get_auplots`. This option provides the most complete species inventories by sites.

Here we use the first option for simplicity and generality (i.e. how these tasks can be performed with other abundance data outside AusPlots). As for the Abundance/Percent Cover data, we first examine species occurrence across all cells (i.e. combinations of site visits and species), and then investigate and plot the total number of (absolute and relative) occurrences for each species.

```
# Presence/Absence across all Cells (i.e. Site Visit x Species)
# =====

# Absolute Presences/Absences
# -----
# Number of Presences
sum(Abundance > 0)
```

```
## [1] 4200
```

```
# Number of Absences
sum(Abundance == 0)
```

```
## [1] 253344
```

```
# Relative (%) Presences/Absences
# -----
num.cells = (nrow(SppBYSites.BioregTop5[1:(dim(SppBYSites.BioregTop5)[1]-3)]) * ncol(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)]))
# % of Presences
sum(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)] > 0) / num.cells
```

```
## [1] 0.01630789
```

```
# % of Absences
sum(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)] == 0) / num.cells
```

```
## [1] 0.9836921
```

```
# Total Presence/Absence for each Species (i.e. per data frame Column)
# =====

# Compute number of sites where each species is present (sum by columns)
head(names(SppBYSites.BioregTop5)) # Species are in columns
```

```
## [1] "Abutilon.fraseri"      "Abutilon.halophilum" "Abutilon.otocarpum"
## [4] "Abutilon.sp."         "Acacia.adoxa"        "Acacia.alleniana"
```

```
SppPres.BioregTop5 = apply(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)]>0, 2, sum)


# Sort results in increasing order
head(sort(SppPres.BioregTop5, decreasing = TRUE))
```

```
##      Annual.forb      Annual.grass      Dead.tree.shrub
##           106              89              49
##      Sida.fibulifera  Aristida.holathera Schizachyrium.fragile
##           39              36              31
```



```
# Compute Percentage Frequencies
SppRelFreq.BioregTop5 = SppPres.BioregTop5 * 100 / nrow(SppBYSites.BioregTop5)

# Plot Species Frequencies
par(mfrow=c(1,1))
spp.freq.p1 = ggplot() + geom_histogram(aes(SppPres.BioregTop5)) +
  ggtitle("Species Sites Occurrence") +
  theme(plot.title = element_text(hjust = 0.5)) +
  xlab("Number of occurrences") + ylab("Number of species")
spp.freq.p2 = ggplot() + geom_histogram(aes(SppRelFreq.BioregTop5)) +
  ggtitle("Species Relative Frequencies") +
  theme(plot.title = element_text(hjust = 0.5)) +
  xlab("Frequency of occurrences (%)") + ylab("Number of species")
grid.arrange(spp.freq.p1, spp.freq.p2, ncol=2)
```



## Species Diversity

On our exploration of the use of Species-level AusPlots data, we now focus on Species Diversity. We first compute 7 common diversity indices, which we then place in a dataset. Finally, as an example, we plot two of these indices (Species Richness and Shanon Diversity Index) for the sites in the 5 most sampled bioregions on a map of Australia.

NOTE: Diversity indices were originally designed to be used with counts of number of individuals per species, rather than percent cover, as a measure of abundance. These indices are also used with percent cover in the literature (see Tomaszkik and Sander, 1987 for an example using coral cover). We need, however, to be aware of the different kind of answers and interpretation of the results required.

```

# Compute and place in a DF the Species Diversity Indices
# =====

# Species Richness
N0 = rowSums(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)] > 0)
# Shannon Entropy
H = diversity(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)])
# Shannon Diversity Index
N1 = exp(H)
# Simpson Diversity Index
N2 = diversity(SppBYSites.BioregTop5[,1:(dim(SppBYSites.BioregTop5)[2]-4)], "inv")
# Shannon Evenness (Hill's ratio)
E1 = N1/N0
# Simpson Evenness (Hill's ratio)
E2 = N2/N0
# Pielou Evenness
J = H/log(N0)

# Create a Data Frame with the Species Diversity Indices
SppBYSites.BioregTop.Div.df = data.frame(N0, H, N1, N2, E1, E2, J)

# Map Species Richness and Shannon Diversity Index (as an example)
# =====

# Add extra info to DataFrame (Bioregions, Longitude, and Latitude)
SppBYSites.BioregTop.Div.df$bioregion.f = SppBYSites.BioregTop5[rownames(SppBYSites.BioregTop5), "bioregion.f"]
SppBYSites.BioregTop.Div.df$longitude = SppBYSites.BioregTop5[rownames(SppBYSites.BioregTop5), "longitude"]
SppBYSites.BioregTop.Div.df$latitude = SppBYSites.BioregTop5[rownames(SppBYSites.BioregTop5), "latitude"]
summary(SppBYSites.BioregTop.Div.df)

```

```
##           N0           H           N1           N2
## Min.      : 1.00    Min.      :0.000    Min.      : 1.000    Min.      : 1.000
## 1st Qu.:13.50    1st Qu.:1.405    1st Qu.: 4.074    1st Qu.: 2.802
## Median :19.00    Median :1.800    Median : 6.050    Median : 4.153
## Mean      :19.18    Mean      :1.798    Mean      : 7.019    Mean      : 4.733
## 3rd Qu.:24.00    3rd Qu.:2.207    3rd Qu.: 9.093    3rd Qu.: 6.074
## Max.      :43.00    Max.      :3.103    Max.      :22.257    Max.      :15.240
##
##           E1           E2           J           bioregion.f
## Min.      :0.08624    Min.      :0.05508    Min.      :0.1727    FLB:42
## 1st Qu.:0.27301    1st Qu.:0.17488    1st Qu.:0.5510    GFU:41
## Median :0.36084    Median :0.23680    Median :0.6464    MDD:50
## Mean      :0.37962    Mean      :0.26661    Mean      :0.6272    SSD:46
## 3rd Qu.:0.45477    3rd Qu.:0.32006    3rd Qu.:0.7248    STP:40
## Max.      :1.00000    Max.      :1.00000    Max.      :0.9610
##
##           NA's      :1
##
## longitude      latitude
## Min.      :132.9    Min.      :-35.08
## 1st Qu.:136.1    1st Qu.: -32.79
## Median :138.2    Median : -28.21
## Mean      :138.3    Mean      :-27.19
## 3rd Qu.:139.3    3rd Qu.: -23.83
## Max.      :145.8    Max.      :-14.05
##
```

```
# Create Species Richness Plot
```

```
Div.SR =
```

```
ggplot(data=SppBYSites.BioregTop.Div.df, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
  geom_point(aes_string(size=N0), pch=21) +
  scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
  scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
  geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)
```


```
# Create Shanon Diversity Index Plot
```

```
Div.ShannonIndex =
```

```
ggplot(data=SppBYSites.BioregTop.Div.df, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
  geom_point(aes_string(size=N1), pch=21) +
  scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
  scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
  geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)
```

```
# Plot the 2 graphs
```

```
grid.arrange(Div.SR, Div.ShannonIndex, ncol=2)
```



## Rank-Abundance Curves & Relative Abundance Models

For the final example of downstream visualisation and analysis of Species-level AusPlots data, we focus on Rank-Abundance Curves (also known as Whittaker Plots). Rank-Abundance Curves provide further information on species diversity. They provide a more complete picture than a single diversity index. Their x-axis represents the abundance rank (from most to least abundant) and in the y-axis the species relative abundance. Thus, they depict both Species Richness (number of different in ranked) and Species Evenness (slope of the line that fits the rank; steep gradient indicates low evenness and a shallow gradient high evenness).


In this section we:

- We plot the Rank-Abundance Curves for the first 5 Site-Visits in our 5 most sampled bioregions dataset.
- We show a quick example of the fitting of possible Models of Relative Abundance for one Community.
- We compute the mean cover for each species in the 5 most sampled Bioregions and then plot the Rank-Abundance Curves for the 5 Bioregions.

```
par(mfrow=c(1,2))

# Rank-Abundance Curves (= Whittaker Plots) for the First 5 Site-Visits
# =====
goeveg::racurves(SppBYSites.BioregTop5[1:5,1:(dim(SppBYSites.BioregTop5)[2]-4)], bw=F)

# Possible Models of Relative Abundance for one Community
# =====
plot(vegan::radfit(round(SppBYSites.BioregTop5[1,1:(dim(SppBYSites.BioregTop5)[2]-4)], digits=0), log="xy"),
     pch=20, main="Rel. Abundance Models for Community NSAMDD0001-56965")
```



```
# Rank-Abundance Curves (= Whittaker Plots) for each Bioregion (using the Spp. Mean Cover)
# =====

# Compute Species Mean Cover for each of the 5 most sampled Bioregions
levels(SppBYSites.BioregTop5$bioregion.f)

## [1] "FLB" "GFU" "MDD" "SSD" "STP"
```

```

# GFU
SppCover.GFU.Mean = apply(SppBYSites.BioregTop5[SppBYSites.BioregTop5$bioregion.f=="GFU",1:(dim(SppBYSites.BioregTop5)[2]-4)], 2, mean)
#head(SppCover.GFU.Mean)

# MDD
SppCover.MDD.Mean = apply(SppBYSites.BioregTop5[SppBYSites.BioregTop5$bioregion.f=="MDD",1:(dim(SppBYSites.BioregTop5)[2]-4)], 2, mean)
#head(SppCover.MDD.Mean)

# PIL
SppCover.PIL.Mean = apply(SppBYSites.BioregTop5[SppBYSites.BioregTop5$bioregion.f=="PIL",1:(dim(SppBYSites.BioregTop5)[2]-4)], 2, mean)
#head(SppCover.PIL.Mean)

# SSD
SppCover.SSD.Mean = apply(SppBYSites.BioregTop5[SppBYSites.BioregTop5$bioregion.f=="SSD",1:(dim(SppBYSites.BioregTop5)[2]-4)], 2, mean)
#head(SppCover.SSD.Mean)

# STP
SppCover.STP.Mean = apply(SppBYSites.BioregTop5[SppBYSites.BioregTop5$bioregion.f=="STP",1:(dim(SppBYSites.BioregTop5)[2]-4)], 2, mean)
#head(SppCover.STP.Mean)

# Create a Matrix with Species Means per Bioregion
SppCover.BioregionMean.m = rbind(SppCover.GFU.Mean, SppCover.MDD.Mean, SppCover.PIL.Mean, SppCover.SSD.Mean, SppCover.STP.Mean)
rownames(SppCover.BioregionMean.m)

```

```


## [1] "SppCover.GFU.Mean" "SppCover.MDD.Mean" "SppCover.PIL.Mean"
## [4] "SppCover.SSD.Mean" "SppCover.STP.Mean"

```

```

# Rank-Abundance Curves (= Whittaker Plots) for the Species Cover Mean in each of the 5 Bioregions
par(mfrow=c(1,1))
goeveg::racurves(SppCover.BioregionMean.m, bw=F)

```



## PROPORTIONAL VEGETATION COVER (= FRACTIONAL COVER): 'fractional\_cover' function

Fractional Cover (FC) is the proportional cover of green vegetation, dead vegetation and bare substrate, based on plot-based point intercept data from AusPlots (as generated by 'get\_ausplots').

Cover fractions are assigned according to the following:

- 'Green' or 'photosynthetic vegetation' is living vascular plant cover.
- 'Brown' or 'non-photosynthetic vegetation' is either vascular plant cover scored as 'dead' or substrate scored as litter, coarse woody debris or cryptogam (see below) that has no other veg cover.
- 'Bare' or 'bare ground' is substrate that is rock, outcrop, gravel or bare soil with no veg cover.

A height rule is applied so that coding to green/brown/bare of the uppermost substrate/vegetation stratum hit at a given point intercept location overrides the others, that is, a dead tree overrides a living shrub beneath and vice versa; substrate coding is overridden by any vegetation cover etc. This means for each of the (usually) 1010 intercepts, there is a single coding and percentage is the number of hits assigned to each fraction, divided by the total number of PIs taken (usually 1010 but can vary) times 100.

There is an option via argument 'ground\_fractional' to calculate fractional ground cover - the same concept applied to only grasses (hummock, tussock, other); sedge; rush; forb; fern; and vine plant growth forms. Presently, cryptogam cover is excluded and included in the non-photosynthetic fraction.

'In canopy sky' is excluded by default (only the substrate is considered for those hits) and applies only to regular fractional cover (as trees are excluded in the green fraction for ground fractional cover by default).

Currently, cryptogam substrate is assigned to the non-photosynthetic fraction.

Occasionally substrate type was not collected ('NC') or could not be assigned to one of the above categories ('Unknwn'), in which case a percent cover will be returned under an 'NA' fraction if there was no veg cover above those points.

The function `fractional_cover` returns a data frame in which plots are rows, columns are fractions (bare, brown, green and NA) and values are percent cover.

In this section we will explore:

- The Latitudinal Pattern in Proportional Vegetation Cover (for a random subest of 200 sites).
- Temporal Variation in fractional cover: Explore, display, and assess (for 5 sites visited twice).

## Latitudinal Pattern in Proportional Vegetation Cover

In this section we will follow these steps:

- Call the `fractional_cover` function on the extracted point intercept data. This calculation may take a few minutes for all AusPlots, so for this example we will work with a random subset of 200 randomly drawn sites.
- Plot the Latitudinal Pattern in Proportional Vegetation Cover (here we use the 'Proportion of Bare Ground'). To do this, we first enrich the dataset with additional variables including: 'Plot' (identifier for each Site-Visit combination), 'bioregion.f', 'longitude', and 'latitude'.
- Fit a Quadratic Model to the data and examine its Fit, as there appears to be a humpbacked relationship in the previous plot (higher proportion of bare ground in the arid inland at mid-latitudes).

```
# First, we call the fractional_cover function on the extracted point intercept data.
# NOTE: Calculation may take a few minutes for all AusPlots, so for this example
# we will pull out a subset of 200 randomly drawn sites to work with.
# The sets site composition will differ each time the script is run,
# as they are random subsets.

# Compute Fractional Cover using function 'fractional_cover`
# -----
AP.200Locs.FC =
fractional_cover(AP.data$veg.PI[AP.data$veg.PI$site_location_name %in%
                                sample(AP.data$site.info$site_location_name, 200), ])
# To use the Full Data set substitute the command above by this one:
# fractional_cover(AP.data$veg.PI[AP.data$veg.PI$site_location_name %in%
#                                AP.data$site.info$site_location_name, ])
#AP.200Locs.FC = na.omit(AP.200Loc.FC)
head(AP.200Locs.FC)
```

```
##              site_unique  bare brown green NA.
## NSABHC0001-53596 NSABHC0001-53596 31.26 42.24 26.51 0.0
## NSABHC0003-53598 NSABHC0003-53598 46.57 28.14 25.29 0.0
## NSABHC0004-53599 NSABHC0004-53599 26.63 36.63 36.73 0.0
## NSABHC0008-53603 NSABHC0008-53603 37.65 30.00 32.35 0.0
## NSABHC0019-57078 NSABHC0019-57078 15.74 48.32 35.94 0.0
## NSABHC0021-57098 NSABHC0021-57098 35.35 42.57 21.98 0.1
```

```
# Enrich with: Bioregion, Latitude, and Longitude
# -----
AP.200Locs.FC = merge(AP.200Locs.FC, AP.data$site.info, by="site_unique")[,c("site_unique",
"bare", "brown", "green", "NA.", "bioregion.f", "longitude", "latitude")]
AP.200Locs.FC = na.omit(AP.200Locs.FC)
head(AP.200Locs.FC)
```



```
##      site_unique  bare brown green NA. bioregion.f longitude  latitude
## 1 NSABHC0001-53596 31.26 42.24 26.51 0.0      BHC  141.4338 -31.89335
## 2 NSABHC0003-53598 46.57 28.14 25.29 0.0      BHC  141.4340 -31.82872
## 3 NSABHC0004-53599 26.63 36.63 36.73 0.0      BHC  141.9481 -31.84728
## 4 NSABHC0008-53603 37.65 30.00 32.35 0.0      BHC  141.5288 -31.88592
## 5 NSABHC0019-57078 15.74 48.32 35.94 0.0      BHC  141.5496 -32.51485
## 6 NSABHC0021-57098 35.35 42.57 21.98 0.1      BHC  141.8683 -32.12007
```

```
summary(AP.200Locs.FC)
```


```
##  site_unique      bare      brown      green
## Length:223      Min.   : 0.10   Min.   : 3.76   Min.   : 0.10
## Class :character 1st Qu.:10.30   1st Qu.:20.89   1st Qu.:22.33
## Mode  :character Median :23.66   Median :30.79   Median :39.41
##              Mean  :28.55   Mean  :30.74   Mean  :40.55
##              3rd Qu.:43.17   3rd Qu.:40.26   3rd Qu.:54.92
##              Max.  :94.06   Max.  :66.34   Max.  :94.52
##
##      NA.      bioregion.f  longitude  latitude
## Min.   :0.0000 SSD      : 25   Min.   :114.6   Min.   : -37.40
## 1st Qu.:0.0000 MDD      : 22   1st Qu.:133.4   1st Qu.: -32.60
## Median :0.0000 FLB      : 19   Median :138.2   Median : -27.39
## Mean   :0.1557 STP      : 16   Mean   :136.1   Mean   : -26.80
## 3rd Qu.:0.0000 GFU      : 11   3rd Qu.:141.0   3rd Qu.: -23.29
## Max.   :6.6300 MAC      : 11   Max.   :151.1   Max.   : -12.22
##              (Other):119
```

```
names(AP.200Locs.FC)
```

```
## [1] "site_unique" "bare"      "brown"      "green"      "NA."
## [6] "bioregion.f" "longitude"  "latitude"
```

```
# Plot out the continental relationship between Fractional Cover
# -----
# Here we use the 'Proportion of Bare Ground' & Latitude

# Plot the relationship between Proportion of Bare Ground (with no kind of vegetation cover a
# bove) and Latitude.
par(mfrow=c(1,1))
plot(bare ~ latitude, data=AP.200Locs.FC, pch=20, bty="l")
```



```
# Quadratic LM of Continental Relationship between Bare Ground Fractional Cover & Latitude
# -----
```


```
# Fit & Examine as Quadratic Linear Model the Continental Relationship between Bare Ground Fractional Cover & Latitude
```

```
AP.200Locs.FC.lm = lm(bare ~ latitude + I(latitude^2), data=AP.200Locs.FC)
summary(AP.200Locs.FC.lm)
```

```
##
## Call:
## lm(formula = bare ~ latitude + I(latitude^2), data = AP.200Locs.FC)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -36.486 -12.251  -1.254   9.732  68.263
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -156.16953   17.71486  -8.816 3.67e-16 ***
## latitude      -15.93834    1.45066 -10.987 < 2e-16 ***
## I(latitude^2)  -0.31864    0.02839 -11.225 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 18.03 on 220 degrees of freedom
## Multiple R-squared:  0.3666, Adjusted R-squared:  0.3608
## F-statistic: 63.66 on 2 and 220 DF,  p-value: < 2.2e-16
```

```
# Predict values from Model Fit
pred.df = data.frame(latitude=seq(from=min(AP.200Locs.FC$latitude), to=max(AP.200Locs.FC$latitude), length.out=50))
pred.df$pred = predict(AP.200Locs.FC.lm, pred.df)

# Plot Predicted Values from Model Fit on Graph with Continental Relationship between Bare Ground Fractional Cover & Latitude
plot(bare ~ latitude, data=AP.200Locs.FC, pch=20, bty="n")
points(pred.df$latitude, pred.df$pred, type="l", lwd=2, col="darkblue")
```



## Temporal Variation in Fractional Cover: Explore, display, and assess (for 5 sites visited twice)

In the second section on Fractional Cover, we first Identify Sites that have been sampled more than once over time (in the 5 most sampled bioregions). Then we visually compare the Temporal Variation in Fractional Cover in these sites using Piecharts.

```
# Find Sites Sampled > 1 time
# -----
# Extract Sites Names
AP.200Locs.FC.locs = sub("\\-.*", "", AP.200Locs.FC$site_unique)
length(AP.200Locs.FC.locs)
```

```
## [1] 223
```

```
# Calculate the Sample Frequency of each Site
AP.200Locs.FC.locs.cnt = count(AP.200Locs.FC.locs)
dim(AP.200Locs.FC.locs.cnt)
```

```
## [1] 196 2
```

```
# Find Sites with > 1 Samples (in veg.IP)
```

```
AP.200Locs.FC.Resampled.locs.cnt = AP.200Locs.FC.locs.cnt[AP.200Locs.FC.locs.cnt$freq > 1,]
dim(AP.200Locs.FC.Resampled.locs.cnt)
```

```
## [1] 27 2
```

```
AP.200Locs.FC.Resampled.locs.cnt = AP.200Locs.FC.Resampled.locs.cnt$x
length(AP.200Locs.FC.Resampled.locs.cnt)
```

```
## [1] 27
```

```
# Subset the Resampled Sites (i.e. with 'freq' > 1)
```

```
# -----
```

```
# Extract AP.200Locs.FC subset for Sites with > 1 Samples (in veg.IP)
```

```
AP.200Locs.FC.Resampled.Locs = AP.200Locs.FC[(AP.200Locs.FC.locs %in% AP.200Locs.FC.Resampled.locs.cnt),]
```

```
#AP.200Locs.FC.Resampled.Locs
```

```
dim(AP.200Locs.FC.Resampled.Locs) # Number of Samples taken in re-visited sites.
```

```
## [1] 54 8
```

```
#Number of Re-visited sites is half this, as each site was sampled twice (so far).
```

```
# Add Year (Started) Sampling of Site-Visit Pair
```

```
# -----
```

```
# Need to specify 'AP.BioregTop5.l$site.info[,c("site_unique", "visit_start_date")]' to avoid  
duplicate columns
```

```
AP.200Locs.FC.Resampled.Locs = merge(AP.200Locs.FC.Resampled.Locs, AP.BioregTop5.l$site.info  
[,c("site_unique", "visit_start_date")],
```

```
by="site_unique")[,c(names(AP.200Locs.FC.Resampled.Locs),  
"visit_start_date")]  
names(AP.200Locs.FC.Resampled.Locs)
```

```
## [1] "site_unique"      "bare"             "brown"  
## [4] "green"            "NA."              "bioregion.f"  
## [7] "longitude"        "latitude"         "visit_start_date"
```

```
#AP.200Locs.FC.Resampled.Locs$visit_start_date
```

```
#substr(AP.200Locs.FC.Resampled.Locs$visit_start_date,1,4)
```

```
AP.200Locs.FC.Resampled.Locs$site_unique.Yr = paste( AP.200Locs.FC.Resampled.Locs$site_unique,  
e,
```

```
substr(AP.200Locs.FC.Resampled.Locs$visit_start_date,1,4),
```

```
sep=". " )
```

```
head(AP.200Locs.FC.Resampled.Locs$site_unique.Yr)
```

```
## [1] "QDASSD0003-56912.2014" "QDASSD0003-57623.2015" "QDASSD0005-56914.2014"
## [4] "QDASSD0005-57625.2015" "QDASSD0006-56915.2014" "QDASSD0006-57626.2015"
```

```
# Plot Pies for the first 5 Resampled Sites (i.e. 10 Site-Visit pairs)
# -----
# Order dataframe to Plot Site-Visit pairs in the appropriate order
AP.200Locs.FC.Resampled.Locs = AP.200Locs.FC.Resampled.Locs[order(AP.200Locs.FC.Resampled.Locs$site_unique),]
head(AP.200Locs.FC.Resampled.Locs)
```


```
##      site_unique  bare brown green  NA. bioregion.f longitude  latitude
## 1 QDASSD0003-56912 48.91 35.45 15.64 0.00      SSD  138.4074 -23.83157
## 2 QDASSD0003-57623 34.42 38.08 27.50 0.00      SSD  138.4074 -23.83157
## 3 QDASSD0005-56914 56.93 24.36 16.83 1.88      SSD  138.4410 -23.69444
## 4 QDASSD0005-57625 31.02 38.06 30.91 0.00      SSD  138.4410 -23.69444
## 5 QDASSD0006-56915 43.37 38.22 18.42 0.00      SSD  138.0984 -23.87954
## 6 QDASSD0006-57626 28.51 23.86 47.62 0.00      SSD  138.0984 -23.87954
##      visit_start_date      site_unique.Yr
## 1 2014-05-01T00:00:00 QDASSD0003-56912.2014
## 2 2015-04-16T00:00:00 QDASSD0003-57623.2015
## 3 2014-05-02T00:00:00 QDASSD0005-56914.2014
## 4 2015-04-26T00:00:00 QDASSD0005-57625.2015
## 5 2014-05-03T00:00:00 QDASSD0006-56915.2014
## 6 2015-04-18T00:00:00 QDASSD0006-57626.2015
```

```
# Plot the Site-Visit pairs
par(mfcol=c(2,5))
for (site.visit.cnt in 1:10) {


  pie( x=as.numeric(AP.200Locs.FC.Resampled.Locs[site.visit.cnt,2:5]),
      col=c("yellow", "brown", "green", "white"),
      labels=names(AP.200Locs.FC.Resampled.Locs[2:5]),
      main=as.character(AP.200Locs.FC.Resampled.Locs[site.visit.cnt,"site_unique.Yr"]) )

} # for site.visit.cnt in 1:20 {
```


QDASSD0003-56912.2014



QDASSD0005-56914.2014



QDASSD0006-56915.2014



QDASSD0007-56916.2014



QDASSD0008-56917.2014



QDASSD0003-57623.2015



QDASSD0005-57625.2015




QDASSD0006-57626.2015



QDASSD0007-57627.2015



QDASSD0008-57628.2015



## GROWTH FORM: `growth_form_table` function (for 5 most sampled bioregions)

The `growth_form_table` function in the `ausplotR` package can be used to generate occurrence matrices for NVIS plant growth forms in plots. The input for this function is a data frame of raw point intercept AusPlots data generated using the `get_ausplots` function. Three metrics can be selected to score species growth form:

- *Presence/Absence* (argument `m_kind = PA` ).
- *Percent Cover*: Based on total frequency of hits (argument `m_kind = percent_cover` ). This is the most useful and commonly used metric. It can be subsequently used in statistical analyses (e.g. MANOVA, Ordination, Classification, etc.) at continental scale where species turnover is too high for some methods to provide meaningful results.
- *Species Richness*: (argument `m_kind = richness` ). Note that when `m_kind` is set to “richness” the `rowSums` of the occurrence matrix can be higher than the observed SR because sometimes the same species is recorded with different growth forms in a plot and therefore the same species can count towards the weights for multiple growth forms.

If Percent Cover is used two types of cover type can be selected:

- *Projected Foliage Cover (PFC)*: Hits scored as ‘in canopy sky’ are removed (argument `cover_type = PFC` ).
- *Opaque Canopy Cover (OCC)*: Hits scored as ‘in canopy sky’ are retained (argument `cover_type = OCC` ).

In this section we will:

- Generate a Plant Growth Forms Percent Cover against Sites Matrix using the `growth_form_table` function.
- Enrich this Matrix with additional information (plot -site-visit-, bioregion, longitude, and latitude).
- Compute Summary Statics for each of the Growth Forms in the 5 most sampled Bioregions (slightly different to those produce by the `summary` function in the `base` package).

- Cluster (Hierarchical Clustering) the Sites-Visits by Plant Growth Forms Percent Cover, colouring the resulting tree branches by bioregion.

## CLUSTERING RESULTS:

- The first Site-Visit (NTAGFU0007-53654) is very different to the rest
- The dendrogram shows clusters formed by single Bioregions at low level; however, at higher-level clusters are composed by Sites-Visits from different Bioregions.

```
# Generate the Growth Form by Site-Visit Matrix
# =====
AP.BRTop5.GrowthFormBYSites = growth_form_table(AP.BioregTop5.l$veg.PI,
m_kind="percent_cover", cover_type="PFC") # % Cover
dim(AP.BRTop5.GrowthFormBYSites) # No of rows and cols in Matrix: Sites x Growth Forms
```

```
## [1] 219 18
```

```
head(AP.BRTop5.GrowthFormBYSites)
```

```
##           Bryophyte  Chenopod  Epiphyte  Fern      Forb      Fungus
## NSAMDD0001-56965      0 19.537815 0.0000000  0 83.1932773 0.4201681
## NSAMDD0002-56952      0  3.024911 0.0000000  0  0.1779359 0.0000000
## NSAMDD0003-56968      0 24.635036 0.0000000  0  9.3065693 0.0000000
## NSAMDD0004-56953      0 45.194805 0.0000000  0 31.9480519 0.0000000
## NSAMDD0005-56969      0 12.923077 0.0000000  0 12.0000000 0.0000000
## NSAMDD0006-56954      0 79.945799 0.2710027  0  3.2520325 0.0000000
##           Grass.tree  Heath.shrub  Hummock.grass      NC  Rush  Sedge
## NSAMDD0001-56965      0           0      0.00000 2.7310924  0      0
## NSAMDD0002-56952      0           0      31.13879 0.0000000  0      0
## NSAMDD0003-56968      0           0      0.00000 0.0000000  0      0
## NSAMDD0004-56953      0           0      0.00000 0.0000000  0      0
## NSAMDD0005-56969      0           0      0.00000 0.9230769  0      0
## NSAMDD0006-56954      0           0      0.00000 0.0000000  0      0
##           Shrub  Shrub.Mallee  Tree.Mallee  Tree.Palm
## NSAMDD0001-56965 0.0000000 0.0000000 0.0000000 0.0000000
## NSAMDD0002-56952 1.6014235 0.5338078 76.8683274 0.0000000
## NSAMDD0003-56968 82.8467153 0.0000000 0.3649635 1.094891
## NSAMDD0004-56953 5.1948052 0.0000000 0.0000000 28.831169
## NSAMDD0005-56969 4.0000000 0.0000000 76.6153846 0.0000000
## NSAMDD0006-56954 0.8130081 0.0000000 0.0000000 32.249322
##           Tussock.grass  Vine
## NSAMDD0001-56965 1.8907563 0
## NSAMDD0002-56952 0.3558719 0
## NSAMDD0003-56968 0.0000000 0
## NSAMDD0004-56953 1.0389610 0
## NSAMDD0005-56969 0.3076923 0
## NSAMDD0006-56954 0.5420054 0
```

```
# Enrich DF
# =====

# Create a 'site_unique' variable in Growth Form by Site-VisitTable to relate both datasets
# -----
AP.BRTop5.GrowthFormBYSites$site_unique = rownames(AP.BRTop5.GrowthFormBYSites)

# Add: Bioregion, Longitude, Latitude
# -----
# Both DF have different number of rows (again!)
dim(AP.BRTop5.GrowthFormBYSites)
```

```
## [1] 219  19
```

```
dim(AP.BioregTop5.l$site.info)
```

```
## [1] 225  44
```

```
# Enrich with: Bioregion, Latitude, and Longitude
AP.BRTop5.GrowthFormBYSites = merge(AP.BRTop5.GrowthFormBYSites, AP.BioregTop5.l$site.info,
  by="site_unique")[,c(names(AP.BRTop5.GrowthFormBYSites),

"bioregion.f", "longitude", "latitude")]
AP.BRTop5.GrowthFormBYSites = na.omit(AP.BRTop5.GrowthFormBYSites)
#head(AP.BRTop5.GrowthFormBYSites)
summary(AP.BRTop5.GrowthFormBYSites)
```



```
##      Bryophyte      Chenopod      Epiphyte      Fern
## Min.      :0.00000 Min.      : 0.000 Min.      : 0.0000 Min.      : 0.0000
## 1st Qu.:0.00000 1st Qu.: 0.000 1st Qu.: 0.0000 1st Qu.: 0.0000
## Median :0.00000 Median : 1.653 Median : 0.0000 Median : 0.0000
## Mean      :0.02633 Mean      : 14.547 Mean      : 0.1224 Mean      : 0.3755
## 3rd Qu.:0.00000 3rd Qu.: 22.438 3rd Qu.: 0.0000 3rd Qu.: 0.0000
## Max.      :5.50459 Max.      :100.000 Max.      :14.2857 Max.      :20.6612
##      Forb      Fungus      Grass.tree      Heath.shrub
## Min.      : 0.000 Min.      :0.000000 Min.      : 0.0000 Min.      :0.00000
## 1st Qu.: 2.696 1st Qu.:0.000000 1st Qu.: 0.0000 1st Qu.:0.00000
## Median : 7.993 Median :0.000000 Median : 0.0000 Median :0.00000
## Mean      :15.271 Mean      :0.001919 Mean      : 0.2582 Mean      :0.01111
## 3rd Qu.:20.674 3rd Qu.:0.000000 3rd Qu.: 0.0000 3rd Qu.:0.00000
## Max.      :94.268 Max.      :0.420168 Max.      :26.8765 Max.      :2.13270
## Hummock.grass      NC      Rush      Sedge
## Min.      : 0.00 Min.      :0.00000 Min.      : 0.000 Min.      : 0.0000
## 1st Qu.: 0.00 1st Qu.:0.00000 1st Qu.: 0.000 1st Qu.: 0.0000
## Median : 0.00 Median :0.00000 Median : 0.000 Median : 0.0000
## Mean      : 12.66 Mean      :0.06355 Mean      : 0.145 Mean      : 0.6841
## 3rd Qu.: 10.34 3rd Qu.:0.00000 3rd Qu.: 0.000 3rd Qu.: 0.0000
## Max.      :183.86 Max.      :2.80374 Max.      :12.349 Max.      :29.2653
##      Shrub      Shrub.Mallee      Tree.Mallee      Tree.Palm
## Min.      : 0.000 Min.      : 0.0000 Min.      : 0.0000 Min.      : 0.0000
## 1st Qu.: 2.851 1st Qu.: 0.0000 1st Qu.: 0.0000 1st Qu.: 0.0000
## Median : 12.863 Median : 0.0000 Median : 0.0000 Median : 0.6623
## Mean      : 21.843 Mean      : 0.8677 Mean      : 7.7763 Mean      :15.5646
## 3rd Qu.: 33.969 3rd Qu.: 0.0000 3rd Qu.: 0.2293 3rd Qu.:26.0450
## Max.      :100.168 Max.      :37.7863 Max.      :91.9786 Max.      :99.1747
## Tussock.grass      Vine      site_unique      bioregion.f
## Min.      : 0.000 Min.      :0.000 Length:219 FLB:42
## 1st Qu.: 1.246 1st Qu.:0.000 Class :character GFU:41
## Median :13.793 Median :0.000 Mode :character MDD:50
## Mean      :23.400 Mean      :0.174 SSD:46
## 3rd Qu.:41.050 3rd Qu.:0.000 STP:40
## Max.      :99.051 Max.      :7.767
## longitude      latitude
## Min.      :132.9 Min.      : -35.08
## 1st Qu.:136.1 1st Qu.: -32.79
## Median :138.2 Median : -28.21
## Mean      :138.3 Mean      : -27.19
## 3rd Qu.:139.3 3rd Qu.: -23.83
## Max.      :145.8 Max.      : -14.05
```

```
names(AP.BRTop5.GrowthFormBYSites)
```

```
## [1] "Bryophyte"      "Chenopod"      "Epiphyte"      "Fern"
## [5] "Forb"          "Fungus"        "Grass.tree"    "Heath.shrub"
## [9] "Hummock.grass" "NC"            "Rush"          "Sedge"
## [13] "Shrub"         "Shrub.Mallee" "Tree.Mallee"  "Tree.Palm"
## [17] "Tussock.grass" "Vine"          "site_unique"   "bioregion.f"
## [21] "longitude"      "latitude"
```

```
# Summary Statistics for Each Growth Form
# =====
AP.BRTop5.GFBYSites.DescStats = data.frame(
  Min = apply(AP.BRTop5.GrowthFormBYSites[,1:(dim(AP.BRTop5.GrowthFormBYSites)[2]-4)], 2,
min), # Minimum
  Med = apply(AP.BRTop5.GrowthFormBYSites[,1:(dim(AP.BRTop5.GrowthFormBYSites)[2]-4)], 2,
median), # Median
  Max = apply(AP.BRTop5.GrowthFormBYSites[,1:(dim(AP.BRTop5.GrowthFormBYSites)[2]-4)], 2,
max), # Maximum
  Mean = apply(AP.BRTop5.GrowthFormBYSites[,1:(dim(AP.BRTop5.GrowthFormBYSites)[2]-4)], 2,
mean), # Mean
  SD = apply(AP.BRTop5.GrowthFormBYSites[,1:(dim(AP.BRTop5.GrowthFormBYSites)[2]-4)], 2,
sd) # Standard Deviation
)
AP.BRTop5.GFBYSites.DescStats = round(AP.BRTop5.GFBYSites.DescStats, 2)
AP.BRTop5.GFBYSites.DescStats
```

##	Min	Med	Max	Mean	SD
## Bryophyte	0	0.00	5.50	0.03	0.37
## Chenopod	0	1.65	100.00	14.55	22.36
## Epiphyte	0	0.00	14.29	0.12	1.00
## Fern	0	0.00	20.66	0.38	1.87
## Forb	0	7.99	94.27	15.27	18.80
## Fungus	0	0.00	0.42	0.00	0.03
## Grass.tree	0	0.00	26.88	0.26	2.26
## Heath.shrub	0	0.00	2.13	0.01	0.15
## Hummock.grass	0	0.00	183.86	12.66	26.21
## NC	0	0.00	2.80	0.06	0.33
## Rush	0	0.00	12.35	0.15	1.17
## Sedge	0	0.00	29.27	0.68	2.89
## Shrub	0	12.86	100.17	21.84	24.18
## Shrub.Mallee	0	0.00	37.79	0.87	4.46
## Tree.Mallee	0	0.00	91.98	7.78	18.28
## Tree.Palm	0	0.66	99.17	15.56	25.38
## Tussock.grass	0	13.79	99.05	23.40	26.34
## Vine	0	0.00	7.77	0.17	0.71

```

# Create and Plot a Dendrogram of the Sites-Visits Clustered by Growth Forms
# =====

# Add rownames to be used as Leaves Names
rownames(AP.BRTop5.GrowthFormBYSites) = AP.BRTop5.GrowthFormBYSites$site_unique


# Create Dendrogram
AP.BRTop5.GFBYSites.dend = as.dendrogram(hclust(dist(AP.BRTop5.GrowthFormBYSites[,1: (dim(AP.
BRTop5.GrowthFormBYSites)[2]-4)]), "average"))

# Color the Leaves by Bioregion
# NOTE: The most sampled bioregions might change as new data is added. If so, bioregions code
s below should be revised.
# The (currently) most common codes correspond to: MDD (Murry Darling Depression),
# SSD (Simpson Strzelecki Dunefields), GFU (Gulf Fall and Uplands), STP (Stony
# Plains), PIL (Pilbara), FLB (Flinders Lofty Block).
# For example, here PIL is commented out 'cos when writting the current version of
# this tutorial it wasn't one of the 5 most sampled bioregions. However, in the
# previous version of this tutorial PIL was included, and FLB wasn't among the 5
# most sampled bioregions.

AP.BRTop5.GrowthFormBYSites$bioregion.col.f = AP.BRTop5.GrowthFormBYSites$bioregion.f
levels(AP.BRTop5.GrowthFormBYSites$bioregion.col.f)[levels(AP.BRTop5.GrowthFormBYSites$bioreg
ion.col.f) == "GFU"] = "darkgreen"
levels(AP.BRTop5.GrowthFormBYSites$bioregion.col.f)[levels(AP.BRTop5.GrowthFormBYSites$bioreg
ion.col.f) == "MDD"] = "magenta"
#levels(AP.BRTop5.GrowthFormBYSites$bioregion.col.f)[levels(AP.BRTop5.GrowthFormBY#Sites$bior
egion.col.f) == "PIL"] = "red"
levels(AP.BRTop5.GrowthFormBYSites$bioregion.col.f)[levels(AP.BRTop5.GrowthFormBYSites$bioreg
ion.col.f) == "FLB"] = "red"
levels(AP.BRTop5.GrowthFormBYSites$bioregion.col.f)[levels(AP.BRTop5.GrowthFormBYSites$bioreg
ion.col.f) == "SSD"] = "yellow"
levels(AP.BRTop5.GrowthFormBYSites$bioregion.col.f)[levels(AP.BRTop5.GrowthFormBYSites$bioreg
ion.col.f) == "STP"] = "cyan"
dend.colors = as.character(AP.BRTop5.GrowthFormBYSites$bioregion.col.f)
#dend.colors
dend.colors = dend.colors[order.dendrogram(AP.BRTop5.GFBYSites.dend)]
#dend.colors
labels_colors(AP.BRTop5.GFBYSites.dend) = dend.colors
# Plot Dendrogram
par(mfrow=c(1,1))
plot(AP.BRTop5.GFBYSites.dend,
      main="Dendrogram of the Sites-Visits Clustered by Growth Forms, with leaves coloured by B
ioregion")

```

Dendrogram of the Sites-Visits Clustered by Growth Forms, with leaves coloured by Bioregion



## TOTAL VEGETATION COVER BY GROWTH FORM AND/OR HEIGHT: single\_cover\_value function (for 5 most sampled bioregions).

Similar to the `growth_form_table` function, the `single_cover_value` function can calculate Vegetation Cover Values per Site from Raw Vegetation Point Intercept data from AusPlots. However, the `single_cover_value` can perform these computations for:

1. Vegetation of *particular growth form types* (i.e. for individual growth form types or any combination of growth form types).
2. Vegetation *higher than a specified height threshold*
3. Vegetation with any combination of *growth form types* and *minimum height*

Specifically `single_cover_value` takes the following inputs via its arguments:

- *Raw Vegetation Point Intercept data from AusPlots* (argument `veg.PI`): A `veg.PI` data frame generated by the `get_ausplots` function (see above).
- *Method used to Calculate Cover* (argument `in_canopy_sky`): A logical value that indicates whether to use in canopy sky hits (i.e. calculate opaque canopy cover) or projected foliage cover. The default value, `FALSE`, calculates projected foliage cover. To calculate opaque canopy cover the argument must be set to `TRUE`.
- *Whether to Calculate Cover for a Subset by Growth Form Type* (argument `by.growth_form`): A logical value that indicates whether to subset by growth form type. The default, `TRUE`, calculates cover for the growth form types specified in the argument `my.growth_forms`. If set to `FALSE` cover calculations are conducted only for the vegetation subsetted by a Minimum Height.
- *Growth Form Types used to Subset Data used for the Cover Calculations* (argument `my.growth_forms`): A character vector specifying the growth form types to subset the data used for the cover calculations. Any combination of growth form types can be used. The default, `c("Tree/Palm", "Tree Mallee")`, is set to represent trees. It applies only when `by.growth_form=TRUE`; otherwise, this argument is ignored and only height subsetting is applied.

- *Minimum Height Threshold used to Subset Data used for the Cover Calculations* (argument `min.height`): A numeric value indicating the minimum height (in metres) of the vegetation to included in the subset of the data used for the cover calculations. A height must be always provided. The default, 5, is set up for a cover of trees. It can be set to zero to ignore height and include any plant hit. If set to a negative number, it will return nonsensical output.

When `by.growth_form = FALSE` and `min.height = 0`, the output is nearly the same as the green cover fraction returned from `fractional_cover`. The values can differ because `fractional_cover` applies a height rule in which the highest intercept at a given point is taken, whereas `single_cover_value` finds any green cover (e.g. when dead trees overhang green understorey). For such general cover purposes, using `fractional_cover` is recommended. `single_cover_value` is best suited to cover subset by height and growth form.

Next, several examples of how to compute, manipulate, and visualise 'Single' Vegetation Cover Fraction (VCF) data are presented. The examples cover different scenarios for subsetting the input vegetation point intercept data frame prior to the calculation of the corresponding VCF. These include:

- Subsetting only by Height
- Subsetting only by Taxonomy
- Subsetting by Height and Taxonomy

## Subsetting by Height only

```
# Subsetting by Height only
# *****

# Compute Single Cover Values Tables
# =====
# Any green vegetation (i.e. >= 0m in height)
veg.cover.gt0 = single_cover_value(AP.BioregTop5.l$veg.PI, by.growth_form=FALSE, min.height=0
)
# Any green vegetation >= 2m in height
veg.cover.gt2 = single_cover_value(AP.BioregTop5.l$veg.PI, by.growth_form=FALSE, min.height=2
)

# Combine all Tables into a Single Data Frame
# =====
# Create a data frame containing all the Vegetation Cover Fractions
AP.BioregTop5.VCF.df = data.frame(site_unique=veg.cover.gt0$site_unique, VCF.gt0=veg.cover.gt0$percentCover, VCF.gt2=veg.cover.gt2$percentCover)
head(AP.BioregTop5.VCF.df)
```

```
##           site_unique VCF.gt0 VCF.gt2
## 1 NSAMDD0001-56965   45.74    0.00
## 2 NSAMDD0002-56952   55.45   39.21
## 3 NSAMDD0003-56968   47.52    4.65
## 4 NSAMDD0004-56953   35.05   10.99
## 5 NSAMDD0005-56969   31.29   23.76
## 6 NSAMDD0006-56954   34.95   11.29
```

```
summary(AP.BioregTop5.VCF.df)
```

```
##           site_unique      VCF.gt0      VCF.gt2
## NSAMDD0001-56965:  1   Min.    : 0.20   Min.    : 0.00
## NSAMDD0002-56952:  1   1st Qu.:20.05   1st Qu.: 0.25
## NSAMDD0003-56968:  1   Median  :32.67   Median  : 7.62
## NSAMDD0004-56953:  1   Mean    :35.82   Mean    :12.76
## NSAMDD0005-56969:  1   3rd Qu.:48.61   3rd Qu.:20.59
## NSAMDD0006-56954:  1   Max.    :84.06   Max.    :70.89
## (Other)           :213
```

```
# Enrich DF
```

```
# =====
```

```
# Compute Vegetation Cover Fractions for Height Ranges
```

```
# -----
```

```
AP.BioregTop5.VCF.df$VCF.0to2 = AP.BioregTop5.VCF.df$VCF.gt0 - AP.BioregTop5.VCF.df$VCF.gt2
head(AP.BioregTop5.VCF.df)
```

```
##           site_unique VCF.gt0 VCF.gt2 VCF.0to2
## 1 NSAMDD0001-56965   45.74    0.00    45.74
## 2 NSAMDD0002-56952   55.45   39.21   16.24
## 3 NSAMDD0003-56968   47.52    4.65   42.87
## 4 NSAMDD0004-56953   35.05   10.99   24.06
## 5 NSAMDD0005-56969   31.29   23.76    7.53
## 6 NSAMDD0006-56954   34.95   11.29   23.66
```

```
summary(AP.BioregTop5.VCF.df)
```

```
##           site_unique      VCF.gt0      VCF.gt2      VCF.0to2
## NSAMDD0001-56965:  1   Min.    : 0.20   Min.    : 0.00   Min.    : 0.20
## NSAMDD0002-56952:  1   1st Qu.:20.05   1st Qu.: 0.25   1st Qu.:11.93
## NSAMDD0003-56968:  1   Median  :32.67   Median  : 7.62   Median :20.41
## NSAMDD0004-56953:  1   Mean    :35.82   Mean    :12.76   Mean    :23.07
## NSAMDD0005-56969:  1   3rd Qu.:48.61   3rd Qu.:20.59   3rd Qu.:32.52
## NSAMDD0006-56954:  1   Max.    :84.06   Max.    :70.89   Max.    :68.02
## (Other)           :213
```

```
# Add: Bioregion, Longitude, Latitude
```

```
# -----
```

```
# Both DF have different number of rows
```

```
dim(AP.BioregTop5.VCF.df)
```

```
## [1] 219   4
```

```
dim(AP.BioregTop5.l$site.info)
```

```
## [1] 225  44
```

```
# Enrich with: Bioregion, Latitude, and Longitude
```

```
AP.BioregTop5.VCF.df = merge(AP.BioregTop5.VCF.df, AP.BioregTop5.l$site.info, by="site_unique")[,c(names(AP.BioregTop5.VCF.df), "bioregion.f", "longitude", "latitude")]
AP.BioregTop5.VCF.df = na.omit(AP.BioregTop5.VCF.df)
head(AP.BioregTop5.VCF.df)
```

```
##           site_unique VCF.gt0 VCF.gt2 VCF.0to2 bioregion.f longitude
## 1 NSAMDD0001-56965    45.74    0.00    45.74         MDD  142.5602
## 2 NSAMDD0002-56952    55.45    39.21    16.24         MDD  142.6026
## 3 NSAMDD0003-56968    47.52     4.65    42.87         MDD  142.6041
## 4 NSAMDD0004-56953    35.05    10.99    24.06         MDD  142.5594
## 5 NSAMDD0005-56969    31.29    23.76     7.53         MDD  143.2039
## 6 NSAMDD0006-56954    34.95    11.29    23.66         MDD  143.1665
##      latitude
## 1 -34.18392
## 2 -34.20482
## 3 -34.20754
## 4 -34.16537
## 5 -33.65619
## 6 -33.66432
```

```
summary(AP.BioregTop5.VCF.df)
```

```
##           site_unique      VCF.gt0      VCF.gt2      VCF.0to2
## NSAMDD0001-56965: 1  Min.   : 0.20  Min.   : 0.00  Min.   : 0.20
## NSAMDD0002-56952: 1  1st Qu.:20.05  1st Qu.: 0.25  1st Qu.:11.93
## NSAMDD0003-56968: 1  Median :32.67  Median : 7.62  Median :20.41
## NSAMDD0004-56953: 1  Mean    :35.82  Mean    :12.76  Mean    :23.07
## NSAMDD0005-56969: 1  3rd Qu.:48.61  3rd Qu.:20.59  3rd Qu.:32.52
## NSAMDD0006-56954: 1  Max.    :84.06  Max.    :70.89  Max.    :68.02
## (Other)           :213
## bioregion.f  longitude      latitude
## FLB:42      Min.    :132.9  Min.    :-35.08
## GFU:41      1st Qu.:136.1  1st Qu.: -32.79
## MDD:50      Median :138.2  Median  :-28.21
## SSD:46      Mean    :138.3  Mean    :-27.19
## STP:40      3rd Qu.:139.3  3rd Qu.: -23.83
##             Max.    :145.8  Max.    :-14.05
##
```

```
names(AP.BioregTop5.VCF.df)
```

```
## [1] "site_unique" "VCF.gt0"      "VCF.gt2"      "VCF.0to2"      "bioregion.f"
## [6] "longitude"   "latitude"
```

```

# Graphical Visualisation
# =====

# VCF 0 to 2m: Map with circle size = the Vegetation Cover Fraction for any green veg.
# -----
# (i.e. >= 0m in height)
AP.BioregTop5.VCF.df.p1 =
ggplot(data=AP.BioregTop5.VCF.df, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
geom_point(aes(size=VCF.0to2), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)

# VCF 0 to 2m: Boxplot
# -----
AP.BioregTop5.VCF.df.p2 =
ggplot(AP.BioregTop5.VCF.df, aes(x=bioregion.f, y=VCF.0to2, color=bioregion.f)) +
geom_boxplot() +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(name="Bioregions (Top 5)", values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
labs(x="Bioregion (5 most sampled)", y = "Vegetation Cover Fraction (0 to 2m)") +
theme(plot.title = element_text(hjust = 0.5))


# VCF >= 2m: Map with circle size = the Vegetation Cover Fraction for any green veg.
# -----
# (i.e. >= 0m in height)
AP.BioregTop5.VCF.df.p3 =
ggplot(data=AP.BioregTop5.VCF.df, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
geom_point(aes(size=VCF.gt2), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)

# VCF >= 2m: Boxplot
# -----
AP.BioregTop5.VCF.df.p4 =
ggplot(AP.BioregTop5.VCF.df, aes(x=bioregion.f, y=VCF.gt2, color=bioregion.f)) +
geom_boxplot() +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(name="Bioregions (Top 5)", values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
labs(x="Bioregion (5 most sampled)", y = "Vegetation Cover Fraction (>= 2m)") +
theme(plot.title = element_text(hjust = 0.5))

# Plot both graphs
# -----
grid.arrange(AP.BioregTop5.VCF.df.p1, AP.BioregTop5.VCF.df.p2,
              AP.BioregTop5.VCF.df.p3, AP.BioregTop5.VCF.df.p4, nrow=2)

```





```
#grid.arrange(AP.BioregTop5.VCF.df.p1, AP.BioregTop5.VCF.df.p2,
#              AP.BioregTop5.VCF.df.p3, AP.BioregTop5.VCF.df.p4, ncol=2)
```

## Subsetting by Taxonomy only

```
# Subsetting by Taxonomy only
# *****

# Compute Single Cover Values Tables
# =====
# Trees (by default my.growth_forms=c("Tree/Palm", "Tree Mallee"))
veg.cover.trees = single_cover_value(AP.BioregTop5.l$veg.PI, min.height=0)
# Grasses (my.growth_forms=c("Hummock.grass", "Tussock.grass"))
veg.cover.grass = single_cover_value(AP.BioregTop5.l$veg.PI, by.growth_form=TRUE, my.growth_forms=c("Hummock grass", "Tussock grass"), min.height=0)

# Combine all Tables into a Single Data Frame
# =====
# Create a data frame containing all the Vegetation Cover Fractions
AP.BioregTop5.VCF.df = data.frame(site_unique=veg.cover.trees$site_unique, VCF.trees=veg.cover.trees$percentCover, VCF.grass=veg.cover.grass$percentCover)
head(AP.BioregTop5.VCF.df)
```

```
##           site_unique VCF.trees VCF.grass
## 1 NSAMDD0001-56965      0.00      0.89
## 2 NSAMDD0002-56952     42.57     17.33
## 3 NSAMDD0003-56968      0.20      0.00
## 4 NSAMDD0004-56953     10.40      0.00
## 5 NSAMDD0005-56969     24.65      0.10
## 6 NSAMDD0006-56954     11.68      0.00
```

```
summary(AP.BioregTop5.VCF.df)
```

```
##           site_unique      VCF.trees      VCF.grass
## NSAMDD0001-56965: 1   Min.   : 0.00   Min.   : 0.00
## NSAMDD0002-56952: 1   1st Qu.: 0.00   1st Qu.: 0.74
## NSAMDD0003-56968: 1   Median : 2.87   Median : 6.53
## NSAMDD0004-56953: 1   Mean    :10.28   Mean    :13.39
## NSAMDD0005-56969: 1   3rd Qu.:15.49   3rd Qu.:21.34
## NSAMDD0006-56954: 1   Max.    :70.89   Max.    :67.43
## (Other)           :213
```

```
# Enrich DF
# =====

# Add: Bioregion, Longitude, Latitude
# -----

# Both DF have different number of rows
dim(AP.BioregTop5.VCF.df)
```

```
## [1] 219   3
```

```
dim(AP.BioregTop5.l$site.info)
```

```
## [1] 225  44
```

```
# Enrich with: Bioregion, Latitude, and Longitude
AP.BioregTop5.VCF.df = merge(AP.BioregTop5.VCF.df, AP.BioregTop5.l$site.info, by="site_uniqu
e")[,c(names(AP.BioregTop5.VCF.df), "bioregion.f", "longitude", "latitude")]
AP.BioregTop5.VCF.df = na.omit(AP.BioregTop5.VCF.df)
head(AP.BioregTop5.VCF.df)
```

```
##           site_unique VCF.trees VCF.grass bioregion.f longitude latitude
## 1 NSAMDD0001-56965      0.00      0.89      MDD  142.5602 -34.18392
## 2 NSAMDD0002-56952     42.57     17.33      MDD  142.6026 -34.20482
## 3 NSAMDD0003-56968      0.20      0.00      MDD  142.6041 -34.20754
## 4 NSAMDD0004-56953     10.40      0.00      MDD  142.5594 -34.16537
## 5 NSAMDD0005-56969     24.65      0.10      MDD  143.2039 -33.65619
## 6 NSAMDD0006-56954     11.68      0.00      MDD  143.1665 -33.66432
```

```
summary(AP.BioregTop5.VCF.df)
```

```
##           site_unique      VCF.trees      VCF.grass      bioregion.f
## NSAMDD0001-56965:  1    Min.    : 0.00    Min.    : 0.00    FLB:42
## NSAMDD0002-56952:  1    1st Qu.: 0.00    1st Qu.: 0.74    GFU:41
## NSAMDD0003-56968:  1    Median : 2.87    Median : 6.53    MDD:50
## NSAMDD0004-56953:  1    Mean     :10.28    Mean     :13.39    SSD:46
## NSAMDD0005-56969:  1    3rd Qu.:15.49    3rd Qu.:21.34    STP:40
## NSAMDD0006-56954:  1    Max.     :70.89    Max.     :67.43
## (Other)           :213
##      longitude      latitude
## Min.    :132.9    Min.    :-35.08
## 1st Qu.:136.1    1st Qu.: -32.79
## Median :138.2    Median : -28.21
## Mean     :138.3    Mean     :-27.19
## 3rd Qu.:139.3    3rd Qu.: -23.83
## Max.     :145.8    Max.     :-14.05
##
```

```
names(AP.BioregTop5.VCF.df)
```

```
## [1] "site_unique" "VCF.trees"   "VCF.grass"   "bioregion.f" "longitude"
## [6] "latitude"
```

```
# Graphical Visualisation
```

```
# =====
```

```
# Trees: Boxplot
```

```
# -----
```

```
AP.BioregTop5.VCF.trees =
```

```
ggplot(AP.BioregTop5.VCF.df, aes(x=bioregion.f, y=VCF.trees, color=bioregion.f)) +
geom_boxplot() +
```

```
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
```

```
scale_fill_manual(name="Bioregions (Top 5)", values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
```

```
labs(x="Bioregion (5 most sampled)", y = "Trees Cover Fraction (>= 0m)") +
```

```
theme(plot.title = element_text(hjust = 0.5))
```

```
# Grass: Boxplot
```

```
# -----
```

```
AP.BioregTop5.VCF.grass =
```

```
ggplot(AP.BioregTop5.VCF.df, aes(x=bioregion.f, y=VCF.grass, color=bioregion.f)) +
geom_boxplot() +
```

```
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
```

```
scale_fill_manual(name="Bioregions (Top 5)", values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
```


```
labs(x="Bioregion (5 most sampled)", y = "Grass Cover Fraction (>= 0m)") +
```

```
theme(plot.title = element_text(hjust = 0.5))
```

```
# Plot both graphs
```

```
# -----
```

```
grid.arrange(AP.BioregTop5.VCF.trees, AP.BioregTop5.VCF.grass, nrow=2)
```



```
#grid.arrange(AP.BioregTop5.BA.trees, AP.BioregTop5.VCF.grass, ncol=2)
```

## Subsetting by Taxonomy and Height

```
# Subsetting by Taxonomy and Height
# *****

# Compute Single Cover Values Tables
# =====
# Trees (by default my.growth_forms=c("Tree/Palm", "Tree Mallee"))
veg.cover.trees.gt5 = single_cover_value(AP.BioregTop5.1$veg.PI, by.growth_form=TRUE, my.growth_forms=c("Tree/Palm", "Tree Mallee"), min.height=5)

# These are the default values for the arguments of the function 'single_cover_value'
# So the following function call would produce exactly the same results
veg.cover.trees.gt5.2 = single_cover_value(AP.BioregTop5.1$veg.PI)
all.equal(veg.cover.trees.gt5, veg.cover.trees.gt5.2)
```

```
## [1] TRUE
```

```
rm(veg.cover.trees.gt5.2)

# Enrich DF
# =====

# Add: Bioregion, Longitude, Latitude
# -----

# Both DF have different number of rows
dim(veg.cover.trees.gt5)
```

```
## [1] 219  2
```

```
dim(AP.BioregTop5.l$site.info)
```

```
## [1] 225 44
```

```
# Enrich with: Bioregion, Latitude, and Longitude
AP.BioregTop5.VCF.trees.gt5.df = merge(veg.cover.trees.gt5, AP.BioregTop5.l$site.info, by="site_unique")[,c(names(veg.cover.trees.gt5), "bioregion.f", "longitude", "latitude")]
AP.BioregTop5.VCF.trees.gt5.df = na.omit(AP.BioregTop5.VCF.trees.gt5.df)
head(AP.BioregTop5.VCF.trees.gt5.df)
```

```
##           site_unique percentCover bioregion.f longitude  latitude
## 1 NSAMDD0001-56965          0.00          MDD 142.5602 -34.18392
## 2 NSAMDD0002-56952          3.56          MDD 142.6026 -34.20482
## 3 NSAMDD0003-56968          0.00          MDD 142.6041 -34.20754
## 4 NSAMDD0004-56953          8.51          MDD 142.5594 -34.16537
## 5 NSAMDD0005-56969          6.93          MDD 143.2039 -33.65619
## 6 NSAMDD0006-56954          8.22          MDD 143.1665 -33.66432
```

```
summary(AP.BioregTop5.VCF.trees.gt5.df)
```

```
##           site_unique  percentCover bioregion.f longitude
## NSAMDD0001-56965: 1   Min.   : 0.000 FLB:42      Min.   :132.9
## NSAMDD0002-56952: 1   1st Qu.: 0.000 GFU:41      1st Qu.:136.1
## NSAMDD0003-56968: 1   Median : 0.200 MDD:50      Median :138.2
## NSAMDD0004-56953: 1   Mean    : 6.283 SSD:46      Mean    :138.3
## NSAMDD0005-56969: 1   3rd Qu.: 6.930 STP:40      3rd Qu.:139.3
## NSAMDD0006-56954: 1   Max.    :70.000           Max.    :145.8
## (Other)           :213
## latitude
## Min.   :-35.08
## 1st Qu.: -32.79
## Median :-28.21
## Mean    :-27.19
## 3rd Qu.: -23.83
## Max.    :-14.05
##
```

```
names(AP.BioregTop5.VCF.trees.gt5.df)
```

```
## [1] "site_unique" "percentCover" "bioregion.f" "longitude"
## [5] "latitude"
```

```
# Graphical Visualisation
```

```
# =====
```

```
# Map with circle size = Percent Cover
```

```
# -----
```

```
AP.BioregTop5.VCF.trees.gt5.p1 =
ggplot(data=AP.BioregTop5.VCF.trees.gt5.df, aes(x=longitude, y=latitude, colour=bioregion.f,
  fill=bioregion.f), alpha =0.5) +
geom_point(aes(size=percentCover), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)
```

```
# Boxplot
```



```
# -----
```

```
AP.BioregTop5.VCF.trees.gt5.p2 =
ggplot(AP.BioregTop5.VCF.trees.gt5.df, aes(x=bioregion.f, y=percentCover, color=bioregion.f))
+ geom_boxplot() +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(name="Bioregions (Top 5)", values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
labs(x="Bioregion (5 most sampled)", y = "Trees Cover Fraction (>= 5m)") +
theme(plot.title = element_text(hjust = 0.5))
```

```
# Plot both graphs
```

```
# -----
```

```
grid.arrange(AP.BioregTop5.VCF.trees.gt5.p1, AP.BioregTop5.VCF.trees.gt5.p2, nrow=2)
```



```
#grid.arrange(AP.BioregTop5.VCF.trees.gt5.p1, AP.BioregTop5.VCF.trees.gt5.p2, ncol=2)
```

## BASAL AREA (OR NUMBER OF BASAL WEDGE HITS): `basal_area` function (for 5 most sampled bioregions).

The `basal_area` function calculates the Basal Area (or Number of Basal Wedge Hits) for each plot, using the raw basal wedge data returned by the `get_ausplots` function also in the `ausplotsR` package. This function returns a data frame with rows representing Plots (or species by plots) and a single column containing the Basal Area (m<sup>2</sup>/ha) or Hit Scores.

In this section we will:

- Compute the Basal Area for each plot (m<sup>2</sup>/ha) using the `basal_area` function.

- Enrich the data frame containing the Basal Area data with additional information (i.e. plot -Site-Visit-, bioregion, longitude, and latitude).
- Display Basal Areas on map of Australia (with Dots size proportional to Basal Area).
- Boxplot of Basal Areas by Bioregion.

```
# Calculate Basal Area
# =====
AP.BioregTop5.BA = basal_area(AP.BioregTop5.l$veg.basal)
summary(AP.BioregTop5.BA)
```

```
## site_unique      basal_area_m2_ha
## Length:111      Min.   : 0.2857
## Class :character 1st Qu.: 1.5813
## Mode  :character Median : 3.9444
##                  Mean   : 5.8483
##                  3rd Qu.: 6.7750
##                  Max.   :40.2500
```

```
head(AP.BioregTop5.BA)
```

```
##      site_unique basal_area_m2_ha
## 1 NSAMDD0002-56952      4.583333
## 2 NSAMDD0004-56953      4.805556
## 3 NSAMDD0005-56969      5.538889
## 4 NSAMDD0006-56954      4.077778
## 5 NSAMDD0007-56970      4.205556
## 6 NSAMDD0009-56971     14.694444
```

```
# Enrich DF
# =====
# Preparation
colnames(AP.BioregTop5.BA)
```

```
## [1] "site_unique"      "basal_area_m2_ha"
```

```
summary(AP.BioregTop5.BA)
```

```
## site_unique      basal_area_m2_ha
## Length:111      Min.   : 0.2857
## Class :character 1st Qu.: 1.5813
## Mode  :character Median : 3.9444
##                  Mean   : 5.8483
##                  3rd Qu.: 6.7750
##                  Max.   :40.2500
```

```
head(AP.BioregTop5.BA)
```



```
##      site_unique basal_area_m2_ha
## 1 NSAMDD0002-56952      4.583333
## 2 NSAMDD0004-56953      4.805556
## 3 NSAMDD0005-56969      5.538889
## 4 NSAMDD0006-56954      4.077778
## 5 NSAMDD0007-56970      4.205556
## 6 NSAMDD0009-56971     14.694444
```

```
# Add: Bioregion, Longitude, Latitude
# -----
# Both DF have different number of rows
dim(AP.BioregTop5.BA)
```

```
## [1] 111  2
```

```
dim(AP.BioregTop5.l$site.info)
```

```
## [1] 225  44
```

```
# Enrich with: Bioregion, Latitude, and Longitude
AP.BioregTop5.BA = merge(AP.BioregTop5.BA, AP.BioregTop5.l$site.info, by="site_unique")[,c(
names(AP.BioregTop5.BA), "bioregion.f", "longitude", "latitude")]
AP.BioregTop5.BA = na.omit(AP.BioregTop5.BA)
head(AP.BioregTop5.BA)
```

```
##      site_unique basal_area_m2_ha bioregion.f longitude  latitude
## 1 NSAMDD0002-56952      4.583333      MDD 142.6026 -34.20482
## 2 NSAMDD0004-56953      4.805556      MDD 142.5594 -34.16537
## 3 NSAMDD0005-56969      5.538889      MDD 143.2039 -33.65619
## 4 NSAMDD0006-56954      4.077778      MDD 143.1665 -33.66432
## 5 NSAMDD0007-56970      4.205556      MDD 141.1608 -33.37998
## 6 NSAMDD0009-56971     14.694444      MDD 141.0655 -33.44049
```

```
summary(AP.BioregTop5.BA)
```

```
## site_unique      basal_area_m2_ha bioregion.f longitude
## Length:111      Min.   : 0.2857 FLB:34      Min.   :132.9
## Class :character 1st Qu.: 1.5813 GFU:34      1st Qu.:137.0
## Mode  :character Median : 3.9444 MDD:28      Median :138.6
##                Mean  : 5.8483 SSD: 9        Mean   :138.7
##                3rd Qu.: 6.7750 STP: 6        3rd Qu.:140.0
##                Max.   :40.2500           Max.   :145.8
## latitude
## Min.   :-35.08
## 1st Qu.: -33.27
## Median :-30.34
## Mean   :-26.81
## 3rd Qu.: -17.90
## Max.   :-14.05
```

```
names(AP.BioregTop5.BA)
```

```
## [1] "site_unique"      "basal_area_m2_ha" "bioregion.f"
## [4] "longitude"        "latitude"
```

```
# Graphical Visualisation
```

```
# =====
```

```
# Map with circle size = Basal Area (m2/ha)
```

```
# -----
```

```
AP.BioregTop5.BA.p1 =
ggplot(data=AP.BioregTop5.BA, aes(x=longitude, y=latitude, colour=bioregion.f, fill=bioregion.f), alpha =0.5) +
geom_point(aes(size=basal_area_m2_ha), pch=21) +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
geom_polygon(data=fortify(aus.sp), aes(x=long, y=lat, group=group), col="black", fill=NA)
```

```
# Boxplot
```


```
# -----
```

```
AP.BioregTop5.BA.p2 =
ggplot(AP.BioregTop5.BA, aes(x=bioregion.f, y=basal_area_m2_ha, color=bioregion.f)) +
geom_boxplot() +
scale_colour_manual(values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
scale_fill_manual(name="Bioregions (Top 5)", values = c("darkgreen", "magenta", "red", "yellow", "cyan")) +
labs(title="Basal Area per Bioregion",x="Bioregion (5 most sampled)", y = "Basal area (m^2/ha)") +
theme(plot.title = element_text(hjust = 0.5))
```


```
# Plot both graphs
```

```
# -----
```

```
grid.arrange(AP.BioregTop5.BA.p1, AP.BioregTop5.BA.p2, nrow=2)
```



Basal Area per Bioregion



```
#grid.arrange(AP.BioregTop5.BA.p1, AP.BioregTop5.BA.p2, ncol=2)
```