

Database Interface Requirements: UniQOS Access Points

Each row is a point in the UniQOS code base (as of 09/10/2026) that needs database access, with the data the UI sends to the database task and the data it needs back. All operations are keyed by phone number.

Code location	Trigger	Input (UI → DB)	Output (DB → UI)
Save contact			
ui/pages/contacts/contact_details.c:115 (“Edit Contact”)	User edits an existing contact	name, phone	Status
ui/pages/phone/call.c:44 (“Add to Contacts”)	User saves the number from a call	name, phone	Status
Delete contact			
ui/pages/contacts/contact_details.c:118 (“Delete Contact”)	User deletes a contact	phone	Status
Get contact (by phone)			
kernel/tasks/mm_task.c:156 (handle_incoming_call) → ui/overlays/incoming_call.c	Incoming call	phone	name (caller ID)
kernel/tasks/mm_task.c:194 (handle_show_sms) → ui/overlays/incoming_text.c	Incoming SMS notification	phone	name (sender)
ui/pages/sms/messages.c:49 (“From:” header)	Conversation opened	phone	name
ui/pages/contacts/contacts.c:143 (INPUT_SELECT)	Contact selected from list	phone	name, phone
Save message (append)			
kernel/tasks/mm_task.c:299 (PAGE_REQUEST_SMS_SEND) ← ui/pages/sms/new_sms.c:51	SMS sent	phone, body, direction = sent, timestamp	Status
kernel/tasks/mm_task.c:194 (handle_show_sms) ← kernel/tasks/cellular_task.c:226	SMS received	phone, body, direction = received, timestamp	Status
Get message (by phone)			
kernel/tasks/mm_task.c:58 (incoming_text_callback, OPEN)	User opens a new SMS	phone	Opens the conversation (message list for phone)
Conversation list rows (new page, from “All Messages”)	Preview of latest message	phone	Latest body, timestamp
Get list			
ui/pages/contacts/contacts.c:17–53, 103, 185 (hardcoded names[] / phones[], max_y = 15)	Contacts page opened / scrolled past 9 rows	start, count = 9	≤ 9 × {name, phone}, total count
ui/pages/sms/messages.c (single message in MessagePageState)	Conversation opened / scrolled	phone, start, count = N	N × {body, direction, timestamp}, newest first
ui/pages/sms/sms.c:131 (“All Messages”, hardcoded “1234567890”)	SMS menu option selected	start, count	List of {phone, name, latest preview, timestamp}, most recent first
ui/pages/phone/call_logs.c (empty file)	Recent calls page (future)	start, count	List of {phone, name, direction, timestamp}

Test code to remove, not wire up: `ui/pages/sms/sms.c:139` (“Favourites”) and `ui/pages/phone/phone.c:142` both raise fake overlays for the test number “1234567890”.