```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.11.11
Pinging 192.168.11.11 with 32 bytes of data:
Reply from 192.168.11.11: bytes=32 time=15ms TTL=126
Reply from 192.168.11.11: bytes=32 time=14ms TTL=126
Reply from 192.168.11.11: bytes=32 time=1ms TTL=126
Reply from 192.168.11.11: bytes=32 time=1ms TTL=126
Ping statistics for 192.168.11.11:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 15ms, Average = 7ms
Cisco Packet Tracer SERVER Command Line 1.0
C:\>ping 192.16811.11
C:\>ping 192.168.11.11
Pinging 192.168.11.11 with 32 bytes of data:
Reply from 192.168.11.11: bytes=32 time=15ms TTL=126
Reply from 192.168.11.11: bytes=32 time=16ms TTL=126
Reply from 192.168.11.11: bytes=32 time=2ms TTL=126
Reply from 192.168.11.11: bytes=32 time=11ms TTL=126
Ping statistics for 192.168.11.11:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 16ms, Average = 11ms
C:\>ping 192.168.11.254
Pinging 192.168.11.254 with 32 bytes of data:
Request timed out.
Request timed out.
Reply from 192.168.11.254: bytes=32 time=2ms TTL=253
Reply from 192.168.11.254: bytes=32 time=2ms TTL=253
Ping statistics for 192.168.11.254:
   Packets: Sent = 4, Received = 2, Lost = 2 (50% loss),
```

Approximate round trip times in milli-seconds: Minimum = 2ms, Maximum = 2ms, Average = 2ms