

MyTix User Manual

Console ticketing platform - operational guide

Purpose

MyTix is a database-backed console application for browsing events, buying and managing tickets, resale, reviews, organizer administration, and analytical reports. This manual describes the workflows currently exposed by the application.

Before you begin

- Configure the database connection values in **.env** (DB_URL, DB_USER, and DB_PASSWORD).
- Run **./run.sh** in WSL/Linux. The script compiles the Java sources with the MySQL connector and starts MyTix.
- Create the database with **sql/schema.sql** and load the sample data with **sql/load.sql** before starting the application.
- Date format is YYYY-MM-DD; date/time format is YYYY-MM-DDTHH:MM; prices use decimals such as 49.99.

Start menu

Choice	What it does
1	Browse as a guest: search events and run reports.
2 / 3	Log in as a customer or organizer using the account ID or email.
4 / 5	Create a customer or organizer account.
0	Exit the application.

Account setup and sign-in

Customer registration asks for name, email, address, date of birth, cardholder name, card number, and expiry. Organizer registration asks for the first four identity fields. Users must be at least 18. After successful registration, the new account is opened automatically. Existing users can sign in by their account ID or matching email and account type.

Guest browsing

Option	Use
Q1	Find performances near a latitude/longitude within a radius; choose a distance or price ranking and direction.
Q2 / Q3	Search by postal code or exact venue address.
Q4	Search within a date/time range with a minimum number of available tickets.

Option	Use
Q5	Combine city, segment, genre, time, price, availability, and seating-type filters. Blank inputs mean no filter.
Q6	View a performance seat-map summary.
Q7	Request the best available seats for a performance, quantity, and optional budget.

Guest reports

Guest access also provides city/venue revenue, taxonomy and location counts, organizer revenue rankings, potential scalpers, customer-order rankings, cancellation leaders, sell-through, resale activity, and frequently occurring comment phrases. Reports requiring a date range prompt for start and end dates.

Customer workflows

Choice	Workflow
1	Reserved booking: choose a performance, payment method, section, row, and one or more seat numbers.
2	General-admission booking: choose a performance, section, payment method, and quantity.
3	Cancel one or more owned tickets by comma-separated ticket numbers.
4	List an owned ticket for resale with an asking price.
5	Withdraw an active resale listing by listing number.
6	Buy an active resale listing using the current customer payment method.
7	Review an attended event: enter its exact title, comment, event rating, and venue rating (both 1-5).

Customer tips

- Where a performance, venue, section, or tier allows an optional ID, press Enter to identify it by its exact name/address and date/time instead.
- For seat or ticket lists, separate numbers with commas, for example: 12, 13, 14.
- Use the exact event title when submitting a review. The system accepts one review only after attendance has been established.

Organizer workflows

Choice	Workflow
1	Create an event: enter segment, genre, title, description, and resale-cap multiplier (for example, 1.20).
2	Add a future performance to an owned event using a venue, performance name, and date/time.
3	Define a named price tier for an owned performance.
4	Assign a section to a price tier for an owned performance.
5	Change an owned event's resale-cap multiplier.
6	Change a price tier only when no ticket in that tier has been sold.
7	Block an unsold reserved seat.
8	Cancel an owned scheduled performance.

Important organizer rules

- A performance must be scheduled in the future and belongs to an event owned by the logged-in organizer.
- A blocked seat cannot already be sold.
- Cancelling a scheduled performance records refunds for active tickets, withdraws active resale listings, and marks the tickets as cancelled by organizer.

Troubleshooting

- “No matching record found” usually means the supplied ID, exact name, address, or time does not match a database record.
- “Price cannot change after a sale” protects price consistency after sales in that tier.
- If startup fails, verify the .env database settings, that MySQL is running, and that the connector JAR named in run.sh is available.
- Use 0 in any menu to return or log out.