

Exemplos de API - PhishGuard Fase 1

Base URL local:

```
http://127.0.0.1:8000
```

1) Health Check

```
curl -X GET "http://127.0.0.1:8000/health"
```

2) Análise de URL

```
curl -X POST "http://127.0.0.1:8000/api/analyze/url" \
-H "Content-Type: application/json" \
-d '{
  "url": "https://ba1.ao/login"
}'
```

Resposta esperada:

```
{
  "score": 80,
  "verdict": "NÃO SEGURO",
  "details": {
    "triggered_rule": "TYPOSQUATTING",
    "domain": "ba1.ao"
  },
  "analysis_id": 1,
  "timestamp": "2026-04-22T10:00:00Z"
}
```

3) Análise de SMS

```
curl -X POST "http://127.0.0.1:8000/api/analyze/sms" \
-H "Content-Type: application/json" \
-d '{
  "phone_number": "+244900000000",
  "body": "Ganhou um prémio! Clique aqui: http://oferta-segura.ao"
}'
```

4) Análise de Email

```
curl -X POST "http://127.0.0.1:8000/api/analyze/email" \
-H "Content-Type: application/json" \
-d '{
  "sender": "fraude@example.com",
  "subject": "Atualize a sua conta agora",
  "headers": "Authentication-Results: mx.google.com; spf=fail dkim=fail
dmarc=fail\nReceived-SPF: fail",
  "body": "Aceda imediatamente: https://multicaixa-seguro-login.com"
}'
```

5) Estatísticas do dashboard

```
curl -X GET "http://127.0.0.1:8000/api/dashboard/stats"
```

Resposta esperada:

```
{
  "total_analyses": 30,
  "total_safe": 11,
  "total_unsafe": 19,
  "unsafe_rate_percent": 63.33,
  "by_channel": {
    "web": 12,
    "sms": 10,
    "email": 8
  },
  "by_verdict": {
    "SEGURO": 11,
    "NÃO SEGURO": 19
  }
}
```

6) Exemplo Python (requests)

```
import requests

base_url = "http://127.0.0.1:8000"
payload = {"url": "https://bai.ao"}

resp = requests.post(f"{base_url}/api/analyze/url", json=payload, timeout=10)
resp.raise_for_status()
print(resp.json())
```