SERVERLESS DISASTER RECOVERY AUTOMATION -

USING CLOUD FUNCTIONS

Comprehensive Seminar submitted in fulfilment of the requirements for the Degree of

BACHELOR OF TECHNOLOGY

COMPUTER SCIENCE AND ENGINEERING

By

A LAHARI - (54)

12213066

Section: 322TH

Supervisor

AMAN DEEP

INTRODUCTION

In today's digital landscape, organizations depend on cloud-based systems to run mission-critical applications and services. Any unexpected failure—whether server crashes, network outages, or data loss—can result in significant downtime and financial impact. Traditional disaster recovery solutions are complex, expensive, and require continuous infrastructure management. This project demonstrates how serverless computing, using Cloud Functions, automates disaster recovery in an event-driven manner without managing servers. The result is faster recovery times, reduced operational costs, and improved system reliability for modern cloud architectures.

PROBLEM STATEMENT

THE CHALLENGE

Modern cloud-based applications require continuous availability to maintain business operations. However, failures such as server crashes, service outages, network issues, or data corruption can occur unexpectedly at any time. These incidents directly impact revenue, customer trust, and operational continuity.

CURRENT LIMITATIONS

Traditional disaster recovery mechanisms rely heavily on manual intervention, dedicated infrastructure, and complex configurations. This approach makes them expensive to maintain and slow to respond when failures occur.

PROPOSED SOLUTION

The proposed system resolves these challenges by using a serverless disaster recovery automation approach. Cloud monitoring services continuously observe the health of cloud resources. When a failure is detected, an alert is automatically generated, which triggers a Cloud Function. This function executes predefined recovery actions such as restarting services, restoring data from backups, or redeploying resources. Since the solution is serverless, there is no need to maintain recovery servers, reducing cost and operational complexity. The automated, event-driven process ensures faster recovery, minimal downtime, and improved system reliability.

OBJECTIVES

1. **Design an Automated Recovery System**
   Develop a serverless architecture that automatically detects failures and executes predefined recovery actions without manual intervention.
2. **Minimize Downtime (Reduce RTO & RPO)**
   Ensure rapid detection and instant recovery execution to significantly reduce system downtime and data loss.
3. **Eliminate Manual Intervention**
   Replace traditional manual disaster recovery processes with event-driven automation for faster and more reliable recovery.
4. **Improve System Reliability and Availability**
   Enhance the resilience of cloud-based applications through continuous monitoring, automatic failover, and service restoration.
5. **Optimize Operational Costs**
   Utilize pay-as-you-go serverless services to reduce infrastructure costs associated with traditional disaster recovery models.
6. **Ensure Scalability and Flexibility**
   Build a solution capable of handling multiple failures simultaneously while allowing easy updates and extension of recovery logic.

LITERATURE SURVEY

1. **Traditional Disaster Recovery Models**
   Early research on disaster recovery focused on **active-passive** and **active-active** architectures, which require duplicate infrastructure running in parallel to ensure recovery. While effective, they incur high costs and operational complexity.
2. **Cloud-Based DR Approaches**
   Many studies show that adopting cloud services improves disaster recovery by offering on-demand resources, scalability, and global reach. Cloud DR strategies commonly use replication and automated scaling to reduce downtime.
3. **Serverless Computing for Resilience**
   Recent literature highlights serverless computing as a promising paradigm for resilient systems. With functions triggered by events, serverless architectures eliminate server provisioning and reduce cost, especially for sporadic workloads like disaster recovery.
4. **Event-Driven Automation**
   Research indicates event-driven automation improves failure detection and response times. Systems that leverage monitoring alerts to trigger actions offer faster recovery compared to manual or schedule-based methods.

REFERENCES/CITATIONS(IEEE-FORMAT)

[1] E. Jonas et al., “Cloud Programming Simplified: A Berkeley View on Serverless Computing,” *University of California, Berkeley*, 2019.

[2] M. Roberts, “Serverless Architectures,” *Martin Fowler Blog*, Mar. 2016.

[3] Amazon Web Services, “AWS Lambda Developer Guide,” AWS Documentation, 2023.

[4] Microsoft, “Azure Functions Documentation,” Microsoft Learn, 2023.

[5] Google Cloud, “Cloud Functions Documentation,” Google Cloud Docs, 2023.

[6] Amazon Web Services, “Disaster Recovery of Workloads on AWS: Recovery in the Cloud,” AWS Whitepaper, 2022.

[7] R. Buyya, C. Vecchiola, and S. T. Selvi, *Mastering Cloud Computing: Foundations and Applications Programming*, Morgan Kaufmann, 2013.

[8] Amazon Web Services, “Amazon CloudWatch User Guide,” AWS Documentation, 2023.

WORKFLOW PROCESS

[Cloud Application / Services]

↓

[Monitoring Service]

↓

[Alert Trigger]

↓

[Cloud Function]

↓

[Backup Restore / Service Recovery]

↓

[Notification System]

WORKFLOW ANALYSIS

- Cloud resources are continuously monitored for availability, performance, and health metrics.
- Monitoring services detect failures, downtime, or abnormal behaviour in real time.
- An automated alert is generated based on predefined thresholds and conditions.
- The alert triggers a Cloud Function through an event-driven architecture.
- The Cloud Function executes predefined disaster recovery actions such as restarting services or restoring data from backups.
- Services are validated, restored to normal operation, and administrators receive detailed recovery notifications.

TECHNOLOGY STACK

METHODOLOGIES

- Serverless Architecture
- Event-Driven Computing
- Automated Monitoring and Alerting
- Cloud-Native Disaster Recovery
- On-Demand Execution (Pay-as-You-Go)

CLOUD SERVICES

- Cloud Functions (AWS Lambda / Azure Functions / GCP Functions)
- Monitoring Service (CloudWatch / Azure Monitor)
- Cloud Storage (S3 / Blob Storage)
- Notification Service (SNS / Email Alerts)

FUNCTIONAL REQUIREMENTS

- Continuous monitoring of cloud resources
- Automatic detection of system failures
- Trigger cloud functions on failure events
- Restore data from backup storage
- Restart or redeploy failed services
- Send recovery notifications to administrators
- Maintain logs of disaster recovery actions

NON-FUNCTIONAL REQUIREMENTS

- **Availability:** System must operate 24/7
- **Scalability:** Should handle multiple failures simultaneously
- **Performance:** Fast response and minimal recovery time
- **Security:** Secure access and data protection
- **Reliability:** Consistent and accurate recovery execution
- **Cost Efficiency:** Pay only for function execution
- **Maintainability:** Easy to update recovery logic

FUTURE SCOPE

- Automated failure detection
- Event-driven disaster recovery
- Serverless execution without infrastructure management
- Automatic data backup and restoration
- Service restart and redeployment
- Real-time alert and notification system
- Scalable and cost-efficient recovery mechanism

KEY CAPABILITIES

- Automated failure detection with intelligent threshold management
- Event-driven disaster recovery orchestrated through cloud-native services
- Serverless execution without infrastructure management overhead
- Automatic data backup and restoration with integrity verification
- Service restart and redeployment with version control
- Real-time alert and notification system with escalation paths
- Scalable and cost-efficient recovery mechanism

CONCLUSION

The **Serverless Disaster Recovery Automation using Cloud Functions** project successfully demonstrates how modern cloud-native technologies can transform traditional disaster recovery mechanisms into an intelligent, automated, and cost-efficient system. By leveraging serverless computing and event-driven architecture, the solution eliminates the need for dedicated recovery infrastructure and manual intervention.

The system ensures continuous monitoring, rapid failure detection, and instant recovery execution through Cloud Functions, significantly reducing Recovery Time Objective (RTO) and Recovery Point Objective (RPO). The pay-as-you-go model makes the solution economically efficient while maintaining high scalability and reliability.

This approach not only enhances system availability and operational continuity but also aligns with modern enterprise cloud strategies focused on automation, resilience, and cost optimization. Overall, the implementation proves that serverless disaster recovery is a practical, scalable, and future-ready solution for maintaining business continuity in cloud-based environments.