

Logic map

This document maps **Assignment 2** requirements to this Penni project.

Global constraints

Requirement ID	Class / File Name	Function / Method	Implementation Description
Inter-screen data via Intent extras and Bundles only	<code>SplashActivity</code> , <code>MainActivity</code> , <code>MainNavFragment</code> , other fragments	Activity lifecycle methods, <code>newInstance</code>	Name: <code>Intent</code> extra <code>NavExtras.EXTRA_DISPLAY_NAME</code> → <code>MainActivity</code> reads intent → <code>MainNavFragment.newInstance(name)</code> puts <code>ARG_DISPLAY_NAME</code> in arguments ; child fragments read <code>arguments</code> ; detail uses <code>putParcelable</code> for <code>Transaction</code> .
Primary UI in Fragments ; Activities as containers only	<code>MainActivity</code> , <code>MainNavFragment</code> , feature fragments	Activity <code>onCreate</code> , <code>NavFragment</code> creation	<code>MainActivity</code> layout is only <code>FragmentManager (fragment_root)</code> . All screens and the bottom bar live under <code>MainNavFragment</code> / other fragments.
All lists use RecyclerView + custom Adapter + ViewHolder	<code>HomeFragment</code> , <code>adapters/</code>	<code>onViewCreated</code> , <code>Adapter</code> methods	Transactions: <code>TransactionAdapter / item_transaction_row.xml</code> . Budgets: <code>BudgetAdapter / budget_card.xml</code> . Categories: <code>CategoryAdapter / item_category_cell.xml</code> .
Folders: Activities, Fragments, Adapters, Models	<code>app/src/main/java/com/smd/penni/</code>	Project Structure	Packages: <code>activities</code> , <code>fragments</code> , <code>adapters</code> , <code>models</code> .

Functional requirements

Requirement ID	Class / File Name	Function / Method	Implementation Description
F1 Intent navigation	<code>SplashActivity</code>	Continue button click handler	<code>Intent(MainActivity)</code> , <code>putExtra(NavExtras.EXTRA_DISPLAY_NAME, name)</code> , <code>startActivity</code> .

Requirement ID	Class / File Name	Function / Method	Implementation Description
F1 Receiving data	MainActivity	onCreate	<code>intent.getStringExtra(NavExtras.EXTRA_DISPLAY_NAME)</code> → <code>MainNavFragment.newInstance(name)</code> (Bundle arguments).
F2 Custom object via Bundle	models/Transaction.kt	Parcelable class	<code>@Parcelize</code> data class <code>Transaction</code> (Product/Task/Event-style domain object).
F2 Detail screen	TransactionDetailFragment	<code>newInstance</code> , <code>requireTransaction</code>	arguments with <code>putParcelable(NavExtras.ARG_TRANSACTION, transaction)</code> .
F2 From RecyclerView row	HomeFragment	TransactionAdapter lambda	<code>parentFragmentManager.commit :</code> <code>replace(R.id.main_nav_content,</code> <code>TransactionDetailFragment.newInstance(transaction)) ,</code> <code>addToBackStack</code> (nested under <code>MainNavFragment</code>).
F3 RecyclerView (vertical list)	HomeFragment , TransactionAdapter	<code>onViewCreated</code> , TransactionViewHolder	Vertical <code>transactions_list</code> , <code>item_transaction_row.xml</code> , <code>ViewHolder</code> in adapter.
F4 Tab fragments (no activity restart)	MainNavFragment	<code>selectTab</code>	<code>childFragmentManager.commit {</code> <code>replace(R.id.main_nav_content, fragment) }</code> for Home / Stats / Profile.
F4 Detail back stack	HomeFragment , TransactionDetailFragment	<code>addToBackStack</code> , Back button	Pops <code>childFragmentManager</code> back stack.
F5 Search / filter	HomeFragment	<code>applyFilters</code> , text watcher, spinner	Search text + category spinner filter the transaction <code>RecyclerView</code> .

GitHub / submission (process)

- Shared repo, pull before work, meaningful commits, merge conflict resolution.
- Submit: project ZIP, `logic_map.pdf` , repository link.