

USER MANUAL

BARC

Brain Atlas Regional Counter

Version 6.06 - Generated May 26, 2026

BARC is a specialized GUI application for analyzing immunofluorescence images. It enables researchers to overlay brain atlas sections, define regions of interest, perform automated cell counting, and export quantitative results.

Laing Lab

<https://github.com/LaingLab/BARC>

Table of Contents

1. Introduction	 3
2. Installation & Requirements	 4
3. Getting Started	 5
4. User Interface Overview	 6
5. File Menu	 7
6. Working with Atlas Sections	 8
7. Paint Tools for Regions of Interest	 10
8. Mask Settings & Cell Detection	 11
9. Manual Cell Editing	 14
10. Counting Cells & Exporting Results	 15
11. Saving & Export Options	 16
12. Keyboard Shortcuts	 17
13. Troubleshooting	 18

1. Introduction

BARC (Brain Atlas Regional Counter) is a specialized desktop application designed for researchers working with immunofluorescence (IF) microscopy images. It combines powerful image analysis tools with brain atlas registration to enable accurate, reproducible regional cell counting.

Purpose

The software allows users to overlay standardized atlas sections onto experimental TIFF images, define regions of interest through painting or atlas-based selection, apply sophisticated cell detection algorithms, and export quantitative results to Excel for further analysis.

Key Capabilities

- Import and display high-resolution TIFF images and multi-page PDF atlas files
- Interactive atlas alignment (translation, rotation, scaling)
- Freehand painting tools to define custom regions of interest
- Advanced, configurable cell detection with multiple thresholding methods
- Manual addition and removal of cells for quality control
- Automated cell counting within defined regions with Excel export
- Saving of annotated images and analysis sessions

NOTE

BARC is particularly valuable for neuroscience studies involving c-Fos, NeuN, or other cell-type specific markers where regional quantification relative to brain anatomy is required.

2. Installation & Requirements

System Requirements

- Windows 10 or later (primary supported platform)
- Python 3.8 or higher
- At least 8 GB RAM recommended for large images

Installation Steps

1. Clone the repository:

```
git clone https://github.com/LaingLab/BARC.git  
cd BARC
```

2. Install dependencies:

```
pip install -r requirements.txt
```

3. Launch the application:

```
cd regioner  
python regioner6.06.py
```

3. Getting Started

Upon launching BARC you are presented with a large central canvas area and a menu bar across the top. The typical workflow follows these steps:

- Import a TIFF image (File > Import TIFF)
- Import an atlas section PDF (File > Import Atlas Section)
- Align the atlas over your image using Move, Rotate, and Resize tools
- Define regions using either Paint tools or by clicking atlas regions
- Configure and preview cell detection parameters (Mask > Show Mask Settings)
- Run cell counting and review results
- Export data to Excel and save annotated images

4. User Interface Overview

The interface is intentionally minimal to maximize screen real estate for image viewing. All functionality is accessed through the top menu bar.

Main Canvas

The large central area displays your experimental image with the atlas overlay on top. You can pan using the scrollbars. Use the mouse wheel to zoom in and out. Zoom is centered on the mouse cursor and keeps painted regions, atlas overlays, and masks perfectly aligned with the background image at all zoom levels. When viewing cell masks (manual or automatic), a split view may appear for comparison.

Menus

File, Edit, Atlas, Paint, Mask, and Cell menus provide access to all features. Many operations also open small auxiliary windows for parameter adjustment.

5. File Menu

Import TIFF

Loads the primary experimental image. Supported formats include single and multi-page TIFFs. After import, the image is automatically scaled to fit the window while preserving aspect ratio.

Import Atlas Section

Opens a PDF file containing brain atlas plates. BARC uses PyMuPDF to render individual pages at high quality. You can navigate between pages of multi-plate PDFs.

Split Tiff

Utility for breaking apart stacked (multi-page) TIFF files into individual images. Useful when your source data contains multiple sections in one file.

Save Flattened Image

Exports a composite image containing both the original TIFF and the currently aligned atlas as a single JPEG. This is useful for figure preparation and record keeping.

Save Paint

Saves freehand painted regions to a reusable file format for later sessions.

6. Working with Atlas Sections

Accurate alignment of the atlas to your experimental image is critical for meaningful regional analysis. BARC provides several interactive tools for this purpose.

Move Atlas

Click and drag the atlas overlay to reposition it over the underlying image. This is the primary tool for coarse alignment.

Rotate

Enter a rotation angle in degrees and apply it. Positive values rotate clockwise. Useful for correcting slight angular differences between your sectioning plane and the atlas.

Resize / Scale

Apply uniform or axis-specific scaling. The Scale dialog also provides fine X and Y adjustment sliders for precise matching of anatomical landmarks.

Brightness & Contrast Adjustments

The atlas rendering can be lightened or darkened independently of the experimental image to improve visibility of boundaries during alignment.

NOTE

Best practice: Identify 3-4 reliable anatomical landmarks (e.g., ventricles, major fiber tracts, cortical boundaries) and align to those rather than trying to match the entire section at once.

7. Paint Tools for Regions of Interest

When the standard atlas regions do not match your experimental needs, the Paint tools allow completely custom region definition.

Start / Stop Paint

Activates freehand drawing mode. Draw directly on the image with the mouse.

Pen vs Eraser

Switch between adding area (Pen) and removing area (Eraser). Brush size is adjustable via the Brushsize dialog.

Import / Save Paint

Painted regions can be saved and reloaded in future sessions, enabling consistent analysis across multiple images or experiments.

Labeling Painted Regions

While in Paint mode (before clicking Stop Paint), you can right-click on any painted stroke to name it. BARC treats each continuous drawing action (mouse button down through release) as a single "structural boundary." All connected line segments belonging to that stroke are grouped together.

When you right-click a stroke:

- The entire connected group is highlighted in yellow for visual feedback.
- A dialog appears allowing you to enter or edit a name for the region.
- Named painted regions are converted into proper analysis zones when you click Stop Paint.
- These named regions participate in cell counting exactly like atlas regions and will appear in your results with the names you assigned.

NOTE

You can only label painted regions while the Paint mode is active (i.e., before you click "Stop Paint"). Once you stop painting, the strokes are committed to the persistent paint layer and the live canvas items used for naming are cleaned up.

8. Mask Settings & Cell Detection

This is the most powerful and configurable part of BARC. The Mask Settings dialog provides fine-grained control over every stage of the cell detection pipeline.

Threshold Methods

The Threshold Method controls how the image is converted to a binary (black and white) mask for cell detection. Four options are available:

- Otsu: Automatically determines the optimal global threshold using Otsu's method. Fast and effective on images with good contrast.
- Adaptive: Uses local areas to determine the threshold. Excellent for images with varying brightness across the field of view.
- Local: Similar to Adaptive but uses a different neighborhood computation. Useful when Adaptive produces too many or too few detections.
- Manual: Uses a fixed threshold value (0.0-1.0) that you specify. Provides maximum reproducibility across batches of images.

Cell Detection Parameters

These parameters control how individual cells are identified from the binary mask:

Manual Threshold

Range: 0.0 to 1.0. Only used when Threshold Method is "manual". Higher values make detection more selective (fewer cells). Lower values increase sensitivity.

Adaptive Block Size

Must be an odd integer (e.g. 51, 101, 151). Size of the local region used for adaptive thresholding. Larger values consider more surrounding area. Smaller values are more sensitive to local changes. Recommended range: 51-151 pixels.

Local Radius

Integer value (typically 5-30). Size of the neighborhood for the Local threshold method. Larger values smooth noise but may miss smaller cells.

Min Cell Size / Max Cell Size

Integer values in pixels. Define the acceptable size range for an object to be counted as a cell. Min Cell Size filters noise and small artifacts. Max Cell Size excludes clumps. Typical values depend on magnification (e.g. Min 20, Max

100-200).

Circularity Threshold

Range: 0.0 to 1.0. How circular a region must be to be accepted as a cell (1.0 = perfect circle). Higher values enforce rounder shapes. Typical value: 0.7.

Min Peak Distance

Integer value (pixels). Minimum distance required between detected cell centers. Helps prevent over-counting of touching cells. Typical values: 5-10 pixels.

Peak Min Intensity

Range: 0.0 to 1.0. Minimum brightness required for a local maximum to be considered a cell center. Higher values detect only brighter cells. Lower values detect dimmer cells. Typical starting value: 0.1.

Watershed Compactness

Range: 0.0 to 1.0. Controls how the watershed algorithm separates touching cells. Higher values favor more compact, rounder boundaries. Lower values follow intensity gradients more closely. Typical value: 0.0.

Base Multiplier & Sensitivity Range

Advanced sensitivity controls. Base Multiplier sets overall detection sensitivity (default ~1.1). Sensitivity Range controls how much the sensitivity slider can influence results (default 0.2).

Preprocessing Pipeline

A full preprocessing chain can be applied before cell detection. Each step can be enabled or disabled independently. The dialog only shows parameters relevant to the selected methods.

Background Method

Options: tophat or none. Controls removal of large-scale background variations. Tophat uses morphological operations and is generally recommended. When enabled, the Ball Radius (structural element size, default 15) controls how large-scale the background variations removed are.

Denoise Method

Options: gaussian, median, bilateral, or none. Reduces noise before detection.

- Gaussian: Applies a Gaussian blur (controlled by Gaussian Sigma, typically 0.1-5.0).
- Median: Better at preserving edges (controlled by Median Kernel size).
- Bilateral: Preserves edges while smoothing (controlled by Bilateral Sigma Color and Bilateral Sigma

Space).

Contrast Method

Options: stretch, clahe, gamma, or none. Enhances contrast before detection.

- Stretch: Simple linear contrast stretching.
- CLAHE (Contrast Limited Adaptive Histogram Equalization): Local contrast enhancement. Controlled by CLAHE Kernel (typically 8-16) and CLAHE Clip Limit (typically 1.0-4.0).
- Gamma: Gamma correction. Values < 1 brighten the image; values > 1 darken it.

Enhance Method

Currently supports Unsharp Mask sharpening. Controlled by Unsharp Radius (typically 0.1-5.0) and Unsharp Amount (strength of sharpening, typically 0.1-5.0). Useful for making cell boundaries crisper.

Both manual mask editing overlays (red) and automatic cell detection masks remain visible and correctly aligned when you zoom in or out using the mouse wheel.

NOTE

Start with the default settings and adjust one parameter at a time while using "Show Mask" to preview the binary detection result. This iterative approach is the fastest way to obtain high-quality cell counts.

Autotune Panel

The Mask Settings dialog includes a convenient Autotune panel with one-click adjustments for common goals. These buttons modify the live detection parameters and immediately reflect in the UI. When you click "Show Mask," the detection will use the updated values.

The available Autotune buttons are:

- More cells - Increases detection sensitivity (lowers size/intensity/circularity thresholds).
- Less cells - Decreases detection sensitivity (raises thresholds).
- Bigger cells - Favors larger objects by raising min/max cell size and compactness.
- Smaller cells - Favors smaller objects by lowering size thresholds.
- Brighter cells - Only detects stronger signals by raising peak intensity threshold.
- Dimmer cells - Detects weaker signals by lowering peak intensity threshold.

You can click any button multiple times for a stronger effect. The changes are applied to the current configuration and will be used the next time cell detection runs (via "Show Mask" or "Count Cells").

9. Manual Cell Editing

No automated detector is perfect. BARC provides direct manual editing tools so you can correct errors before counting.

Add / Remove Cells

- Add Cell - Click or paint to mark additional cells that the detector missed.
- Remove Cell - Erase false positives (dust, autofluorescence, etc.).
- Brush Size - Adjustable via the Brushsize control in the Paint menu.

Edits are applied to a separate overlay mask and can be toggled on and off for comparison. All manual edits are included in the final cell count.

10. Counting Cells & Exporting Results

Once regions are defined and detection parameters are tuned, click "Count Cells" under the Cell menu.

BARC will compute the number of detected cells within each named region and present a summary. You will be prompted to save the results as an Excel (.xlsx) file containing:

- Region name
- Cell count
- Region area (pixels)
- Cell density (if applicable)

The Excel file is the primary deliverable for statistical analysis and figure preparation.

11. Saving & Export Options

- Flattened Image (JPEG) - Final figure-ready composite of image + atlas + annotations
- Paint files - Reusable region definitions
- Excel results - Quantitative data for downstream analysis

12. Keyboard Shortcuts

Shortcut	Action
Ctrl + Z	Undo last action (move, rotate, paint, highlight, etc.)
Ctrl + S	Save flattened image

13. Troubleshooting

Common Issues

- Cells not detected: Try lowering Peak Min Intensity or switching to Adaptive threshold.
- Too many false positives: Increase Min Cell Size and Circularity Threshold.
- Atlas looks blurry: Re-render at higher zoom or adjust brightness settings.
- Performance is slow: Close other applications; very large images benefit from 16 GB+ RAM.

Getting Help

For bugs or feature requests, please open an issue on the GitHub repository:

<https://github.com/LaingLab/BARC>

Thank you for using BARC

We hope this software accelerates your research. Feedback and contributions are always welcome.