PrepPressure — Task Package v3 (Users + Authentication)

This package replaces the v2 PDF package. The project now has **user accounts and JWT authentication**. Every backend endpoint requires a token except `register` and `login`. Users create **questions** and **interviews** that all other users can see, but **only the owner can edit or delete** them. Any user can **take** an interview (an *attempt*), get a **result page** for each attempt, and has a **profile page** with statistics. The backend serves a **Swagger page at `/docs`** where every endpoint can be tested with a token.

Files in this package

File	What it is	Commit it as
`01_Master_Project_Specification.md`	What the app does, data model, rules, scoring	`docs/SPECIFICATION.md`
`02_API_CONTRACT.md`	**Frozen** endpoint, request, response, error and storage contract	`docs/API-CONTRACT.md`
`03_Team_Coordination.md`	Ownership map, the "no waiting" rules, Git workflow, integration day	`docs/TEAM-OWNERSHIP.md`
`04_Laith_Tasks.md`	Frontend shell, auth pages, take-interview, results, profile	—

File	What it is	Commit it as
`05_Esmaeel_Tasks.md`	Backend attempts: timing, answers, scoring, results	—
`06_Badr_Tasks.md`	Backend platform, auth, users, profile stats, Swagger `/docs`	—
`07_Shiam_Tasks.md`	Backend questions + interviews modules, test plan, full-flow test	—
`08_Adham_Tasks.md`	Frontend questions + interviews pages	—

Hassan has no tasks assigned while unavailable.

How the "nobody waits" design works (short version)

1. The API contract (`02`) is **frozen before anyone codes**. It fixes every URL, field name, error code, MongoDB collection name and stored document shape. Everyone codes against the contract, not against each other's code.
2. **Every file has exactly one owner.** No two people edit the same file. The only exception is a single registration line (see `03` , section 3) added at merge time.
3. Backend modules never import each other. When one module needs another's data it reads the MongoDB collection by its contract name. Authentication is a **global guard**, so other modules don't import it either.
4. Frontend features never import each other. Each feature has its own API file and types copied from the contract, and its own mock data so it works before the backend exists.
5. Each person tests their own module alone (backend tests replace the auth guard with a fake one; frontend uses mocks).

Important note before starting

The old master spec said the teacher's specification is the top authority, and it said **accounts were not allowed**. This v3 adds accounts on purpose. **Confirm with the teacher that this change is accepted** before the team starts. The other course rules are kept: no Mongoose `populate`, no aggregation pipelines, numeric public IDs, no code execution, no secrets in Git.