1. Employee Salary Initialization

```
import java.util.*;
class Employee {
   int empId;
   String empName;
   int salary;
   Employee(int id, String name, int sa) {
      empId = id;
      empName = name;
      salary = sa;
   }
   void displayEmployee() {
      System.out.println("Employee id is: " + empId);
      System.out.println("Employee name is: " + empName);
      System.out.println("Employee salary is: " + salary);
   }
   public static void main(String[] args) {
      Employee de = new Employee(1, "Lajitha", 50000);
      de.displayEmployee();
   }
}
```

2.) **Product Price Calculation**

```
import java.util.*;
```

```
class Product {
    int productId;
    String productName;
    int price;
    double quantity;
    Product(int id, String n, int p, double q) {
        productId = id;
        productName = n;
        price = p;
        quantity = q;
    }
    void calculateTotalPrice() {
        double totalPrice = price * quantity;
        System.out.println("Product Id : " + productId);
        System.out.println("Product Name : " + productName);
        System.out.println("Price : " + price);
        System.out.println("Quantity : " + quantity);
        System.out.println("Total Price : " + totalPrice);
    }
    public static void main(String[] args) {
        Product p = new Product(1, "Laptop", 50000, 1);
        p.calculateTotalPrice();
    }
}
```

3. Student Grade System

```
import java.util.*;
class Student {
  int studentId;
  String studentName;
  int marks;
  Student(int id,String n,int m){
     studentId=id;
     studentName=n;
     marks=m;
  }
  void calculateGrade(){
     if(marks>=90){
        System.out.println("Grade A");
     }
     else if(marks >= 75){
        System.out.println("Grade B");
  }
     else if(marks >= 50){
         System.out.println("Grade C");
         }
     else{
         System.out.println("Fail");
     }
}
```

```
    public static void main(String[] args) {
      Student s1=new Student(1,"Lajitha",85);
      Student s2=new Student(2,"Suba",95);
       Student s3=new Student(3,"Singam",75);
        Student s4=new Student(4,"Meenu",65);
         Student s5=new Student(5,"Suzy",45);

       s1.calculateGrade();
        s2.calculateGrade();
         s3.calculateGrade();
          s4.calculateGrade();
           s5.calculateGrade();
    }
}
```

4. Bank Account Deposit Scenario

```
import java.util.*;
class BankAccount {
    int accountNumber;
    String accountHolderName;
    double balance;
    BankAccount(int ac_no, String ac_name, double b) {
        accountNumber = ac_no;
        accountHolderName = ac_name;
        balance = b;
    }
```

```
    void deposit(double amount) {
        balance = balance + amount;
        System.out.println("Deposit Amount: " + amount);
    }
    void displayBalance() {
        System.out.println("Account Number: " + accountNumber);
        System.out.println("Account Holder Name: " + accountHolderName);
        System.out.println("Balance: " + balance);
    }
    public static void main(String[] args) {
        BankAccount ba = new BankAccount(101, "Lajitha", 5000);
        ba.deposit(1000);
        ba.displayBalance();
    }
}
```