Easy

Table: Products

```
+------------------+---------+
| Column Name      | Type    |
+------------------+---------+
| product_id       | int     |
| product_name     | varchar |
| product_category | varchar |
+------------------+---------+
```
product_id is the primary key (column with unique values) for this table.
This table contains data about the company's products.

Table: Orders

```
+---------------+---------+
| Column Name   | Type    |
+---------------+---------+
| product_id    | int     |
| order_date    | date    |
| unit          | int     |
+---------------+---------+
```
This table may have duplicate rows.
product_id is a foreign key (reference column) to the Products table.
unit is the number of products ordered in order_date.

Write a solution to get the names of products that have at least 100 units ordered in **February 2020** and their amount.

Return the result table in **any order**.

The result format is in the following example.

Example 1:

Input:
Products table:
```
+-------------+-----------------------+------------------+
| product_id  | product_name          | product_category |
+-------------+-----------------------+------------------+
| 1           | Leetcode Solutions    | Book             |
| 2           | Jewels of Stringology | Book             |
| 3           | HP                    | Laptop           |
| 4           | Lenovo                | Laptop           |
| 5           | Leetcode Kit          | T-shirt          |
+-------------+-----------------------+------------------+
```
Orders table:
```
+--------------+--------------+----------+
| product_id   | order_date   | unit     |
+--------------+--------------+----------+
| 1            | 2020-02-05   | 60       |
| 1            | 2020-02-10   | 70       |
| 2            | 2020-01-18   | 30       |
| 2            | 2020-02-11   | 80       |
| 3            | 2020-02-17   | 2        |
```

3	2020-02-24	3
4	2020-03-01	20
4	2020-03-04	30
4	2020-03-04	60
5	2020-02-25	50
5	2020-02-27	50
5	2020-03-01	50

Output:

product_name	unit
Leetcode Solutions	130
Leetcode Kit	100

Explanation:

Products with product_id = 1 is ordered in February a total of (60 + 70) = 130.
Products with product_id = 2 is ordered in February a total of 80.
Products with product_id = 3 is ordered in February a total of (2 + 3) = 5.
Products with product_id = 4 was not ordered in February 2020.
Products with product_id = 5 is ordered in February a total of (50 + 50) = 100.

```
# Write your MySQL query statement below
SELECT product_name,SUM(unit) AS unit
FROM Products
JOIN Orders USING (product_id)
WHERE order_date BETWEEN '2020-02-01' AND '2020-02-29'
GROUP BY product_name
HAVING unit>=100;
```