Easy

Table: Activity

++
Column Name Type
++
machine_id int
process_id int
activity_type enum
timestamp float
+ + +

The table shows the user activities for a factory website.

(machine_id, process_id, activity_type) is the primary key (combination of columns with unique values) of this table.

machine id is the ID of a machine.

process id is the ID of a process running on the machine with ID machine id.

activity type is an ENUM (category) of type ('start', 'end').

timestamp is a float representing the current time in seconds.

'start' means the machine starts the process at the given timestamp and 'end' means the machine ends the process at the given timestamp.

The 'start' timestamp will always be before the 'end' timestamp for every (machine id, process id) pair.

There is a factory website that has several machines each running the **same number of processes**. Write a solution to find the **average time** each machine takes to complete a process.

The time to complete a process is the 'end' timestamp minus the 'start' timestamp. The average time is calculated by the total time to complete every process on the machine divided by the number of processes that were run.

The resulting table should have the machine_id along with the **average time** as processing_time, which should be **rounded to 3 decimal places**.

Return the result table in any order.

The result format is in the following example.

Example 1:

Input:

Activity table:

```
| machine_id | process_id | activity_type | timestamp |
0
       0
               start
                        0.712
                         | 1.520
0
       0
               end
0
       | 1
               start
                        3.140
0
       | 1
               end
                        4.120
1
       0
               start
                       0.550
       0
                        1.550
1
               end
       | 1
               start
                       0.430
1
1
       | 1
               end
                        1.420
2
       0
               start
                        4.100
2
        0
               end
                        4.512
2
       1
               start
                        2.500
2
               end
       | 1
                        | 5.000
```

```
+-----+
Output:
| machine_id | processing_time |
+----+
       0.894
       0.995
      1.456
Explanation:
There are 3 machines running 2 processes each.
Machine 0's average time is ((1.520 - 0.712) + (4.120 - 3.140)) / 2 = 0.894
Machine 1's average time is ((1.550 - 0.550) + (1.420 - 0.430)) / 2 = 0.995
Machine 2's average time is ((4.512 - 4.100) + (5.000 - 2.500)) / 2 = 1.456
# Write your MySQL query statement below
SELECT
  al.machine id,
  ROUND(AVG(a2.timestamp -a1.timestamp),3)AS processing time
FROM Activity a1
JOIN Activity a2 ON
  a1.machine id = a2.machine id
  AND al. process id = a2. process id
  AND al.activity type = 'start'
  AND a2.activity type = 'end'
GROUP BY a1.machine id;
```