

CS 3.307

# Performance Modeling for Computer Systems

**Tejas Bodas**

Assistant Professor, IIIT Hyderabad

# Markov Process

# Markov Process

- ▶ There are two versions of Markov chains- Discrete time and Continuous time.

# Markov Process

- ▶ There are two versions of Markov chains- Discrete time and Continuous time.
- ▶ A stochastic process  $\{X_n, n \in \mathbb{Z}_+\}$  is a discrete time Markov chain if for any  $n_1 < n_2 < \dots < n_k < n$ ,

$$P(X_n = j | X_{n_1} = x_1, \dots, X_{n_k} = i) = P(X_n = j | X_{n_k} = i)$$

# Markov Process

- ▶ There are two versions of Markov chains- Discrete time and Continuous time.
- ▶ A stochastic process  $\{X_n, n \in \mathbb{Z}_+\}$  is a discrete time Markov chain if for any  $n_1 < n_2 < \dots < n_k < n$ ,

$$P(X_n = j | X_{n_1} = x_1, \dots, X_{n_k} = i) = P(X_n = j | X_{n_k} = i)$$

- ▶  $\{X(t), t \geq 0\}$  is a Markov process (ctmc) if for  $t_1 < t_2 < \dots < t_n < t$ ,

$$P(X(t) = j | X(t_1) = x_1, \dots, X(t_n) = i) = P(X(t) = j | X(t_n) = i)$$

# Markov Process

- ▶ There are two versions of Markov chains- Discrete time and Continuous time.
- ▶ A stochastic process  $\{X_n, n \in \mathbb{Z}_+\}$  is a discrete time Markov chain if for any  $n_1 < n_2 < \dots < n_k < n$ ,

$$P(X_n = j | X_{n_1} = x_1, \dots, X_{n_k} = i) = P(X_n = j | X_{n_k} = i)$$

- ▶  $\{X(t), t \geq 0\}$  is a Markov process (ctmc) if for  $t_1 < t_2 < \dots < t_n < t$ ,

$$P(X(t) = j | X(t_1) = x_1, \dots, X(t_n) = i) = P(X(t) = j | X(t_n) = i)$$

- ▶ This is known as the Markov property.

# Markov Process

- ▶ There are two versions of Markov chains- Discrete time and Continuous time.
- ▶ A stochastic process  $\{X_n, n \in \mathbb{Z}_+\}$  is a discrete time Markov chain if for any  $n_1 < n_2 < \dots < n_k < n$ ,

$$P(X_n = j | X_{n_1} = x_1, \dots, X_{n_k} = i) = P(X_n = j | X_{n_k} = i)$$

- ▶  $\{X(t), t \geq 0\}$  is a Markov process (ctmc) if for  $t_1 < t_2 < \dots < t_n < t$ ,

$$P(X(t) = j | X(t_1) = x_1, \dots, X(t_n) = i) = P(X(t) = j | X(t_n) = i)$$

- ▶ This is known as the Markov property.
- ▶ State space in both cases can be integers or general  $(\mathbb{R}^d)$

# Markov Process

- ▶ There are two versions of Markov chains- Discrete time and Continuous time.
- ▶ A stochastic process  $\{X_n, n \in \mathbb{Z}_+\}$  is a discrete time Markov chain if for any  $n_1 < n_2 < \dots < n_k < n$ ,

$$P(X_n = j | X_{n_1} = x_1, \dots, X_{n_k} = i) = P(X_n = j | X_{n_k} = i)$$

- ▶  $\{X(t), t \geq 0\}$  is a Markov process (ctmc) if for  $t_1 < t_2 < \dots < t_n < t$ ,

$$P(X(t) = j | X(t_1) = x_1, \dots, X(t_n) = i) = P(X(t) = j | X(t_n) = i)$$

- ▶ This is known as the Markov property.
- ▶ State space in both cases can be integers or general  $(\mathbb{R}^d)$
- ▶ We will stick with integer or finite state space



Example: Coin with memory!

## Example: Coin with memory!

- ▶ In a Markovian coin with memory, the outcome of the next toss depends on the current toss.

## Example: Coin with memory!

- ▶ In a Markovian coin with memory, the outcome of the next toss depends on the current toss.
- ▶  $X_n = 1$  for heads and  $X_n = -1$  otherwise.  $\mathcal{S} = \{+1, -1\}$ .

## Example: Coin with memory!

- ▶ In a Markovian coin with memory, the outcome of the next toss depends on the current toss.
- ▶  $X_n = 1$  for heads and  $X_n = -1$  otherwise.  $\mathcal{S} = \{+1, -1\}$ .
- ▶ Sticky coin :  $P(X_{n+1} = 1|X_n = 1) = 0.9$  and  $P(X_{n+1} = -1|X_n = -1) = 0.8$  for all  $n$ .

## Example: Coin with memory!

- ▶ In a Markovian coin with memory, the outcome of the next toss depends on the current toss.
- ▶  $X_n = 1$  for heads and  $X_n = -1$  otherwise.  $\mathcal{S} = \{+1, -1\}$ .
- ▶ Sticky coin :  $P(X_{n+1} = 1|X_n = 1) = 0.9$  and  $P(X_{n+1} = -1|X_n = -1) = 0.8$  for all  $n$ .
- ▶ Flippy Coin:  $P(X_{n+1} = 1|X_n = 1) = 0.1$  while  $P(X_{n+1} = -1|X_n = -1) = 0.3$  for all  $n$ .

## Example: Coin with memory!

- ▶ In a Markovian coin with memory, the outcome of the next toss depends on the current toss.
- ▶  $X_n = 1$  for heads and  $X_n = -1$  otherwise.  $\mathcal{S} = \{+1, -1\}$ .
- ▶ Sticky coin :  $P(X_{n+1} = 1|X_n = 1) = 0.9$  and  $P(X_{n+1} = -1|X_n = -1) = 0.8$  for all  $n$ .
- ▶ Flippy Coin:  $P(X_{n+1} = 1|X_n = 1) = 0.1$  while  $P(X_{n+1} = -1|X_n = -1) = 0.3$  for all  $n$ .
- ▶ This can be represented by a transition diagram (see board)

## Example: Coin with memory!

- ▶ In a Markovian coin with memory, the outcome of the next toss depends on the current toss.
- ▶  $X_n = 1$  for heads and  $X_n = -1$  otherwise.  $\mathcal{S} = \{+1, -1\}$ .
- ▶ Sticky coin :  $P(X_{n+1} = 1|X_n = 1) = 0.9$  and  $P(X_{n+1} = -1|X_n = -1) = 0.8$  for all  $n$ .
- ▶ Flippy Coin:  $P(X_{n+1} = 1|X_n = 1) = 0.1$  while  $P(X_{n+1} = -1|X_n = -1) = 0.3$  for all  $n$ .
- ▶ This can be represented by a transition diagram (see board)
- ▶ The transition probability matrix  $P$  for the two cases is
$$P_s = \begin{bmatrix} 0.9 & .1 \\ 0.2 & 0.8 \end{bmatrix} \text{ and } P_f = \begin{bmatrix} 0.1 & 0.9 \\ 0.7 & 0.3 \end{bmatrix}$$

## Example: Coin with memory!

- ▶ In a Markovian coin with memory, the outcome of the next toss depends on the current toss.
- ▶  $X_n = 1$  for heads and  $X_n = -1$  otherwise.  $\mathcal{S} = \{+1, -1\}$ .
- ▶ Sticky coin :  $P(X_{n+1} = 1|X_n = 1) = 0.9$  and  $P(X_{n+1} = -1|X_n = -1) = 0.8$  for all  $n$ .
- ▶ Flippy Coin:  $P(X_{n+1} = 1|X_n = 1) = 0.1$  while  $P(X_{n+1} = -1|X_n = -1) = 0.3$  for all  $n$ .
- ▶ This can be represented by a transition diagram (see board)
- ▶ The transition probability matrix  $P$  for the two cases is
$$P_s = \begin{bmatrix} 0.9 & .1 \\ 0.2 & 0.8 \end{bmatrix} \text{ and } P_f = \begin{bmatrix} 0.1 & 0.9 \\ 0.7 & 0.3 \end{bmatrix}$$
- ▶ The row corresponds to present state and the column corresponds to next state.



Running example: Dice with memory!

# Running example: Dice with memory!

- ▶ In a markovian dice with memory, the outcome of the next roll depends on the current roll.

# Running example: Dice with memory!

- ▶ In a markovian dice with memory, the outcome of the next roll depends on the current roll.
- ▶  $X_n = i$  for  $i \in \mathcal{S}$  where  $\mathcal{S} = \{1, \dots, 6\}$ .

# Running example: Dice with memory!

- ▶ In a markovian dice with memory, the outcome of the next roll depends on the current roll.
- ▶  $X_n = i$  for  $i \in \mathcal{S}$  where  $\mathcal{S} = \{1, \dots, 6\}$ .
- ▶ Example transition probability matrix

$$P = \begin{bmatrix} 0.9 & .1 & 0 & 0 & 0 & 0 \\ 0 & .9 & .1 & 0 & 0 & 0 \\ 0 & 0 & 0.9 & 0.1 & 0 & 0 \\ 0 & 0 & 0 & 0.9 & 0.1 & 0 \\ 0 & 0 & 0 & 0 & 0.9 & 0.1 \\ 0.1 & 0 & 0 & 0 & 0 & 0.9 \end{bmatrix}$$

# Running example: Dice with memory!

- ▶ In a markovian dice with memory, the outcome of the next roll depends on the current roll.
- ▶  $X_n = i$  for  $i \in \mathcal{S}$  where  $\mathcal{S} = \{1, \dots, 6\}$ .

- ▶ Example transition probability matrix

$$P = \begin{bmatrix} 0.9 & .1 & 0 & 0 & 0 & 0 \\ 0 & .9 & .1 & 0 & 0 & 0 \\ 0 & 0 & 0.9 & 0.1 & 0 & 0 \\ 0 & 0 & 0 & 0.9 & 0.1 & 0 \\ 0 & 0 & 0 & 0 & 0.9 & 0.1 \\ 0.1 & 0 & 0 & 0 & 0 & 0.9 \end{bmatrix}$$

- ▶ In the ctmc counterpart for these examples, imagine the coin tosses itself/ dice rolls itself after waiting in the state for a random time that is exponentially distributed. (more later)

# Time-homogenous Markov Process

- ▶ A DTMC is said to be time homogeneous if the one step transition probabilities are same at all time.

# Time-homogenous Markov Process

- ▶ A DTMC is said to be time homogeneous if the one step transition probabilities are same at all time.
- ▶  $P(X_{n+1} = j | X_n = i) = P(X_{n+1+s} = j | X_{n+s} = i) := p_{ij}$

# Time-homogenous Markov Process

- ▶ A DTMC is said to be time homogeneous if the one step transition probabilities are same at all time.
- ▶  $P(X_{n+1} = j | X_n = i) = P(X_{n+1+s} = j | X_{n+s} = i) := p_{ij}$
- ▶ One step transition probability matrix  $P = [[p_{ij}]]$



# Time-homogenous Markov Process

- ▶ A DTMC is said to be time homogeneous if the one step transition probabilities are same at all time.
- ▶  $P(X_{n+1} = j | X_n = i) = P(X_{n+1+s} = j | X_{n+s} = i) := p_{ij}$
- ▶ One step transition probability matrix  $P = [[p_{ij}]]$
- ▶  $i, j \in \mathcal{S}$  which is countable and  $|\mathcal{S}| \leq \infty$

For a CTMC ...

## For a CTMC ...

- For a time homogeneous CTMC, we have

$$\begin{aligned} P(X(t) = j | X(t_n) = i) &= P(X(t + s) = j | X(t_n + s) = i) \\ &= P(X(t - t_n) = j | X(0) = i). \end{aligned}$$

## For a CTMC ...

- ▶ For a time homogeneous CTMC, we have

$$\begin{aligned} P(X(t) = j | X(t_n) = i) &= P(X(t + s) = j | X(t_n + s) = i) \\ &= P(X(t - t_n) = j | X(0) = i). \end{aligned}$$

- ▶ We have a transition probability matrix with entries  $p_{ij}(t)$ , i.e.,  $P(t) = [[p_{ij}(t)]]$ .

# DTMC – Time spent in a state

## DTMC – Time spent in a state

- ▶ For a time homogeneous DTMC, we have a transition probability matrix with entries  $p_{ij}$ , i.e.,  $P = [[p_{ij}]]$ .

## DTMC – Time spent in a state

- ▶ For a time homogeneous DTMC, we have a transition probability matrix with entries  $p_{ij}$ , i.e.,  $P = [[p_{ij}]]$ .
- ▶ Let  $Y_n = \inf \{s > 0 : X_{n+s} \neq X_n\}$

# DTMC – Time spent in a state

- ▶ For a time homogeneous DTMC, we have a transition probability matrix with entries  $p_{ij}$ , i.e.,  $P = [[p_{ij}]]$ .
- ▶ Let  $Y_n = \inf \{s > 0 : X_{n+s} \neq X_n\}$
- ▶  $Y_n$  is the remaining time that the process spends in whichever state it is in, at time  $n$ .



# DTMC – Time spent in a state

- ▶ For a time homogeneous DTMC, we have a transition probability matrix with entries  $p_{ij}$ , i.e.,  $P = [[p_{ij}]]$ .
- ▶ Let  $Y_n = \inf \{s > 0 : X_{n+s} \neq X_n\}$
- ▶  $Y_n$  is the remaining time that the process spends in whichever state it is in, at time  $n$ .
- ▶ Consider a Markov coin, its state transition matrix and diagram

# DTMC – Time spent in a state

- ▶ For a time homogeneous DTMC, we have a transition probability matrix with entries  $p_{ij}$ , i.e.,  $P = [[p_{ij}]]$ .
- ▶ Let  $Y_n = \inf \{s > 0 : X_{n+s} \neq X_n\}$
- ▶  $Y_n$  is the remaining time that the process spends in whichever state it is in, at time  $n$ .
- ▶ Consider a Markov coin, its state transition matrix and diagram
- ▶  $Y_n$  is geometric random variable.

# DTMC – Time spent in a state

- ▶ For a time homogeneous DTMC, we have a transition probability matrix with entries  $p_{ij}$ , i.e.,  $P = [[p_{ij}]]$ .
- ▶ Let  $Y_n = \inf \{s > 0 : X_{n+s} \neq X_n\}$
- ▶  $Y_n$  is the remaining time that the process spends in whichever state it is in, at time  $n$ .
- ▶ Consider a Markov coin, its state transition matrix and diagram
- ▶  $Y_n$  is geometric random variable.
- ▶ What would be the time spent in a state for a continuous time Markov chain ?

# CTMC – Time spent in a state

## CTMC – Time spent in a state

- ▶ For a time homogeneous CTMC, we have a transition probability matrix with entries  $p_{ij}(t)$ , i.e.,  $P(t) = [[p_{ij}(t)]]$ .

## CTMC – Time spent in a state

- ▶ For a time homogeneous CTMC, we have a transition probability matrix with entries  $p_{ij}(t)$ , i.e.,  $P(t) = [[p_{ij}(t)]]$ .
- ▶ Let  $Y_t = \inf\{s > 0 : X(t + s) \neq X(t)\}$

## CTMC – Time spent in a state

- ▶ For a time homogeneous CTMC, we have a transition probability matrix with entries  $p_{ij}(t)$ , i.e.,  $P(t) = [[p_{ij}(t)]]$ .
- ▶ Let  $Y_t = \inf\{s > 0 : X(t + s) \neq X(t)\}$
- ▶  $Y_t$  is the remaining time that the process spends in whichever state it is in, at time  $t$ .

## CTMC – Time spent in a state

- ▶ For a time homogeneous CTMC, we have a transition probability matrix with entries  $p_{ij}(t)$ , i.e.,  $P(t) = [[p_{ij}(t)]]$ .
- ▶ Let  $Y_t = \inf\{s > 0 : X(t + s) \neq X(t)\}$
- ▶  $Y_t$  is the remaining time that the process spends in whichever state it is in, at time  $t$ .
- ▶ Intuitively, the time spent in a state should depend only on what state it is in, and not on the previous state.



# CTMC – Time spent in a state

- ▶ For a time homogeneous CTMC, we have a transition probability matrix with entries  $p_{ij}(t)$ , i.e.,  $P(t) = [[p_{ij}(t)]]$ .
- ▶ Let  $Y_t = \inf\{s > 0 : X(t + s) \neq X(t)\}$
- ▶  $Y_t$  is the remaining time that the process spends in whichever state it is in, at time  $t$ .
- ▶ Intuitively, the time spent in a state should depend only on what state it is in, and not on the previous state.

## Theorem

$$P(Y_t > u | X(t) = i) := \bar{G}_i(u) = e^{-a_i u}$$

for all  $i \in S$  and  $t \geq 0, u \geq 0$  and for some real number  $a_i \in [0, \infty]$ .

# Proof 1

## Proof 1

►  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$

## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$

## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$
- ▶  $P(AB|C) = P(A|BC)P(B|C)$

## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$
- ▶  $P(AB|C) = P(A|BC)P(B|C)$
- ▶ Due to Markov property we have  $P(AB|C) = P(A|B)P(B|C)$

## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$
- ▶  $P(AB|C) = P(A|BC)P(B|C)$
- ▶ Due to Markov property we have  $P(AB|C) = P(A|B)P(B|C)$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(p) = i, p \in [t, t + u]) =$

## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$
- ▶  $P(AB|C) = P(A|BC)P(B|C)$
- ▶ Due to Markov property we have  $P(AB|C) = P(A|B)P(B|C)$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(p) = i, p \in [t, t + u]) =$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(t + u) = i) = \bar{G}_i(v)$



## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$
- ▶  $P(AB|C) = P(A|BC)P(B|C)$
- ▶ Due to Markov property we have  $P(AB|C) = P(A|B)P(B|C)$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(p) = i, p \in [t, t + u]) =$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(t + u) = i) = \bar{G}_i(v)$
- ▶  $P(X(p) = i, p \in [t, t + u] | X(t) = i) = \bar{G}_i(u)$

## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$
- ▶  $P(AB|C) = P(A|BC)P(B|C)$
- ▶ Due to Markov property we have  $P(AB|C) = P(A|B)P(B|C)$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(p) = i, p \in [t, t + u]) =$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(t + u) = i) = \bar{G}_i(v)$
- ▶  $P(X(p) = i, p \in [t, t + u] | X(t) = i) = \bar{G}_i(u)$
- ▶  $\bar{G}_i(u + v) = \bar{G}_i(u)\bar{G}_i(v)$

## Proof 1

- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t, t + u + v] | X(t) = i)$
- ▶  $\bar{G}_i(u + v) = P(X(s) = i, s \in [t + u, t + u + v]; X(p) = i, p \in [t, t + u] | X(t) = i)$
- ▶  $P(AB|C) = P(A|BC)P(B|C)$
- ▶ Due to Markov property we have  $P(AB|C) = P(A|B)P(B|C)$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(p) = i, p \in [t, t + u]) =$
- ▶  $P(X(s) = i, s \in [t + u, t + u + v] | X(t + u) = i) = \bar{G}_i(v)$
- ▶  $P(X(p) = i, p \in [t, t + u] | X(t) = i) = \bar{G}_i(u)$
- ▶  $\bar{G}_i(u + v) = \bar{G}_i(u)\bar{G}_i(v)$
- ▶ Only CCDF function which satisfies this equation is the exponential distribution. This requires a proof. We will skip this part.