LAB-7
OUTPUT

```
   CREATE DATABASE SUPPLIER;


CREATE TABLE SUPPLIERS(SID BIGINT(5) PRIMARY KEY, SNAME
VARCHAR(20), CITY VARCHAR(20));
INSERT INTO SUPPLIERS VALUES(10001,'ACME WIDGET','BANGALORE');
INSERT INTO SUPPLIERS VALUES(10002,'JOHNS ','KOLKATA');
INSERT INTO SUPPLIERS VALUES(10003,'VIMAL','MUMBAI');
INSERT INTO SUPPLIERS VALUES(10004,'RELIANCE ','DELHI');
SELECT * FROM SUPPLIERS;
CREATE TABLE PARTS(PID BIGINT(5) PRIMARY KEY, PNAME VARCHAR(20),
COLOR VARCHAR(10));
INSERT INTO PARTS VALUES(20001,'BOOK','RED');
INSERT INTO PARTS VALUES(20002,'PEN','RED');
INSERT INTO PARTS VALUES(20003,'PENCIL','GREEN');
INSERT INTO PARTS VALUES(20004,'MOBILE ','GREEN');
INSERT INTO PARTS VALUES(20005,'CHARGER','BLACK');
SELECT * FROM PARTS;
CREATE TABLE CATALOG(SID BIGINT(5), PID BIGINT(5), FOREIGN KEY(SID)
REFERENCES SUPPLIERS(SID), FOREIGN KEY(PID) REFERENCES PARTS(PID),
COST FLOAT(6), PRIMARY KEY(SID, PID));
INSERT INTO CATALOG VALUES(10001,20001,10);
INSERT INTO CATALOG VALUES(10001,20002,10);
INSERT INTO CATALOG VALUES(10001,20003,30);
INSERT INTO CATALOG VALUES(10001,20004,10);
INSERT INTO CATALOG VALUES(10001,20005,10);
INSERT INTO CATALOG VALUES(10002,20001,10);
INSERT INTO CATALOG VALUES(10002,20002,20);
INSERT INTO CATALOG VALUES(10003,20003,30);
INSERT INTO CATALOG VALUES(10004,20003,40);
SELECT * FROM CATALOG;
```

```sql
/* 1 - FIND THE PNAMES OF PARTS FOR WHICH THERE IS SOME SUPPLIER. */
SELECT DISTINCT P.PNAME
FROM PARTS P, CATALOG C
WHERE P.PID = C.PID;


/* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY PART */
SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM
PARTS P WHERE NOT EXISTS (SELECT C.SID FROM CATALOG C WHERE C.SID =
S.SID AND C.PID = P.PID));


/* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY RED PART. */
SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM
PARTS P WHERE P.COLOR = 'RED' AND (NOT EXISTS (SELECT C.SID FROM
CATALOG C WHERE C.SID = S.SID AND C.PID = P.PID)));


/* FIND THE PNAMES OF PARTS SUPPLIED BY ACME WIDGET SUPPLIERS AND BY NO ONE
ELSE */
SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID
= C.PID AND C.SID = S.SID AND S.SNAME = 'ACME WIDGET' AND NOT EXISTS
(SELECT * FROM CATALOG C1, SUPPLIERS S1 WHERE P.PID = C1.PID AND
C1.SID = S1.SID AND S1.SNAME <> 'ACME WIDGET');


/* FIND THE SIDS OF SUPPLIERS WHO CHARGE MORE FOR SOME PART THAN THE AVERAGE
COST OF THAT PART (AVERAGED OVER
ALL THE SUPPLIERS WHO SUPPLY THAT PART).
*/
SELECT DISTINCT C.SID FROM CATALOG C
WHERE C.COST > ( SELECT AVG (C1.COST)
FROM CATALOG C1
WHERE C1.PID = C.PID );
```

```
/* FOR EACH PART, FIND THE SNAME OF THE SUPPLIER WHO CHARGES THE MOST FOR
THAT PART.*/
SELECT P.PID, S.SNAME

FROM PARTS P, SUPPLIERS S, CATALOG C

WHERE C.PID = P.PID

AND C.SID = S.SID

AND C.COST = (SELECT MAX(C1.COST)

FROM CATALOG C1

WHERE C1.PID = P.PID);



/* FIND THE SIDS OF SUPPLIERS WHO SUPPLY ONLY RED PARTS.*/
SELECT DISTINCT C.SID

FROM CATALOG C

WHERE NOT EXISTS ( SELECT *

FROM PARTS P

WHERE P.PID = C.PID AND P.COLOR <> 'RED' );
```

movie × | airline × | SUPPLIERS ×

File Edit View Query Database Server Tools Scripting Help

Query 1 ×

Limit to 1000 rows

```
13   INSERT INTO PARTS VALUES(20002,'PEN','RED');
14   INSERT INTO PARTS VALUES(20003,'PENCIL','GREEN');
15   INSERT INTO PARTS VALUES(20004,'MOBILE ','GREEN');
16   INSERT INTO PARTS VALUES(20005,'CHARGER','BLACK');
17   SELECT * FROM PARTS;
18   CREATE TABLE CATALOG(SID BIGINT(5), PID BIGINT(5), FOREIGN KEY(SID)
19       REFERENCES SUPPLIERS(SID), FOREIGN KEY(PID) REFERENCES PARTS(PID),
20       COST FLOAT(6), PRIMARY KEY(SID, PID));
```

SQLAdditions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

PID	PNAME	COLOR
20001	BOOK	RED
20002	PEN	RED
20003	PENCIL	GREEN
20004	MOBILE	GREEN
20005	CHARGER	BLACK
NULL	NULL	NULL

Result Grid

Form Editor

SUPPLIERS 1 | PARTS 2 × | CATALOG 3 | Result 4 | SUPPLIERS 5 | SUPPLIERS 6 | Result 7 | Apply | Revert

Context Help | Snippets

Output

Action Output

#	Time	Action	Message	Duration / Fetch
28	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE NOT...	1 row(s) returned	0.000 sec / 0.000 sec
29	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE P.C...	2 row(s) returned	0.000 sec / 0.000 sec
30	20:17:02	SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID = C.PID AND C.SID = S.SID A...	2 row(s) returned	0.000 sec / 0.000 sec
31	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE C.COST > (SELECT AVG (C1.COST) FROM CATALOG ...	2 row(s) returned	0.000 sec / 0.000 sec
32	20:17:02	SELECT P.PID, S.SNAME FROM PARTS P, SUPPLIERS S, CATALOG C WHERE C.PID = P.PID AND C.SID = S...	6 row(s) returned	0.000 sec / 0.000 sec
33	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P WHERE P.PI...	2 row(s) returned	0.000 sec / 0.000 sec
34	20:17:13	EXPLAIN SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P W...	OK	0.000 sec

Object Info | Session

Type here to search | 24°C Partly sunny | ENG | 20:20 22-06-2021

---

movie × | airline × | SUPPLIERS ×

File Edit View Query Database Server Tools Scripting Help

Query 1 ×

Limit to 1000 rows

```
29   INSERT INTO CATALOG VALUES(10004,20003,40);
30   SELECT * FROM CATALOG;
31   /* 1 - FIND THE PNAMES OF PARTS FOR WHICH THERE IS SOME SUPPLIER. */
32   SELECT DISTINCT P.PNAME
33       FROM PARTS P, CATALOG C
34       WHERE P.PID = C.PID;
35
36   /* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY PART */
```

SQLAdditions

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Field Types

#	Field	Schema	Table	Type	Character Set
1	SID	supplier	catalog	BIGINT	binary
2	PID	supplier	catalog	BIGINT	binary
3	COST	supplier	catalog	FLOAT	binary

Result Grid

Form Editor

SUPPLIERS 1 | PARTS 2 | CATALOG 3 × | Result 4 | SUPPLIERS 5 | SUPPLIERS 6 | Result 7 | Apply | Revert

Context Help | Snippets

Output

Action Output

#	Time	Action	Message	Duration / Fetch
28	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE NOT...	1 row(s) returned	0.000 sec / 0.000 sec
29	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE P.C...	2 row(s) returned	0.000 sec / 0.000 sec
30	20:17:02	SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID = C.PID AND C.SID = S.SID A...	2 row(s) returned	0.000 sec / 0.000 sec
31	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE C.COST > (SELECT AVG (C1.COST) FROM CATALOG ...	2 row(s) returned	0.000 sec / 0.000 sec
32	20:17:02	SELECT P.PID, S.SNAME FROM PARTS P, SUPPLIERS S, CATALOG C WHERE C.PID = P.PID AND C.SID = S...	6 row(s) returned	0.000 sec / 0.000 sec
33	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P WHERE P.PI...	2 row(s) returned	0.000 sec / 0.000 sec
34	20:17:13	EXPLAIN SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P W...	OK	0.000 sec

Object Info | Session

Type here to search | 24°C Partly sunny | ENG | 20:20 22-06-2021

MySQL Workbench — Screenshot 1

Tabs: movie | airline | SUPPLIERS

Menu: File Edit View Query Database Server Tools Scripting Help

Query 1:

```
31    /* 1 - FIND THE PNAMES OF PARTS FOR WHICH THERE IS SOME SUPPLIER. */
32    SELECT DISTINCT P.PNAME
33      FROM PARTS P, CATALOG C
34     WHERE P.PID = C.PID;
35
36    /* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY PART */
37    SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM
38    PARTS P WHERE NOT EXISTS (SELECT C.SID FROM CATALOG C WHERE C.SID =
```

Result Grid:

PNAME
BOOK
PEN
PENCIL
MOBILE
CHARGER

Tabs: SUPPLIERS 1 | PARTS 2 | CATALOG 3 | Result 4 | SUPPLIERS 5 | SUPPLIERS 6 | Result 7 | Read Only

Output — Action Output:

#	Time	Action	Message	Duration / Fetch
28	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE NOT...	1 row(s) returned	0.000 sec / 0.000 sec
29	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE P.C...	2 row(s) returned	0.000 sec / 0.000 sec
30	20:17:02	SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID = C.PID AND C.SID = S.SID A...	2 row(s) returned	0.000 sec / 0.000 sec
31	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE C.COST > (SELECT AVG (C1.COST) FROM CATALOG ...	2 row(s) returned	0.000 sec / 0.000 sec
32	20:17:02	SELECT P.PID, S.SNAME FROM PARTS P, SUPPLIERS S, CATALOG C WHERE C.PID = P.PID AND C.SID = S...	6 row(s) returned	0.000 sec / 0.000 sec
33	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P WHERE P.PI...	2 row(s) returned	0.000 sec / 0.000 sec
34	20:17:13	EXPLAIN SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P W...	OK	0.000 sec

24°C Partly sunny ENG 20:21 22-06-2021

MySQL Workbench — Screenshot 2

Tabs: movie | airline | SUPPLIERS

Menu: File Edit View Query Database Server Tools Scripting Help

Query 1:

```
36    /* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY PART */
37    SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM
38    PARTS P WHERE NOT EXISTS (SELECT C.SID FROM CATALOG C WHERE C.SID =
39    S.SID AND C.PID = P.PID));
40
41    /* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY RED PART. */
42    SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM
43    PARTS P WHERE P.COLOR = 'RED' AND (NOT EXISTS (SELECT C.SID FROM
```

Result Grid:

SNAME
ACME WIDGET

Tabs: SUPPLIERS 1 | PARTS 2 | CATALOG 3 | Result 4 | SUPPLIERS 5 | SUPPLIERS 6 | Result 7 | Read Only

Output — Action Output:

#	Time	Action	Message	Duration / Fetch
28	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE NOT...	1 row(s) returned	0.000 sec / 0.000 sec
29	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE P.C...	2 row(s) returned	0.000 sec / 0.000 sec
30	20:17:02	SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID = C.PID AND C.SID = S.SID A...	2 row(s) returned	0.000 sec / 0.000 sec
31	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE C.COST > (SELECT AVG (C1.COST) FROM CATALOG ...	2 row(s) returned	0.000 sec / 0.000 sec
32	20:17:02	SELECT P.PID, S.SNAME FROM PARTS P, SUPPLIERS S, CATALOG C WHERE C.PID = P.PID AND C.SID = S...	6 row(s) returned	0.000 sec / 0.000 sec
33	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P WHERE P.PI...	2 row(s) returned	0.000 sec / 0.000 sec
34	20:17:13	EXPLAIN SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P W...	OK	0.000 sec

24°C Partly sunny ENG 20:21 22-06-2021

```
36        /* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY PART */
37   ⊝  SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM
38      PARTS P WHERE NOT EXISTS (SELECT C.SID FROM CATALOG C WHERE C.SID =
39        S.SID AND C.PID = P.PID));
40
41        /* FIND THE SNAMES OF SUPPLIERS WHO SUPPLY EVERY RED PART. */
42   ⊝  SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM
43      PARTS P WHERE P.COLOR = 'RED' AND (NOT EXISTS (SELECT C.SID FROM
```

Result Grid | Filter Rows: Export: Wrap Cell Content:

SNAME
ACME WIDGET
JOHNS

Result Grid | Form Editor

SUPPLIERS 1   PARTS 2   CATALOG 3   Result 4   SUPPLIERS 5   SUPPLIERS 6 ×   Result 7   Read Only   Context Help   Snippets

Output
Action Output

#	Time	Action	Message	Duration / Fetch
28	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE NOT...	1 row(s) returned	0.000 sec / 0.000 sec
29	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE P.C...	2 row(s) returned	0.000 sec / 0.000 sec
30	20:17:02	SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID = C.PID AND C.SID = S.SID A...	2 row(s) returned	0.000 sec / 0.000 sec
31	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE C.COST > (SELECT AVG (C1.COST) FROM CATALOG ...	2 row(s) returned	0.000 sec / 0.000 sec
32	20:17:02	SELECT P.PID, S.SNAME FROM PARTS P, SUPPLIERS S, CATALOG C WHERE C.PID = P.PID AND C.SID = S...	6 row(s) returned	0.000 sec / 0.000 sec
33	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P WHERE P.PI...	2 row(s) returned	0.000 sec / 0.000 sec
34	20:17:13	EXPLAIN SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P W...	OK	0.000 sec

Object Info   Session

24°C Partly sunny   ENG   20:22   22-06-2021

```
43      PARTS P WHERE P.COLOR = 'RED' AND (NOT EXISTS (SELECT C.SID FROM
44        CATALOG C WHERE C.SID = S.SID AND C.PID = P.PID)));
45
46        /* FIND THE PNAMES OF PARTS SUPPLIED BY ACME WIDGET SUPPLIERS AND BY NO ONE ELSE */
47      SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID
48        = C.PID AND C.SID = S.SID AND S.SNAME = 'ACME WIDGET' AND NOT EXISTS
49   ⊝  (SELECT * FROM CATALOG C1, SUPPLIERS S1 WHERE P.PID = C1.PID AND
50        C1.SID = S1.SID AND S1.SNAME <> 'ACME WIDGET');
```

Result Grid | Filter Rows: Export: Wrap Cell Content:

PNAME
MOBILE
CHARGER

Result Grid | Form Editor

SUPPLIERS 1   PARTS 2   CATALOG 3   Result 4   SUPPLIERS 5   SUPPLIERS 6   Result 7 ×   Read Only   Context Help   Snippets

Output
Action Output

#	Time	Action	Message	Duration / Fetch
28	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE NOT...	1 row(s) returned	0.000 sec / 0.000 sec
29	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE P.C...	2 row(s) returned	0.000 sec / 0.000 sec
30	20:17:02	SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID = C.PID AND C.SID = S.SID A...	2 row(s) returned	0.000 sec / 0.000 sec
31	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE C.COST > (SELECT AVG (C1.COST) FROM CATALOG ...	2 row(s) returned	0.000 sec / 0.000 sec
32	20:17:02	SELECT P.PID, S.SNAME FROM PARTS P, SUPPLIERS S, CATALOG C WHERE C.PID = P.PID AND C.SID = S...	6 row(s) returned	0.000 sec / 0.000 sec
33	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P WHERE P.PI...	2 row(s) returned	0.000 sec / 0.000 sec
34	20:17:13	EXPLAIN SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P W...	OK	0.000 sec

Object Info   Session

24°C Partly sunny   ENG   20:22   22-06-2021

home | movie × | airline × | SUPPLIERS ×

File   Edit   View   Query   Database   Server   Tools   Scripting   Help

Navigator

SCHEMAS

Filter objects

▶ airline
▶ airline_db
▶ banking
▶ movie
▶ order_processing
▶ student_enrol

Administration   Schemas

Information

No object selected

Object Info   Session

Query 1 ×

Limit to 1000 rows

```
59
60        /* FOR EACH PART, FIND THE SNAME OF THE SUPPLIER WHO CHARGES THE MOST FOR THAT PART.*/
61  ●  SELECT P.PID, S.SNAME
62        FROM PARTS P, SUPPLIERS S, CATALOG C
63        WHERE C.PID = P.PID
64        AND C.SID = S.SID
65        AND C.COST = (SELECT MAX(C1.COST)
66        FROM CATALOG C1
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

PID	SNAME
20001	JOHNS
20001	ACME WIDGET
20002	JOHNS
20003	RELIANCE
20004	ACME WIDGET
20005	ACME WIDGET

Result Grid

Form Editor

CATALOG 3 | Result 4 | SUPPLIERS 5 | SUPPLIERS 6 | Result 7 | CATALOG 8 | Result 9 × | ⓘ Read Only

SQLAdditions

◀ ▶

Jump to

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Context Help   Snippets

Output

Action Output

#	Time	Action	Message	Duration / Fetch
●	28	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE NOT...	1 row(s) returned	0.000 sec / 0.000 sec
●	29	20:17:02	SELECT S.SNAME FROM SUPPLIERS S WHERE NOT EXISTS (SELECT P.PID FROM PARTS P WHERE P.C...	2 row(s) returned	0.000 sec / 0.000 sec
●	30	20:17:02	SELECT P.PNAME FROM PARTS P, CATALOG C, SUPPLIERS S WHERE P.PID = C.PID AND C.SID = S.SID A...	2 row(s) returned	0.000 sec / 0.000 sec
●	31	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE C.COST > (SELECT AVG (C1.COST) FROM CATALOG ...	2 row(s) returned	0.000 sec / 0.000 sec
●	32	20:17:02	SELECT P.PID, S.SNAME FROM PARTS P, SUPPLIERS S, CATALOG C WHERE C.PID = P.PID AND C.SID = S...	6 row(s) returned	0.000 sec / 0.000 sec
●	33	20:17:02	SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P WHERE P.PI...	2 row(s) returned	0.000 sec / 0.000 sec
●	34	20:17:13	EXPLAIN SELECT DISTINCT C.SID FROM CATALOG C WHERE NOT EXISTS (SELECT * FROM PARTS P W...	OK	0.000 sec

Type here to search

24°C Partly sunny   ENG   20:23   22-06-2021