EXPERIMENT 15

Title: Analyze Web Server Logs Using the Webalizer Tool

AIM

To analyze the performance and usage statistics of a web server using the Webalizer log-analysis tool.

ALGORITHM

1. Start the system and ensure that a web server access log is available.
2. Install Webalizer and identify the web server log file.
3. Configure Webalizer with the log-file path and the output directory.
4. Run Webalizer to process the access log.
5. Generate the HTML statistics report.
6. Open the report in a web browser, usually from the configured output directory.
7. Analyze visits, page requests, files, hits, bandwidth, and monthly usage statistics.

PROCEDURE (Linux example)

The following commands are an example for a Debian/Ubuntu-based Linux system. The exact package name and log path may vary by distribution and web-server setup.

```
# 1. Install Webalizer
sudo apt update
sudo apt install webalizer

# 2. Check that an Apache access log exists
ls -l /var/log/apache2/access.log

# 3. Create a directory for the HTML report
sudo mkdir -p /var/www/html/webalizer

# 4. Generate the report from the access log
sudo webalizer -o /var/www/html/webalizer /var/log/apache2/access.log

# 5. Open the report in a browser
# http://localhost/webalizer/
```

SAMPLE OUTPUT

Webalizer generates an HTML report containing monthly and daily usage statistics. The table below is illustrative; actual values depend on the access log processed.

Month	Visits	Pages	Files	Hits
January	1,200	3,620	5,210	7,345
February	1,450	3,915	5,740	8,120
March	1,635	4,260	6,240	8,480
Total	**4,285**	**11,795**	**17,190**	**23,945**

RESULT

Thus, the Webalizer tool was used to analyze web-server access logs and generate a report showing usage statistics such as visits, page requests, files, hits, and bandwidth.

Note: The sample table contains example values for record-writing purposes, not results from a real server log. Run the commands on a system you administer and use its generated report for actual statistics.