Methods in each class

Each table lists a method and its role in the flow.

TitanShifter

Method	Role in the flow
TitanShifter(String…)	Builds a shifter from text fields
TitanShifter(typed…)	Builds a shifter from typed values
getIsHostile()	Reports hostile or friendly
getPowerLevel()	Reports the shifter's power
TitanForm(String) / TitanForm(int)	Creates a transformation tied to one specific shifter
TitanForm.getPowerSurge()	Returns the surge produced by that transformation
CoordinatePower.triggerCoordinate()	Attempts the Coordinate ability for a friendly shifter; reports success
CoordinatePower.getActiveTitansControlled()	Returns how many titans the Coordinate now controls
assessCombatReadiness()	Returns a readiness result for a power value

ScoutSquad

Method	Role in the flow
ScoutSquad(String)	Builds a squad with only a leader
ScoutSquad(String, String…)	Builds a squad with a leader and members
getFullRoster()	Returns leader followed by members
canEngage()	Tells whether this squad can take on a given titan
isDeployed() / setDeployed()	Read or change deployment status
getSquadPower() / boostSquadPower()	Read or increase squad power

WallDistrict

Method	Role in the flow
WallDistrict(String)	Builds a district with just a name
WallDistrict(String, String, Integer[][])	Builds a district with integrity and kill matrix
decodeSignal()	Converts the two signal strings into urgency and titan count
calculateTotalConfirmedKills()	Returns the district's total confirmed kills
get/setSpottedTitan()	Stores or returns the titan seen in this district
verifyTitanIdentification()	Tells whether two report IDs refer to the same titan

BattleOfWallRose

Method	Role in the flow
addDistrict() / registerSquad() / registerTitan()	Store objects in the master class; report whether stored
deploySquadUnits(…)	Returns total units for one or several squad sizes
findFriendlyShifter()	Returns the first non-hostile registered titan, or nothing

executeDefenseOperation()	Runs the full defense operation