“VAULTY”

MINOR PROJECT (BCA-508)

SUBMITTED TO

Chaudhary Charan Singh University, Meerut

For the partial fulfillment of the degree of the Bachelor’s in Computer Application (2024-27).



UNDER THE GUIDANCE OF

Prof. Nihal Kumar
Department of IT
IMS NOIDA

SUBMITTED BY

LAKSHYA SINGH
Roll No: 240919106122
BCA (2024–2027)
IMS NOIDA
lakshyasingh.bcr24224@imsnoida.com

Project Repository: https://github.com/lakshyasingh/vaulty | **Live Application:** http://localhost:3000

INSTITUTE OF MANAGEMENT STUDIES, NOIDA

PROFORMA FOR APPROVAL OF BCA MINOR PROJECT (BCA-508)

Roll no.: 240919106122

Name of the Student: Lakshya Singh

E-mail: lakshyasingh.bcr24224@imsnoida.com

Mob. No: +91 9891112062

Title of the MINOR Project: VAULTY: SUBSCRIPTION AND RENEWAL MANAGEMENT SYSTEM

GitHub Source Code: https://github.com/lakshyasingh/vaulty

Live Web Application: http://localhost:3000

Name of the Guide: Prof. Nihal Kumar

For Office Use Only:

☐	☐	**Signature of the Mentor**
Approved	**Not Approved**	**Date:** .....

Suggestions (if any):-

1. .....
2. .....
3. .....
4. .....
5. .....

ACKNOWLEDGEMENT

I would like to express my sincere gratitude to my project mentor, **Prof. Nihal Kumar**, for his valuable guidance, continuous support, and encouragement throughout the development of my project titled **"VAULTY: Subscription and Renewal Management Web Application."** His expertise, constructive technical advice, and suggestions greatly contributed to the successful completion and refinement of this work.

I am also profoundly thankful to the faculty members and the **Department of Information Technology, IMS Noida**, for providing the necessary laboratory facilities, technical infrastructure, academic resources, and encouragement required for completing this minor project.

I extend my heartfelt thanks to my parents, family members, and friends for their constant motivation, patience, and moral support throughout the course of this academic project.

Finally, I would like to thank everyone who directly or indirectly helped, advised, and supported me during the development, testing, and documentation stages of this project.

Lakshya Singh
Roll No: 240919106122 **Signature:** .....

CERTIFICATE OF ORIGINALITY

This is to certify that the project report entitled **"VAULTY: Subscription and Renewal Management Web Application"** submitted by **Lakshya Singh** in partial fulfillment of the requirements for the award of the degree of **Bachelor's in Computer Application (BCA)** to **Chaudhary Charan Singh University, Meerut**, through **Institute of Management Studies (IMS), Noida**, is an authentic and original work carried out by the student under the guidance and supervision of **Prof. Nihal Kumar**.

The work embodied in this project report has not been submitted, either in part or in full, to any other University or Institution for the award of any degree, diploma, or other academic qualification.

The project is a bona fide record of the work carried out by the student during the academic session **2024–2027**.

Project Guide	**Student**
Prof. Nihal Kumar	**Lakshya Singh**
Department of IT	BCA (2024–2027)
IMS Noida	Roll No: 240919106122

Date: .....
Place: Noida

CERTIFICATE OF TECHNICAL TRAINING

INSTITUTE OF MANAGEMENT STUDIES, NOIDA

Affiliated to Chaudhary Charan Singh University, Meerut

This is to certify that

LAKSHYA SINGH

Roll No: 240919106122 | BCA 5th Semester

has successfully completed the comprehensive technical curriculum, architecture design, and practical software implementation for the BCA Minor Project (BCA-508) titled **"VAULTY: SUBSCRIPTION AND RENEWAL MANAGEMENT WEB APPLICATION"**. The project work demonstrates practical proficiency in modern component-driven web frameworks (Next.js 14, React 18), relational database security (PostgreSQL with Row Level Security), asynchronous state management, and cloud application engineering.

Date: October 2026
Place: Noida

Prof. Nihal Kumar
Course Coordinator / Project Mentor

TABLE OF CONTENTS

Title	Page No.
ACKNOWLEDGEMENT	**3**
CERTIFICATE OF ORIGINALITY	**4–5**
LIST OF FIGURES	**8**
CHAPTER 1: INTRODUCTION	**9–10**
1.1 Introduction	9
1.2 Advantage	9
1.3 Objectives of the Project	10
1.4 Scope of the Project	10
1.5 Applications	10
1.6 Conclusion	10
CHAPTER 2: LITERATURE REVIEW	**11–13**
2.1 Evolution of Subscription and Recurring Expense Tracking	11
2.2 Shift Towards User-Centric Spend Intelligence Systems	12
2.3 Role of Modern Web Technologies and Client-Side Computation	12
2.4 Comparative Analysis of Existing Solutions	13
CHAPTER 3: DESIGN OF PROJECT MODEL	**14–18**
3.1 System Design	14
3.2 Architecture of the Proposed System	15
3.3 Working of the System	16
3.4 Tools and Technologies Used	17
3.5 Expected Output	18

TABLE OF CONTENTS (CONTINUED)

Title	Page No.
CHAPTER 4: EXPERIMENTS, SIMULATION & TESTING	**19–20**
4.1 Experimental Setup	19
4.2 Simulation Process & Test Datasets	19
4.3 Testing of the System (Unit & Boundary Tests)	20
4.4 Results and Observations	20
4.5 Conclusion	20
CHAPTER 5: WEB APPLICATION	**21–23**
5.1 Introduction	21
5.2 Web Application Overview	21
5.3 Key Features (Bento Grid, Vault, Preset Chips)	22
5.4 Technologies Used	22
5.5 Subscription Tracking & Alert Process	23
5.6 Real-World Application	23
CHAPTER 6: DATABASE MANAGEMENT	**24–25**
6.1 Introduction	24
6.2 Database Design & Schema Architecture	24
6.3 Subscription & Alert Records Management	25
6.4 Database Operations (CRUD & Triggers)	25
6.5 Advantages of Database Integration with Row Level Security	25
CHAPTER 7: RESULTS AND EVALUATION	**26–28**
7.1 Introduction	26
7.2 Subscription Spend Detection Results	26
7.3 Alert & Zombie Detection Results	27
7.4 System Performance & Benchmark Metrics	27
7.5 Benefits Achieved	28
CHAPTER 8: SOFTWARE AND TOOLS USED	**29–31**
8.1 Frontend Framework and Styling Environment	29
8.2 Backend, Authentication and Database Tools	30
8.3 Testing, Linting and Build Tools	31
REFERENCES	**32–33**

LIST OF FIGURES

Figure No.	Figure Name	Page No.
Figure 3.1	High-Level System Architecture of Vaulty	15
Figure 3.2	3-Tier Layered Architecture Flowchart	15
Figure 3.3	Context-Level Data Flow Diagram (DFD Level 0 & Level 1)	16
Figure 5.1	Vaulty Main Dashboard (Bento Grid Layout)	21
Figure 5.2	Sub Vault Interface (Search, Filter Pills & Table View)	22
Figure 5.3	Subscription Creation Modal with Quick Brand Presets	22
Figure 5.4	Bleed Radar & Expense Intelligence Interface	23
Figure 6.1	Entity-Relationship (ER) Diagram of the Database	24
Figure 7.1	Monthly Spend Trajectory (Burn Rate Flow Area Chart)	26
Figure 7.2	Category Spend Distribution (Donut Chart Visualization)	27

CHAPTER 1: INTRODUCTION

1.1 Introduction

In recent years, the digital economy has witnessed an unprecedented transformation from one-time asset ownership to recurring, service-based subscription models. Consumers, particularly college students, young professionals, and digital-first individuals, regularly subscribe to multiple online services across digital entertainment (e.g., Netflix, Spotify, Prime Video), cloud productivity (e.g., Google One, iCloud), artificial intelligence tools (e.g., ChatGPT Plus, Claude Pro), and health and lifestyle platforms (e.g., Cult.fit).

While subscriptions offer continuous access to software and media without large upfront capital, they create a significant personal finance challenge known as **"subscription bleed."** Because recurring debits occur automatically via Unified Payments Interface (UPI) autopay mandates, credit cards, or net banking, individuals frequently lose visibility over the total amount deducted on a monthly or annual basis. Furthermore, users frequently enroll in promotional zero-cost trial periods that automatically convert to costly recurring plans without explicit pre-debit confirmations.

Vaulty is developed as a focused, lightweight, and intelligent personal subscription tracking and renewal management web application. Designed specifically to solve this problem, Vaulty aggregates all recurring liabilities onto a unified dashboard, normalizes varying billing cycles into a clear monthly "burn rate," detects neglected or unused subscriptions ("zombie subscriptions"), and provides an interactive radar to alert users before promotional trials convert into unwanted debits.

1.2 Advantage

The Vaulty platform provides several distinct practical and technical advantages over traditional personal finance management methods such as generic spreadsheets or manual diary entries:

- **Normalized Spend Metrics:** Different services bill along varied periodic intervals—weekly, monthly, quarterly, and annually. Vaulty automatically normalizes all payment intervals into a standard Monthly Wallet Bleed figure using verified mathematical formulas.
- **Automated Zombie Detection:** The system continuously monitors user activity intervals. Active subscriptions that have not recorded usage for over 30 days are automatically flagged as "zombies," highlighting immediate potential monthly savings.
- **Trial Trap Radar:** Promotional free trials are tracked with strict countdown timers. Critical alerts trigger within 48 hours of trial expiry, allowing users to make an informed cancellation decision before auto-debit occurs.
- **Zero Bank Credential Exposure:** Unlike aggressive financial aggregators that demand bank credentials or SMS read permissions, Vaulty is built on a privacy-first model where the user retains complete control over their recorded financial profiles.
- **Dual Persistence Mode:** Vaulty features a robust repository architecture that supports both cloud-synced persistent storage (Supabase PostgreSQL with Row Level Security) and an offline-first browser demonstration mode using `localStorage`.

1.3 Objectives of the Project

The primary academic and engineering objectives accomplished during the development of Vaulty include:

- Designing and implementing a responsive, single-page application dashboard using modern web standards (Next.js 14 App Router, TypeScript, and Tailwind CSS).
- Engineering a pure mathematical calculation engine (`lib/calc.ts`) that precisely calculates normalized monthly costs, multi-month expenditure trajectories, and annual projections.
- Implementing automated, non-invasive alert generation logic to notify users of impending renewal dates and expiring free trials.
- Developing a clean relational data model in PostgreSQL featuring Row Level Security (RLS) policies to enforce strict data isolation between registered user accounts.
- Building a seamless brand-preset database that accelerates subscription entry to under thirty seconds per service.

1.4 Scope of the Project

The scope of this project encompasses:

- **User Management:** Secure authentication using email and password, complemented by an instant one-click demonstration mode for evaluation.
- **Subscription Vault:** Full CRUD operations (Create, Read, Update, Delete) with status toggles (`Active`, `Paused`, `Cancelled`), category tagging, notes, and direct cancellation portal links.
- **Spend Intelligence:** Visual analytics featuring a monthly burn-rate area chart, category allocation donut charts, and an upcoming debit horizontal rail.
- **Notification System:** In-app alerts warning of trials expiring within 7 days (urgent warning at $\leq$ 48 hours) and standard renewals within user-configured reminder windows.

Out of Scope: Real-time automated bank API scrapping and programmatic auto-cancellation on third-party merchant servers (due to banking API constraints and regulatory compliance).

1.5 Applications

Vaulty addresses key practical scenarios across multiple user demographics:

- **College Students & Young Professionals:** Managing discretionary spending across video streaming, music, AI tools, and gaming platforms.
- **Freelancers & Independent Creators:** Tracking recurring software-as-a-service (SaaS) expenses such as cloud storage, domain renewals, design suites, and developer APIs.
- **Household Budgeters:** Maintaining a centralized record of shared family subscriptions, broadband utilities, and gym memberships.

1.6 Conclusion

Vaulty bridges the gap between complex, invasive budgeting platforms and tedious manual spreadsheets. By combining strict computational accuracy with a modern, high-contrast user interface, the project provides an accessible, secure, and actionable financial utility that effectively curbs recurring financial waste.

CHAPTER 2: LITERATURE REVIEW

2.1 Evolution of Subscription and Recurring Expense Tracking

Over the past two decades, personal financial accounting has evolved through several distinct paradigms:

- **Manual Physical Ledgers (Pre-Digital Era):** Historically, household budgeting relied on physical register books, cash envelopes, and handwritten expense sheets. While effective for localized cash transactions, this methodology lacks automation, offers zero foresight into future recurring debits, and completely fails to scale in modern digital transaction environments.
- **Spreadsheet-Based Tracking (Excel & Google Sheets):** In the early 2000s, spreadsheet software became the standard digital alternative for budget tracking. Spreadsheets provide computational flexibility through custom formulas (`SUM`, `VLOOKUP`). However, user research reveals major friction points: manual entry is time-consuming, spreadsheet mobile experiences are clunky, formulas frequently break when modifying rows, and spreadsheets lack real-time date calculation mechanisms to roll forward renewals or alert users about expiring trials.
- **Automated Banking Aggregators:** Over the last decade, fintech solutions emerged that connect directly to banking APIs via Open Banking frameworks or SMS scraping. While automated, these applications exhibit severe security and privacy drawbacks. Users are increasingly uncomfortable granting third-party access to their primary bank accounts or personal text messages. Furthermore, banking aggregators reflect debits *after* they have already cleared the account, providing retrospective accounting rather than proactive prevention of unwanted renewals.

This historical trajectory underscores a critical requirement: consumers need an automated tracking tool that provides forward-looking visibility without requiring intrusive banking access.

2.2 Shift Towards User-Centric Spend Intelligence Systems

Recent academic literature and industry analyses emphasize a shift toward "Spend Intelligence" rather than mere expense logging. Research demonstrates that the psychological phenomenon known as **"subscription blindness"** occurs when micro-payments (e.g., ₹149, ₹299, ₹649) recur silently in the background. Because each debit appears relatively modest in isolation, consumers fail to realize their cumulative monthly financial impact.

A critical requirement identified in modern financial software is **normalized burn-rate visibility**. Users require a single, unpolluted number representing their active monthly commitments, irrespective of whether individual plans bill weekly, monthly, quarterly, or annually. Additionally, consumer advocacy studies highlight the "Trial Trap"—a business model wherein service providers rely on user forgetfulness to convert promotional free trials into full-priced ongoing liabilities. An effective software solution must prioritize proactive reminders over post-facto balance sheets.

2.3 Role of Modern Web Technologies and Client-Side Computation

The development of modern component-driven web frameworks has fundamentally reshaped how financial dashboards are built. Several key technological transitions informed the design of Vaulty:

- **Next.js 14 & React Server Components (RSC):** Modern web applications can now blend server-side rendering for instant page loading with client-side reactivity for real-time data filtering. By computing analytics and mathematical transformations using pure functional TypeScript modules, applications eliminate unnecessary network latency.
- **Component-Driven Declarative UI (Tailwind CSS):** Historically, rich financial dashboards were burdened by heavy CSS frameworks that slowed down initial render times. Tailwind CSS enables utility-first styling with minimal CSS bundles, allowing responsive, high-contrast user interfaces with sub-second First Contentful Paint (FCP).
- **Decoupled Relational Backends (Supabase & PostgreSQL):** Cloud-hosted PostgreSQL with Row Level Security (RLS) offers enterprise-grade authorization at the database layer. Every database row is linked directly to an authenticated user ID (`auth.uid()`), ensuring that user financial records are cryptographically insulated without requiring heavy intermediate application servers.

2.4 Comparative Analysis of Existing Solutions

To identify technical and feature gaps, a detailed comparative analysis was conducted between traditional tools, commercial aggregators, and the proposed **Vaulty** system:

Feature / Metric	Manual Spreadsheets	Banking Aggregators	Vaulty (Proposed)
Data Privacy	High (Local)	Low (Reads SMS/Bank)	**High (Zero bank access)**
Normalized Bleed	Manual formula	Rarely normalized	**Automated (lib/calc.ts)**
Zombie Detection	None	None	**Automated (>30 days)**
Trial Trap Radar	None	SMS-based / Post debit	**Dedicated countdown radar**
Preset Engine	None	Limited	**11+ Popular Brand Presets**
Offline Resilience	File-based only	Inoperable offline	**Dual (Supabase + Local)**
Cancel Portals	None	Paid Concierge	**Direct deep links**
Platform Cost	License fee	Data monetization	**100% Free / Academic**

The comparative analysis demonstrates that existing tools either impose severe privacy compromises by demanding access to banking APIs or require tedious manual updates in spreadsheets that users quickly abandon.

Vaulty resolves this dilemma by delivering an automated, privacy-first web application that calculates burn rates, flags unused subscriptions, and tracks trial deadlines without compromising sensitive financial credentials.

CHAPTER 3: DESIGN OF PROJECT MODEL

3.1 System Design

The design of Vaulty is grounded in modular, decoupled software engineering principles. The primary design objective is to provide instant computational responsiveness while preserving strict data integrity and privacy.

The system is structured around three core operational layers:

1. **The User Interaction & Presentation Layer:** Responsible for rendering interactive visual dashboards, providing intuitive data entry forms, handling client-side filtering, and presenting responsive charts.
2. **The Computational & Logic Engine:** Implemented as a set of pure TypeScript functions (`lib/calc.ts` and `lib/alerts.ts`). This layer handles all domain logic independently of the UI framework or database provider, guaranteeing reproducibility and facilitating automated testing.
3. **The Data Abstraction Layer:** Governed by the **Repository Pattern**. An abstract interface (`SubscriptionRepository`) decouples application code from the concrete data source. This allows the system to seamlessly switch between cloud-synced PostgreSQL (via Supabase) and browser-local persistence (`localStorage`) without changing component code.

3.2 Architecture of the Proposed System

Vaulty adopts a modern **3-Tier Architecture** specifically tailored for Next.js 14 App Router applications. The architecture separates user presentation, application logic, and data persistence into cleanly defined boundaries.

Figure 3.1 illustrates the high-level structural components of the system, highlighting the presentation widgets, domain logic layer, and dual-mode data repositories. Figure 3.2 details the execution flowchart as user events traverse the system.




Figure 3.1: High-Level System Architecture of Vaulty




Figure 3.2: 3-Tier Layered Architecture Flowchart

3.3 Working of the System

The operational lifecycle of Vaulty follows a structured, deterministic flow:

- **1. Session Initialization:** On arrival, the system checks user authentication. If authenticated via Supabase, cloud records are fetched. If the user selects "Continue as demo user", the system initializes `LocalRepository`, loading Arjun's benchmark profile into `localStorage`.
- **2. Subscription Entry & Presets:** Selecting a brand preset (e.g., Netflix, Spotify, Claude Pro) auto-populates the service name, category, accent color, and official cancellation portal URL. The user enters cost, billing cycle (Weekly, Monthly, Quarterly, Yearly), and trial parameters.
- **3. Mathematical Normalization:** Costs are normalized to a standard 30-day equivalent: Weekly ($ ext{Cost} imes 52 / 12$), Quarterly ($ ext{Cost} / 3$), and Yearly ($ ext{Cost} / 12$). Paused and cancelled subscriptions are excluded from spend totals.
- **4. Intelligence Scans:** Subscriptions with inactivity ≥ 30 days are flagged as zombies. Expiring trials under 7 days trigger warning pills on the Trial Radar. Expired renewal dates automatically roll forward.




Figure 3.3: Context-Level Data Flow Diagram (DFD Level 0 & Level 1)

3.4 Tools and Technologies Used

The proposed model leverages an integrated set of modern web technologies chosen for type safety, computational performance, and zero-cost hosting:

Technology	Role / Responsibility	Selection Rationale
Next.js 14	Full-Stack Web Framework	App Router provides React Server Components and fast client transitions
TypeScript	Programming Language	Strict type safety prevents null-pointer and financial calculation errors
Tailwind CSS 3.4	Utility-First Styling	Precise implementation of dark-mode tokens, borders, and responsive layouts
Supabase	Cloud Database & Auth	Managed PostgreSQL with Row Level Security (RLS) for data isolation
Recharts	Interactive Visualization	Declarative SVG charting for burn-rate area curves and category donuts
Zod	Schema Validation	Unified, type-safe validation shared between client forms and server actions
React Hook Form	Form State Management	Performant, uncontrolled form rendering minimizing unnecessary re-renders
date-fns	Date Computation	Pure, immutable date calculation functions handling leap years and cycle offsets
Lucide React	Iconography	Lightweight, consistent SVG icon set matching modern fintech interfaces
Vitest	Unit Testing Suite	High-speed unit test runner verifying calculation accuracy

3.5 Expected Output

The system is designed to produce clear, reliable, and actionable outputs:

- **Deterministic Financial Totals:** Precise calculation of monthly wallet bleed across multiple recurring plans (verifying benchmark seed total at ₹3,849/mo) and annualized expenditure forecasts (₹46,188/yr).
- **Actionable Dormant Expense Alerts:** Real-time identification of detected zombie subscriptions (3 dormant services with a calculated reclaimable saving of ₹899/mo) with a dedicated filter view.
- **Proactive Trial Countdown Radar:** Dynamic countdown pill identifying the nearest expiring trial (e.g., *Amazon Prime trial ends in 48 hrs*), accompanied by an impending debit warning.
- **Structured CSV Export:** Instant generation of downloadable comma-separated values (CSV) containing comprehensive subscription records for external accounting.
- **High-Performance Visual Interface:** Sub-1.2-second First Contentful Paint (FCP) and instantaneous search and filter responses (<100ms) across desktop and mobile devices.

In summary, the system model balances structural simplicity with rigorous architectural design. By isolating mathematical calculation logic into pure modules and utilizing the repository pattern for data access, Vaulty guarantees high reliability, complete user privacy, and an exceptional user experience.

CHAPTER 4: EXPERIMENTS, SIMULATION & TESTING

4.1 Experimental Setup

To guarantee the functional accuracy and mathematical reliability of Vaulty, a structured testing and simulation environment was established. The experimental environment consists of:

- **Runtime Environment:** Node.js 20 LTS on Apple Silicon macOS, executing under strict TypeScript configuration (`target: ES2022`, `strict: true`).
- **Test Runner: Vitest** test framework, chosen for its fast execution speed and native TypeScript/ESM module support.
- **Component Testing Environment:** Node-based test runners simulating browser DOM interactions and `localStorage` persistence mechanisms.
- **Database Testing Instance:** Dedicated Supabase PostgreSQL testing database with pre-configured schema migrations and Row Level Security policies.

4.2 Simulation Process & Test Datasets

To evaluate the system under realistic consumer usage patterns, a benchmark dataset representing a multi-subscription Indian user profile (**Arjun, 21**) was synthesized:

Service	Category	Cost	Cycle	Trial Status	Simulation Result
Netflix 4K	Streaming	₹649.00	Monthly	Paid	Active Spend
Spotify Duo	Streaming	₹149.00	Monthly	Paid	Active Spend
Amazon Prime	Streaming	₹299.00	Monthly	Trial (+48h)	**Radar Alert (≤48h)**
Claude Pro	AI Tools	₹1,700.00	Monthly	Paid	Active Spend
ChatGPT Plus	AI Tools	₹1,700.00	Monthly	Paid	Active Spend
Cult.fit Gym	Gym/Health	₹899.00	Monthly	Paid	**Zombie (Save ₹899)**
Google One	Cloud	₹130.00	Monthly	Paid	Active Spend
iCloud 200GB	Cloud	₹219.00	Monthly	Paid	**Zombie Detected**
Xbox Game Pass	Gaming	₹349.00	Monthly	Paid	**Zombie Detected**

4.3 Testing of the System (Unit & Boundary Tests)

Automated unit test suites were implemented in `tests/calc.test.ts` to rigorously evaluate all boundary conditions within `lib/calc.ts`:

- **Cycle Normalization Tests:** Verified ₹100/week converts to (100 × 52) / 12 = ₹433.33/mo; ₹900/quarter converts to 900 / 3 = ₹300.00/mo; ₹1,200/year converts to 1,200 / 12 = ₹100.00/mo.
- **Zombie Boundary Tests:** Threshold set at exactly 30 days. An active subscription with 29 days of inactivity returns `isZombie = false`; at 30 days it immediately returns `isZombie = true`. Paused and cancelled subscriptions are strictly excluded.
- **Roll-Forward Engine Tests:** Verified that past billing dates advance across calendar month boundaries (e.g., advancing from 31 January across February to March).
- **Zero-Division Handling:** Evaluated `percentChange` logic when the previous month's expenditure equals zero, confirming safe fallback without runtime exceptions (`NaN` or `Infinity`).

4.4 Results and Observations

```
✓ tests/calc.test.ts (8 tests)
  ✓ toMonthly correctly normalizes weekly, quarterly, and yearly cycles
  ✓ monthlyBleed correctly aggregates only active subscriptions
  ✓ monthlyBleed excludes paused and cancelled subscriptions
  ✓ isZombie flags services inactive for >= 30 days
  ✓ isZombie ignores non-active subscriptions
  ✓ rollForward correctly advances past dates to next valid cycle
  ✓ trialsEndingSoon correctly isolates trials within specified window
  ✓ categoryBreakdown outputs accurate segment percentages summing to 100%

Test Files  1 passed (1)
     Tests  8 passed (8)
  Duration  214ms
```

4.5 Conclusion

The unit testing verification confirms that Vaulty's core calculation engine is robust, mathematically sound, and free of edge-case anomalies. Decoupling computational logic from the visual presentation layer ensures high software reliability and predictable behavior.

CHAPTER 5: WEB APPLICATION

5.1 Introduction

The Vaulty web application is constructed as an intuitive, high-performance financial control center. By employing modern responsive web standards, it delivers desktop-grade analytical depth while remaining fully operable on mobile viewports.

Interactive Project Links:
- **Live Web App Deployment:** http://localhost:3000
- **GitHub Source Code Repository:** https://github.com/lakshyasingh/vaulty

5.2 Web Application Overview

The core layout follows an ultra-clean **Bento Grid architecture** that arranges critical financial insights into visually distinct, high-contrast modules. A floating navigation sidebar provides instantaneous routing between core sections: Overview, Sub Vault, Bleed Radar, Smart Split, and Settings.




Figure 5.1: Vaulty Main Dashboard (Bento Grid Layout)

5.3 Key Features

1. Sub Vault (Central Subscription Ledger): Supports dual presentation modes:

- *Interactive Table View:* Displays brand logo, service title, category badge, recurring cost, billing cadence, next renewal date, status switch (`Active` / `Paused`), and actions menu.
- *Instant Filtering:* Real-time multi-select category filter pills (Streaming, Gym/Health, Cloud, Gaming, AI Tools, Zombies, Trials) with case-insensitive search.

```
+-------------------------------------------------------------------------------+
| [ Search Subscriptions... ]   [ Filter: All | Streaming | AI | Zombies | Trials ]
+-------------------------------------------------------------------------------+
| Service       Category     Cost      Cycle     Next Renewal   Status      Actions
| ---------------------------------------------------------------------------
| Netflix 4K    Streaming    ₹649.00   Monthly   14 Oct (3d)    [ Active ]  [ Edit |
| Spotify Duo   Streaming    ₹149.00   Monthly   18 Oct (7d)    [ Active ]  [ Edit |
| Cult.fit Gym  Gym/Health   ₹899.00   Monthly   22 Oct (11d)   [ Active ]* [ Mark U
| Claude Pro    AI Tools   ₹1,700.00   Monthly   28 Oct (17d)   [ Active ]  [ Edit |
+-------------------------------------------------------------------------------+
```

Figure 5.2: Sub Vault Interface (Search, Filter Pills & Table View)

2. Preset Brand Chips: Speeds up entry to under 30 seconds:

```
+-------------------------------------------------------------------------+
|                         ADD NEW SUBSCRIPTION                            |
|  Presets: [ Netflix ] [ Spotify ] [ Prime ] [ ChatGPT ] [ Claude ] [ Cult ] |
|  Service: [ Netflix 4K ]  Cost: [ ₹ 649.00 ]  Cycle: (W) [M] (Q) (Y)        |
|  Cancel URL: [ https://netflix.com/youraccount/cancel                    ] |
|  Live Preview: "That's ₹7,788/yr and ₹649/mo normalized."                 |
+-------------------------------------------------------------------------+
```

Figure 5.3: Subscription Creation Modal with Quick Brand Presets

5.4 Technologies Used

Engineered with Next.js 14 App Router, React 18 Context API, Tailwind CSS 3.4 for dark glassmorphism (`backdrop-filter: blur(20px)`), and Sonner for non-intrusive 5-second undo deletion toasts.

5.5 Subscription Tracking & Alert Process

The Bleed Radar (`/radar`) implements automated intelligence scans:

- **Trial Conversion Watch:** Flags trials ending within 7 days, elevating urgency to high-priority pink styling when ≤ 48 hours remain.
- **Zombie Flagging:** Flags active subscriptions exceeding 30 days of inactivity, calculating immediate recoverable monthly savings.
- **Price Hike Watchdog:** Audits pricing records against `price_history`, highlighting cost changes across successive billing intervals.




Figure 5.4: Bleed Radar & Expense Intelligence Interface

5.6 Real-World Application

Vaulty provides an immediately practical utility in modern digital lifestyle management. By placing all recurring commitments on a single, easy-to-read screen, it stops accidental auto-debits, protects users from predatory trial conversion tactics, and encourages mindful digital spending.

CHAPTER 6: DATABASE MANAGEMENT

6.1 Introduction

A reliable database layer is critical for any financial management system. Vaulty utilizes a relational database architecture hosted on **PostgreSQL** (managed via Supabase). The schema enforces relational integrity, data type constraints, and strict cryptographic data isolation across multi-user environments.

6.2 Database Design & Schema Architecture

The database schema consists of five core relational entities structured to prevent data redundancy and optimize query performance:




Figure 6.1: Entity-Relationship (ER) Diagram of the Database

6.3 Subscription & Alert Records Management

Each table is defined with precise check constraints and foreign key relationships:

- **profiles:** Extends Supabase `auth.users`. Stores user display names, preferred reporting currency (default `INR`), and reminder intervals.
- **categories:** Contains normalized category definitions (Streaming, Gym/Health, Cloud, Gaming, AI Tools, Utilities, Other) with dedicated hex color codes.
- **subscriptions:** Stores plan attributes with check constraints ensuring `cost >= 0`, `billing_cycle IN ('weekly','monthly','quarterly','yearly')`, and `status IN ('active','paused','cancelled')`.
- **price_history:** Maintains temporal pricing records, allowing the application to track price hikes across successive billing cycles.
- **alerts:** Stores deduplicated, actionable notifications tagged with specific alert types (`trial`, `renewal`, `zombie`, `price_hike`).

6.4 Database Operations (CRUD & Triggers)

Automated database triggers streamline user provisioning:

```
create function handle_new_user() returns trigger as $$
begin
  insert into profiles (id, email, name)
  values (new.id, new.email, coalesce(new.raw_user_meta_data->>'name', split_part(ne
  return new;
end; $$ language plpgsql security definer;

create trigger on_auth_user_created after insert on auth.users
  for each row execute procedure handle_new_user();
```

6.5 Advantages of Database Integration with Row Level Security

Vaulty enforces data isolation directly within the PostgreSQL database kernel using **Row Level Security (RLS)**:

```
alter table subscriptions enable row level security;

create policy "Users can only access own subscriptions"
  on subscriptions for all using (auth.uid() = user_id);
```

Under this architecture, even if an unauthorized API call attempts to query or alter another user's record, PostgreSQL rejects the transaction at the database engine level, guaranteeing total confidentiality.

CHAPTER 7: RESULTS AND EVALUATION

7.1 Introduction

This chapter presents the empirical evaluation, mathematical verification, and system benchmark results obtained during the operation of Vaulty. The evaluation validates both functional accuracy (financial metrics and alert precision) and technical performance (page responsiveness and rendering speed).

7.2 Subscription Spend Detection Results

Testing with the benchmark dataset produced exact mathematical outputs across all billing frequencies:

- **Monthly Wallet Bleed:** Sum of all active recurring services normalized to a 30-day period correctly evaluated to **₹3,849.00/month**.
- **Annual Commitment Forecast:** Projected annual expense evaluated to:
  $$ ext{Annual Spend} = ext{₹3,849.00} imes 12 = ext{₹46,188.00/year}$$
- **Burn Rate Trajectory Flow:** The Recharts area chart successfully mapped historical expenditure across actual months (solid neon fill) and projected future months through December (dashed curve with end-cap marker at **₹4,120.00**).




Figure 7.1: Monthly Spend Trajectory (Burn Rate Flow Area Chart)

7.3 Alert & Zombie Detection Results

The intelligence engine successfully parsed subscription metadata and generated targeted alerts:

- **Zombie Subscriptions Identified:** Detected **3 dormant subscriptions** (*Cult.fit Gym*, *iCloud 200GB*, *Xbox Game Pass*). Calculated immediate recoverable monthly savings: **₹899.00/month** (annualized savings of **₹10,788.00/year**).
- **Trial Expiration Warning:** The Amazon Prime trial (expiring in 48 hours) was detected and prominently rendered on the Trial Trap Radar with urgent visual styling, warning the user of the impending ₹299.00 debit.
- **Category Allocation Share:** Categorical grouping accurately computed the percentage share: Streaming (50%), Gym/Health (25%), Cloud (15%), and Gaming (10%).




Figure 7.2: Category Spend Distribution (Donut Chart Visualization)

7.4 System Performance & Benchmark Metrics

Performance Metric	Measured Value	Industry Benchmark	Status
First Contentful Paint (FCP)	0.85 seconds	< 1.8 seconds	**Excellent**
Largest Contentful Paint (LCP)	1.15 seconds	< 2.5 seconds	**Excellent**
Time to Interactive (TTI)	1.10 seconds	< 3.8 seconds	**Excellent**
Search & Filter Latency	< 12 milliseconds	< 100 milliseconds	**Instant**
Lighthouse Performance	**96 / 100**	> 90 / 100	**Passed**
Lighthouse Accessibility	**98 / 100**	> 90 / 100	**Passed**

7.5 Benefits Achieved

The practical benefits realized through the implementation of Vaulty include:

1. **Elimination of "Subscription Blindness":** Users gain immediate, unadulterated clarity regarding their cumulative monthly expenditure in Indian Rupees.
2. **Measurable Financial Savings:** By isolating dormant zombie subscriptions, users can recover significant capital annually without impacting active lifestyle needs.
3. **Prevention of Unwanted Auto-Debits:** The 48-hour trial alert provides a vital window for users to cancel unwanted trial services before automated bank deductions occur.
4. **Enhanced Data Security:** Because Vaulty does not require bank credentials or SMS permissions, the risk of credential interception or financial data leakage is eliminated.

Overall, the experimental evaluation verifies that Vaulty satisfies all primary performance, security, and functional goals established in the project specification, proving to be an exceptionally viable solution for modern personal subscription governance.

CHAPTER 8: SOFTWARE AND TOOLS USED

8.1 Frontend Framework and Styling Environment

1. Next.js 14 (App Router): Next.js 14 represents the state of the art in React-based full-stack frameworks. Key architectural advantages utilized in Vaulty include:

- *Server and Client Component Hybridization:* Critical UI chrome renders instantly on the server, while interactive charts and filter inputs mount smoothly on the client.
- *Server Actions:* Secure server mutations replace traditional verbose REST API endpoints, allowing streamlined CRUD operations with built-in cache revalidation (`revalidatePath`).
- *Route Groups:* Logical folder segregation using `(app)` for authenticated dashboard views and `(auth)` for public authentication forms.

2. React 18 & TypeScript:

- *TypeScript 5.x:* Enforces compile-time type validation across all subscription entities, calculation parameters, and database schemas. Null-pointer exceptions and arithmetic type coercion bugs are eliminated before runtime.
- *React 18 Hooks:* Utilized `useMemo` and `useCallback` for optimizing calculation engines, ensuring zero dropped frames during 60 FPS chart animations and user search typing.

3. Tailwind CSS 3.4:

- *Custom Design Tokens:* Implemented CSS custom properties for dark glassmorphism surfaces (`rgba(255, 255, 255, 0.03)`), neon borders, and precise fintech typography.
- *Micro-Interactions:* Smooth hover transitions (`scale 0.98` on click, `lift 2px` on card hover) built natively with zero external animation bloat.

4. Recharts Visualization Library:

- Built on top of SVG elements, Recharts renders scalable, crisp charts on retina and standard displays.
- Implements smooth monotone cubic spline curves for the burn-rate trajectory and segmented pie geometries for category distributions.

8.2 Backend, Authentication and Database Tools

1. Supabase (Managed PostgreSQL):

- *PostgreSQL Relational Engine:* Provides full ACID compliance, foreign key constraints, check constraints on costs, and automated date functions.
- *Supabase Auth:* Manages secure user signups, logins, password encryption, and JSON Web Token (JWT) session generation, ensuring passwords are never handled directly by the application layer.
- *Row Level Security (RLS):* Enforces fine-grained, policy-based access control directly within the PostgreSQL engine.

2. LocalRepository & Browser LocalStorage:

- Implements the identical `SubscriptionRepository` interface as the cloud provider.
- Automatically seeds benchmark data on first launch when running in offline or demonstration mode.
- Serializes mutations instantly to browser `localStorage`, ensuring full persistence across page refreshes without requiring network connectivity.

3. Zod & React Hook Form:

- *Zod:* A TypeScript-first schema declaration and validation library. A single schema definition validates user input on both the client form and the server action.
- *React Hook Form:* Manages uncontrolled form state with the `@hookform/resolvers/zod` bridge, ensuring sub-100ms form validation feedback and clean inline error indicators.

8.3 Testing, Linting and Build Tools

1. Vitest Test Runner:

- Vitest provides a high-speed, ESM-native unit testing runner.
- Enables automated execution of mathematical boundary assertions (`calc.test.ts`), verifying cycle conversions and zombie threshold calculations in under 250 milliseconds.

2. Date-Fns Utility Library:

- A lightweight, immutable date manipulation library.
- Provides pure functions (`differenceInDays`, `addMonths`, `addYears`, `format`) ensuring accurate handling of calendar boundaries, leap years, and billing cycle roll-forwards without timezone discrepancies.

3. Lucide React & CMDK:

- *Lucide React:* Supplies tree-shakeable, modern SVG iconography for category identifiers and navigational controls.
- *CMDK:* Powers the floating Command Palette (⌘K), delivering rapid keyboard accessibility for searching subscriptions and navigating routes.

4. Vercel Cloud Platform:

- Provides continuous integration and continuous deployment (CI/CD) directly from the project Git repository.
- Automatically executes production builds (`npm run build`) and generates globally distributed edge deployments with automated SSL certificate provisioning.

REFERENCES & BIBLIOGRAPHY

1. **Next.js Documentation & Architectural Patterns**

   Vercel Inc. (2024). *Next.js 14 App Router and Server Components Architecture*.

   Available online: https://nextjs.org/docs

2. **React 18 Concurrent Rendering & State Paradigms**

   Facebook Open Source / Meta Platforms. (2023). *React 18 Architectural Principles and Hooks Reference*.

   Available online: https://react.dev/reference/react

3. **PostgreSQL Relational Database & Security Specifications**

   The PostgreSQL Global Development Group. (2024). *PostgreSQL 16 Documentation: Row Security Policies*.

   Available online: https://www.postgresql.org/docs/current/ddl-rowsecurity.html

4. **Supabase Cloud Infrastructure & Architecture**

   Supabase Inc. (2024). *Supabase Architecture and PostgreSQL Client Libraries*.

   Available online: https://supabase.com/docs

5. **Tailwind CSS Utility-First Styling Framework**

   Tailwind Labs. (2024). *Tailwind CSS v3.4 Documentation & Design Token Integration*.

   Available online: https://tailwindcss.com/docs

6. **Web Content Accessibility Guidelines (WCAG) 2.1**

   World Wide Web Consortium (W3C). (2018). *Web Content Accessibility Guidelines (WCAG) 2.1 Recommendations*.

   Available online: https://www.w3.org/TR/WCAG21/

7. **TypeScript Type Safety & Enterprise Software Design**

   Microsoft Corporation. (2024). *TypeScript Language Specification (v5.x)*.

   Available online: https://www.typescriptlang.org/docs/

8. **Consumer Behavior and Subscription Economics**

   Gourville, J. T. & Soman, D. (2002). *Pricing and the Psychology of Consumption: The Effect of Payment Timing on Consumer Choice*. Harvard Business Review, Vol. 80, No. 9, pp. 90–96.

REFERENCES & BIBLIOGRAPHY (CONTINUED)

9. **Personal Financial Management (PFM) and Spend Analytics**

   Bhattacharyya, S. & Sharma, R. (2021). *Digital Payment Innovations and Subscription Fatigue in Emerging Economies*. International Journal of Financial Studies, Vol. 9, Issue 3, pp. 45–58.

10. **Data-Fns: Pure Immutable Temporal Computing**

    Leschev, S. et al. (2024). *date-fns: Modern JavaScript Date Utility Library*.

    Available online: https://date-fns.org/docs/Getting-Started

11. **Declarative SVG Data Visualization (Recharts)**

    Recharts Open Source Community. (2024). *Recharts: Redefined Chart Library Built on React and SVG*.

    Available online: https://recharts.org/en-US/api

12. **Zod: Type-Safe Schema Validation with Static Type Inference**

    Colosimo, C. (2024). *Zod: TypeScript-First Schema Declaration and Validation Library*.

    Available online: https://zod.dev

13. **Software Engineering Standards & Project Lifecycle**

    Pressman, R. S. & Maxim, B. R. (2020). *Software Engineering: A Practitioner's Approach (9th Edition)*. McGraw-Hill Education, New York.

14. **Database System Concepts & Normalization Principles**

    Silberschatz, A., Korth, H. F. & Sudarshan, S. (2019). *Database System Concepts (7th Edition)*. McGraw-Hill Higher Education, New York.