

ISO 9001-2015,WHO, FDA,
European CE Nortified &
ISO-13485 Certified



ALPHA^R
SUDARSHAN

CE
European CE
Nortified

Rectal Thermometer

1.It has be latex free Rectal stick thermometer with large LCD screen display.Rectal stick is been covered with disposable rectal sheath. It have provided with 100 disposable rectal sheaths with each unit. It have quick 30 seconds read time. 6.Should be reusable
Temperature range 90.0-109.9 F/ 32.0-42.9 C
Standards



2. Height Stadiometer

1. Capacity : 150 Kg ,Graduation: 100g, Tare, auto hold, body mass index functions, Automatic zero setting, Operable on mains and rechargeable batteries , Stadiometer (with head rod) attached to weighing scale ,Remote display ,Measuring range: 60-180cm, Graduation: 1mm, Weight measurement time <5 sceonds CE approval certification Standards
ISO certification



3. Torch with 2 Batteries (1.6V) ISI mark
LED light with extra bulb Replaceable battery

4. Torch with 3 Batteries (1.6V) ISI mark
LED light with extra bulb Replaceable battery



5. Inch Tape Vinyl - coated, 1.5m. Vinyl - coated fibreglass measuring tape
Metal tip finishing at both endsReads both in cm and inch Length, 1.5 m / 5 ftMinimal graduation: 0.5 cm / 0.2 inch Width, approx: 1.3 cm Thickness, appox: 0.36 mm
Device is produced by ISO certified manufacturer



6. Instrument Drum (small)

Dressing Drum Small, 22 x 20 Circular, Hinged Lid with Hasp, Catch and Sliding Shutter, st/st, Internal Diameter 22 x 20cm depth. Standards ISO certification

7. Instrument Drum (medium)

Dressing Drum Medium, 22 x 22 Circular, Hinged Lid with Hasp, Catch and Sliding Shutter, st/st, Internal Diameter 22 x 14cm depth.
Standards ISO certification

8. Instrument Drum (large)

Dressing Drum Big Dressing Drum Large, 30 x 27cm Circular, Hinged Lid with Hasp, Catch and Sliding Shutter, st/st, Internal Diameter 30 x 27cm depth.
StandardsISO certification



9. Digital Sliding Vernier caliper

Digital LCD Display, With Screw Stop, Thumb Grip, Thumb Dial, and Extra 1.5V Button Cell BatteryMeasures Metric: 0-150 mm and in Inches: 1-6 in, Converts Between the Two Decimal and Fractional Inches, Converts Between The Two Hardened Stainless Steel, Shaft Measurement Prot Resolution: 0.01mm,0.0005", 1/64" Accuracy: +/- 0.03mm, 0.001"



Manufactured By : SUDARSHAN CHEMICALS India 324007 0744-2362345, 09414188018

CE, ISO 9001:2015, WHO, FDA & ISO-13485 CERTIFIED
With first prize awarded at Haroti Udyog Mela year 2003