ISO 9001-2015,WHO, FDA, European CE Nortified & ISO-13485 Certified









ASE-116 (d) MORTUARY CHAMBER 4 BODIES

Used for storing cadaverous under low temperature cool conditions in order to prevent decomposition. Most Useful for Hospitals, Airports, Railways etc. These units are double walled with outer & inner made of Stainless Steel Sheets 20 SWG grade of corrosion resistance SS 304 with Handled and lock arrangement for all chamber vertically position. Chamber is divided into four individual compartments each. The gap between inner and outer chamber is filled with polyurethane Puff 60 to 80 mm approx to avoid thermal loss. Air circulation by forced Air circulation. Automatic locking facility of carriage for storage when returned to close position. The front face lifting hinged door is lined with magnetic gasket seal between the door and cabinet increases system efficiency side opening. Stainless Steel trays with telescopic Mechanism fabricated of extruded aluminium with nylon rubber to carry dead bodies are provided with handles so as the carry dead bodies. Internal Drainages system given to wash the unit inside the chamber. Refrigeration unit outside the chambers. Trolley Trays travel on nylon rollers fitted for easy movement and can be remove out side. Exterior surface anti rust coated duly finished. CFC free Hermetically sealed heavy duty ISI 1.5 KW compressor Gas R134a/R404/R22. Condenser is Efficient with Auto condensate evaporating and defrosting system, Evaporator internal forced drought system. Temperature range of 0-2°C to 4°C. Unit is fitted with LCD Digital Temperature microprocessor based Controller cum indicator, Door Buzzer Alarms, Audio-Visual Alarms to warn High and Low Temperatures with power failure alarm. Temperature Chart Recorder with three weeks independent paperless & inkless weekly circular chart recorder. The unit is Supplied complete with trays, cord and plug, to work on 220/ 230 volts or 420 V Three phase A.C Supply. Long electricity cable wire fitting including power point installation. Supply with Voltage Stabilizer. With three year guaranty. Electrical Safety IEC 60601-1

Additional features:

Standby Arrangement system if main system failures.

Internal Diamations approx.

W 685 mm x D 2140mm x H 460mm

Supplied with OPTIONAL ACCESSORIES USED IN MORTUARY CHAMBER.

Manufactured By: SUDARSHAN CHEMICALS India 324007 0744-2362345, 09414188018

CE, ISO 9001:2015, WHO, FDA & ISO-13485 CERTIFIED With first prize awarded at Haroti Udyog Mela year 2003