ISO 9001-2015,WHO, FDA, European CE Nortified & ISO-13485 Certified









ASE-110a DEEP FREEZER VERTICAL ALPHA

Deep Freezers made of complete Powder coated,

Deep Freezer with -10 to -25 degree C upright model Equipped with LCD displayand provide real-time and historical graphing of temperature Electronic door with security lock, small castors, external dry alarm contacts, LED lightning antimicrobialexterior paint, and a microprocessor control system with high/low temp, door ajar alarms, and password security with user specific access, door lock which provides additional security for expensive samples and reagents from unauthorized users external coating with anti-bacterial surfaces, to eliminate 99.99% of surface bacteria within 24 hoursof exposure and ensure environment friendly. Interior for sample protection. Internal LED lightingsave up 70% power with less heat exposure than fluorescent or incandescentlighting: and provide standard wheel/casters as well, for easy location ormovementInclude intelligent automaticdefrost system offering superior product protection with long-term reliabilityand exceptional product quality; thermocouple on the evaporator detecting iceformation; defrosting only when needed to keep units at optimum performance, keeping chamber temperature within safe limits; no risks for samples duringfreezer cold wall defrostedlt has forced air design insteadof regular cold wall for both refrigerator and freezer, rapid cool-down andvery fast recovery due to fan assistance, fast temperature equilibration, superior sample protection It provide high-performance protection for precious samples such as molecular biology, chemicals, reagents and kits Temp. Range -10 °C to -25 °C Temperature Uniformly Range ±3°C Door solid pre-coated steel white color, with ergonomic handle in aluminum thas alarms open door, high/lowtemperature, power failure, clogged condenser filter Controller Standard is 0.1°Cresolution, password protectionIt have defrost Intelligent automatic system It is CE CertificatedIt have door lock key lockLighting LEDIt have dry contact alarm dry contact to connect to remote alarms. Mounted with standard casters. Shelves or Drawers 4 Nos. Typical Power consumption Power requirements 220-240V, AC, 50Hz single phase .Temperature controls and circuit by Compressor/Condensing Units CFC free & eco friendly refrigerant. The gap between the inner and outer wall is filled with Puff insulation to avoid thermal loss. 4/5 freezer drawers for storage Perforated Sheet with lock on each drawer. Audiovisual alarm for high/low se points, Door lock arrangement. Unit is fitted with Control penal having all control and circuitry are housed at the top fitted with temperature controller cum indicator microprocessor based LED display System built-in multi alarm system with memory function. Other changes will be done on request or as per user specification..

Capacity Approx: 210,340,400,500 Ltr

Manufactured By: SUDARSHAN CHEMICALS India 324007 0744-2362345, 09414188018

CE, ISO 9001:2015, WHO, FDA & ISO-13485 CERTIFIED With first prize awarded at Haroti Udyog Mela year 2003