

Computer and Network Security: Integrity and Authentication

Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include: <http://commons.wikimedia.org> (Wikipedia, Wikimedia and workbooks); <http://www.sxc.hu> and <http://www.pixabay.com>

Outline

- **Modern Cryptography**

- Overview

- Confidentiality

- Background: Definition, Crypto-analysis, One Time Pads
 - Symmetric key encryption, Block modes
 - Asymmetric key encryption

- **Integrity (includes Authentication)**

- Hashes, **MAC**, Digital signature

Recap: Integrity and Authentication

- Focus: Communication framework

Definition:

- Integrity (data): Has the data been modified in transit?
- Authentication: Am I talking with the right person?

- ~~• Hashes/Message Digests: Integrity~~
- **Message Authentication Codes (MACs): Integrity and Authentication**
 - Based on Shared key
- Digital Signatures: Integrity and Authentication
 - Based on Asymmetric key algorithm

Message Authentication Codes (MACs)


- Also referred to as keyed hash function
 - A secret key is needed for evaluation
- Provides both Integrity and Authentication
 - Only someone with identical key can verify hash
 - Does not provide confidentiality
 - Require similar properties as hash functions (pre-image resistance, weak/strong collision resistance)

MAC vs Hash

- A virus can modify a file and its hash also (recalculate) → cannot detect tampering
- Virus can modify file but cannot calculate new MAC since it does not know the secret key

Details


- M: message, k: secret key shared between A and B
- A sends message and tag
- B verifies received message with tag
 - Matches, accept (authentic + untampered)
 - No match, reject (tampered/unauthentic or corrupted)



Security Model

Attacker does not know k

Attacker can input *any* messages M_1, \dots, M_n of its choice and get corresponding tag



Attacker succeeds if it outputs a forgery; i.e., (M, tag)

$$M \neq M_i \text{ for all } i$$

$$V(k, M, tag) = 1$$


Want $\Pr[\text{winning}] \sim 0$ (time bound)

Two Types (Popular)

- Block Cipher based (e.g. CBC mode)
- Hash based (but with key)
 - Faster
 - Code more readily available


MAC Construction

- Use secret key algorithms to compute MAC
- Remember Cipher Block Chaining (CBC)?
- Last block ciphertext of CBC is CBC residue (=MAC)
- Send $\langle M, \text{CBC residue} \rangle$



MAC Construction

- Send $\langle M, \text{CBC residue} \rangle$
- Modify M , CBC residue invalid
 - Except 1 in 2^{64} times (CBC residue = 64 bits)
- Works well if M is not to be kept secret




Subtleties

Message M

- Ensure confidentiality \rightarrow CBC encrypt M; Send C (Ciphertext)
 - Cannot detect tampering, especially by machines
- Ensure integrity + authentication \rightarrow Send $\langle M, \text{CBC residue} \rangle$
 - Message M is in the open
- How to ensure both confidentiality and integrity and authentication? **Need attention to details!**


Version-1:

- Send $\langle C, \text{CBC residue} \rangle$
- Does not work. Why?
 - Attacker can modify C and set CBC residue to last block of C
 - Some parts may decrypt to garbage in text but may be ok in some situations




Version-2

- CBC encrypt $\langle M \mid \text{CBC residue} \rangle$
 - $|$ means concatenation
- Does not work. Why?
 - Last block always encrypts zero



Version-3

- CBC encrypt ($M \parallel \text{CRC}$)
 - CRC: checksum on the message
 - May work but suspect
- Replace CRC with cryptographic hash of M
 - Requires two cryptographic passes (one for hash, one for CBC)
 - Stronger but has not received much attention or used much



Version-4

- Send $\langle C, \text{CBC residue} \rangle$
- But use two keys
 - k_1 for CBC residue of M
 - k_2 for CBC encryption of M
 - k_1 and k_2 can be related to each other
- Requires two cryptographic passes

Two Types (Popular)


- ~~• Block Cipher based (e.g. CBC mode)~~
- Hash based (but with key)
 - Faster
 - Code more readily available

MAC with a Hash

- Refresh: Mac for integrity and authentication
 - Send $\langle M, \text{CBC residue} \rangle$
 - CBC residue based on secret key algorithm
- Secret key but no secret key algorithm (e.g DES, AES)
- Many subtleties!


Version-1: Secret Prefix method

- Send $\text{hash}(k \parallel M)$ (=MAC)
- Insecure: If attacker knows M and $\text{hash}(k \parallel M)$; he can construct MAC of a longer message i.e. $\text{hash}(k \parallel M \parallel y)$ for message $M \parallel y$



Version-2: Secret Prefix, half MAC


- Send half the bits of $\text{MAC} = \text{hash}(k \mid M)$
 - E.g. lower order 64 bits of a 128 bit digest
 - Cannot continue due to partial information




Version-3: Secret Suffix Method

- Send $\text{hash}(M \parallel k)$ (=MAC)
- Fixes problem with prefix method. Why?
- Insecure if hash is not collision resistant





.....



Version-4: Envelope Method

- Send $\text{hash}(k | M | k)$
 - Appending front provides collision resistance
 - Appending back provides protection from extending message
- HMAC: More widely used (e.g. in IPsec, SSL)
 - Complex but roughly: $\text{hash}(k | \text{hash}(k | M))$

Integrity+Confidentiality

- Many possibilities
- More Popular
 - MAC-then-Encrypt: $E_k(M \parallel \text{MAC}(M))$ (E.g. TLS)
 - Encrypt-and-MAC: $E_k(M) \parallel \text{MAC}(M)$ (E.g. SSH)
 - **Encrypt-then-MAC: $E_k(M) \parallel \text{MAC}(E_k(M))$** (E.g. IPsec)
- Encrypt-then-MAC: reaches the highest definition of security

Summary

- MACs based on ‘key’ provide both integrity and authentication
- Two types: block cipher and hashes
- Usage: Attention to detail important
- To provide both confidentiality and integrity, use “Encrypt-then-MAC”