

Command	Purpose	Syntax	Example
ls	list directory content	ls [option] [path]	ls
cd	change directory	cd [path]	cd /var/log
pwd	current directory	pwd	pwd
mkdir	create directory	mkdir [option] directory name	mkdir new_dir
rmdir	remove empty dir - only	rmdir directory name	rmdir old_dir - only
rm	remove files	rm filename	rm file.txt
cp	copy files or dir - only	cp filename	cp file1.txt /home/user/
mv	move file or directory	mv filename	mv file1.txt /home/user/
cat	Concatenate & display file content	cat file-name	cat file.txt
tty	Print filename of terminal	tty	tty
who am i	Show current logged in	whoami	whoami
who	Show who logged in	who	user1 user2
touch	create empty file	touch [option] filename	touch newfile.txt
cal	display ^{current} calendar or current month	cal [option] [month] [year]	cal OR cal 12 2024
man	display manual (documentation)	man [command]	man ls
date	display or set date & time	date [option] [+Format]	date
chmod	change file permission	chmod [permission] filename	chmod 755 script.sh
grep	search specific pattern or text within file	grep [option] pattern [file...]	grep "error" logfile.txt
tput	initialize terminal faster or setting	tput [options] [capability]	tput clear
bc	Basic Calculator	bc [option] - [file]	bc 2+3

Output —

Enter a no : 0
The no is zero.

Qs Ladder if else

```
read -p "Enter your marks:" marks
if [ $marks -ge 90 ];
then
    echo "Grade A"
elif [ $marks -ge 75 ];
then
    echo "Grade B"
elif [ $marks -ge 50 ];
then
    echo "Grade C"
else
    echo "Fail"
fi
```

Output —

Enter your marks : 85
Grade B

Qs For loop

```
for i in {1..5}
do
    echo "Number: $i"
done
```

Output —

Number: 1
Number: 2
Number: 3
Number: 4
Number: 5

Q6. while loop

```
i = 1
while [ $i -le 5 ]
do
    echo "Number: $i"
    ((i++))
done
```

Output —

```
Number: 1
Number: 2
Number: 3
Number: 4
Number: 5
```

Q7 Nested loop

```
for i in {1..3}
do
    for j in {1..2}
    do
        result=$((i*j))
        echo "$i * $j = $result"
    done
done
```

Output —

```
1 2 3
2 4 6
3 6 9
```

Q8. Switch case —

```
echo "Enter no. n:"
read n
read b
echo "Enter operation (+, -, *, /):"
read op
case $op in
    "+")
        echo "Result: $((a+b))";;
    "-")
        echo "Result: $((a-b))";;
    "*" )
        echo "Result: $((a*b))";;
```

Q10. Array -

```
fruits = ("Apple" "Banana" "Cherry")  
echo "All fruits" ${fruits[@]}  
echo "Enter a new fruit:"  
read new-fruit  
fruit = fruit + ($new-fruit)  
echo "Updated fruits:"  
for fruit in "${fruits[@]}";  
do  
  echo $fruit  
done
```

Q6. while loop

```
i = 1
while [ $i -le 5 ]
do
    echo "Number: $i"
    ((i++))
done
```

Output —

```
Number: 1
Number: 2
Number: 3
Number: 4
Number: 5
```

Q7 Nested loop

```
for i in {1..3}
do
    for j in {1..2}
    do
        result=$((i*j))
        echo "$i * $j = $result"
    done
done
```

Output —

```
1 2 3
2 4 6
3 6 9
```

Q8. Switch case —

```
echo "Enter no. n:"
read n
read b
echo "Enter operation (+, -, *, /):"
read op
case $op in
    "+")
        echo "Result: $((a+b))";;
    "-")
        echo "Result: $((a-b))";;
    "*")
        echo "Result: $((a*b))";;
```