

CP CODING BLOCKS ANSWERS

1.

```
def find_max_value(arr):  
    return max(arr)  
N = int(input())  
if N < 0:  
    print("N cannot be Negative")  
else:  
    arr = []  
    for _ in range(N):  
        num = int(input())  
        arr.append(num)  
    max_value = find_max_value(arr)  
    print(max_value)
```

2.

```
L = input().split()  
L.reverse()  
print(L)
```

3.

```
N = int(input())  
for _ in range(N):  
    car_number = input().strip()  
    even_sum = sum(int(d) for d in car_number  
if int(d) % 2 == 0)  
    odd_sum = sum(int(d) for d in car_number  
if int(d) % 2 != 0)  
    print("Yes" if even_sum % 4 == 0 or  
odd_sum % 3 == 0 else "No")
```

4.

```
w = int(input().strip())  
if w > 2 and w % 2 == 0:  
    print("YES")  
else:  
    print("NO")
```

5.

```
N=int(input())
for i in range(1,N+1):
    for j in range(0,N-i):
        print(" ",end=" ")
    for k in range(i):
        print("*",end=" ")
    print()
```

6.

```
N = int(input())
for i in range (1, N+1):
    print("*" * i)
```

7.

```
N = int(input())
for i in range(1,N + 1):
    for j in range(1, i+1):
        print(j, end=" ")
    print()
```

8.

```
n = int(input())

arr = list(map(int, input().split()))

unique_number = 0
for num in arr:
    unique_number ^= num

print(unique_number)
```

9.

```
import math
N = int(input())
print(math.factorial(N))
```

10.

```
N = int(input())
for i in range(1, N):
    print(i, end=' ')
print()
for i in range(N-1, 0, -1):
    print(i, end=' ')
```

11.

```
def is_palindrome(arr, start, end):
    if start >= end:
        return True
    if arr[start] != arr[end]:
        return False
    return is_palindrome(arr, start + 1, end - 1)
N = int(input())
arr = [int(input()) for _ in range(N)]
result = is_palindrome(arr, 0, N - 1)
if result:
    print("true")
else:
    print("false")
```

12.

```
S = input()
if S == S[::-1]:
    print("Palindrome")
else:
    print("Not a palindrome")
```

13.

```
def find_index(arr, M):  
    return arr.index(M) if M in arr else -1  
  
N = int(input())  
arr = [int(input()) for _ in range(N)]  
M = int(input())  
print(find_index(arr, M))
```

15.

```
def find_pairs(arr, target):  
    arr.sort()  
    left = 0  
    right = len(arr) - 1  
    while left < right:  
        current_sum = arr[left] + arr[right]  
        if current_sum == target:  
            print("{} and {}".format(arr[left], arr[right]))  
            left += 1  
            right -= 1  
        elif current_sum < target:  
            left += 1  
        else:  
            right -= 1  
  
N = int(input())  
arr = []  
for _ in range(N):  
    arr.append(int(input()))  
target = int(input())  
find_pairs(arr, target)
```

16.

```

def max_subarray_sum(arr):
    max_sum = float('-inf')
    current_sum = 0
    for num in arr:
        current_sum += num
        max_sum = max(max_sum, current_sum)
        if current_sum < 0:
            current_sum = 0
    return max_sum

N = int(input())
arr = [int(input()) for _ in range(N)]
print(max_subarray_sum(arr))

```

17.

```

def count_digit_occurences(number, digit):
    return str(number).count(str(digit))

try:
    number = int(input())
    digit = int(input())
    if digit < 0 or digit > 9:
        print("Digit must be between 0 and 9")
    else:
        print(count_digit_occurences(number, digit))
except ValueError:
    print("Please enter valid integers")

```

18.

```

N = int(input())
a, b = 0, 1
for _ in range(2, N+1):
    a, b = b, a + b
print(b if N > 0 else a)

```

19.

```
N=int(input())
ev=""
odd=""
for i in range(1,N):
    if(i%2==0):
        ev+=str(i)+" "
    else:
        odd+=str(i)+" "+odd
print(odd.strip(),ev.strip())
```

20.

```
def reverse_string(s):
    return s[::-1]
if __name__=="__main__":
    s = input().strip()
    print(reverse_string(s))
```