Various Forms Of "fa" Lup

Int main()

Initializate in jor" is ophial

int m;

far(; fest-cond; short)

printy (" [nh a no:");

scang (" ./.l", &n);


far(; n >= 1; n --)

printy (" [n./.l", n);

rehn o;

```
#include <stdio.h>
int main()
{
    int n;
    printf("Enter an int:");
    scanf("%d",&n);
    for(;;)
    {
        if(n<=0)
            break;
        printf("\n%d",n);
        n--;
    }
    return 0;
}</pre>
```

Using The Keyword "continue"



```
#include <stdio.h>
int main()
{
  int i;
  for(i=1;i<=10;i++)
     if(i==6)
       break;
     printf("\n%d",i);
  }
  return 0;
OUTPUT:
1
2
3
4
5
```

```
#include <stdio.h>
int main()
{
  int i;
  for(i=1;i<=10;i++)
     if(i==6)
       continue;
     printf("\n%d",i);
  }
  return 0;
OUTPUT:
=======
1
2
3
4
5
7
8
9
10
```

```
#include <stdio.h>
int main()
{
    int i;
    for(i=1;i<=10;i++)
    {
        if(i%2==0)
            continue;
        printf("\n%d",i);
    }
    return 0;
}
OUTPUT:
========
1
3
5
7
9
```