

## Steps Required For Development /s Rng

- ① Writing The "Source Code"
- ② Compilation of The "Source Code"
- ③ Executing  $\frac{\text{OS + CPU}}{\text{or Platform}}$

I : Integrable

D : Development

E : Environment

<u>IDG</u>	<u>Company</u>
① ✓ <u>Tc</u>	① Borland
② ✓ Code Blocks	② Various
③ ✓ VS Code	③ Microsoft
④ Dev C++	④ Bloodshed
⑤ X-Code	⑤ Apple

### The First C Language Program


TC ( Borland )

```

File Edit . . . . . Compile Run Help
#include <stdio.h>
#include <conio.h> } header file
void main()
{
    clrscr();
    printf("Hello User");
}


```


Function



.h

Header Files





What are header files and why do we use them?

=====

In C and C++ languages any file which has the extension **.h** is called as a header file.

These header files are developed by the company which designs the compiler or IDE of C language and they contain a huge collection of predefined programs called as **functions**.

For example: All mathematical functions like `sqrt()`, `pow()`, `sin()`, `cos()`, `tan()`, `log()`, etc. are available in a header file called **math.h**. Similarly all the functions which can draw different geometrical figures like `circle()`, `rectangle()`, `ellipse()`, `polygon()`, `line()`, `arc()`, `bar()`, etc. are available in a header file called **graphics.h**.

Like this there are around 50 header files provided by Turbo IDE and each of these header files contain around 60-70 predefine functions.

Now when we write a program in C language then we can simplify our task by using the above mentioned functions. But to use any of these functions we must first attach the required header file in our program and for this C language provides us a command called **#include**