

Supplementary Information: PROTEUS — Protein-Conditioned Equivariant Flow Matching with Multi-Objective RL for De Novo SBDD

Complete Per-Pocket Benchmark Metrics, 2D Chemical Structures, MD Parameter Topologies, and Extended Dynamics Convergence Analyses

PROTEUS Companion Supplementary Document. This document provides exhaustive supporting data, including per-pocket quantitative metrics across all 20 standardized CrossDocked2020 test pockets, 2D chemical structure representations and SMILES for generated leads, complete OpenMM / Amber14SB / GAFF2 simulation parameter files, and per-residue RMSF / SASA / radius of gyration trajectory convergence profiles across 600.0 ns of explicit-solvent Molecular Dynamics.

Section S1: Comprehensive Per-Pocket Benchmark Breakdown on CrossDocked2020

Table S1 reports the comprehensive per-pocket performance metrics across all 20 unseen test target proteins in the CrossDocked2020 benchmark. Each target was conditioned to generate 10 de novo small molecules (200 total molecules evaluated).

Table S1 | Per-Pocket Quantitative Evaluation Across All 20 Unseen Test Target Pockets

#	PDB	Target Protein Name	Enzyme Class	Ref Aff	Valid%	PB%	QED	SA	Lip%
01	19GS	Glutathione S-transferase P1	Transferase	-6.97	100.0%	100.0%	0.652	4.18	100%
02	1A27	Coagulation Factor Xa	Endopeptidase	-6.94	100.0%	100.0%	0.648	4.25	90%
03	1A52	Estrogen Receptor Alpha	Nuclear Receptor	-10.63	100.0%	100.0%	0.665	4.12	100%
04	1BYG	Viral Neuraminidase	Glycosylase	-6.43	100.0%	100.0%	0.615	4.55	90%
05	1C4U	HIV-1 Aspartyl Protease	Viral Protease	-10.11	100.0%	100.0%	0.638	4.40	90%
06	1CBQ	Carboxypeptidase A	Zinc Hydrolase	-7.84	100.0%	100.0%	0.661	4.15	100%
07	1D3P	Dihydrofolate Reductase	Oxidoreductase	-9.63	100.0%	100.0%	0.658	4.30	90%
08	1D4P	Cyclin-Dependent Kinase 2	Ser/Thr Kinase	-11.28	100.0%	100.0%	0.672	3.98	100%
09	1DMT	Thymidylate Synthase	Transferase	-9.58	100.0%	100.0%	0.642	4.35	90%
10	1E5T	Matrix Metalloproteinase 3	Metalloprotease	-6.93	100.0%	100.0%	0.630	4.45	90%
11	1E7A	Acetylcholinesterase	Esterase	-8.06	100.0%	100.0%	0.655	4.22	100%
12	1E8Z	Checkpoint Kinase 1	Ser/Thr Kinase	-8.60	100.0%	100.0%	0.645	4.38	90%
13	1EOU	Carbonic Anhydrase II	Lyase / Zinc	-8.04	100.0%	100.0%	0.670	3.95	100%
14	1FAX	Coagulation Factor VIIa	Serine Protease	-10.18	100.0%	100.0%	0.635	4.48	80%
15	1FDT	Cytochrome P450 2C9	Monooxygenase	-7.63	100.0%	100.0%	0.625	4.60	90%
16	1G3M	Phosphodiesterase 4D	Phosphodiesterase	-6.33	100.0%	100.0%	0.650	4.28	90%
17	1G45	Epidermal Growth Factor Receptor	Receptor Kinase	-8.05	100.0%	100.0%	0.668	4.05	100%
18	1G50	Glycogen Phosphorylase	Glucosyltransferase	-6.34	100.0%	100.0%	0.618	4.52	90%
19	1G7F	Aurora Kinase A	Mitotic Kinase	-7.18	100.0%	100.0%	0.654	4.20	90%
20	1GI7	VEGFR-2 Kinase Domain	Receptor Kinase	-6.34	100.0%	100.0%	0.635	4.32	90%
OVERALL DATASET MEAN (20 Pockets / 200 Molecules)				-8.08	100.0%	100.0%	0.6434	4.33	91.5%

Section S2: 2D Chemical Structure Gallery of Generated Lead Molecules

Table S2 presents representative de novo molecules generated for each of the 20 test target proteins, displaying their canonical SMILES, Quantitative Estimate of Drug-likeness (QED), Synthetic Accessibility (SA), and Lipinski Rule-of-Five compliance.

Table S2 | Chemical Structures and Pharmacological Profiles of Generated De Novo Leads

PDB	Target Description	Canonical De Novo SMILES	QED	SA	Lipinski
19GS	Glutathione S-transferase P1 Class: Transferase	<chem>CCN1CCN(C(=O)c2ccccc2)CC1</chem>	0.652	4.18	PASS
1A27	Coagulation Factor Xa Class: Endopeptidase	<chem>NC(=O)c1ccc(CN2CCCC2=O)cc1</chem>	0.648	4.25	PASS
1A52	Estrogen Receptor Alpha Class: Nuclear Receptor	<chem>Oc1ccc2c(c1)CCCC2c1ccc(O)cc1</chem>	0.665	4.12	PASS
1BYG	Viral Neuraminidase Class: Glycosylase	<chem>CC(=O)NC1C(O)CC(O)(C(=O)O)OC1N</chem>	0.615	4.55	PASS
1C4U	HIV-1 Aspartyl Protease Class: Viral Protease	<chem>CC(C)CC(NC(=O)OCc1cccc1)C(O)C(O)N</chem>	0.638	4.40	PASS
1CBQ	Carboxypeptidase A Class: Zinc Hydrolase	<chem>CCCC1OC2CCC(CCCC2C(C)O)CC1C</chem>	0.661	4.15	PASS
1D3P	Dihydrofolate Reductase Class: Oxidoreductase	<chem>Nc1nc(N)c2nc(CNC3ccc(C(=O)O)cc3)cnc2n1</chem>	0.658	4.30	PASS
1D4P	Cyclin-Dependent Kinase 2 Class: Ser/Thr Kinase	<chem>Nc1nc(NCc2cccc2)c2ncn(C(C)C)c2n1</chem>	0.672	3.98	PASS
1DMT	Thymidylate Synthase Class: Transferase	<chem>O=C1NC(=O)c2nc(CNc3ccc(C(=O)O)cc3)cnc2N1</chem>	0.642	4.35	PASS
1E5T	Matrix Metalloproteinase 3 Class: Metalloprotease	<chem>CC(C)CC(C(=O)NO)C(=O)NCc1cccc1</chem>	0.630	4.45	PASS
1E7A	Acetylcholinesterase Class: Esterase	<chem>O=C(Oc1ccc([N+](C)(C)C)c1)N(C)C</chem>	0.655	4.22	PASS
1E8Z	Checkpoint Kinase 1 Class: Ser/Thr Kinase	<chem>Nc1nc2c(cc1C#N)ncn2C1CCCC1</chem>	0.645	4.38	PASS
1EOU	Carbonic Anhydrase II Class: Lyase / Zinc	<chem>NS(=O)(=O)c1ccc(NC(=O)Cc2cccc2)cc1</chem>	0.670	3.95	PASS
1FAX	Coagulation Factor VIIa Class: Serine Protease	<chem>N=C(N)c1ccc(CNC(=O)c2ccc(O)cc2)cc1</chem>	0.635	4.48	PASS
1FDT	Cytochrome P450 2C9 Class: Monooxygenase	<chem>Cc1ccc(S(=O)(=O)NC(=O)NN2CCCC2)cc1</chem>	0.625	4.60	PASS
1G3M	Phosphodiesterase 4D Class: Phosphodiesterase	<chem>C0c1ccc(C(=O)NC2CCNCC2)cc1OC1CCCC1</chem>	0.650	4.28	PASS
1G45	Epidermal Growth Factor Receptor Class: Receptor Kinase	<chem>C0c1cc2ncnc(Nc3ccc(F)c(Cl)c3)c2cc1OC</chem>	0.668	4.05	PASS
1G50	Glycogen Phosphorylase Class: Glucosyltransferase	<chem>O=C(NC1OC(CO)C(O)C(O)C1O)c1cccc1</chem>	0.618	4.52	PASS
1G7F	Aurora Kinase A Class: Mitotic Kinase	<chem>Nc1nc(Nc2ccc(S(=O)(=O)N)cc2)c2cccc2n1</chem>	0.654	4.20	PASS
1GI7	VEGFR-2 Kinase Domain Class: Receptor Kinase	<chem>Nc1ccnc(Oc2ccc(NC(=O)Nc3ccc(Cl)cc3)cc2)n1</chem>	0.635	4.32	PASS

Section S3: All-Atom Molecular Dynamics Force Field & Simulation Protocol

S3.1 Receptor and Ligand Force Field Parametrization

To guarantee rigorous physical fidelity in our 600.0 ns explicit-solvent simulations, all molecular topologies were constructed using state-of-the-art biophysical force field parameters:

- **Protein Receptor Force Field:** The protein structures (1HFR, 1HK5, 1CBQ) were parameterized using the modern **Amber14SB** force field ('amber14-all.xml'). Missing heavy atoms and missing hydrogen atoms were reconstructed via PDBFixer at physiological pH 7.4. All aspartate and glutamate residues were modeled in their standard unprotonated carboxylate states (deprotonated, -1 charge), lysine and arginine residues were protonated (+1 charge), and histidine tautomeric states (HIE/HID/HIP) were assigned based on local hydrogen-bonding network analysis and active-site metal coordination.
- **De Novo Ligand Force Field:** Generated small molecules were parameterized with the **General Amber Force Field 2 (GAFF2)**. Atomic partial charges were derived using the semi-empirical **AM1-BCC (Austin Model 1 with Bond Charge Correction)** protocol implemented in OpenFF Toolkit and RDKit. Bonded parameters (equilibrium bond lengths, valence angles, and proper/improper torsional potentials) were verified to ensure zero parameter missing flags.
- **Solvent Model:** Solvated in an explicit, orthogonal periodic boundary box with **TIP3P water** ('amber14/tip3p.xml'), with a minimum solute-to-box boundary buffer distance of 10.0 Å along all three Cartesian axes.
- **Ionization & Neutralization:** Systems were neutralized with appropriate sodium (Na+) or chloride (Cl-) counterions and brought to a physiological ionic concentration of **0.15 M NaCl** using Joung-Cheatham monovalent ion parameters.

Table S3 | Summary of Simulation System Topologies and Solvation Box Dimensions Across 600 ns Suite

Target PDB	Enzyme Superfamily	Protein Atoms	Ligand Atoms	TIP3P Water Mol	Total System Atoms
1HFR	Dihydrofolate Reductase	2,489	42	8,642	28,457
1HK5	Casein Kinase II	5,362	45	14,890	50,077
1CBQ	Carboxypeptidase A	4,891	48	12,450	42,291

S3.2 Numerical Integration and Long-Range Electrostatics Protocol

Simulations were executed on NVIDIA CUDA hardware using OpenMM 8.1 with mixed-precision arithmetic. Long-range electrostatic interactions were computed using the **Particle Mesh Ewald (PME)** method with a real-space direct cutoff of 10.0 Å, a tolerance of 0.0005, and 4th-order B-spline interpolation over an automated Fourier grid. Lennard-Jones van der Waals interactions were smoothly switched to zero between 9.0 Å and 10.0 Å with long-range isotropic dispersion corrections applied to energy and pressure.

Equations of motion were integrated using the **Langevin Middle Integrator** with a time step of **2.0 fs** and a collision friction coefficient of 1.0 ps⁻¹ at 300.0 K. All covalent bonds involving hydrogen atoms were constrained using the SHAKE/SETTLE algorithm. Isothermal-isobaric (NPT) ensembles were maintained at 1.0 bar using a Monte Carlo Barostat with volume adjustments attempted every 25 integration steps.

Section S4: Comprehensive Biophysical Dynamics Convergence Analyses




Figure S1 | Master Tri-Target 600.0 ns Continuous Explicit-Solvent MD Trajectories. Uninterrupted 200.0 ns time-series RMSD curves for (A) 1HFR, (B) 1HK5, and (C) 1CBQ. Solid colored lines denote heavy-atom ligand RMSD (stabilizing at 1.42 Å), and dotted lines indicate protein backbone C α RMSD (1.18 Å). All systems reach thermal equilibrium within 5.0 ns and remain well below the 2.0 Å instability threshold for 100,000,000 steps.

S4.1 Analysis of Radius of Gyration (Rg) and Structural Compactness

To confirm that the target proteins do not undergo denaturation or global conformational unfolding upon ligand binding, we tracked the **Radius of Gyration (Rg)** across the full 200.0 ns trajectories:

- **1HFR Complex:** Maintained an initial Rg of 15.42 Å and stabilized at **15.38 $\pm$ 0.06 Å**, indicating perfect globular compactness throughout the simulation.
- **1HK5 Complex:** Initial Rg was 21.15 Å, converging to **21.08 $\pm$ 0.09 Å**, showing that the bi-lobed kinase architecture preserves its catalytic hinge cleft without domain splaying.
- **1CBQ Complex:** Initial Rg of 19.82 Å remained exceptionally rigid at **19.78 $\pm$ 0.07 Å** across all 100M steps.

S4.2 Solvent-Accessible Surface Area (SASA) Desolvation Profiling

Binding of high-affinity ligands is driven by hydrophobic desolvation entropy. We measured the solvent-accessible surface area of the binding pocket across the trajectory:

- **1HFR Pocket SASA:** Decreased from 520.4 Å² (apo-state) to **312.6 $\pm$ 14.2 Å²** upon lead binding, shielding the hydrophobic core from bulk solvent.
- **1HK5 Pocket SASA:** Decreased from 680.1 Å² to **385.4 $\pm$ 18.0 Å²**, confirming tight steric occlusion of the ATP hinge channel.
- **1CBQ Pocket SASA:** Decreased from 595.0 Å² to **340.2 $\pm$ 15.6 Å²**, sealing the catalytic zinc chamber.

Section S5: Intrinsic ADMET Oracle & Structural Safety Filter Specifications

PROTEUS enforces an intrinsic, multi-tiered ADMET architecture during continuous DDPO trajectory updates and inference sampling:

Table S4 | Detailed SMARTS Structural Alert Specifications (PAINS & BRENK MedChem Alerts)

Filter Category	Substructure Motif	SMARTS Pattern Definition	Action / Penalty
PAINS #1	Cyanostilbene	<chem>[*]1:[*6]:[*6]:[*6]([*6]:[*6]:[*6]:1)-[*6]=[*6]-[*6]#[*7]</chem>	Instant Rejection
PAINS #2	Sulfonyl Halide / Reactive	<chem>[*6]-[*16](=[*8])=[*8]</chem>	Instant Rejection
PAINS #3	Organic Azide	<chem>[*6]-[*7]=[*7]=[*7]</chem>	Instant Rejection
PAINS #4	Dicyanoolefin	<chem>[*6]=[*6](-[*6]#[*7])-[*6]#[*7]</chem>	Instant Rejection
PAINS #5	Alkyl Peroxide	<chem>[*8]-[*8]</chem>	Instant Rejection
MedChem Alert #1	Trisubstituted Hydrazine	<chem>[N;X3]([N;X3])[N;X3]</chem>	Instant Rejection
MedChem Alert #2	Azo Compound (Mutagenic)	<chem>[N;X2]=[N;X2]</chem>	Instant Rejection
Nitrogen Safety	Nitrogen Ratio > 35%	$N_atoms / Total_atoms > 0.35$	Exploit Gate (-0.4)
Ring Strain	3- / 4-Membered Fused Cages	Aziridine, Diazirine, Oxirane, Cyclopropane	Score Penalty (-0.40/ring)

Section S6: Zero-Leakage 100-Target Generalization & Headroom Discovery

To evaluate zero-shot generalization without data leakage, we curated an expanded suite of 100 non-redundant PDB pockets strictly disjoint from the 8,907 training structures ($\text{Train} \cap \text{Benchmark}_{20} \cap \text{Expanded}_{100} = \emptyset$).

Table S5 | Target-Level Headroom Stratification and Therapeutic Enzyme Superfamily Breakdown

Target Stratification	Pocket Count (N)	Baseline Reward (G0)	RL Reward	Reward Delta	Win Rate (%)
Low Baseline ($G0 < 0.58$)	14 PDBs	0.5421	0.6065	+0.0644	85.7%
Mid Baseline ($0.58 \leq G0 \leq 0.68$)	62 PDBs	0.6382	0.6471	+0.0089	51.6%
High Baseline ($G0 > 0.68$)	24 PDBs	0.7135	0.7082	-0.0053	37.5%
Kinases (ATP Hinge Clefts)	18 PDBs	0.6214	0.6498	+0.0284	66.7%
Proteases (Catalytic Cleavage)	16 PDBs	0.6340	0.6555	+0.0215	62.5%
Compact / Occluded Pockets	20 PDBs	0.6180	0.6422	+0.0242	65.0%

Statistical Correlation: Pearson $r = -0.584$ ($p = 2.34e-10$) between baseline reward and RL improvement, proving that RL acts as an adaptive rescue mechanism on difficult targets.

Section S7: Hyperparameter Specifications & Training Infrastructure

Table S6 | Complete Hyperparameter Specifications for Pre-Training and RL Co-Folding

Hyperparameter	Pre-Training Phase (Flow Matching)	Fine-Tuning Phase (Multi-Objective PPO RL)
Model Architecture	SE(3)-Equivariant Continuous GNN	SE(3)-Equivariant Continuous GNN
Number of EGNN Layers	6 Equivariant Interaction Layers	6 Equivariant Interaction Layers
Hidden Feature Dimension	128	128
RBF Distance Encodings	20 Gaussian Kernels (0.0 to 10.0 Å)	20 Gaussian Kernels (0.0 to 10.0 Å)
Continuous Flow Prior	Standard Normal $N(0, I)$	Standard Normal $N(0, I)$
ODE Numerical Solver	Midpoint Runge-Kutta (2nd Order)	Midpoint Runge-Kutta (2nd Order)
ODE Integration Steps	20 steps ($\Delta t = 0.05$)	20 steps ($\Delta t = 0.05$)
Optimizer	AdamW ($\text{lr} = 1e-4$, $\text{wd} = 1e-6$)	AdamW ($\text{lr} = 2e-5$, $\text{wd} = 1e-6$)
Batch Size	32 pocket-ligand pairs	16 pocket-ligand pairs
PPO Clip Epsilon	N/A	0.20
GAE Lambda / Discount	N/A	$\lambda = 0.95$, $\gamma = 0.99$
KL Penalty Coefficient	N/A	$\beta = 0.05$
Reward Weights	N/A	$w_{\text{QED}} = 2.0$, $w_{\text{pK}} = 1.0$, $w_{\text{SA}} = 0.25$, $w_{\text{Lip}} = 1.5$
Training Hardware	NVIDIA RTX 4090 / A100 Tensor Core	NVIDIA RTX 4090 / A100 Tensor Core

Section S8: Reproducibility & Open-Source Code Availability

The complete open-source codebase, training recipes, dataset loaders, pre-trained network checkpoints, OpenMM simulation scripts, and PyMOL trajectory sessions are made publicly available at:

GitHub Repository: <https://github.com/Lalith2007/Co-folding-flow-matching-with-physics-driven-RL-for-SBDD>