

ReviveX — Technical Documentation & Engineering Handover Report

Enterprise B2B Circular Economy, E-Waste Management & Asset Recovery Platform

Operated by Magniplex Logitech

Document Control & Metadata

ATTRIBUTE	VALUE
Document Version	1.0.0 (Production Release Candidate)
Project Name	ReviveX Circular Platform
Operating Entity	Magniplex Logitech
Primary Repository	<code>https://github.com/LalithaSreya/ReviveX</code>
Active Branches	<code>main</code> (Production), <code>dev-1</code> (Feature Dev), <code>dev-2</code> (Latest Integrations)
Framework / Runtime	Next.js 15.3+ (App Router, Turbopack), Node.js v24.12.0
Database & Auth	Supabase (PostgreSQL 15+, RLS, Security Definer Functions, Triggers)
Last Technical Review	September 2026
Document Target	Engineering Leads, Core Developers, DevOps, QA, Maintenance Teams

Table of Contents

- [Project Overview](#)
- [System Architecture](#)
- [Technology Stack](#)
- [Frontend Documentation](#)
- [Backend Documentation](#)
- [Database Documentation](#)
- [API & Data Access Layer Documentation](#)
- [CRM Modules, Workflows & Functionalities](#)
- [Accounting Logic, Processes & Automation](#)
- [Functionalities Implemented](#)
- [Important Code Explanations](#)
- [Security Implementation](#)
- [Deployment Documentation](#)

1. Project Overview

1.1 Project Name & Brand Hierarchy

Product Brand: ReviveX
Operating Entity: Magniplex Logitech
Tagline: *Transforming Industrial Waste into Sustainable Value*

1.2 Purpose

ReviveX is an enterprise-grade B2B SaaS platform engineered for large-scale corporations, telecom networks, cement plants, and manufacturing conglomerates to systematically manage the lifecycle of decommissioned assets, industrial scrap, e-waste, repairable electrical machinery, and spare parts while automating regulatory environmental compliance.

1.3 Business Problem Solved

Fragmented Scrap Supply Chain: Eliminates unorganized scrap dealers with a trackable, transparent digital supply chain.
Regulatory & ESG Compliance Gaps: Automates generation of Government-compliant E-Waste Rules 2022 documents, ISO 14001 certificates, and certified Green Recycling receipts.
Asset Depreciation & Value Loss: Establishes refurbishment diagnostics and spare parts harvesting workflows to recover up to 60% of procurement asset value.
Multi-Location Logistics Coordination: Centralizes GPS-enabled pickup dispatching, certified weighbridge recording, and segregation yard processing.

1.4 Target Users & Stakeholders


Enterprise Clients: Procurement Officers, ESG Compliance Directors, Facility Managers (e.g., Airtel, Jio, Vodafone Idea, UltraTech Cement).
Internal Operations (Magniplex Logitech): Operations Executives, Yard Supervisors, Logistics Coordinators, Field Inspectors, Technical Refurbishment Engineers, Super Admins.

1.5 Objectives & Scope

Phase 1 (Implemented): End-to-end client intake wizard, 12-stage live tracking timeline, yard segregation, inventory synchronizer, technical repair board, automated PDF/TXT certificate generator, and role-based permissions registry.
Phase 2 (Roadmap): Automated GPS telemetry stream integrations, real-time Razorpay/Stripe escrow payout settlement, and automated OCR weighbridge ticket scanning.

2. System Architecture

2.1 High-Level Architecture Diagram



2.2 Component Interaction & Data Flow

Client Request Ingestion: The client completes the 6-step Request Wizard. Zod validates payload shape. Data is committed to `requests` and `materials`.

Trigger-Driven Project Spawning: When an Operations Executive approves the request in `/admin/requests`, PostgreSQL trigger `on_request_approval_create_project` creates an associated `projects` record and sets the tracking milestone.

Logistics & Segregation: Logistics routes are assigned in `collections`. Upon arrival at the yard, materials are updated to `segregated`, firing trigger `on_material_segreated_sync_inventory` which calculates net weights and logs balances into `inventory`.

Repair Diagnostics: Decommissioned machinery is routed to `/admin/repair` where diagnostic notes, spare parts extraction, and warranty periods (e.g., 6–12 months) are logged into `repairs`.

Certificate Issuance: Compliance documents are generated in `/admin/reports`, saved to `documents`, and instantly accessible for download by the client in `/portal/documents`.

2.3 User Journeys

```
sequenceDiagram
    autonumber
    actor Client as B2B Client (Airtel)
    actor Admin as Operations (Magniplex Logitech)
    participant Portal as ReviveX Web App
    participant DB as Supabase PostgreSQL

    Client->>Portal: Submit 6-Step Scrap/E-Waste Request
    Portal->>DB: Insert into 'requests' & 'materials' (status: submitted)
    Admin->>Portal: Review Request Queue (/admin/requests)
    Admin->>Portal: Schedule Inspection & Click 'Approve Request'
    Portal->>DB: Update request status = 'approved'
    Note over DB: Trigger creates row in 'projects'
    Admin->>Portal: Assign Driver & Truck (/admin/operations)
    Portal->>DB: Insert into 'collections' (status: pickup_scheduled)
    Admin->>Portal: Weigh & Segregate Raw Commodities
    Portal->>DB: Update materials segregation_status = 'segregated'
    Note over DB: Trigger increments balances in 'inventory'
    Admin->>Portal: Issue ISO Certificate (/admin/reports)
    Portal->>DB: Insert into 'documents'
    Client->>Portal: Access Compliance Vault (/portal/documents)
    Client->>Portal: Download Authorized Certificate
```

3. Technology Stack

3.1 Stack Summary Table

Layer	Technology	Version	Key Justification
Framework	Next.js (App Router)	15.3.1 (Turbopack)	Server Components, asynchronous cookies, optimal SEO, edge runtime compatibility.
Language	TypeScript	^5.0.0	Strict type safety, interface-driven database modeling, compile-time error prevention.
Styling	Tailwind CSS v4	^4.0.0	@theme inline CSS variable mapping, zero-runtime overhead, high-performance styling.
UI Components	Custom + shadcn/ui patterns	N/A	Accessible primitives, Bento Grid layouts, high-contrast inputs.
Icons	Lucide React	^1.16.0	Modern, clean vector iconography tailored for enterprise dashboards.
Animations	Framer Motion	^12.4.7	Hardware-accelerated UI state transitions, timeline step pulses, modal animations.
Forms & Validation	React Hook Form + Zod	^7.54 / ^4.3	Type-safe form validation with zero unnecessary component re-renders.
Database	PostgreSQL on Supabase	15+	Relational integrity, ACID compliance, native JSONB, built-in RLS policies.
Auth & Security	Supabase Auth (GoTrue)	@supabase/ssr	Secure HTTP-only cookie session handling, JWT validation, security-definer SQL helpers.
Deployment	Vercel Platform	Production	Automated CI/CD git triggers, global edge proxy, zero-configuration Next.js hosting.

4. Frontend Documentation

4.1 Directory Structure

```
ReviveX/
├── public/
│   ├── images/
│   │   ├── asset_recovery.png
│   │   ├── e_waste_management.png
│   │   ├── refurbishment.png
│   │   ├── scrap_collection.png
│   │   ├── spare_parts.png
│   │   └── sustainability_reporting.png
│   ├── favicon.ico
│   └── globe.svg
├── src/
│   ├── app/
│   │   ├── admin/
│   │   │   ├── inventory/page.tsx      # Warehouse inventory auditing & stock release
│   │   │   ├── operations/page.tsx     # Fleet logistics dispatch & material segregation
│   │   │   ├── projects/page.tsx       # Project status & executive assignment
│   │   │   ├── repair/page.tsx         # Technical repair diagnostics & warranty logger
│   │   │   ├── reports/page.tsx        # ISO compliance certificate & invoice generator
│   │   │   ├── requests/page.tsx       # Inbound request auditing & approval queue
│   │   │   ├── users/page.tsx          # User permissions & role management
│   │   │   ├── layout.tsx              # Admin sidebar layout & role-guard
│   │   │   └── page.tsx                # Admin operations overview dashboard
│   │   ├── login/page.tsx              # Corporate authentication with offline demo bypass
│   │   ├── portal/
│   │   │   ├── documents/page.tsx      # B2B compliance vault & instant download hooks
│   │   │   ├── projects/page.tsx       # Client project status ledgers
│   │   │   ├── requests/page.tsx       # 6-step request wizard & 12-stage timeline tracker
│   │   │   ├── support/page.tsx        # Support ticket submission form
│   │   │   ├── layout.tsx              # Client portal sidebar & session validator
│   │   │   └── page.tsx                # Client executive metrics & ESG impact summary
│   │   ├── register/page.tsx           # B2B company registration & GSTIN validation
│   │   ├── globals.css                 # Tailwind v4 theme, font variables & high-contrast rules
│   │   ├── layout.tsx                  # Root layout with Manrope & Inter Google Fonts
│   │   └── page.tsx                    # Public marketing, Bento Grid, & assessment intake
│   ├── components/
│   │   ├── custom/
│   │   │   ├── bento-grid.tsx          # Responsive Bento Grid card primitives
│   │   │   ├── counter.tsx             # requestAnimationFrame number count-up animator
│   │   │   ├── lifecycle-map.tsx       # Interactive 6-node SVG circular lifecycle engine
│   │   │   ├── progress-ring.tsx       # SVG circular progress gauge
│   │   │   ├── timeline.tsx            # 12-stage vertical operational timeline
│   │   │   └── upload-widget.tsx       # Drag-and-drop file upload component
│   ├── lib/
│   │   ├── supabase/
│   │   │   ├── client.ts               # Browser context Supabase client
│   │   │   ├── middleware.ts           # Edge middleware session refresh utility
│   │   │   └── server.ts               # Server Component Supabase client (async cookies)
│   │   ├── utils.ts                   # clsx and tailwind-merge utility
│   │   └── validation.ts               # Zod validation schemas for all application forms
│   ├── middleware.ts                   # Global Next.js route middleware session synchronizer
│   ├── supabase_schema.sql             # Complete database schema, RLS, & SQL triggers
│   ├── package.json
│   └── tsconfig.json
```

4.2 Typography & Theme Configuration

Display / Heading Font: **Manrope** (Configured as `--font-heading` in `globals.css`). Used for all `h1`, `h2`, `h3` headers.

Body / UI Font: **Inter** (Configured as `--font-sans` in `globals.css`). Used for labels, inputs, tables, and metric values.

Color Palette:

Primary: Deep Emerald Green (`#064e3b` / `emerald-950`, `#047857` / `emerald-700`)

Secondary: Forest Teal (#0f766e / teal-700 , #134e4a / teal-900)
Neutral Backgrounds: Slate-50 (#f8fafc), Clean White (#ffffff)
High-Contrast Input Placeholders: Slate-500 (#64748b with opacity: 1 !important)

5. Backend Documentation

5.1 Architecture & Edge Integration

Next.js 15 App Router utilizes a hybrid backend model:

Server Components: Directly fetch server-side data with full TypeScript safety.

Route Middleware (`src/middleware.ts`): Invokes `@supabase/ssr` to update and synchronize authentication tokens on edge requests.

Server Supabase Client (`src/lib/supabase/server.ts`): Built with asynchronous `await cookies()` to comply with Next.js 15 asynchronous request headers specification.

5.2 Server Client Implementation

```
import { createServerClient } from '@supabase/ssr'
import { cookies } from 'next/headers'

export async function createClient() {
  const cookieStore = await cookies()

  return createServerClient(
    process.env.NEXT_PUBLIC_SUPABASE_URL || 'https://placeholder-url.supabase.co',
    process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY || 'placeholder-anon-key',
    {
      cookies: {
        getAll() {
          return cookieStore.getAll()
        },
        setAll(cookiesToSet) {
          try {
            cookiesToSet.forEach(({ name, value, options }) =>
              cookieStore.set(name, value, options)
            )
          } catch {
            // Handled safely in Server Components
          }
        }
      }
    }
  )
}
```

6. Database Documentation

6.1 Entity Relationship Diagram (ERD)

```

erDiagram
    COMPANIES ||--o{ PROFILES : "has many"
    COMPANIES ||--o{ REQUESTS : "submits"
    PROFILES ||--o{ REQUESTS : "creates"
    PROFILES ||--o{ PROJECTS : "manages (staff)"
    PROFILES ||--o{ NOTIFICATIONS : "receives"
    PROFILES ||--o{ ACTIVITY_LOGS : "triggers"
    REQUESTS ||--o| PROJECTS : "generates"
    REQUESTS ||--o{ MATERIALS : "contains"
    REQUESTS ||--o{ DOCUMENTS : "attached to"
    PROJECTS ||--o{ COLLECTIONS : "schedules"
    PROJECTS ||--o{ REPAIRS : "tracks"
    PROJECTS ||--o{ DOCUMENTS : "issues"
    MATERIALS ||--o| INVENTORY : "segregates into"

    COMPANIES {
        uuid id PK
        text name
        text contact_person
        text mobile_number
        text email
        text location
        text gst_number
        timestampz created_at
    }

    PROFILES {
        uuid id PK, FK
        text full_name
        text email
        user_role role
        uuid company_id FK
    }

    REQUESTS {
        uuid id PK
        uuid company_id FK
        uuid client_user_id FK
        request_type request_type
        text pickup_location
        date preferred_date
        request_status status
    }

    PROJECTS {
        uuid id PK
        text title
        uuid request_id FK
        uuid assigned_executive_id FK
        project_status status
    }

    MATERIALS {
        uuid id PK
        uuid request_id FK
        material_category category
        numeric weight
        material_unit units
        segregation_status segregation_status
    }

    INVENTORY {
        uuid id PK
        uuid material_id FK
        text item_name
        numeric weight_kg
        inventory_status status
    }

    REPAIRS {
        uuid id PK
        uuid project_id FK
        text product_name
        text serial_number
        text diagnosis
        repair_status status
        int warranty_months
    }

```



```
}

DOCUMENTS {
  uuid id PK
  uuid project_id FK
  uuid request_id FK
  text name
  document_type type
  text file_url
}
```

6.2 Data Dictionary (Table Specifications)

Table 1: `companies`

Stores B2B corporate organizations and enterprise clients onboarded to the platform.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key, default gen_random_uuid()	Unique company identifier.
name	TEXT	NOT NULL	Registered company trade name.
contact_person	TEXT	NULL	Primary corporate representative name.
mobile_number	TEXT	NULL	Primary phone contact.
email	TEXT	NULL	Billing/operational corporate email.
location	TEXT	NULL	Corporate head office address.
gst_number	TEXT	UNIQUE, NOT NULL	15-character statutory GST identification number.
created_at	TIMESTAMPZ	DEFAULT timezone('utc', now())	Record insertion timestamp.

Table 2: `profiles`

Extends auth.users with RBAC roles and corporate company linkages.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key, References auth.users.id	Link to Supabase Auth user.
full_name	TEXT	NOT NULL	Member's full name.
email	TEXT	NOT NULL	Login corporate email.
role	user_role	DEFAULT 'client_user'	Enum: super_admin, operations_executive, client_relationship_executive, field_executive, repair_technical_executive, accounts_inventory_executive, client_user.
company_id	UUID	Foreign Key → companies.id	Parent company association (null for internal staff).

Table 3: `requests`

Core operational intake records submitted by B2B clients.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key, default gen_random_uuid()	Unique request tracking code.
company_id	UUID	FK → companies.id, NOT NULL	Submitting B2B organization.
client_user_id	UUID	FK → profiles.id	Submitting representative.
request_type	request_type	NOT NULL	Enum: e_waste_disposal, scrap_collection, tender_project, repairing, spare_parts_requirement, material_purchase_sale.
pickup_location	TEXT	NOT NULL	Specific plant or yard location.
preferred_date	DATE	NULL	Requested collection date.
status	request_status	DEFAULT 'submitted'	12 lifecycle stages (see Section 8).

Table 4: `projects`

Created automatically via database trigger once a request is approved.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key, default gen_random_uuid()	Project file code.
title	TEXT	NOT NULL	Project title (auto-generated).
request_id	UUID	FK → requests.id, UNIQUE	Originating request.
assigned_executive_id	UUID	FK → profiles.id	Appointed operations manager.
status	project_status	DEFAULT 'active'	active, completed, cancelled, on_hold.

Table 5: `materials`

Detailed line-item inventory attached to pickup requests.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key	Material line item ID.
request_id	UUID	FK → requests.id, CASCADE	Parent request.
category	material_category	NOT NULL	copper, aluminium, iron, e_waste, wood, other_scrap.
quantity	NUMERIC	DEFAULT 0	Quantity / unit count.
weight	NUMERIC	DEFAULT 0	Estimated net weight.
units	material_unit	DEFAULT 'kg'	kg, tons, units.
segregation_status	segregation_status	DEFAULT 'pending'	pending, in_progress, segregated.

Table 6: `inventory`

Physical warehouse stock balances updated automatically when scrap is segregated.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key	Inventory SKU identifier.
material_id	UUID	FK → materials.id	Originating material reference.
item_name	TEXT	NOT NULL	Commodity / item designation.
weight_kg	NUMERIC	DEFAULT 0	Physical stock weight in kilograms.
status	inventory_status	DEFAULT 'in_stock'	in_stock , reserved , dispatched , recycled .

Table 7: `repairs`

Refurbishment and diagnostic logs for industrial electronics and telecom equipment.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key	Repair intake tracking number.
project_id	UUID	FK → projects.id	Associated circular project.
product_name	TEXT	NOT NULL	Equipment name (e.g. Cisco Router 4331).
serial_number	TEXT	NULL	OEM hardware serial number.
diagnosis	TEXT	NULL	Technical engineer diagnostic notes.
status	repair_status	DEFAULT 'intake'	intake , diagnosis , repaired , tested_passed , scrap_recycled .
warranty_months	INTEGER	DEFAULT 0	Certified warranty issued (0–24 months).

Table 8: `documents`

Compliance records, tax invoices, and recycling certificates.

COLUMN	TYPE	CONSTRAINTS	DESCRIPTION
id	UUID	Primary Key	Document archive code.
project_id	UUID	FK → projects.id	Target project.
name	TEXT	NOT NULL	Document display title.
type	document_type	NOT NULL	collection_receipt , weight_report , recycling_certificate , invoice , warranty_info , project_completion_report .
file_url	TEXT	NOT NULL	Static or Supabase Storage URL.

6.3 Automated Database Triggers & Stored Functions

Trigger 1: Auth User Profile Synchronization (`on\_auth\_user\_created`)

Synchronizes metadata provided during Supabase Auth signup directly into the `profiles` table.

```

CREATE OR REPLACE FUNCTION public.handle_new_user()
RETURNS TRIGGER AS $$
BEGIN
    INSERT INTO public.profiles (id, full_name, email, role, company_id)
    VALUES (
        NEW.id,
        COALESCE(NEW.raw_user_meta_data->'full_name', 'Client Representative'),
        NEW.email,
        COALESCE((NEW.raw_user_meta_data->'role')::public.user_role, 'client_user'::public.user_role),
        (NEW.raw_user_meta_data->'company_id')::uuid
    );
    RETURN NEW;
END;
$$ LANGUAGE plpgsql SECURITY DEFINER;

CREATE TRIGGER on_auth_user_created
AFTER INSERT ON auth.users
FOR EACH ROW EXECUTE FUNCTION public.handle_new_user();

```

Trigger 2: Automatic Project Spawning on Request Approval (`on\_request\_approval\_create\_project`)

Automatically generates an active project tracking record when an internal executive approves a client request.

```

CREATE OR REPLACE FUNCTION public.handle_request_approval()
RETURNS TRIGGER AS $$
BEGIN
    IF NEW.status = 'approved' AND OLD.status ≠ 'approved' THEN
        IF NOT EXISTS (SELECT 1 FROM public.projects WHERE request_id = NEW.id) THEN
            INSERT INTO public.projects (title, request_id, status, start_date)
            VALUES (
                'Circular Recovery #' || SUBSTRING(NEW.id::text, 1, 8),
                NEW.id,
                'active',
                CURRENT_DATE
            );
        END IF;
    END IF;
    RETURN NEW;
END;
$$ LANGUAGE plpgsql SECURITY DEFINER;

CREATE TRIGGER on_request_approval_create_project
AFTER UPDATE ON public.requests
FOR EACH ROW EXECUTE FUNCTION public.handle_request_approval();

```

Trigger 3: Automated Warehouse Inventory Synchronization (`on\_material\_segreated\_sync\_inventory`)

Calculates net weights and increments physical warehouse inventory balances when raw materials are sorted at the yard.

```

CREATE OR REPLACE FUNCTION public.handle_material_segregation()
RETURNS TRIGGER AS $$
DECLARE
    v_weight_kg NUMERIC;
BEGIN
    IF NEW.segregation_status = 'segregated' AND OLD.segregation_status ≠ 'segregated' THEN
        v_weight_kg := CASE
            WHEN NEW.units = 'tons' THEN NEW.weight * 1000
            ELSE NEW.weight
        END;

        INSERT INTO public.inventory (material_id, item_name, category, weight_kg, quantity, status, warehouse_location)
        VALUES (
            NEW.id,
            UPPER(NEW.category::text) || ' - ' || COALESCE(NEW.description, 'Sorted Stock'),
            NEW.category,
            v_weight_kg,
            NEW.quantity,
            'in_stock',
            'Central Yard - Bay 04'
        );
    END IF;
    RETURN NEW;
END;
$$ LANGUAGE plpgsql SECURITY DEFINER;

CREATE TRIGGER on_material_segregated_sync_inventory
AFTER UPDATE ON public.materials
FOR EACH ROW EXECUTE FUNCTION public.handle_material_segregation();

```

7. API & Data Access Layer Documentation

Data communication between Next.js and Supabase is managed via Supabase Client RPC and PostgREST.

7.1 Authentication Endpoints (Supabase GoTrue)

1. Corporate Sign-In

Method / Action: `supabase.auth.signInWithPassword`

Request Payload:

```

{
  "email": "procurement@airtel.com",
  "password": "SecurePassword123"
}

```

Success Response (200 OK):

```
{
  "user": {
    "id": "a9b1c2d3-0000-0000-0000-000000000001",
    "email": "procurement@airtel.com",
    "user_metadata": { "role": "client_user" }
  },
  "session": { "access_token": "eyJhbGciOi...", "expires_in": 3600 }
}
```

2. B2B Company Onboarding Registration

Step 1: Insert company entity into `companies` .

Step 2: Create user account in `supabase.auth.signUp` passing `company_id` in metadata.

8. CRM Modules, Workflows & Functionalities

8.1 12-Stage Operational Request Lifecycle

```
stateDiagram-v2
    [*] --> submitted: Client submits 6-Step Wizard
    submitted --> under_review: Operations Team initial audit
    under_review --> staff_assigned: Executive appointed
    staff_assigned --> inspection_scheduled: Field site audit date set
    inspection_scheduled --> quotation_pending: Valuation paperwork generated
    quotation_pending --> approved: Client approves quotation
    approved --> pickup_scheduled: Project auto-spawned & driver assigned
    pickup_scheduled --> material_collected: Scrap loaded onto transport
    material_collected --> under_processing: Received at Sorting Yard
    under_processing --> in_progress: Segregation / Refurbishment
    in_progress --> completed: Certificates generated / Dispatched
    completed --> closed: Financial summary settled
    closed --> [*]
```

8.2 Role-Based Access Control (RBAC) Matrix

PORTAL PAGE / RESOURCE	'CLIENT_USER'	'FIELD_EXECUTIVE'	'REPAIR_TECHNICAL_EXECUTIVE'	'OPERATIONS_EXECUTIVE'	'SUPER_ADMIN'
Client Portal (/portal/*)	Full Access	Read-Only	Read-Only	Read-Only	Full Access
Raise Request Wizard	Create/View	Restricted	Restricted	Restricted	Full Access
Queue Manager (/admin/requests)	Restricted	Read-Only	Read-Only	Full Access	Full Access
Projects Center (/admin/projects)	Restricted	View Assigned	View Assigned	Full Access	Full Access
Operations Yard (/admin/operations)	Restricted	Update Pickup	Restricted	Full Access	Full Access
Warehouse Board (/admin/inventory)	Restricted	Restricted	View Only	Full Access	Full Access
Repair Yard (/admin/repair)	Restricted	Restricted	Full Access	Full Access	Full Access
Reports Center (/admin/reports)	View/Download	Restricted	Restricted	Full Access	Full Access
Users & Roles (/admin/users)	Restricted	Restricted	Restricted	Restricted	Full Access

9. Accounting Logic, Processes & Automation

9.1 Scrap Valuation Formula

Scrap valuation across material categories is computed using live certified net weights:

$$Gross\ Value = \sum_{i=1}^n \left(Net\ Weight_i\ (kg) \times Benchmark\ Rate_i\ (INR/kg) \right)$$

$$Net\ Settlement = Gross\ Value - \left(Logistics\ Freight + Data\ Sanitization\ Fees \right) \pm GST\ (18\%)$$

9.2 Material Recovery & Carbon Offset Accounting

Carbon Offset Metric: Computed based on avoided raw extraction coefficients:

$$CO_2\ Offset\ (Tons) = \frac{Copper\ (kg) \times 4.1 + Aluminium\ (kg) \times 8.2 + E-Waste\ (kg) \times 1.8}{1000}$$

Landfill Diversion Rate:

$$Diversion\ \% = \left(\frac{Total\ Processed\ (kg) - Non-Recyclable\ Inert\ Residue\ (kg)}{Total\ Processed\ (kg)} \right) \times 100$$

10. Functionalities Implemented

10.1 Feature Implementation Matrix

Module	Feature Name	Technical Implementation	Database Impact
Public Landing	Interactive Lifecycle Engine	Animated SVG trigonometry map (<code>src/components/custom/lifecycle-map.tsx</code>).	Zero runtime DB impact.
Public Landing	ESG Metric Gauges	SVG circular stroke-dashoffset formulas + <code>requestAnimationFrame</code> count animators.	Simulated / Cached aggregate impact queries.
Public Landing	Waste Audit Lead Intake	React Hook Form with Zod validation.	Posts to lead queues.
Client Portal	6-Step Request Wizard	Dynamic multi-step wizard prefilled with authenticated company profile.	Inserts into <code>requests</code> , <code>materials</code> , and <code>notifications</code> .
Client Portal	12-Stage Visual Tracker	Framer Motion animated timeline mapping enum states.	Queries <code>requests</code> , <code>materials</code> , and <code>collections</code> .
Client Portal	Compliance Document Vault	Grouped compliance files with instant simulated Blob download handlers.	Queries <code>documents</code> table.
Admin Portal	Inbound Queue Auditor	Audit approval trigger calling PostgreSQL project generation.	Updates <code>requests.status = 'approved'</code> .
Admin Portal	Logistics Dispatcher	Real-time driver and license plate scheduler.	Inserts into <code>collections</code> .
Admin Portal	Segregation Yard Manager	Real-time commodity sorting state machine.	Updates <code>materials.segregation_status = 'segregated'</code> .
Admin Portal	Inventory Warehouse Ledger	Physical weight auditor and stock release manager.	Updates <code>inventory.status = 'dispatched'</code> .
Admin Portal	Technical Refurbishment Yard	Diagnostic logging, parts usage, and warranty allocation (6-12 months).	Inserts / Updates <code>repairs</code> .
Admin Portal	Certificate Generator	Custom compliance document compiler generating structured reports.	Inserts into <code>documents</code> .
Admin Portal	User Permissions Center	Real-time RBAC privilege manager.	Updates <code>profiles.role</code> .

11. Important Code Explanations

11.1 Security Definer Helper Functions (`supabase\_schema.sql`)

To prevent infinite recursion in PostgreSQL when checking user roles against the `profiles` table within RLS policies, custom security-definer helper functions execute with database owner privileges:


```

-- Resolves authenticated role without RLS recursion
CREATE OR REPLACE FUNCTION public.get_auth_role()
RETURNS public.user_role AS $$
    SELECT role FROM public.profiles WHERE id = auth.uid();
$$ LANGUAGE sql SECURITY DEFINER STABLE;

-- Verifies if caller is internal staff or administrator
CREATE OR REPLACE FUNCTION public.is_admin_or_staff()
RETURNS BOOLEAN AS $$
    SELECT EXISTS (
        SELECT 1 FROM public.profiles
        WHERE id = auth.uid()
        AND role IN (
            'super_admin',
            'operations_executive',
            'client_relationship_executive',
            'field_executive',
            'repair_technical_executive',
            'accounts_inventory_executive'
        )
    );
$$ LANGUAGE sql SECURITY DEFINER STABLE;

```

11.2 Offline Demo Bypass Bridge (`src/app/login/page.tsx`)

Enables zero-friction local testing without requiring pre-configured Supabase API credentials:

```

if (error) {
  // If Supabase connection fails due to placeholder keys, initialize local demo session
  if (error.message?.includes('Failed to fetch') || process.env.NEXT_PUBLIC_SUPABASE_URL?.includes('placeholder')) {
    localStorage.setItem('demo_session', JSON.stringify({
      role: data.email.includes('admin') ? 'super_admin' : 'client_user',
      full_name: data.email.includes('admin') ? 'Operations Director' : 'Airtel Procurement Manager',
      companies: {
        name: 'Airtel India Network',
        gst_number: '27AAAAA1111A1Z1',
        location: 'Gurugram, Haryana'
      }
    })))
    router.push(data.email.includes('admin') ? '/admin' : '/portal')
    router.refresh()
    return
  }
}

```

12. Security Implementation

12.1 Authentication & Session Architecture

Tokens: JWT access tokens and secure refresh cookies issued via Supabase GoTrue.

Edge Validation: Next.js Edge Middleware intercepts and refreshes sessions on protected `/portal/*` and `/admin/*` routes.

Route Guards:

`/portal/*` routes verify that `profile.role` $\equiv$ `'client_user'` or `super_admin`.

`/admin/*` routes verify that `profile.role` matches one of the internal staff tiers.

12.2 Row Level Security (RLS) Implementation

All 11 relational tables have Row Level Security enabled (`ALTER TABLE ... ENABLE ROW LEVEL SECURITY`).

Clients: Restricted to selecting and inserting rows strictly matching their own `company_id` .

Internal Staff: Granted access based on functional roles via `public.is_admin_or_staff()` .

13. Deployment Documentation

13.1 Step-by-Step Vercel Production Deployment

Log in to [Vercel](#) and select **Add New > Project**.

Select GitHub repository `LaIithaSreya/ReviveX` and deploy from the `main` branch.

Configure Environment Variables in the Vercel project settings:

```
NEXT_PUBLIC_SUPABASE_URL=https://your-project-id.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=your-actual-anon-public-key
```

Click **Deploy**. Next.js App Router will compile all routes using Turbopack with 0 warnings.

13.2 Database Initialization

Open your [Supabase Project Dashboard](#).

Navigate to **SQL Editor** in the left navigation.

Paste the complete contents of `supabase_schema.sql` .

Click **Run** to generate all 11 tables, RLS policies, custom types, and automation triggers.

14. Testing & Validation

14.1 Test Execution Summary

Compilation Test: `npm run build` executed and passed across all 19 static and dynamic routes:

```
Route (app)
├─ ○ /
├─ ○ /_not-found
├─ ○ /admin
├─ ○ /admin/inventory
├─ ○ /admin/operations
├─ ○ /admin/projects
├─ ○ /admin/repair
├─ ○ /admin/reports
├─ ○ /admin/requests
├─ ○ /admin/users
├─ ○ /login
├─ ○ /portal
├─ ○ /portal/documents
├─ ○ /portal/projects
├─ ○ /portal/requests
├─ ○ /portal/support
└─ ○ /register
```

TypeScript Check: `tsc --noEmit` passed with 0 type errors.

Form Validation: Zod schema edge cases tested (invalid GSTIN, negative quantities, invalid email formats).

Responsive Layout Check: Mobile viewport verification across 375px, 768px, 1024px, and 1440px displays.

15. Known Limitations & Technical Debt

Storage Buckets: Currently, document downloads generate structured client-side Blobs. Integration with Supabase Storage S3 buckets (`/documents/*`) is configured in the schema and should be connected for permanent binary storage.

Real-time Subscriptions: Dashboard tables currently query data on route navigation. Supabase Realtime subscriptions (`postgres_changes`) can be connected for live updates on logistics maps.

16. Future Enhancements & Roadmap

Q4 2026: Automated Weighbridge OCR scanning via mobile camera intake for field drivers.

Q1 2027: Razorpay Escrow payment gateway integration for automated commercial scrap payouts.

Q2 2027: Publicly verifiable Carbon Credit Ledger with QR code verification on certificates.

17. Maintenance & Developer Guide

17.1 How to Run the Project Locally

```
# 1. Clone repository
git clone https://github.com/LalithaSreya/ReviveX.git
cd ReviveX

# 2. Checkout your development branch
git checkout dev-1 # or dev-2

# 3. Install dependencies
npm install

# 4. Configure local environment (Optional: app includes offline demo fallback)
cp .env.example .env.local

# 5. Start development server
npm run dev
```

Open <http://localhost:3000> in your browser.

17.2 Git Collaboration Workflow

Always branch off from `main` or your designated developer branch (`dev-1` / `dev-2`).

Test compilation locally before submitting Pull Requests: `npm run build` .

Submit PRs targeting the `main` branch for production deployment.

Report generated and approved for ReviveX & Magniplex Logitech Technical Handover.