

Correct

Marked out of 3.00

🚩 [Flag question](#)

Objective

This is a simple challenge to help you practice printing to stdout.

We're starting out by printing the most famous computing phrase of all time! In the editor below, use either `printf` or `cout` to print the string ***Hello, World!*** to stdout.

Input Format

You do not need to read any input in this challenge.

Output Format

Print ***Hello, World!*** to stdout.

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include<stdio.h>

int main()
{
    printf("Hello, World!");
    return 0;
}
```


| | Expected | Got | |
|---|---------------|---------------|---|
| ✓ | Hello, World! | Hello, World! | ✓ |

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

 [Flag question](#)

Objective

This challenge will help you to learn how to take a character, a string and a sentence as input in C.

To take a single character **ch** as input, you can use `scanf("%c", &ch);` and `printf("%c", ch)` writes a character specified by the argument `char` to `stdout`:

```
char ch;  
scanf("%c", &ch);  
printf("%c", ch);
```

This piece of code prints the character **ch**.

Task

You have to print the character, **ch**.

Input Format

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include<stdio.h>
int main()
{char ch;
    scanf("%c",&ch);
    printf("%c",ch);
    return 0;
}
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | C | C | C | ✓ |

Passed all tests! ✓

Question **3**

Correct

Marked out of 7.00

 [Flag question](#)

Objective

The fundamental data types in c are int, float and char. Today, we're discussing int and float data types.

The printf() function prints the given statement to the console. The syntax is printf("format string",argument_list);. In the function, if we are using an integer, character, string or float as argument, then in the format string we have to write %d (integer), %c (character), %s (string), %f (float) respectively.

The scanf() function reads the input data from the console. The syntax is scanf("format string",argument_list);. For ex: The scanf("%d",&number) statement reads integer number from the console and stores the given value in variable **number**.

To input two integers separated by a space on a single line, the command is scanf("%d %d", &n, &m), where **n** and **m** are the two integers.

Task

Your task is to take two numbers of **int data type**, two numbers of float data type as input and output their sum.

second line.

Sample Input

10 4

4.0 2.0

Sample Output

14 6

6.0 2.0

Explanation

When we sum the integers **10** and **4**, we get the integer **14**. When we subtract the second number **4** from the first number **10**, we get **6** as their difference.

When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include<stdio.h>
int main()
{
int a,b;
float c,d;
scanf( "%d %d\n", &a,&b);
scanf( "%f %f", &c,&d);
printf( "%d %d\n", a+b,a-b);
printf( "%.1f %.1f", c+d,c-d);
return 0;
}
```

| | Input | Expected | Got | |
|---|-----------------|-------------------|-------------------|---|
| ✓ | 10 4 4.0 2.0 | 14 6 6.0 2.0 | 14 6 6.0 2.0 | ✓ |
| ✓ | 20 8 8.0 4.0 | 28 12 12.0 4.0 | 28 12 12.0 4.0 | ✓ |

Passed all tests! ✓

Question **1**

Correct

Marked out of 3.00

 [Flag question](#)

Write a program to input a name (as a single character) and marks of three tests as m1, m2, and m3 of a student considering all the three marks have been given in integer format.

Now, you need to calculate the average of the given marks and print it along with the name as mentioned in the output format section.

All the test marks are in integers and hence calculate the average in integer as well. That is, you need to print the integer part of the average only and neglect the decimal part.

Input format :

Line 1 : Name(Single character)

Line 2 : Marks scored in the 3 tests separated by single space.

Output format :

First line of output prints the name of the student.

Second line of the output prints the average mark.

Constraints


```

1  #include<stdio.h>
2  int main()
3  {int m1,m2,m3;
4  char a;
5  scanf("%c\n",&a);
6  scanf("%d %d %d",&m1,&m2,&m3);
7  printf("%c\n",a);
8  printf("%d",(m1+m2+m3)/3);
9  return 0;
10 }

```

| | Input | Expected | Got | |
|---|---------------|----------|---------|---|
| ✓ | A 3 4 6 | A 4 | A 4 | ✓ |
| ✓ | T 7 3 8 | T 6 | T 6 | ✓ |
| ✓ | R 0 100 99 | R 66 | R 66 | ✓ |

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

 [Flag question](#)

Some C data types, their format specifiers, and their most common bit widths are as follows:

- *Int* ("%d"): 32 Bit integer
- *Long* ("%ld"): 64 bit integer
- *Char* ("%c"): Character type
- *Float* ("%f"): 32 bit real value
- *Double* ("%lf"): 64 bit real value

Reading

To read a data type, use the following syntax:

```
scanf("`format_specifier`, &val)
```

For example, to read a *character* followed by a *double*:

```
char ch;
```

```
double d;
```

```
scanf("%c %lf", &ch, &d);
```

For the moment, we can ignore the spacing between format specifiers.

Printing

To print a data type, use the following syntax:

```
printf("`format_specifier`" val)
```

Note: You can also use *cin* and *cout* instead of *scanf* and *printf*; however, if you are taking a million numbers as input and printing a million lines, it is faster to use *scanf* and *printf*.

Input Format

Input consists of the following space-separated values: *int*, *long*, *char*, *float*, and *double*, respectively.

Output Format

Print each element on a new line in the same order it was received as input. Note that the floating point value should be correct up to 3 decimal places and the double to 9 decimal places.

Sample Input

3 12345678912345 a 334.23 14049.30493

Sample Output

3

12345678912345

a

334.230

14049.304930000

Explanation

Print *int* **3**,

followed by *long* **12345678912345**,

followed by *char* **a**,

followed by *float* **334.23**,

followed by *double* **14049.30493**.

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {int num;
4 long i;
5 char ch;
6 float deci3;
7 double deci9;
8 scanf("%d %ld %c %f %lf",&num,&i,&ch,&deci3,&deci9);
9 printf("%d \n",num);
10 printf("%ld \n",i);
11 printf("%c \n",ch);
12 printf("%.3f \n",deci3);
13 printf("%.9lf \n",deci9);
14 return 0;
15 }

```

| | Input | Expected | Got |
|---|---------------------------------------|--|---|
| ✓ | 3 12345678912345 a 334.23 14049.30493 | 3 12345678912345 a 334.230 14049.304930000 | 3 12345678912345 a 334.230 14049.30493000 |

Passed all tests! ✓

Question **3**

Correct

Marked out of 7.00

 [Flag question](#)

Write a program to print the **ASCII value** and the two adjacent characters of the given character.

Input

E

Output

69

D F

Answer: (penalty regime: 0 %)

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char ch;
5     scanf("%c",&ch);
6     printf("%d",ch);
7     printf("\n%c %c",ch-1,ch+1);
8     return 0;
9 }
```

| | Input | Expected | Got | |
|---|-------|-----------|-----------|---|
| ✓ | E | 69 D F | 69 D F | ✓ |

Passed all tests! ✓