DesignLights Consortium

Model Number	ALI-BPL-1X4-15/20/30/40/50W-6CCT-LB-S1
Classification	Premium
Primary Use	Low-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	50 W
Reported Light Output	6500 lm
Reported CCT	3000 K
Reported CRI (Ra)	81
Product ID	S-HSXP9M
DLC Family Code	SLFHBC
Listing Status	Listed
Date Qualified	2025-01-22

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-HSXP9M
Manufacturer	American lighting industry corp
Brand	Astrelights Inc
Model Number	ALI-BPL-1X4-15/20/30/40/50W-6CCT-LB-S1
Parent	Yes
Classification	Premium
DLC Family Code	SLFHBC
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Low-Bay
Primary Use Designation	Low-Bay Luminaires for Commercial and Industrial Buildings

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	Sensor Receptacle
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	6500 lm
Reported Efficacy (AC)	130 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	81
Reported R9	1
Reported IES Rf	81
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Minimum Light Output	1950 lm
Reported Maximum Light Output	6500 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	6500 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	50 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	15 W
Reported Maximum Input Wattage	50
Reported Default Input Wattage	50 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120

Tested Light Output	6371 lm
Tested Efficacy (AC)	128.7 lm/W
Tested CCT	3033 K
Tested CRI (Ra)	82
Tested R9	3
Tested IES Rf	84
Tested IES Rg	97
Tested Duv	-0.0008

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	49.52 W
Tested Total Harmonic Distortion	10.4 %
Tested Power Factor	0.965

VERSION HISTORY VIEW DETAILS

2025-01-22	Listed	5.1	Premium